cabur



Electronic
Products for electrical panels

February 2009 edition



UNI EN-ISO 9001



UNI EN-ISO 14001

cabur

WARNING **If not specified, the technical data in this catalogue are typical and measured at 25°C (77°F), 230 Vac, Unom, Vdc and rated current; ripple is measured at 20 MHz with probe connected to 0.1 µF. The technical data in this catalogue are typical and are not binding for Cabur and may be modified without prior notice, simply for production or improvement and/or evolution reason. Please contact our technical-commercial offices for any relevant confirmation or updates. For more informations visit our web site www.cabur.eu.**

Catalogue printed on FSC certified, ecological and recyclable glossy paper.
FSC (Forest Stewardship Council) is an international non-profit organization devoted to encouraging the responsible management of the world's forests through an environmentally friendly and economically sustainable policy.

Design, layout, illustrations and printing: Dogma Srl - Savona, Italy



Quality wins! That's guaranteed!

Quality, reliability, high technology, know-how, efficient use are all aspects and features of a product of primary importance.
For the safety and piece of mind of its Customers, Cabur designs and creates its Electronic Products with great care, using selected materials and components, in perfect harmony with the Quality choices made by the company in the last few decades. That's why we can guarantee our electronic products for five years.

Cabur's electronic products warranty

Cabur guarantees its electronic products against manufacturing defects and faults as well as defects due to their parts and/or components (except for wearable parts and/or components) for 5 years starting from the date of the shipping document issued by Cabur.

www.cabur.eu/5

Summary

Introduction

Cabur . . . . page 6
Products range . . . . page 8
Web site . . . . page 9
Quality and environment . . . . page 10
Standards and Directives . . . . page 11

Power supplies

Introduction . . . . page 12
Quick selection table . . . . page 14
CSD series - modular single-phase switching power supply - Domotic Power . . . . page 16
CSF series - single-phase switching power supply - Cool Power . . . . page 21
Single-phase switching power supply in IP65 housing . . . . page 30
CSP series - single-phase switching power supply - Easy Power . . . . page 31
CSW series - single and 2-phase switching power supply - Universal Power . . . . page 35
CSB series - 2-phase switching power supply - Triple power . . . . page 38
CSG series - 3-phase switching power supply - Triple power . . . . page 38
CSA series - DC/DC switching converters . . . . page 48
CSE series - switching power supply with 24 Vac input . . . . page 50
CL series - Adjustable linear power supply input 24 Vac . . . . page 52
AR series - filtered power supply without transformer . . . . page 53
Accessory for charging buffer batteries . . . . page 55
Batteries holder module . . . . page 57
CSC series - switching power supply with integrated battery charger . . . . page 58
Accessory for power supplies redundant parallel connections . . . . page 59

Surge protection devices

Introduction . . . . page 60
Pluggable surge protection devices . . . . page 61

Overcurrent protection devices

Introduction . . . . page 62
Adjustable electronic overcurrent protection . . . . page 63

EMI Filters

Quick selection table . . . . page 64
TDV series - 3-phase filter without neutral . . . . page 65
TDS series - 3-phase filter without neutral . . . . page 66
TDDS series - 3-phase filter without neutral . . . . page 67
TDSS series - 3-phase filter without neutral . . . . page 68
TYT series - 3-phase filter with neutral . . . . page 69
TY series - compact three-phase filter with neutral . . . . page 70
DK series - single-cell single-phase filter . . . . page 71
DP series - double-cell single-phase filter . . . . page 72

Signal conditioners

Introduction . . . . page 73
Quick selection table . . . . page 75
Programmable analog signal converters . . . . page 78
Analog signal converters . . . . page 82
Passive galvanic isolators . . . . page 88
Analog signal to frequency converters . . . . page 89
Universal temperature converters . . . . page 90
Programmable converters for RTD sensor . . . . page 91
Programmable converters for TC J and K sensor . . . . page 92
Temperature to frequency converters . . . . page 93
Current to threshold converters . . . . page 94

Current to analog signal converters . . . . . page 95
Frequency to analog signal converters . . . . . page 96
Analog to digital converters . . . . . page 98
Digital to analog converters . . . . . page 99
Analog signal to threshold converters . . . . . page 100
Load cells converter . . . . . page 101
Auxiliary power supply for sensors and potentiometers . . . . . page 102
NPN and PNP signal inverter . . . . . page 103

Electromechanical relay modules

Single relay quick selection table . . . . . page 104
R series - single relay DC input . . . . . page 105
CM series - single relay DC input . . . . . page 107
CM series - single relay AC input . . . . . page 110
CKR and CWRE series - Relay modules . . . . . page 113
Multiple relays quick selection table . . . . . page 116
24 V SPDT multiple relay modules . . . . . page 117
24 V DPDT multiple relay modules . . . . . page 121
24 V SPDT multiple relay modules with test button . . . . . page 124
12 Vdc SPDT multiple relay modules . . . . . page 125
12 Vdc DPDT multiple relay modules . . . . . page 126
48 Vdc DPDT multiple relay modules . . . . . page 127
110...120 V SPDT multiple relay modules . . . . . page 128
230 Vac SPDT multiple relay modules . . . . . page 129
12-24 V SPDT multiple socket modules without relays . . . . . page 130
12-24 V DPDT multiple socket modules without relays . . . . . page 131
CR and CRE series - super compact relay modules . . . . . page 132
PLC and CN interfaces quick selection table for . . . . . page 135
PLC Siemens S7 interfaces modules . . . . . page 136
PLC Telemecanique interfaces modules . . . . . page 139

Solid state relay modules

Quick selection table . . . . . page 140
Single solid state relays modules . . . . . page 141
Modular single solid state relays modules . . . . . page 144
SPDT single solid state relays modules . . . . . page 146
Signal optoisolators . . . . . page 147
Multiple solid state relays modules . . . . . page 148

Passive interface modules

Quick selection table . . . . . page 152
SUB-D / terminals interfaces . . . . . page 153
FLAT-cable / terminals interfaces . . . . . page 156
Components holder modules . . . . . page 158
Diodes holder modules . . . . . page 159
LED testing module . . . . . page 161
Lamp testing module . . . . . page 162
Distribution modules . . . . . page 163
Modular diodes holder modules . . . . . page 164

Accessories

Electronic circuit housing . . . . . page 165
Plug-in and screw type jumpers . . . . . page 167
Marking system . . . . . page 169
DIN rail clamp . . . . . page 169
Mounting rails . . . . . page 170

Index . . . . . page 172

cabur

- **Terminal blocks for electrical boards**
  polyamide screw clamp, spring-clamp terminal blocks, melamine insulated terminal blocks, terminal boards for metering panels, high current terminal blocks
- **Electronic products for electrical boards**
  power supplies, analog modules, relay modules, signal converters
- **Installation products**
  junction boxes terminals, distribution terminal boards, polyamide 12-pole terminal boards, connection systems for photovoltaic equipments
- **Multipole connectors**





If you wish to receive complete and updated technical documentation on Cabur products, please send a request using the dedicated form that you can download online on the www.cabur.eu website
http://www.cabur.eu/documentations

or just fill in, and send the form below

PLEASE SEND ME THE COMPREHENSIVE TECHNICAL DOCUMENTATION

Surname ..... Name ..... Function .....

Company Name ..... Field of activity: ❑ Distributor ❑ Installer ❑ Panel Builder ❑ Other

Address ..... Town ..... Postcode .....

Telephone ..... Fax ..... E-mail .....

Data supplied shall be kept by Cabur Srl and processed on printed forms, confidentially protected, with the sole purpose to allow Cabur, its agents, retailers and partners to deliver commercial information and services. Data contribution is optional. Nevertheless the non-authorization to data processing implies the impossibility of receiving information and commercial bargains. At any moment you may avail yourselves of the rights as prescribed in the Italian decree 196/2203. In order to ask for a copy of the data supplied, obtain its modification or its cancellation from our archives, or to exercise the rights as per article 7 of above mentioned law decree, you may send a written request to: Cabur Srl - Marketing department - Località Isola Grande, 45 - 17041 Altare (SV, Italy). The holder of data processing is: Cabur Srl, Località Isola Grande 45, Altare (SV), Italy.

I agree to my personal data being processed for the a.m. purposes.
Signature

.....

PLEASE PHOTOCOPY AND SEND BY FAX AT +39 019 58999280

Cabur 1952 2009

Shortly after its foundation, back in 1952, Cabur became a leading manufacturer of electrical panel terminal blocks, by focusing on installers' needs and providing leading edge technical solutions that, in some cases, would become popular in the industry.
In particular, in our product design and manufacturing, we have pioneered a quality focus on raw materials, functionality, reliability over time, and respect for the environment. That is the reason why Cabur was granted Class 1E (Equipment for Nuclear Power Generating Stations) qualification as early as in 1985 and, in addition, the ISO 9001/UNI-EN 29001 (Quality) and ISO 14001 (Environment) certifications, as well as compliance to Atex standards for "Ex e" installations on the most important terminal block lines.

UNI EN-ISO 14001

UNI EN-ISO 9001


The Headoffices

In 2006 a significant growth in company structure urged the organization to move from the historic site in Albissola Marina to a new logistic and manufacturing centre in Altare (SV).
Rather than moving abroad, Cabur has opted to invest in Italy, by acquiring a new state-of-the-art 15,000 sqm production site.
By doubling our production surface and increasing our staff with the recruitment of new people, we will be able to rationalise and make our current production processes, logistics, and sales, even more efficient.

cabur

Località Isola Grande 45
17041 Altare (SV)
ITALY
Tel. +39 019 58999.1
Fax +39 019 58999280
e-mail: info@cabur.it






Product range

With over 50 years of experience, Cabur develops and produces, by its own designs, a wide range of products for the electrical industry, providing the best in working conditions, in terms of operability and reliability.
Current production of:

- **Terminal blocks for electrical boards**
- **Electronic products for electrical boards**
- **Installation products**

Fully meets users' varied and complex installation needs.
Our varied and diversified production represents the optimal synthesis of Cabur's long experience as partner of Italy's most important Industries and Research Laboratories, combined with foreign activities and collaboration, always with the aim of pinpointing and meeting users' installation needs.





In particular as a result of a specific planning decision, products in our "standard" series are designed to meet the fundamental requirements of the most severe installation conditions and environments, thus avoiding to produce special product series for specific applications. This kind of planning has determined a clear qualitative improvement in the entire production, as well as a more streamlined and simplified product management, first of all to the advantage of the Distribution, which can guarantee to final Clients the most efficient service.

In addition to terminal blocks, Cabur product offering features a full range of electronic products for electric panels for plant and machine automation and process control. These products are designed for an easy deploy and for easy material management, thanks to the use of innovative and leading-edge technology.



Following an agreement with Tyco Electronics, Cabur distributes in the Italian market the HTS **heavy duty connector line**, which enlarges and completes the product range with over 250 items, presenting a series of highly qualified solutions.
HTS was selected as our partner for their strong experience in this field, their reliability and top material and finished product quality.



Highest ...mass produced quality

We guarantee top performance of our contacts and maximum flexibility of connection solutions.
A full range of standard products for automation panels is available at all major Wholesalers. Full support is provided by Cabur sales force both in Italy and in over 30 countries abroad, as well as by our Engineers, in order to provide our clients with the best installation solutions.


www.cabur.eu web site



On our web site, our customers and industry operators can always get up-to-date information on new products and sales offers.
All data sheets of Cabur product range, including those in this Catalogue, are available on our online catalogue featuring advanced user-friendly search functions.

Moreover, on our web site you can:
- ask our specialists for technical information and application advice
- contact our sales staff and ask them for estimates
- download manuals and other technical literature
- get access to quality and compliance certificates
- look at our latest sales literature
- ask for free catalogues and brochures
- … and much more.

By this newsletter, Cabur communicates also via e-mail its main innovations and commercial activities to all those who apply for it through the registration form.
In conclusion, Cabur web site (**www.cabur.eu**) is the ideal tool to get real time information and contacts with our company.



www.cabur.eu

Real time information on our company, products, and certifications

In order to be promptly updated about the availability of new technical and commercial documentation, please register on the site and join the newsletter service.

Quality and environment

ISO 9001 CSQ Certification

UNI EN-ISO 9001



Until recently, Cabur "Quality" was simply recognised through the appreciation of its customers. This has allowed the company to become a leader in Italy in the design, production and distribution of "terminal blocks for electrical panels" and, more recently, to extend its products offering to the segment of "electronic products" with recognised reliability levels in both Italian and foreign markets.
Obviously, this cannot be the result of improvisation, but of a constant organisation process begun back in 1985 with the definition and implementation of a Quality Assurance Programme based on ANSI N 45.2 (referred to the particularly severe nuclear environment) that has involved the entire structure of the Company and has made each function and worker responsible for quality standards.
Since 1995, CSQ (international institute for the certification of business quality systems) has certified the Quality system designed and adopted by Cabur.
The Quality system refers to the most complete and severe standard amongst UNI EN ISO 9000 series defining the requirements for Total Quality in Companies, that is ISO 9001, including the activities of Product Design, Development, Manufacturing and Customer Service.
After the issue of the new Edition of the Standard (ISO 9001.2000), the whole Quality System has been revised and renewed to be fully compliant with the new regulations. This compliance was confimed by CSQ with the new Certificate issued in 2003.

**THE QUALITY OF OUR PRODUCTS IS JUDGED BY OUR CUSTOMERS.
OUR QUALITY ASSURANCE SYSTEM IS CERTIFIED BY CSQ.**

ISO 14001 CSQ Certification

UNI EN-ISO 14001



In its continuous improvement process, CABUR has adopted an environmental management system since 2001, obtaining the international CSQ UNI EN 14001 recognition.
This goal represents a guarantee given of the respect Cabur has for the surrounding environment as well as a demonstration of the adoption of environmental safeguard rules and, additionally, a pledge for constant ecological improvement.
This kind of Certification is still quite uncommon in Italy; Cabur has nevertheless been able to achieve and add it to its corporate philosophy, which is always aimed at the anticipation, rather than to the passive adaptation, of those needs that are becoming more and more urgent and global. Environment is undoubtedly one of these issues and, anticipating many other companies, not only in Italy, Cabur firmly decided to adopt a system that monitors and prevents environmental risk, inherent to every stage of its manufacturing process.
Operational procedures and other paper documentation were unified and harmonised with the running Quality Assurance System and the manual, becoming of both Quality and Environmental Management, is now a complete reference point. The Quality Assurance and Environmental Management Department is at your complete disposal to provide any further information and/or clarification on the entire Quality / Environment System and Customer Service. Cabur can provide you with a copy of both CSQ and EQNET certificates, or with a copy of the Quality and Environmental Management manual.

Standards and directives

The 2002/95/CE Directive

The 2002/95/CE Directive, known as RoHS, sets limits to the use of specific dangerous materials in electric and electronic devices.
The Directive applies exclusively to devices included in the following categories, as listed in attachment 1A of 2002/96/EC Directive, also knows as WEEE, excluding categories 8 and 9.

1. Large appliances excluding fixed ones
2. Small appliances
3. IT and telecommunication appliances
4. Consumers' appliances
5. Lighting appliances
6. Electric and electronic tools, excluding large fixed industrial tools
7. Toys and devices for hobbies and sports
10. Vending machines

Cabur Products' compliance to RoHS Directive

Cabur products are generally deployed in electric panels for electric distribution and for industrial automation, which are excluded from the application field of the RoHS Directive, as components of "fixed industrial tools" and of "fixed installations".
Nevertheless, in consideration of the needs of those Customers deploying Cabur products into devices and appliances that need to be RoHS compliant, we have decided to review our production according to RoHS Directive requirements.
From the beginning of the year we have been disposing of non-compliant items, not only to reduce dangerous substances but to eliminate them completely from components in our production, with a Zero Tolerance mindset.
The small amount of our products which is currently non-RoHS compliant consists of dated stocked parts or of those few items that cannot be produced by different materials or process yet. In any case, as mentioned above, these items are deployed in product categories that are not listed in the RoHS Directive application field.
Our staff is available for further details both on our products and on the application of the RoHS Directive.
For more information, please click on www.cabur.eu

CE Marking

All products in this catalogue meet all EU applicable standards when the catalogue was printed. Therefore, all required CE markings are placed on the products and on all product related documents.

Do not hesitate to contact our staff for any further information and/or explanations on Reference Standards. Cabur Customer Service can provide you with certificates of compliance to Reference Standards, type approvals, and CE markings.



Cabur power house

Cabur continues to renew and expand the range of power supplies for the use in industrial automation of vehicles, overhaul of processes and plants by improving technologies and product services und by introducing new models.

Quality and safety: Cabur ist the first Italian company to obtain the special approval UL508C Industrial Control Equipment for devices used for the processes in the industrial automation, in conformity with the direction IEC950, EN60950 for Electric Safety and thus EC labelled.

Innovation and research: in 1997 Cabur was the first italian company to produce switching power supplies for Din guide with universal input 120-230 Vac, while others were offering power supplies with outperformed, heavy and cumbersome step-down network transformer.
With the new generation of products presented in this catalogue, Carbur aimed at obtaining the highest possible output, to reduce energy costs and working temperatures altough reducing the dimensions of power supplies. By increasing the output, the dissipated power is reduced and besides the duration of the power supplies it is possible to reduce the thermic stress of the components for more reliability and savings while running.
By using circuit tecnologies and innovative components, we obtained the highest output on the market with over 94% in three-phase. The new three-phase power supply of 20°/24V has an output of 94.5%, supplies 480 W and dissipates only 28W compared to more than 50 W dissipated in other products: 25 W saved, less heat and much more reliability.
The new generation of power supplies has all the characteristics of flexibility and functionality for use of the previous series:
– all models are adequate for a network voltage of 100-120-230-240 Vac with a range of 90…264 Vac/110…370 Vdc which makes it possible to use them all over the world
– new mono- two-phase power supplies of the CEW series with an extended range from 185…550 Vac in only one model
– the output voltage of the power supplies above 2 A can be adjusted between 24 to 27.5 Vdc
– all models supply a high output peak power (above 200% for 200 ms or 1 sec according to the model) to start the hardest loads and guarantee the selectivity of safety fusibles on the 24 V line
– there are the versions with alarm contact and diode in an “o-ring” available on the output for the redundant parallel connection and all standard power supplies can be connected in parallel to sum power.

EN61000-3-2: all the models are in conformity with the EN61000-3-2 regulations of emissions of harmonic currents in low-voltage power supply systems, in force since 01/01/2001. By using our power suppli systems, the user can declare the conformity of its own panel to the EMC directives without additional external Emi filters and without knowing points 1,2, 3,4 which may be unknown to the user or vary from one panel to the next or from client to client.

Thermic protection: all models are equipped with protections against overtemperature adjusted at 60° C with full load: in case of insufficient ventilation of the panel, continous overload and high ambient temperature you avoid a broken power supply because of overheating and you reduce the thermic stress. The area of functioning of ambient temperature ranges from 20 a + 50°C for all models with full load without derating (except other indications).

Protection from short-overload: the protection from short-circuit and overload is used to protect the power supply from break down through overcurrent and subsequent overheating above the limits supported by the components. This function can be designed by starting with different applicable needs, with practical results and very different costs. In an automated process, the conditions for use, the value and the nature of the load can vary a lot, they are not known to those who project power supplies and sometimes not even to the users. The power supply in automation must reconcile needs which are in contrast between each other: protect themselves from overcurrent, but at the same time try to feed loads which call for a high peak current, work at ambient temperatures of max 45° C according to the regulation and sometimes also above in critical ventilation situations and furthermore guarantee high reliability and acepptable costs.

Choice of tecnology for protection of power supplies in automated processes:
– the overcurrent protection must support the high peak currents required by loads such as filament lamps, capacitive loads (dc/dc converter and filter condensators when switching on are almost a short-circuit for some ms) or inductive loads (engines in dc, electromagnets, etc.) at the peak they require currents above 5-10 times their nominal power and furthermore all these loads must sometimes be started synchronously.
– high peak power must be supplied for a sufficient time in oder to “start” the loads, for at least about ten ms or even up to 1-2 s according to the power of the power supply
– if the power supply has a high power and supplies a number of power outlets protected by fusibiles, the circuit protection from the short circuit/overload must guarantee the selectivity of the operation of the protections from overcurrent by burning the fusible of the broken load before its internal protection circuit intervenes by switching off the output or reducing the voltage and output power.
– the ambient temperature to which the project must refer to in order to measure the components, the admitted overcurrent and its duration must be equal or superior to 45°C, established in the directives regarding electric panels; the ambient temperature is a basic reference parameter because besides on supplied power and output, the heating of components depends also on ambient temperature.

To protect the power supply you can use various tecniques:
– switch off the output as soon as possible: it is safe and costs less but it does not enable you to start heavy loads or to burn fuse on the 24 Vdc line
– constant power protection: if the admitted overcurrent is sufficiently high it enables you to start heavy loads, but if the overload lasts longer the power supply is always working with overload
– hiccup protection: combines the two tecniques listed above and admits over +200% of overcurrent for a relatively long time and then it switches off the output for a even longer break; the result is that you obtain the necessary peak of power when heavy loads are coming in with less heating of the components and during the break it cools down instead of being in continous overload such as it is the case for protections with constant power.

The protection with Hiccup tecnology with overcurrent output admitted up to +200% of the nominal power for a time duration between 200ms to over 1s (according to the power of the model) which has shown to be effective and reliable in practice for many processes in the field of automation.

Environment and RoHs conformity: as our products are not included in the Rohs WEEE directive, Cabur has adapted its own products. Cabur is one of the first italian companies to obtain the International Environmental Certificate UNI EN ISO 14001, certified by CSQ on ecologically compatible treatment of all materials necessary during the working cycle in order to produce its own products.

Filtered power supplies: a few components for a simple, reliable and economic solution in order to supply engines in dc or loads able to work without problems also with reciprocating wastage relatively high in output (ripple) and variations of output voltage equal to ±10%, due to the variations of loads and variations of network. The filtered power supplies supply continous non- stabilized voltage and if combined with underdimensioned transformers, in cases where the load calls for high power with a simultaneous decrease of the network voltage, the output voltage can decrease remarkably and cause a disfunctioning of the supplied devices. They are not recommended in case of a network voltage which cannot guarantee major stability or a voltage at least equal to ±10% of the nominal voltage provided by the regulations.

Linear power supplies: Cabur produces linear power supplies with small power and high performace, reliabilty and an acceptable price. The linear power supplies make only a small part of the market and are offered as standard products, even though the performance of the high quality switching tecnology permits to realize compact power supplies with a very superior performance.

“Custom” power supplies: Cabur plans and produces “custom” power supplies on request of the client to be able to meet the requirements of the directives and the high demands. Furthermore our lab offers a tecnical documentation and the measures which prove the conformity of the products with the directives on Electric Safety and Eletromagnetic compatibility, besides the necessary tecnical support to define the characteristics of the product on the basis of the client’s needs and our own experience.

Cabur offers three different technologies with the right performance and price

	Switching	Linear	Filtered
Efficiency	>87%	< 50%	80%
Energy dissipated	14%	> 50%	20%
Mains var. tolerance	90-264 Vac	207-257 Vac	218-240 Vac
Load var. stability	> ± 50 mV	> ± 200 mV	> ± 2.5 V
Ripple	@ 100 mV_{pp}	@ 100 mV_{pp}	≥ 2 V_{pp}
Weight	reduced	high	high
Dimensions	small	high	high
Cost	higher	higher	low
EMI	below standard limits	low	low

Which power supply unit to use

Switching
- with highly variable line voltages (from 90 to 246 Vac)
- with electronic loads
- when high Vdc stability is required
- to reduce energy consumption, dissipated heat, weight, dimensions

Linear
- with line voltages stable within +10%
- with electronic loads
- for applications requiring very low electromagnetic emissions

Filtered
- with very stable line voltages within +5%
- with loads having high tolerance to high ripple
- with loads having high tolerance to variations of 25 Vdc
- to reduce costs

GENERAL NOTES

All technical data indicated in this catalogue are "typical", and are measured at 25°C, rated input voltage, rated output voltage and current, after 10 min warm up; ripple is measured at rated input and output, 20 MHz, probe on 100 nF.

Length of insulation stripping: 9 mm, model with fixed terminals; 6 mm, model with pluggable terminals.

Cooling: distance the power supply units 2 cm (1") from adjacent devices and at least 5 cm (2") from other equipment on the upper and lower sides.
We recommend to mount the power supply on horinzontal DIN rails.

Assembly: the power supply units are equipped with an EN 50.022 guide fitting. For a better stability we recommend attaching the guide to the panel, also in the point where the power supply unit is to be mounted.

DC input supply voltage: it is possible to supply the input of 90...264 Vac wide range models with 100....370 Vdc following these indications: reduce output current 25%, min. input DC voltage 100 Vdc, respect input polarity indicated on instruction sheet. Models with double voltage input cannot be supplied with DC voltage lower than 220 Vdc.

Redundant parallel and parallel connection: models with the letter P in their type and Cat. No. are supplied as standard with the output protection diode for redundant parallel and parallel connection.
We recommend adjusting to the same voltage (tolerance + 50 mV) the outputs of all the power supply units, applying the same calibration load, before connecting them in parallel and using power supply units of the same model.
If two power supply units not provided with an internal diode (standard versions) have to be connected in parallel, the connection shown in Figure 1 has to be applied out.
The CSDB module allows to connect in redundant parallel power supplies with 12, 15, 24 and 48 Vdc output voltages up to 15 A total max.




figure 1

Connection in series of two power supply units: possible by connecting a diode in anti-parallel to the output of each power supply unit, dimensioned to withstand the max. current of the power supply unit (see Figure 2).

Dual voltage output power supplies: if a specific model with dual output is not available, dual output voltage can de achieved by connecting the outputs of two power supply unit as in Figure 3.

Power good signal available on "P" models: failure signal is provided by a 1A /30 Vdc SPST or SPDT contact (depending on model) of an internal relay: contact is closed when functions are all OK, contact is opened in case of AC line shut off, overload or short circuit on 24 Vdc line or power supply failure.




figure 2




figure 3

NOTES FOR POWER SUPPLY UNITS WITH TRANSFORMER SECONDARY INPUT

Isolation: this series of power supply units is not isolated.

Type of use: they are suitable for use in PELV (one pole of the Protective Extra Low Voltage earthed) and SELV (Safety Extra Low Voltage, no pole earthed). The transformer used must have double or reinforced isolation in accordance with CEI 14.6 / EN 60742.
In the case of use in PELV circuits, only earth one pole of the 24 Vdc of the power supply unit. In the case of use in SELV circuits, do not earth the input earth terminal.

Do not connect to the negative pole of the power supply output (- Vdc) together with one pole of the AC secondary source; this condition will damage the power supply; the secondary output vltage of the transformer must be kept isolated from ground and only the negative pole of the power supply output can be grounded for safety.




figure 4




figure 5

Power supply quick selection table

These tables allow you to quickly select only the items, then check if all product's technical data meet your application requirements.

Switching power supply - Cool Power series

Output voltage	Output current	Input voltage	Notes	Type	Cat. No.	Page
10…15 Vdc	1.5…1 A	90…264 Vac / 100...320 Vdc	(1) (9) (11)	CSF30B	XCSF30B	22
12…15 Vdc	6 A	90…264 Vac / 100...370 Vdc	(1) (8) (9) (11)	CSF85B	XCSF85B	24
12…15 Vdc	7 A	90…264 Vac / 100...370 Vdc	(1) (8) (9) (11)	CSF120B	XCSF120B	26
12…15 Vdc	16 A	120 Vac / 230 Vac	(2) (8) (9) (11)	CSF240B	XCSF240B	28
24 Vdc	1.2 A	90…264 Vac / 100...320 Vdc	(1) (11)	CSF30C	XCSF30C	22
24 Vdc	3.5 A	90…264 Vac / 100...370 Vdc	(1) (8) (11)	CSF85C	XCSF85C	24
24 Vdc	3.5 A	90…264 Vac / 100...370 Vdc	(1) (7) (8) (11)	CSF85CP	XCSF85CP	24
24 Vdc	5 A	90…264 Vac / 100...370 Vdc	(1) (8) (11)	CSF565	XCSF565	30
24 Vdc	5 A	90…264 Vac / 100...370 Vdc	(1) (8) (11)	CSF120C	XCSF120C	26
24 Vdc	5 A	90…264 Vac / 100...370 Vdc	(1) (7) (8) (11)	CSF120CP	XCSF120CP	26
24 Vdc	10 A	120 Vac / 230 Vac	(2) (8) (11)	CSF240C	XCSF240C	28
24 Vdc	10 A	120 Vac / 230 Vac	(2) (7) (8) (11)	CSF240CP	XCSF240CP	28
24 Vdc	20 A	120 Vac / 230 Vac	(2) (8) (11)	CSF500C	XCSF500C	29
48 Vdc	2.5 A	90…264 Vac / 100...370 Vdc	(1) (8) (11)	CSF120D	XCSF120D	26
48 Vdc	2.5 A	90…264 Vac / 100...370 Vdc	(1) (7) (8) (11)	CSF120DP	XCSF120DP	26
48 Vdc	5 A	120 Vac / 230 Vac	(2) (8) (11)	CSF240D	XCSF240D	28
48 Vdc	10 A	120 Vac / 230 Vac	(2) (8) (11)	CSF500D	XCSF500D	29

Single-phase switching power supply - Easy Power series

Output voltage	Output current	Input voltage	Notes	Type	Cat. No.	Page
24 Vdc	3.5 A	90…264 Vac / 100...370 Vdc	(1) (11)	CSP85C	XCSP85C	32
24 Vdc	5 A	90…264 Vac / 100...370 Vdc	(1) (11)	CSP120C	XCSP120C	33
24 Vdc	10 A	120 Vac / 230 Vac	(2) (11)	CSP240C	XCSP240C	34

Single-phase switching power supply - Domotic Power series

Output voltage	Output current	Input voltage	Notes	Type	Cat. No.	Page
5…15 Vdc	3...1.5 A	90…264 Vac / 100...370 Vdc	(1) (9) (11)	CSD30E	XCSD30E	18
±12…±15	0.6 A	90…264 Vac / 100...370 Vdc	(1) (9) (11)	CSD30F	XCSD30F	18
12 Vdc	1.2 A	90…264 Vac / 100...370 Vdc	(1) (11)	CSD15B	XCSD15B	17
12…15 Vdc	3.5…3 A	90…264 Vac / 100...370 Vdc	(1) (9) (11)	CSD50B	XCSD50B	19
24 Vdc	0.6 A	90…264 Vac / 100...370 Vdc	(1) (11)	CSD15C	XCSD15C	17
24 Vdc	1.2 A	90…264 Vac / 100...370 Vdc	(1) (11)	CSD30C	XCSD30C	18
24 Vdc	2 A	90…264 Vac / 100...370 Vdc	(1) (11)	CSD50C	XCSD50C	19
24 Vdc	3 A	90…264 Vac / 100...370 Vdc	(1) (11)	CSD70C	XCSD70C	20

Single and two-phase switching power supply - Universal Power series

Output voltage	Output current	Input voltage	Notes	Type	Cat. No.	Page
12…15 Vdc	8…7 A	185…550 Vac	(3) (9) (11)	CSW120B	XCSW120B	36
12…15 Vdc	16…15 A	185...550 Vac	(3) (8) (9) (11)	CSW240B	XCSW240B	37
24 Vdc	5 A	185...550 Vac	(3) (11)	CSW120C	XCSW120C	36
24 Vdc	10 A	185...550 Vac	(3) (8) (11)	CSW240C	XCSW240C	37
48 Vdc	5 A	185...550 Vac	(3) (8) (11)	CSW240D	XCSW240D	37

Note

(1) wide range single-phase input
(2) double range single-phase input
(3) single-phase and two-phase input
(4) two-phase input
(5) three-phase input
(6) input from a secondary of a transformer
(7) with Oring diode for redundant parallel
(8) with failure contact (power good)
(9) with adjustable output
(10) DC/DC converter
(11) UL508C approved

Power supply quick selection table

These tables allow you to quickly select only the items, then check if all product's technical data meet your application requirements.

Two and three-phase switching power supply - Triple Power series

Output voltage	Output current	Input voltage	Notes	Type	Cat. No.	Page
24 Vdc	3.5 A	340…550 Vac / 507…700 Vdc	(4) (9) (11)	CSB85C	XCSB85C	39
24 Vdc	6 A	340…550 Vac / 507…700 Vdc	(4) (11)	CSB150C	XCSB150C	40
24 Vdc	10 A	340…550 Vac / 507…700 Vdc	(5) (8) (11)	CSG240C	XCSG240C	42
24 Vdc	20 A	340…550 Vac / 507…700 Vdc	(5) (8) (11)	CSG500C	XCSG500C	43
24 Vdc	30 A	340…550 Vac / 507…700 Vdc	(5) (8) (11)	CSG720C	XCSG720C	44
24 Vdc	42 A	340…550 Vac / 507…700 Vdc	(5) (11)	CSG42	XCSG42	45
24 Vdc	40 A	340…550 Vac / 507…700 Vdc	(5) (8) (11)	CSG960C	XCSG960C	46
24 Vdc	100 A	340…550 Vac / 507…700 Vdc	(5) (11)	CSG2400C	XCSG2400C	47
48 Vdc	10 A	340…550 Vac / 507…700 Vdc	(5) (8) (11)	CSG500D	XCSG500D	43
48 Vdc	15 A	340…550 Vac / 507…700 Vdc	(5) (8) (11)	CSG720D	XCSG720D	44
48 Vdc	20 A	340…550 Vac / 507…700 Vdc	(5) (8) (11)	CSG960D	XCSG960D	46
48 Vdc	50 A	340…550 Vac / 507…700 Vdc	(5) (11)	CSG2400D	XCSG2400D	47

Switching power supply out 24 Vdc in IP65 case

Output voltage	Output current	Input tipology	Input voltage	Notes	Type	Cat. No.	Page
24 Vdc	5 A	Single-phase	90…264 Vac / 100...370 Vdc	(1) (8)	CSF565	XCSF565	30

Switching power supply with input from transformer and out 24 Vdc

Output voltage	Output current	Input tipology	Input voltage	Notes	Type	Cat. No.	Page
24 Vdc	3 A	From transformer	24 Vac	(6)	CSE3	XCSE3	50
24 Vdc	5 A	From transformer	24 Vac	(6)	CSE5	XCSE5	50
24 Vdc	10 A	From transformer	24 Vac	(6)	CSE10	XCSE10	51

Linear power supply with adjustable output 1.2...24 Vdc

Output voltage	Output current	Input tipology	Input voltage	Notes	Type	Cat. No.	Page
1.2…24 Vdc	1.5 A	From transformer	9…26 Vac	(6) (9)	CL1R	XCL1R	52
1.2…24 Vdc	5 A	From transformer	9…26 Vac	(6) (9)	CL5R	XCL5R	52

Filtered power supply with not stabilised output

Output voltage	Output current	Input tipology	Input voltage	Notes	Type	Cat. No.	Page
12…24 Vdc	1 A	From transformer	9…20 Vac	(6)	AR1	XAR1	53
12…24 Vdc	2 A	From transformer	9…20 Vac	(6)	AR2	XAR2	53
12…24 Vdc	4 A	From transformer	9…20 Vac	(6)	AR4	XAR4	54
12…24 Vdc	6 A	From transformer	9…20 Vac	(6)	AR6	XAR6	54

Note

(1) wide range single-phase input
(2) double range single-phase input
(3) single-phase and two-phase input
(4) two-phase input
(5) three-phase input
(6) input from a secondary of a transformer
(7) with Oring diode for redundant parallel
(8) with failure contact (power good)
(9) with adjustable output
(10) DC/DC converter
(11) UL508C approved

Modular switching power supply CSD series

DOMOTIC POWER

Domotic Power series
It includes single-phase switching supplies with up to 75W for applications in civil and industrial automation.
Its housing is designed adopting the sizes of DIN standard modular products for units integrated into modular control panels and may also be used in standard switchboards or small-depth panels.

Suggested uses
- Applications in industrial automation
- Applications in civil automation
- General applications in systems fit into small remote panels

Main features
- The 90…264 Vac and 110…370 Vdc input makes them suitable for use on all power supply lines.
- These power supplies are Insulation Class 2, thus they don't require grounding, which reduces costs and times during installation into remote panels, surveillance and monitoring systems.
- Their high efficiency reduces energy consumption and working temperature and allows their use in small panels.
- Their backup power allows the supply of continuous current at least +25% above the rated value up to 45°C without exceeding standard temperature limits and ensuring safety and reliability.
- Dimensioned power supply and surge protection supplying breakaway starting currents 150% above the rated value required by heavy loads.
- Thermal protection prevents faults caused by prolonged overload at high ambient temperatures.
- Their internal components' high efficiency and excellent ventilation offer small dimensions and IP20 protection against accidental contacts in compliance with IEC529.








Single-phase switching power supply 120-230 Vac output power 15 W


- Single-phase input 90…264 Vac and DC 100…370 Vdc
- Short circuit, overload, over temperature, input overvoltage protections
- Isolation Class 2, no grounding needed
- Compact dimensions
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the DIN rail clamp.
(2) Over 50°C (122°F) apply a derating: C version: -0.015 A/°C; B version: -0.03 A/°C.
(3) Overload and short circuit current depends on the total line resistance

BLOCK DIAGRAM



VERSIONS	Cod. XCSD15C	Cod. XCSD15B
Output 24 Vdc 0.6 A	**CSD15C**	
Output 24 Vdc 0.6 A redundant version	–	
Output 12 Vdc 1.2 A		**CSD15B**
Output 48 Vdc 0.3 A		–

INPUT TECHNICAL DATA	
Input rated voltage	**120–230 Vac** (range 90…264 Vac / 100…370 Vdc)
Frequency	47...63 Hz
Current @ nominal Iout (Uin 120 /230 Vac)	0.3 A / 0.16 A ± 10%
Inrush peak current	< 5 A
Power factor	> 0.6
Internal protection fuse	T 1 A replaceable
External protection on AC line	circuit breaker: 2 A - C characteristic - fuse: T 2 A


OUTPUT TECHNICAL DATA		
Output rated voltage	**24 Vdc**	**12 Vdc** ± 0.5 Vdc
Output adjustable range	—	—
Continuous current	**0.6 A** @ 50°C (2)	**1.2 A** @ 50°C (2)
Overload limit	1.08 A (3)	2.16 A (3)
Short circuit peak current	—	—
Load regulation	< 1%	< 1%
Ripple @ nominal ratings	≤ 30 mVpp	≤ 30 mVpp
Hold up time @ In (Uin 120 / 230 Vac)	>12 ms / >20 ms	>12 ms / >20 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection	
Status display	"DC OK" green LED	
Alarm contact threshold	–	–
Parallel connection	possible	possible
Redundant parallel connection	possible with external ORing diode	possible with external ORing diode

GENERAL TECHNICAL DATA		
Efficiency (Uin 120 / 230 Vac)	>85% / >87%	>85% / >87%
Dissipated power (Uin 120 / 230 Vac)	19 W / 13 W	21 W / 15 W
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (2)	
Input/output isolation	3 KVac / 60 s SELV output	
Input/ground isolation	class 2 without PE connection	
Output/ground isolation	class 2 without PE connection	
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508	
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11	
MTBF @ 25°C @ nominal ratings	>750'000 h acc. to SN 29500 / >250'000 h acc. to MIL Std. HDBK 217F	
Overvoltage category/Pollution degree	II / 2	
Protection degree	IP 20 IEC 529, EN60529	
Connection terminal	2.5 mm^2 fixed screw type	
Housing material	UL94V-0 plastic material	
Approx. weight	130 g (5.12 oz)	
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components	

MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—

Single-phase switching power supply 120-230 Vac output power 30 W


- Single-phase input 90…264 Vac and DC 100…370 Vdc
- Short circuit, overload, over temperature, input overvoltage protections
- Isolation Class 2, no grounding needed
- Compact dimensions
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the DIN rail clamp.
(2) Over 50°C (122°F) apply a derating: C and F versions: -0.03 A/°C; E version: -0.08…-0.04 A/°C.
(3) Overload and short circuit current depends on the total line resistance.
(4) Output current depends on the output voltage: 3.3A @ 5Vdc, 2A @ 9Vdc, 2.2A @ 12Vdc, 1.5A @ 15Vdc.


BLOCK DIAGRAM



VERSIONS	Cod. XCSD30C		Cod. XCSD30E	Cod. XCSD30F
Output 24 Vdc 1.2 A	**CSD30C**			
Output 24 Vdc 1.2 A redundant version		**–**		
Output 5…15 Vdc 3.3…1.5 A			**CSD30E**	
Output ±12...±15 Vdc 0.6 A				**CSD30F**
INPUT TECHNICAL DATA				
Input rated voltage	**120–230 Vac** (range 90…264 Vac / 100…370 Vdc)			
Frequency	47...63 Hz			
Current @ nominal Iout (Uin 120 /230 Vac)	0.55 A / 0.28 A ± 10%		0.45 A / 0.25 A ± 10%	0.4 A / 0.2 A ± 10%
Inrush peak current	< 13 A		< 13 A	< 13 A
Power factor	> 0.6			
Internal protection fuse	T 2 A replaceable			
External protection on AC line	circuit breaker: 3 A - C characteristic - fuse: T 3.15 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**		**5…15 Vdc**	**±12...±15 Vdc**
Output adjustable range	—		5…15 Vdc	±12...±15 Vdc
Continuous current	**1.2 A** @ 50°C (2)		**3.3…1.5 A** @ 50°C (2)(4)	**2 x 0.6 A** @ 50°C (2)
Overload limit	1.6 (3)		4 A (3)	>2 x 0.8 A (3)
Short circuit peak current	—		—	—
Load regulation	< 1%		< 1%	< 1%
Ripple @ nominal ratings	≤ 50 mVpp		≤ 50 mVpp	≤ 50 mVpp
Hold up time @ In (Uin 120 / 230 Vac)	>30 ms / >60 ms		>50 ms / >100 ms	>50 ms / >100 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	"DC OK" green LED			
Alarm contact threshold	–	–	–	–
Parallel connection	possible		possible	possible
Redundant parallel connection	possible with external ORing diode		possible with external ORing diode	possible with external ORing diode
GENERAL TECHNICAL DATA				
Efficiency (Uin 120 / 230 Vac)	>85% / >87%		>87% / >89%	>87% / >89%
Dissipated power (Uin 120 / 230 Vac)	5.2 W / 4.5 W		4.5 W / 3.7 W	4.5 W / 3.7 W
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (2)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	class 2 without PE connection			
Output/ground isolation	class 2 without PE connection			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>750'000 h acc. to SN 29500 / >250'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	2.5 mm² fixed screw type			
Housing material	UL94V-0 plastic material			
Approx. weight	200 g (7.06 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

Single-phase switching power supply 120-230 Vac output power 50 W


- Single-phase input 90…264 Vac and DC 100…370 Vdc
- Short circuit, overload, over temperature, input overvoltage protections
- Isolation Class 2, no grounding needed
- Compact dimensions
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the DIN rail clamp.
(2) With 100...127 Vdc input voltage, constant output power and Ta>45°C, the output current must be derated by 25%
(3) Over 50°C (122°F) apply a derating: C version: -0.06 A/°C; B version: -0.085 A/°C.
(4) Overload and short circuit current depends on the total line resistance.


BLOCK DIAGRAM



VERSIONS	Cod. XCSD50C		Cod. XCSD50B	
Output 24 Vdc 2.2 A	**CSD50C**			
Output 24 Vdc 2.2 A redundant version		–		
Output 12…15 Vdc 3.5...3 A			**CSD50B**	
Output 48 Vdc 1.1 A				–
INPUT TECHNICAL DATA				
Input rated voltage	**120–230 Vac** (range 90…264 Vac / 100…370 Vdc) (2)			
Frequency	47...63 Hz			
Current @ nominal Iout (Uin 120 /230 Vac)	0.9 A / 0.5 A ± 10%			
Inrush peak current	< 15 A			
Power factor	> 0.6			
Internal protection fuse	T 2 A replaceable			
External protection on AC line	circuit breaker: 3 A - C characteristic - fuse: T 3.15 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**		**12…15 Vdc**	
Output adjustable range	–		12…15 Vdc	
Continuous current	**2.2 A** @ 50°C (3)		**3.5…3 A** @ 50°C (3)	
Overload limit	3 A (4)		4.37…3.75 A (4)	
Short circuit peak current	—		—	
Load regulation	< 1%		< 1%	
Ripple @ nominal ratings	≤ 50 mVpp		≤ 50 mVpp	
Hold up time @ In (Uin 120 / 230 Vac)	>20 ms / >40 ms		>20 ms / >40 ms	
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	"DC OK" green LED			
Alarm contact threshold	–		–	
Parallel connection	possible		possible	
Redundant parallel connection	possible with external ORing diode		possible with external ORing diode	
GENERAL TECHNICAL DATA				
Efficiency (Uin 120 / 230 Vac)	>88% / >90%		>88% / >90%	
Dissipated power (Uin 120 / 230 Vac)	6.8 W / 5.5 W		6.8 W / 5.5 W	
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	class 2 without PE connection			
Output/ground isolation	class 2 without PE connection			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>750'000 h acc. to SN 29500 / >250'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	2.5 mm² fixed screw type			
Housing material	UL94V-0 plastic material			
Approx. weight	200 g (7.06 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

Single-phase switching power supply 120-230 Vac output power 70 W


- Single-phase input 90…264 Vac and DC 100…370 Vdc
- Short circuit, overload, over temperature, input overvoltage protections
- Isolation Class 2, no grounding needed
- Compact dimensions
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the DIN rail clamp.
(2) With 100...127 Vdc input voltage, constant output power and Ta>45°C, the output current must be derated by 25%.
(3) Over 50°C (122°F) apply a derating: C version: -0.15 A/°C.
(4) Overload and short circuit current depends on the total line resistance.

BLOCK DIAGRAM




VERSIONS	Cod. XCSD70C			
Output 24 Vdc 3 A	**CSD70C**			
Output 24 Vdc 3 A redundant version		–		
Output 12…15 Vdc 5…4 A			–	
Output 48 Vdc 1.5 A				–
INPUT TECHNICAL DATA				
Input rated voltage	**120–230 Vac** (range 90…264 Vac / 100…370 Vdc) (2)			
Frequency	47...63 Hz			
Current @ nominal Iout (Uin 120 /230 Vac)	1.25 A / 0.8 A ± 10%			
Inrush peak current	< 15 A			
Power factor	> 0.6			
Internal protection fuse	T 2 A not replaceable			
External protection on AC line	circuit breaker: 4 A C characteristic - fuse: T 3.15 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**			
Output adjustable range	24...27.5 Vdc			
Continuous current	**3 A** @ 55°C (3)			
Overload limit	4 A (4)			
Short circuit peak current	—			
Load regulation	< 1%			
Ripple @ nominal ratings	≤ 60 mVpp			
Hold up time @ In (Uin 120 / 230 Vac)	>15 ms / >30 ms			
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	"DC OK" green LED			
Alarm contact threshold	–			
Parallel connection	possible			
Redundant parallel connection	possible with external ORing diode			
GENERAL TECHNICAL DATA				
Efficiency (Uin 120 / 230 Vac)	>87% / >89%			
Dissipated power (Uin 120 / 230 Vac)	10.4 W / 8.6 W			
Operating temperature range	–20...+60°C, with derating over 55°C (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	class 2 without PE connection			
Output/ground isolation	class 2 without PE connection			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>750'000 h acc. to SN 29500 / >250'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	2.5 mm² fixed screw type			
Housing material	UL94V-0 plastic material			
Approx. weight	250 g (8.82 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

Switching power supply CSF series

COOL POWER

Cool Power series
It includes DIN-rail single-phase switching power supplies, specifically designed for applications in industrial automation and process control switchboards and panels. They can supply 50% above the rated voltage for more than 5 sec. keeping the output voltage constant and the alarm contact controlled by a voltage threshold switching over when the voltage drops 90% below the rated value. **Thanks to these features and to the numerous international certifications, this series of power supplies allows engineers to meet with all the requirements of the new EN 60204-1 Machinery Directive.**



Suggested uses
- Applications in industrial automation requiring high levels of efficiency and reliability
- Applications requiring selectivity of surge protection devices on DC lines.
- Application in machinery automation requiring high levels of reliability in terms of control and safety voltage
- Applications in process control
- Heavy duty uses
- Applications in civil automation

Main features
- The 90…264 Vac and 110…370 Vdc input makes them suitable for use on all power supply lines.
- Threshold alarm contact warning when the voltage drops 90% below the rated value.
- Versions with integrated Oring diode for redundant parallel connections, avoiding the use of external devices and reducing dimensions and installation costs.
- Their high efficiency reduces energy consumption and components' operating temperature allowing their use in small panels and under severe ambient conditions.
- Their backup power allows the supply of current and voltage at least +50% above the rated value at 45°C for a few minutes without exceeding standard temperature limits and ensuring safety and reliability.
- The output voltage may be adjusted and the output is protected against the input of surges coming from the DC line and caused by inductive loads.
- The output is equipped with double electronic protection devices preventing dangerous voltages which may damage powered components in the event of internal faults.
- Thermal protection prevents faults in the event of prolonged overloads at high ambient temperatures.
- Their design ensures excellent ventilation to internal components, small dimensions and IP20 protection against accidental contacts in compliance with IEC529.
- Thanks to their high efficiency and excellent ventilation, they are the smallest devices available on the market.








Single-phase switching power supply 120-230 Vac output power 30 W


- Single-phase input 90…264 Vac and DC 100…370 Vdc
- Short circuit, overload, over temperature protection
- Isolation Class 2, no grounding needed
- Compact dimensions
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the DIN rail clamp.
(1) Version available upon request; for information call our sales department, local agent or representative
(2) With 100...127 Vdc input voltage, constant output power and Ta>45°C, the output current must be derated by 25%
(3) Over 50°C (122°F) apply a derating: C version: -0.03 A/°C; B version: -0.038 A/°C; F version: -0.013 A/°C
(4) Overload and short circuit current depends on the total line resistance.

BLOCK DIAGRAM



VERSIONS	Cod. XCSF30C	Cod. XCSF30B	Cod. XCSF30F
Output 24 Vdc 1.2 A	**CSF30C**		
Output 10…15 Vdc 1.5 A		**CSF30B**	
Output ±12...±15 Vdc 0.5 A			**CSF30F (1)**

INPUT TECHNICAL DATA			
Input rated voltage	**120–230 Vac** (range 90…264 Vac / 100…370 Vdc) (2)		
Frequency	47...63 Hz		
Current @ nominal Iout (Uin 120 /230 Vac)	0.55 A / 0.3 A ± 10%	0.35 A / 0.2 A ± 10%	
Inrush peak current	< 25 A		
Power factor	> 0.60		
Internal protection fuse	T 1,25 A not replaceable		
External protection on AC line	circuit breaker: 2 A - C characteristic - fuse: T 2 A		
OUTPUT TECHNICAL DATA			
Output rated voltage	**24 Vdc ± 10%**	**12 – 15 Vdc**	**±12 ±15 Vdc**
Output adjustable range	—	10…15 Vdc	±12…±15 Vdc
Continuous current	**1.2 A** @ 50°C (3)	**1.5…1 A** @ 50°C (3)	**0.5 A** @ 50°C (3)
Overload limit	1.4 A (4)	1.7…1.2 A (4)	0.8…0.6 A (4)
Short circuit peak current	—	—	—
Load regulation	< 1%		
Ripple @ nominal ratings	≤ 50 mVpp		
Hold up time @ In (Uin 120 / 230 Vac)	>10 ms / >30 ms		
Overload / short circuit protections	hiccup at the overload limit with auto reset		
Status display	"DC OK" green LED		
Alarm contact threshold	—		
Parallel connection	possible		
Redundant parallel connection	possible with external ORing diode		
GENERAL TECHNICAL DATA			
Efficiency (Uin 120 / 230 Vac)	>86% / >87%		
Dissipated power (Uin 120 / 230 Vac)	4.7 W / 4.3 W		
Operating temperature range	–20...+60°C, with derating over 50°C (3)		
Input/output isolation	3 KVac / 60 s SELV output		
Input/ground isolation	class 2 without PE connection		
Output/ground isolation	class 2 without PE connection		
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508, UL60950		
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11		
MTBF @ 25°C @ nominal ratings	>750'000 h acc. to SN 29500 / >250'000 h acc. to MIL Std. HDBK 217F		
Overvoltage category/Pollution degree	II / 2		
Protection degree	IP 20 IEC 529, EN60529		
Connection terminal	2.5 mm² fixed screw type		
Housing material	UL94V-0 plastic material		
Approx. weight	140 g (4.94 oz)		
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components		
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**		
Mounting rail type according to IEC60715/G32	—		

Single-phase switching power supply 120-230 Vac output power 40…72 W

- Single-phase input 90…264 Vac and DC 100…370 Vdc
- Short circuit, overload, over temperature, input and output overvoltage protections
- High outrush current to guarantee downstream overcurrent protections selectivity and to start-up heavy loads
- Compact dimensions
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the terminal blocks and the DIN clamp.
(2) With 100...127 Vdc input voltage, constant output power and Ta>45°C, the output current must be derated by 25%
(3) Over 45°C (113°F) apply derating: CSF3-CSF3P: -0.07 A/°C; B version: -0.1 A/°C; versione A: -0.13 A/°C
(4) Overload and short circuit current depends on the total line resistance.


BLOCK DIAGRAM

Item available till sell-out, will be replaced by **CSF85** series…

VERSIONS	Cod. XCSF3	Cod. XCSF3P	Cod. XCSF3B	Cod. XCSF3A
Output 24 Vdc 4 A	**CSF3**			
Output 24 Vdc 4 A redundant version		**CSF3P**		
Output 12…15 Vdc 6 A			**CSF3B**	
Output 5 Vdc 8 A				**CSF3A**
INPUT TECHNICAL DATA				
Input rated voltage	**120–230 Vac** (range 90…264 Vac / 100…370 Vdc) (2)			
Frequency	47...63 Hz			
Current @ nominal Iout (Uin 120 /230 Vac)	1.3A / 0.7 A ± 10%			
Inrush peak current	< 20 A			
Power factor	> 0.7			
Internal protection fuse	T 2 A replaceable			
External protection on AC line	circuit breaker: 4 A C characteristic - fuse: T 4 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**		**12…15 Vdc**	**5 Vdc**
Output adjustable range	23...27.5 Vdc		12…15 Vdc	—
Continuous current	**4 A** @ 45°C (3)		**6 A** @ 45°C (3)	**8 A** @ 45°C (3)
Overload limit	6 A (4)		8.5 A (4)	10.5 A (4)
Short circuit peak current	—		—	—
Load regulation	< 1%		< 1%	< 1%
Ripple @ nominal ratings	≤ 40 mVpp		≤ 40 mVpp	≤ 40 mVpp
Hold up time @ In (Uin 120 / 230 Vac)	>10 ms / >20 ms		>10 ms / >20 ms	>10 ms / >20 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	"DC OK" green LED / "DC OK" alarm contact			
Alarm contact threshold	–		–	–
Parallel connection	possible		possible	possible
Redundant parallel connection	possible with external ORing diode	factory provided with internal ORing diode	possible with external ORing diode	
GENERAL TECHNICAL DATA				
Efficiency (Uin 120 / 230 Vac)	>86% / >90%		>86% / >90%	>83% / >86%
Dissipated power (Uin 120 / 230 Vac)	12 W / 8 W		12 W / 8 W	8 W / 7 W
Operating temperature range	–20...+60°C, with derating 45°C / over temperature protection (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	1.5 KVac / 60 s			
Output/ground isolation	0.5 KVac / 60 s			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	2.5 mm² pluggable screw type			
Housing material	aluminium and stainless steel			
Approx. weight	515 g (18.18 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

Single-phase switching power supply 120-230 Vac output power 85 W


- Single-phase input 90…264 Vac and DC 100…370 Vdc
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- High outrush current to guarantee downstream overcurrent protections selectivity and to start-up heavy loads
- Failure contact for Uout -10%
- Compact dimensions
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the DIN rail clamp.
(2) With 100...127 Vdc input voltage, constant output power and Ta>45°C, the output current must be derated by 25%
(3) Over 45°C (113°F) apply derating: CSF3-CSF3P: -0.07 A/°C; B version: -0.1 A/°C; versione A: -0.13 A/°C
(4) Overload and short circuit current depends on the total line resistance.

BLOCK DIAGRAM



VERSIONS	Cod. XCSF85C	Cod. XCSF85CP	Cod. XCSF85B	
Output 24 Vdc 3.5 A	**CSF85C**			
Output 24 Vdc 3.5 A redundant version		**CSF85CP**		
Output 12…15 Vdc 6 A			**CSF85B**	
Output 48 Vdc 1.8 A				–

INPUT TECHNICAL DATA				
Input rated voltage	**120–230 Vac** (range 90…264 Vac / 100…370 Vdc) (2)			
Frequency	47...63 Hz			
Current @ nominal Iout (Uin 120 /230 Vac)	1.6 A / 0.9 A ± 10%			
Inrush peak current	< 20 A			
Power factor	> 0.65			
Internal protection fuse	T 2 A replaceable			
External protection on AC line	circuit breaker: 4 A - C characteristic - fuse: T 4 A			

OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**		**12…15 Vdc**	
Output adjustable range	23...27.5 Vdc		12…15 Vdc	
Continuous current	**3.5 A** @ 50°C (3)		**6 A** @ 50°C (3)	
Overload limit	6 A per >30 s with Uout >Un x 0.9 (4)		9 A per >30 s with Uout >Un x 0.9 (4)	
Short circuit peak current	10 A per 50 ms (4)		10 A per 50 ms (4)	
Load regulation	< 1%		< 1%	
Ripple @ nominal ratings	≤ 70 mVpp		≤ 30 mVpp	
Hold up time @ In (Uin 120 / 230 Vac)	>20 ms / >70 ms		>15 ms / >60 ms	
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	"DC OK" green LED / "DC OK" alarm contact/ "Overload" red LED			
Alarm contact threshold	21.6 Vdc		10.8 Vdc	
Parallel connection	possible		possible	
Redundant parallel connection	possible with external ORing diode	factory provided with internal ORing diode	possible with external ORing diode	

GENERAL TECHNICAL DATA			
Efficiency (Uin 120 / 230 Vac)	>85% / >89%	>83% / >87%	
Dissipated power (Uin 120 / 230 Vac)	15 W / 11 W	17 W / 13 W	
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (3)		
Input/output isolation	3 KVac / 60 s SELV output		
Input/ground isolation	1.5 KVac / 60 s		
Output/ground isolation	0.5 KVac / 60 s		
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508, UL60950		
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11		
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F		
Overvoltage category/Pollution degree	II / 2		
Protection degree	IP 20 IEC 529, EN60529		
Connection terminal	2.5 mm² pluggable screw type		
Housing material	aluminium		
Approx. weight	400 g (14.12 oz)		
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components		

MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—

Single-phase switching power supply 120-230 Vac output power 96…144 W

- Single-phase input 90…264 Vac and DC 100…370 Vdc
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- High outrush current to guarantee downstream overcurrent protections selectivity and to start-up heavy loads
- Compact dimensions
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the terminal blocks and the DIN clamp.
(1) Not available
(2) With 100...127 Vdc input voltage, constant output power and Ta>45°C, the output current must be derated by 25%
(3) Over 45°C (113°F) apply derating: CSF5-CSF5P: -0.1 A/°C; B version: -0.13 A/°C; D version: -0.04 A/°C
(4) Overload and short circuit current depends on the total line resistance.


BLOCK DIAGRAM

Item available till sell-out, will be replaced by **CSF120** series…

VERSIONS	Cod. XCSF5	Cod. XCSF5P	Cod. XCSF5B	Cod. XCSF5D
Output 24 Vdc 6 A	**CSF5**			
Output 24 Vdc 6 A redundant version		**CSF5P**		
Output 12…15 Vdc 8 A			**CSF5B**	
Output 48 Vdc 2.5 A				**CSF5D**
INPUT TECHNICAL DATA				
Input rated voltage	**120–230 Vac** (range 90…264 Vac / 100…370 Vdc) (2)			
Frequency	47...63 Hz			
Current @ nominal Iout (Uin 120 /230 Vac)	1.8 A / 1 A ± 10%			
Inrush peak current	< 20 A			
Power factor	> 0.7			
Internal protection fuse	T 3.15 A replaceable			
External protection on AC line	circuit breaker: 4 A - C characteristic - fuse: T 4 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**		**12…15 Vdc**	**48 Vdc**
Output adjustable range	23...27.5 Vdc		12…15 Vdc	45…55 Vdc
Continuous current	**6 A** @ 45°C (3)		**8 A** @ 45°C (3)	**2.5 A** @ 45°C (3)
Overload limit	10 A (4)		14 A (4)	4 A (4)
Short circuit peak current	—		—	—
Load regulation	< 1%		< 1%	< 1%
Ripple @ nominal ratings	≤ 40 mVpp		≤ 50 mVpp	≤ 50 mVpp
Hold up time @ In (Uin 120 / 230 Vac)	>10 ms / >20 ms		>10 ms / >20 ms	>10 ms / >20 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	"DC OK" green LED / "DC OK" alarm contact			
Alarm contact threshold	–		–	–
Parallel connection	possible		possible	possible
Redundant parallel connection	possible with external ORing diode	factory provided with internal ORing diode	possible with external ORing diode	
GENERAL TECHNICAL DATA				
Efficiency (Uin 120 / 230 Vac)	>87% / >91%		>86% / >90%	>86% / >90%
Dissipated power (Uin 120 / 230 Vac)	18 W / 12 W		17 W / 12 W	19 W / 13 W
Operating temperature range	–20...+60°C, with derating over 45°C / over temperature protection (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	1.5 KVac / 60 s			
Output/ground isolation	0.5 KVac / 60 s			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	2.5 mm² pluggable screw type			
Housing material	aluminium and stainless steel			
Approx. weight	515 g (18.18 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

Single-phase switching power supply 120-230 Vac output power 120 W


- Single-phase input 90…264 Vac and DC 100…370 Vdc
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- High outrush current to guarantee downstream overcurrent protections selectivity and to start-up heavy loads
- Failure contact for Uout -10%
- Compact dimensions
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the terminal blocks and the DIN clamp.
(2) With 100...127 Vdc input voltage, constant output power and Ta>45°C, the output current must be derated by 25%
(3) Over 50°C (122°F) apply a derating -0.1 A/°C, max 60°C
(4) Overload and short circuit current depends on the total line resistance.

BLOCK DIAGRAM



VERSIONS	Cod. XCSF120C	Cod. XCSF120CP	Cod. XCSF120B	Cod. XCSF120D
Output 24 Vdc 5 A	**CSF120C**			
Output 24 Vdc 5 A redundant version		**CSF120CP**		
Output 12…15 Vdc 7 A			**CSF120B**	
Output 48 Vdc 2.5 A				**CSF120D**
INPUT TECHNICAL DATA				
Input rated voltage	**120–230 Vac** (range 90…264 Vac / 100…370 Vdc) (2)			
Frequency	47...63 Hz			
Current @ nominal Iout (Uin 120 /230 Vac)	1.9 A / 1.1 A ± 10%			
Inrush peak current	< 20 A			
Power factor	> 0.65			
Internal protection fuse	T 3.15 A replaceable			
External protection on AC line	circuit breaker: 4 A - C characteristic - fuse: T 4 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**		**12…15 Vdc**	**48 Vdc**
Output adjustable range	23...27.5 Vdc		12…15 Vdc	45…55 Vdc
Continuous current	**5 A** @ 50°C (3)		**7 A** @ 50°C (3)	**2.5 A** @ 50°C (3)
Overload limit	8 A for >30 s with Uout >Un x 0.9 (4)		8 A for >30 s with Uout >Un x 0.9 (4)	8 A for >30 s with Uout >Un x 0.9 (4)
Short circuit peak current	15 A per 50 ms (4)		15 A per 50 ms (4)	7.5 A per 50 ms (4)
Load regulation	< 1%		< 1%	< 1%
Ripple @ nominal ratings	≤ 30 mVpp		≤ 40 mVpp	≤ 30 mVpp
Hold up time @ In (Uin 120 / 230 Vac)	>17 ms / >72 ms		>24 ms / >80 ms	>16 ms / >81 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	"DC OK" green LED / "DC OK" alarm contact/ "Overload" red LED			
Alarm contact threshold	<21.6 Vdc		<10.8 Vdc	<43.2 Vdc
Parallel connection	possible		possible	possible
Redundant parallel connection	possible with external ORing diode	factory provided with internal ORing diode	possible with external ORing diode	
GENERAL TECHNICAL DATA				
Efficiency (Uin 120 / 230 Vac)	>86% / >90%		>85% / >89%	>86% / >90%
Dissipated power (Uin 120 / 230 Vac)	19 W / 13 W		21 W / 15 W	20 W / 13 W
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	1.5 KVac / 60 s			
Output/ground isolation	0.5 KVac / 60 s			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508, UL60950			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	2.5 mm² pluggable screw type			
Housing material	aluminium			
Approx. weight	400 g (14.12 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

Single-phase switching power supply 120-230 Vac output power 192…240 W

- Single-phase input 120 and 230 Vac
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- High outrush current to guarantee downstream overcurrent protections selectivity and to start-up heavy loads
- Suitable for applications in SELV and PELV circuits
- High efficiency and low dissipated power



NOTES

The depth dimension includes the terminal blocks and the DIN clamp.
(2) Double input selectable with external jumper, DC supply allow only between 300 and 350 Vdc
(3) Over 45°C (113°F) apply derating: CSF10-CSF10P: -0.16 A/°C; B version: -0.27 A/°C; D version: -0.08 A/°C
(4) Overload and short circuit current depends on the total line resistance.


BLOCK DIAGRAM

Item available till sell-out, will be replaced by **CSF240** series…

VERSIONS	Cod. XCSF10	Cod. XCSF10P	Cod. XCSF10B	Cod. XCSF10D
Output 24 Vdc 10 A	**CSF10**			
Output 24 Vdc 10 A redundant version		**CSF10P**		
Output 12…15 Vdc 16 A			**CSF10B**	
Output 48 Vdc 5 A				**CSF10D**
INPUT TECHNICAL DATA				
Input rated voltage	**120 - 230 Vac** (range 90…132 Vac / 185…264 Vac / 300...350 Vdc) (2)			
Frequency	47...63 Hz			
Current @ nominal Iout (Uin 120 /230 Vac)	3.5A / 1.8 A ± 10%			
Inrush peak current	< 35 A			
Power factor	> 0.6 / >0.85			
Internal protection fuse	T 6.3 A replaceable			
External protection on AC line	circuit breaker: 6 A C characteristic - fuse: T 6.3 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**		**12…15 Vdc**	**48 Vdc**
Output adjustable range	22.5...27.5 Vdc		12…15 Vdc	45…55 Vdc
Continuous current	**10 A** @ 45°C (3)		**16 A** @ 45°C (3)	**5 A** @ 45°C (3)
Overload limit	20 A (4)		17 A (4)	5.5 A (4)
Short circuit peak current	—		—	—
Load regulation	< 1%		< 1%	< 1%
Ripple @ nominal ratings	≤ 60 mVpp		≤ 60 mVpp	≤ 60 mVpp
Hold up time @ In (Uin 120 / 230 Vac)	>20 ms / >40 ms		>20 ms / >40 ms	>20 ms / >40 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	"DC OK" green LED / "DC OK" alarm contact			
Alarm contact threshold	–		–	–
Parallel connection	possible		possible	possible
Redundant parallel connection	possible with external ORing diode	factory provided with internal ORing diode	possible with external ORing diode	
GENERAL TECHNICAL DATA				
Efficiency (Uin 120 / 230 Vac)	>87% / >90%		>87% / >90%	>87% / >90%
Dissipated power (Uin 120 / 230 Vac)	35 W / 27 W		35 W / 27 W	36 W / 27 W
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	1.5 KVac / 60 s			
Output/ground isolation	0.5 KVac / 60 s			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	2.5 mm² pluggable screw type			
Housing material	aluminium and stainless steel			
Approx. weight	920 g (32.48 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

Single-phase switching power supply 120-230 Vac output power 240 W


- Single-phase input 120 and 230 Vac
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- High outrush current to guarantee downstream overcurrent protections selectivity and to start-up heavy loads
- Failure contact for Uout -10%
- Compact dimensions
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the terminal blocks and the DIN clamp.
(2) Double input selectable with external jumper, DC supply allow only between 300 and 350 Vdc
(3) Over 50°C (122°F) apply a derating: C version, CP: -0.25 A/°C; B version: -0.4 A/°C; D version: -0.13 A/°C.
(4) Overload and short circuit current depends on the total line resistance.


BLOCK DIAGRAM



VERSIONS	Cod. XCSF240C	Cod. XCSF240CP	Cod. XCSF240B	Cod. XCSF240D
Output 24 Vdc 10 A	**CSF240C**			
Output 24 Vdc 10 A redundant version		**CSF240CP**		
Output 12…15 Vdc 16 A			**CSF240B**	
Output 48 Vdc 5 A				**CSF240D**
INPUT TECHNICAL DATA				
Input rated voltage	**120 - 230 Vac** (range 90…132 Vac / 185…264 Vac / 300...350 Vdc) (2)			
Frequency	47...63 Hz			
Current @ nominal Iout (Uin 120 /230 Vac)	3.5 A / 1.8 A ± 10%			
Inrush peak current	< 35 A			
Power factor	> 0.6			
Internal protection fuse	T 6.3 A replaceable			
External protection on AC line	circuit breaker: 6 A C characteristic - fuse: T 6.3 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**		**12…15 Vdc**	**48 Vdc**
Output adjustable range	23...27.5 Vdc		12…15 Vdc	45…55 Vdc
Continuous current	**10 A** @ 50°C (3)		**16 A** @ 50°C (3)	**5 A** @ 50°C (3)
Overload limit	15 A for >30 s with Uout >Un x 0.9 (4)		14 A for >30 s with Uout >Un x 0.9 (4)	7.5 A for >30 s with Uout >Un x 0.9 (4)
Short circuit peak current	>25 A for 400 ms (4)		>25 A for 400 ms (4)	>25 A for 400 ms (4)
Load regulation	< 1%		< 1%	< 1%
Ripple @ nominal ratings	≤ 50 mVpp		≤ 50 mVpp	≤ 50 mVpp
Hold up time @ In (Uin 120 / 230 Vac)	>30 ms / >60 ms		>30 ms / >60 ms	>30 ms / >60 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	"DC OK" green LED / "DC OK" alarm contact/ "Overload" red LED			
Alarm contact threshold	21.6 Vdc		10.8 Vdc	43.2 Vdc
Parallel connection	possible		possible	possible
Redundant parallel connection	possible with external ORing diode	factory provided with internal ORing diode	possible with external ORing diode	
GENERAL TECHNICAL DATA				
Efficiency (Uin 120 / 230 Vac)	>88% / >90%		>87% / >90%	>88% / >90%
Dissipated power (Uin 120 / 230 Vac)	32 W / 27 W		35 W / 27 W	32 W / 27 W
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	1.5 KVac / 60 s			
Output/ground isolation	0.5 KVac / 60 s			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508, UL60950			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	2.5 mm² pluggable screw type			
Housing material	aluminium			
Approx. weight	920 g (32.48 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

Single-phase switching power supply 120-230 Vac output power 500 W


- Single-phase input 120 and 230 Vac
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- High outrush current to guarantee downstream overcurrent protections selectivity and to start-up heavy loads
- Compact dimensions
- Suitable for applications in SELV and PELV circuits
- Failure contact for Uout -10%



NOTES

The depth dimension includes the DIN rail clamp.
(2) Double input selectable with external jumper, DC supply allow only between 300 and 350 Vdc
(3) Over 50°C (122°F) apply a derating: C version: -0.5 A/°C; D version: -0.25 A/°C.
(4) Overload and short circuit current depends on the total line resistance.
(5) "Cool Power" version with threshold alarm and "Overload" LED available from October


BLOCK DIAGRAM



VERSIONS	Cod. XCSF500C			Cod. XCSF500D
Output 24 Vdc 20 A	–			
Output 24 Vdc 20 A redundant version		**CSF500C**		
Output 12…15 Vdc 40 A			–	
Output 48 Vdc 10 A				**CSF500D**
INPUT TECHNICAL DATA				
Input rated voltage	**120–230 Vac** (range 90…132 Vac / 185…264 Vac / 300...350 Vdc) (2)			
Frequency	47...63 Hz			
Current @ nominal Iout (Uin 120 /230 Vac)	4.1 A / 2 A ± 10%			
Inrush peak current	< 25 A with electronic limiter			
Power factor	> 0.75 with PFC			
Internal protection fuse	—			
External protection on AC line	circuit breaker: 16 A C characteristic - fuse: T 15 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**			**48 Vdc**
Output adjustable range	24...28 Vdc			45…55 Vdc
Continuous current	**20 A** @ 50°C (3)			**10 A** @ 50°C (3)
Overload limit	30 A for >5 s with Uout >Un x 0.9 (4)			15 A for >5 s with Uout >Un x 0.9 (4)
Short circuit peak current	>50 A for 5 s (4)			>50 A for 5 s (4)
Load regulation	< 0.5%			< 0.5%
Ripple @ nominal ratings	≤ 50 mVpp			≤ 50 mVpp
Hold up time @ In (Uin 120 / 230 Vac)	>12 ms / >20 ms			>12 ms / >20 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	"DC OK" green LED / "DC OK" alarm contact/ "Overload" red LED (5)			
Alarm contact threshold	21.6 Vdc (5)			43.2 Vdc (5)
Parallel connection	possible			possible
Redundant parallel connection	factory provided with internal ORing diode			factory provided with internal ORing diode
GENERAL TECHNICAL DATA				
Efficiency (Uin 120 / 230 Vac)	>90% / >92%			>90% / >92%
Dissipated power (Uin 120 / 230 Vac)	55 W / 43 W			55 W / 43 W
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	1.5 KVac / 60 s			
Output/ground isolation	0.5 KVac / 60 s			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	4 and 6 mm² fixed screw type			
Housing material	aluminium			
Approx. weight	1,3 kg (45.89 oz)			
Mounting information	vertical on rail, allow 20 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

Single-phase switching power supply 120-230 Vac IP65 protection degree

- Single-phase input 90…264 Vac and DC 100…370 Vdc
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- Suitable to be mounted directly on the machinery frame, don't require any protective enclosure
- IP65 pluggable screw connectors
- Suitable for applications in SELV and PELV circuits




NOTES

The depth dimension includes the terminal blocks and the DIN clamp.

(1) With 100...127 Vdc input voltage, constant output power and Ta>45°C, the output current must be derated by 25%

(2) Overload and short circuit current depends on the total line resistance.

BLOCK DIAGRAM



VERSIONS	Cod. XCSF565
Output 24 Vdc 5 A	**CSF5-65**

INPUT TECHNICAL DATA	
Input rated voltage	**120–230 Vac** (range 90…264 Vac / 100…370 Vdc) (1)
Frequency	47...63 Hz
Current @ nominal Iout (Uin 120 /230 Vac)	1.8 A / 1 A ± 10%
Inrush peak current	< 20 A
Power factor	> 0.7
Internal protection fuse	T 3.15 A replaceable
External protection on AC line	circuit breaker: 4 A - C characteristic - fuse: T 4 A
OUTPUT TECHNICAL DATA	
Output rated voltage	**24 Vdc**
Output adjustable range	23...27.5 Vdc
Continuous current	**5 A** @ 60°C
Overload limit	8 A (2)
Short circuit peak current	—
Load regulation	< 1%
Ripple @ nominal ratings	≤ 50 mVpp
Hold up time @ In (Uin 120 / 230 Vac)	>10 ms / >20 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection
Status display	"DC OK" green LED / "DC OK" alarm contact
Alarm contact threshold	—
Parallel connection	possible
Redundant parallel connection	possible with external ORing diode
GENERAL TECHNICAL DATA	
Efficiency (Uin 120 / 230 Vac)	>87% / >90%
Dissipated power (Uin 120 / 230 Vac)	18 W / 12 W
Operating temperature range	–20...+60°C / over temperature protection
Input/output isolation	3 KVac / 60 s SELV output
Input/ground isolation	1.5 KVac / 60 s
Output/ground isolation	0.5 KVac / 60 s
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F
Overvoltage category/Pollution degree	II / 2
Protection degree	IP 20 IEC 529, EN60529
Connection terminal	2.5 mm² IP65 pluggable screw connectors
Housing material	aluminium
Approx. weight	1.9 Kg (67.02 oz)
Mounting information	vertical on rail or panel mounting by means of screws
MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—

Switching power supply CSP series

EASY POWER

Easy Power series
It includes DIN-rail single-phase switching power supplies for general automation and installation applications. They are the recommended low-cost choice for uses where loads do no require high breakaway starting currents.

Suggested uses
- Applications in civil automation
- General applications in the installation of systems

Main features
- Equipped with 120 - 230 Vac input, they are suitable for use in all single-phase networks.
- Their high efficiency reduces energy consumption and components' operating temperature allowing their use in small panels and under severe ambient conditions.
- Backup power +20% above the rated voltage up to 45°C without exceeding standard temperature limits and ensuring safety and reliability.
- The output voltage may be adjusted and is protected against the input of surges caused by inductive loads on the DC line and is equipped with double electronic protection devices preventing damages to powered equipment in the event of internal faults.
- Short-circuit, overload and thermal protection devices prevent faults in the event of prolonged overloads at high ambient temperatures.
- Their design ensures excellent ventilation to internal components, very small dimensions and IP20 protection against accidental contacts in compliance with IEC529.
- Compared to other products having similar power and costs, they offer higher performances, functions and reliability.










Single-phase switching power supply 120-230 Vac output power 85 W


- Single-phase input 90…264 Vac and DC 100…370 Vdc
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- Suitable in civil automation and general applications in the installation of systems
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the terminal blocks and the DIN clamp.
(2) With 100...127 Vdc input voltage, constant output power and Ta>45°C, the output current must be derated by 25%
(3) Over 45°C (113°F) apply a derating of -0.05 A/°C
(4) Overload and short circuit current depends on the total line resistance.

BLOCK DIAGRAM



VERSIONS	Cod. XCSP85C			
Output 24 Vdc 3.5 A	**CSP85C**			
Output 24 Vdc 3.5 A redundant version		**–**		

INPUT TECHNICAL DATA	
Input rated voltage	**120–230 Vac** (range 90…264 Vac / 100…370 Vdc) (2)
Frequency	47...63 Hz
Current @ nominal Iout (Uin 120 /230 Vac)	1.3A / 0.7 A ± 10%
Inrush peak current	< 20 A
Power factor	> 0.7
Internal protection fuse	T 2 A replaceable
External protection on AC line	circuit breaker: 4 A - C characteristic - fuse: T 4 A


OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**			
Output adjustable range	23...27.5 Vdc			
Continuous current	**3.5 A** @ 45°C (3)			
Overload limit	>5 A (4)			
Short circuit peak current	—			
Load regulation	< 1%			
Ripple @ nominal ratings	≤ 40 mVpp			
Hold up time @ In (Uin 120 / 230 Vac)	>10 ms / >20 ms			
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	“DC OK” green LED			
Alarm contact threshold	—			
Parallel connection	possible			
Redundant parallel connection	possible with external ORing diode			

GENERAL TECHNICAL DATA	
Efficiency (Uin 120 / 230 Vac)	>86% / >90%
Dissipated power (Uin 120 / 230 Vac)	12 W / 8 W
Operating temperature range	-10...+50°C, with derating over 45°C / over temperature protection (3)
Input/output isolation	3 KVac / 60 s SELV output
Input/ground isolation	1.5 KVac / 60 s
Output/ground isolation	0.5 KVac / 60 s
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11
MTBF @ 25°C @ nominal ratings	>400'000 h acc. to SN 29500 / >100'000 h acc. to MIL Std. HDBK 217F
Overvoltage category/Pollution degree	II / 2
Protection degree	IP 20 IEC 529, EN60529
Connection terminal	2.5 mm² pluggable screw type
Housing material	aluminium and stainless steel
Approx. weight	515 g (18.18 oz)
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components

MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—

Single-phase switching power supply 120-230 Vac output power 120 W


- Single-phase input 90…264 Vac and DC 100…370 Vdc
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- Suitable in civil automation and general applications in the installation of systems
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the terminal blocks and the DIN clamp.
(2) With 100...127 Vdc input voltage, constant output power and Ta>45°C, the output current must be derated by 25%
(3) Over 45°C (113°F) apply a derating of -0.083 A/°C
(4) Overload and short circuit current depends on the total line resistance.

BLOCK DIAGRAM



VERSIONS	Cod. XCSP120C			
Output 24 Vdc 5 A	**CSP120C**			
Output 24 Vdc 5 A redundant version		**–**		

INPUT TECHNICAL DATA	
Input rated voltage	**120–230 Vac** (range 90…264 Vac / 100…370 Vdc) (2)
Frequency	47...63 Hz
Current @ nominal Iout (Uin 120 /230 Vac)	1.8 A / 1 A ± 10%
Inrush peak current	< 20 A
Power factor	> 0.7
Internal protection fuse	T 3.15 A replaceable
External protection on AC line	circuit breaker: 4 A - C characteristic - fuse: T 4 A


OUTPUT TECHNICAL DATA	
Output rated voltage	**24 Vdc**
Output adjustable range	23...27.5 Vdc
Continuous current	**5 A** @ 45°C (3)
Overload limit	6 A (4)
Short circuit peak current	—
Load regulation	< 1%
Ripple @ nominal ratings	≤ 40 mVpp
Hold up time @ In (Uin 120 / 230 Vac)	>10 ms / >20 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection
Status display	"DC OK" green LED
Alarm contact threshold	—
Parallel connection	possible
Redundant parallel connection	possible with external ORing diode

GENERAL TECHNICAL DATA	
Efficiency (Uin 120 / 230 Vac)	>87% / >91%
Dissipated power (Uin 120 / 230 Vac)	18 W / 12 W
Operating temperature range	-10...+50°C, with derating over 45°C / over temperature protection (3)
Input/output isolation	3 KVac / 60 s SELV output
Input/ground isolation	1.5 KVac / 60 s
Output/ground isolation	0.5 KVac / 60 s
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11
MTBF @ 25°C @ nominal ratings	>400'000 h acc. to SN 29500 / >100'000 h acc. to MIL Std. HDBK 217F
Overvoltage category/Pollution degree	II / 2
Protection degree	IP 20 IEC 529, EN60529
Connection terminal	2.5 mm² pluggable screw type
Housing material	aluminium and stainless steel
Approx. weight	515 g (18.18 oz)
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components

MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—

Single-phase switching power supply 120-230 Vac output power 240 W


- Single-phase input 120 and 230 Vac
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- Suitable in civil automation and general applications in the installation of systems
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the terminal blocks and the DIN clamp.
(2) Double input selectable with external jumper, DC supply allow only between 300 and 350 Vdc
(3) Over 45°C (113°F) apply a derating of -0.083 A/°C
(4) Overload and short circuit current depends on the total line resistance.

BLOCK DIAGRAM



VERSIONS	Cod. XCSP240C			
Output 24 Vdc 10 A	**CSP240C**			
Output 24 Vdc 10 A redundant version		**–**		

INPUT TECHNICAL DATA	
Input rated voltage	**120–230 Vac** (range 90…132 Vac / 185…264 Vac / 300...350 Vdc) (2)
Frequency	47...63 Hz
Current @ nominal Iout (Uin 120 /230 Vac)	3.5A / 1.8 A ± 10%
Inrush peak current	< 35 A
Power factor	> 0.6 / >0.85
Internal protection fuse	T 6.3 A replaceable
External protection on AC line	circuit breaker: 6 A C characteristic - fuse: T 6.3 A

OUTPUT TECHNICAL DATA	
Output rated voltage	**24 Vdc**
Output adjustable range	23...27.5 Vdc
Continuous current	**10 A** @ 45°C (3)
Overload limit	>14 A (4)
Short circuit peak current	—
Load regulation	< 1%
Ripple @ nominal ratings	≤ 60 mVpp
Hold up time @ In (Uin 120 / 230 Vac)	>20 ms / >40 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection
Status display	"DC OK" green LED
Alarm contact threshold	—
Parallel connection	possible
Redundant parallel connection	possible with external ORing diode

GENERAL TECHNICAL DATA	
Efficiency (Uin 120 / 230 Vac)	>87% / >90%
Dissipated power (Uin 120 / 230 Vac)	35 W / 27 W
Operating temperature range	-10...+50°C, with derating over 45°C / over temperature protection (3)
Input/output isolation	3 KVac / 60 s SELV output
Input/ground isolation	1.5 KVac / 60 s
Output/ground isolation	0.5 KVac / 60 s
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11
MTBF @ 25°C @ nominal ratings	>400'000 h acc. to SN 29500 / >100'000 h acc. to MIL Std. HDBK 217F
Overvoltage category/Pollution degree	II / 2
Protection degree	IP 20 IEC 529, EN60529
Connection terminal	2.5 mm² pluggable screw type
Housing material	aluminium and stainless steel
Approx. weight	920 g (32.48 oz)
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components

MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—

Switching power supply CSW series

UNIVERSAL POWER


Universal Power Series
It includes DIN-rail single/two-phase switching power supplies with 185…550 Vac universal input for applications in industrial automation and process control. The input circuit's technology protects them against surges caused by faults in three-phase networks with neutral, increasing the application's reliability.

Suggested uses
- In single or three-phase systems requiring great flexibility
- Applications in industrial automation and process control
- Heavy duty uses
- Applications in civil automation


Main features
- The wide-range input 185…550 Vac may be supplied single-phase 230…240 Vac, two-phase 208 Vac and two-phase 400…500 Vac ensuring excellent adaptability to AC networks and enabling to get rid of the isolating transformer.
- The two-phase input enables to reduce dimensions, wiring, installation costs and space inside the panel.
- They enable to get rid of the transformer for adapting to power voltages.
- Versions with DC OK alarm contact.
- Their high efficiency reduces energy consumption and components' operating temperature allowing their use in small panels and under severe ambient conditions.
- Great backup power allowing to supply at least + 30% above the rated voltage for 5 seconds, up to 45°C without exceeding standard temperature limits and ensuring safety and reliability.
- The output voltage may be adjusted and is protected against the input of surges on the DC line and is equipped with double electronic protection devices disconnecting output in the event of internal faults.
- Dimensioned short-circuit and overload protection supplying breakaway starting currents 150% above the rated value required by heavy loads; thermal protection prevents failures in the event of prolonged overloads at high ambient temperatures.
- Their design ensures excellent ventilation to internal components, very small dimensions and IP20 protection against accidental contacts in compliance with IEC529.
- Thanks to their high efficiency and excellent ventilation, they are the smallest devices available on the market.

Greater reliability
Compared to single-phase power supplies, this Series is more reliable in industrial applications. The input stage uses components with 900 V operating voltage, which are more resistant to voltage peaks in industrial power lines compared to components used in single-phase supplies, whose operating voltage is 550V in high-quality power supplies, but often 400...450 V in low-cost products.
Being able to work from 185 to 550 Vac, these power supplies are immune to power failures; at 230 Vac input (L1-N), when another device connected to L2-N goes short, the neutral rises up to approx. 400 Vac and the input is supplied phase/phase until the protection is activated, which takes place - at best -in 300 ms; this is one of the most common causes of damages to 230-Vac single-phase power supplies in industrial applications.
Another example of faults in 230-Vac single-phase devices powered between phase-neutral is due to the disconnection or accidental interruption of the panel's neutral from the system's neutral: failing to return to the neutral point, the neutral rises up to phase voltage applying approx. 400 Vac to single-phase loads, inevitably damaging the system.





Typical application with three-phase network and neutral. The latter is used to obtain a 230-Vac voltage in order to supply power to loads (in the example, a simple bulb) and power supplies.




A simple short-circuit on the load causes a rise in the neutral's potential, all the devices connected to it will be powered between two phases, i.e. with a value of approx. 340...400 Vac instead of 230 Vac.





1 or 2-phase switching power supply 230-400-500 Vac output power 120 W

- Both single-phase and two-phase input 185...550 Vac
- High reliability and immunity against over voltage due to failures on AC line
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- High outrush current to guarantee downstream overcurrent protections selectivity and to start-up heavy loads
- High efficiency and low dissipated power
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the terminal blocks and the DIN clamp.


(1) Version available upon request; for information call our sales department, local agent or representative

(2) 550 Vdc max for UL508

(3) Over 50°C (122°F) apply a derating of about 3 W/°C

(4) Overload and short circuit current depends on the total line resistance.


BLOCK DIAGRAM



VERSIONS	Cod. XCSW120C		Cod. XCSW120B	
Output 24 Vdc 5 A	**CSW120C**			
Output 24 Vdc 5 A redundant version		–		
Output 12…15 Vdc 7 A			**CSW120B**	
Output 48 Vdc 2.5 A				–
INPUT TECHNICAL DATA				
Input rated voltage	**230-400-500 Vac** (range 185…550 Vac / 270…770 Vdc) (2)			
Frequency	47...63 Hz			
Current @ Iout max. (Uin 230 / 400 Vac)	1.1 A / 0.55 A			
Inrush peak current	< 20 A			
Power factor	> 0.65			
Internal protection fuse	–			
External protection on AC line	circuit breaker: 2 X 6 A C characteristic - fuse: 2 X T 3.15 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**		**12…15 Vdc**	
Output adjustable range	24...27.5 Vdc		12…15 Vdc	
Continuous current	**5 A** @ 50°C (3)		**8 A** @ 12 Vdc / **7 A** @ 15 Vdc	
Overload limit	7.5 A for >5 s with Uout >Un x 0.9 (4)		8.8…7.7 A for >5 s with Uout >Un x 0.9 (4)	
Short circuit peak current	15 A for 0.5 s (4)		> 15 A for 0.5 s (4)	
Load regulation	< 1%		< 1%	
Ripple @ nominal ratings	≤ 50 mVpp		≤ 50 mVpp	
Hold up time (Uin 230 / 400 Vac)	>20 ms / >200 ms		>20 ms / >200 ms	
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	"DC OK" green LED			
Alarm contact threshold	–		–	
Parallel connection	possible		possible	
Redundant parallel connection	possible with external ORing diode		possible with external ORing diode	
GENERAL TECHNICAL DATA				
Efficiency (Uin 230 / 400 Vac)	>86% / >88%		>84% / >86%	
Dissipated power (Uin 230 / 400 Vac)	20 W / 16 W		20 W / 17 W	
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	2 KVac / 60 s			
Output/ground isolation	0.5 KVac / 60 s			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	2.5 mm² pluggable screw type			
Housing material	aluminium and stainless steel			
Approx. weight	600 g (21.18 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

1 or 2-phase switching power supply 230-400-500 Vac output power 240 W


- Both single-phase and two-phase input 185...550 Vac
- High reliability and immunity against over voltage due to failures on AC line
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- High outrush current to guarantee downstream overcurrent protections selectivity and to start-up heavy loads
- High efficiency and low dissipated power
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the terminal blocks and the DIN clamp.
(1) Version available upon request; for information call our sales department, local agent or representative
(2) 550 Vdc max for UL508
(3) Over 50°C (122°F) apply a derating of about 3 W/°C
(4) Overload and short circuit current depends on the total line resistance.

BLOCK DIAGRAM



VERSIONS	Cod. XCSW240C		Cod. XCSW240B	Cod. XCSW240D
Output 24 Vdc 10 A	**CSW240C**			
Output 24 Vdc 10 A redundant version		–		
Output 12…15 Vdc 16...15 A			**XCSW240B (1)**	
Output 48 Vdc 5 A				**XCSW240D (1)**
INPUT TECHNICAL DATA				
Input rated voltage	**230-400-500 Vac** (range 185…550 Vac / 270…770 Vdc) (2)			
Frequency	47...63 Hz			
Current @ Iout max. (Uin 230 / 400 Vac)	2 A / 1 A			
Inrush peak current	< 20 A			
Power factor	> 0.65			
Internal protection fuse	–			
External protection on AC line	circuit breaker: 2 X 6 A C characteristic - fuse: 2 X T 6.3 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**		**12…15 Vdc**	**48 Vdc**
Output adjustable range	24...27.5 Vdc		12…15 Vdc	45…55 Vdc
Continuous current	**10 A** @ 50°C (3)		**16 A** @ 12 Vdc / **15 A** @ 15 Vdc	**5 A** @ 50°C (3)
Overload limit	15 A for >5 s with Uout >Un x 0.9 (4)		20…18 A for >5 s with Uout >Un x 0.9 (4)	6 A for >5 s with Uout >Un x 0.9 (4)
Short circuit peak current	20 A for 0.5 s (4)		20 A for 0.5 s (4)	20 A for 0.5 s (4)
Load regulation	< 1%		< 1%	< 1%
Ripple @ nominal ratings	≤ 80 mVpp		≤ 80 mVpp	≤ 80 mVpp
Hold up time (Uin 230 / 400 Vac)	>20 ms / >120 ms		>20 ms / >120 ms	>20 ms / >120 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	"DC OK" green LED / "DC OK" alarm contact			
Alarm contact threshold	–		–	–
Parallel connection	possible		possible	possible
Redundant parallel connection	possible with external ORing diode		possible with external ORing diode	possible with external ORing diode
GENERAL TECHNICAL DATA				
Efficiency (Uin 230 / 400 Vac)	>88% / >90%		>87% / >89%	>88% / >90%
Dissipated power (Uin 230 / 400 Vac)	33 W / 27 W		34 W / 28 W	33 W / 27 W
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	2 KVac / 60 s			
Output/ground isolation	0.5 KVac / 60 s			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	2.5 mm² pluggable screw type			
Housing material	aluminium and stainless steel			
Approx. weight	1 Kg (35.3 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

Switching power supply CSB and CSG series

TRIPLE POWER

Triple Power series
It includes 400…500 Vac single-phase and three-phase switching power supplies for applications in industrial automation.
They can supply + 50% breakaway starting current above the rated voltage for 5 seconds, keeping output voltage constant and ensuring power supply to the system. They are equipped with an alarm contact controlled by a voltage threshold switching over when the voltage drops 90% below the rated value. **Thanks to these features and to the numerous international certifications, this series of power supplies allows engineers to meet with all the requirements of the new EN 60204-1 Machinery Directive.**



Suggested uses
- Applications in machinery automation requiring high levels of reliability in terms of control and safety voltage
- In applications requiring selectivity of surge protection devices on DC lines
- Applications in industrial automation
- Heavy duty uses




Main features
- Equipped with 340…550 Vac / 507…770 Vdc, they are suitable for use on all power lines.
- Their high efficiency reduces energy consumption and components' operating temperature allowing their use in small panels and under severe ambient conditions.
- Great backup power allowing to supply at least + 50% above the rated voltage for 5 seconds, keeping output voltage constant up to 45°C without exceeding standard temperature limits and ensuring safety and reliability.
- The output voltage may be adjusted and is protected against the input of surges on the DC line and is equipped with double electronic protection devices preventing damages to powered components in the event of internal faults.
- Dimensioned short-circuit and overload protection supplying breakaway starting currents 150% above the rated value required by heavy loads.
- Thermal protection prevents faults in the event of prolonged overloads at high ambient temperatures.
- Their design ensures excellent ventilation to internal components, very small dimensions and IP20 protection against accidental contacts in compliance with IEC529.





2-phase switching power supply 400-500 Vac output power 85 W


- Two-phase input 340...550 Vac
- It saves cabling costs and line protection costs
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- High outrush current to guarantee downstream overcurrent protections selectivity and to start-up heavy loads
- High efficiency and low dissipated power
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the terminal blocks and the DIN clamp.
(2) 550 Vdc max for UL508
(3) Over 50°C (122°F) apply a derating of about 2 W/°C
(4) Overload and short circuit current depends on the total line resistance.


BLOCK DIAGRAM



VERSIONS	Cod. XCSB85C			
Output 24 Vdc 3.5 A	**CSB85C**			
Output 24 Vdc 3.5 A redundant version		—		
Output 12…15 Vdc 7 A			—	
Output 48 Vdc 1.75 A				—
INPUT TECHNICAL DATA				
Input rated voltage	**400–500 Vac** (range 340…550 Vac) (2)			
Frequency	47...63 Hz			
Current @ Iout max. (Uin 400 / 500 Vac)	0.5 A / 0.45 A			
Inrush peak current	< 50 A			
Power factor	> 0.65			
Internal protection fuse	—			
External protection on AC line	circuit breaker: 2 X 6 A C characteristic - fuse: 2 X T 6.3 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**			
Output adjustable range	24...27.5 Vdc			
Continuous current	**3.5 A @ 50°C (3)**			
Overload limit	6 A for >5 s with Uout >Un x 0.9 (4)			
Short circuit peak current	15 A for 0.4 s (4)			
Load regulation	< 1%			
Ripple @ nominal ratings	≤ 60 mVpp			
Hold up time (Uin 400 / 500 Vac)	>50 ms / >60 ms			
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	"DC OK" green LED			
Alarm contact threshold	–			
Parallel connection	possible			
Redundant parallel connection	possible with external ORing diode			
GENERAL TECHNICAL DATA				
Efficiency (Uin 400 / 500 Vac)	>88% / >90%			
Dissipated power (Uin 400 / 500 Vac)	12 W / 9 W			
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	2 KVac / 60 s			
Output/ground isolation	0.5 KVac / 60 s			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	2.5 mm² pluggable screw type			
Housing material	aluminium			
Approx. weight	600 g (21.18 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

2-phase switching power supply 400-500 Vac output power 150 W


- Two-phase input 340...550 Vac
- It saves cabling costs and line protection costs
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- High outrush current to guarantee downstream overcurrent protections selectivity and to start-up heavy loads
- High efficiency and low dissipated power
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the terminal blocks and the DIN clamp.
(2) 550 Vdc max for UL508
(3) Over 50°C (122°F) apply a derating of about 3.75 W/°C
(4) Overload and short circuit current depends on the total line resistance.


BLOCK DIAGRAM



VERSIONS	Cod. XCSB150C			
Output 24 Vdc 5 A	**CSB150C**			
Output 24 Vdc 5 A redundant version		—		
Output 12…15 Vdc 8...7 A			—	
Output 48 Vdc 3 A				—
INPUT TECHNICAL DATA				
Input rated voltage	**400–500 Vac** (range 340…550 Vac) (2)			
Frequency	47...63 Hz			
Current @ Iout max. (Uin 400 / 500 Vac)	0.7 A / 0.55 A			
Inrush peak current	< 50 A			
Power factor	> 0.65			
Internal protection fuse	—			
External protection on AC line	circuit breaker: 2 X 6 A C characteristic - fuse: 2 X T 6.3 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**			
Output adjustable range	24...27.5 Vdc			
Continuous current	**6 A @ 50°C (3)**			
Overload limit	9 A for >5 s with Uout >Un x 0.9 (4)			
Short circuit peak current	20 A for 0.4 s (4)			
Load regulation	< 1%			
Ripple @ nominal ratings	≤ 60 mVpp			
Hold up time (Uin 400 / 500 Vac)	>50 ms / >60 ms			
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	"DC OK" green LED			
Alarm contact threshold	–			
Parallel connection	possible			
Redundant parallel connection	possible with external ORing diode			
GENERAL TECHNICAL DATA				
Efficiency (Uin 400 / 500 Vac)	>90% / >91%			
Dissipated power (Uin 400 / 500 Vac)	17 W / 15 W			
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	2 KVac / 60 s			
Output/ground isolation	0.5 KVac / 60 s			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	2.5 mm² pluggable screw type			
Housing material	aluminium			
Approx. weight	600 g (21.18 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

3-phase switching power supply 400-500 Vac output power 240 W

- Three-phase input 340...550 Vac or two-phase with derating
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- High outrush current to guarantee downstream overcurrent protections selectivity and to start-up heavy loads
- High efficiency and low dissipated power
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the DIN rail clamp.
(2) 550 Vdc max for UL508
(3) Over 50°C (122°F) apply a derating of about 3.75 W/°C
(4) Overload and short circuit current depends on the total line resistance.


BLOCK DIAGRAM

Items sold until sell-out,
will be replaced by **CSG240** series…

VERSIONS	Cod. XCSG10			
Output 24 Vdc 10 A	**CSG10**			
Output 24 Vdc 10 A redundant version		—		
Output 12…15 Vdc 20 A			—	
Output 48 Vdc 5 A				—
INPUT TECHNICAL DATA				
Input rated voltage	**400–500 Vac** (range 340…550 Vac / 507…770 Vdc) (2)			
Frequency	47...63 Hz			
Current @ Iout max. (Uin 400 / 500 Vac)	0.6 A / 0.42 A			
Inrush peak current	< 50 A			
Power factor	> 0.7			
Internal protection fuse	—			
External protection on AC line	circuit breaker: 3 X 6 A C characteristic - fuse: 3 X T 1.5 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**			
Output adjustable range	24…28 Vdc			
Continuous current	**10 A** @ 50°C (3)			
Overload limit	>20 A			
Short circuit peak current	—			
Load regulation	< 1%			
Ripple @ nominal ratings	≤ 50 mVpp			
Hold up time (Uin 400 / 500 Vac)	>10 ms / >20 ms			
Overload / short circuit protections	hiccup at the overload limit with auto reset / manual reset / constant power / over temperature protection			
Status display	"DC OK" green LED			
Alarm contact threshold	–			
Parallel connection	possible			
Redundant parallel connection	possible with external ORing diode			
GENERAL TECHNICAL DATA				
Efficiency (Uin 400 / 500 Vac)	>90% / >90%			
Dissipated power (Uin 400 / 500 Vac)	27 W / 27 W			
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	2 KVac / 60 s			
Output/ground isolation	0.5 KVac / 60 s			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	4 and 6 mm² fixed screw type			
Housing material	aluminium			
Approx. weight	1 Kg (35.30 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

3-phase switching power supply 400-500 Vac output power 240 W


- Three-phase input 340...550 Vac or two-phase with derating
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- High outrush current to guarantee downstream overcurrent protections selectivity and to start-up heavy loads
- High efficiency and low dissipated power
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the DIN rail clamp.
(2) 550 Vdc max for UL508
(3) Over 50°C (122°F) apply a derating of about 6 W/°C
(4) Overload and short circuit current depends on the total line resistance.


BLOCK DIAGRAM



VERSIONS	Cod. XCSG240C			
Output 24 Vdc 10 A	**CSG240C**			
Output 24 Vdc 10 A redundant version		—		
Output 12…15 Vdc 20 A			—	
Output 48 Vdc 5 A				—
INPUT TECHNICAL DATA				
Input rated voltage	**400–500 Vac** (range 340…550 Vac / 507…770 Vdc) (2)			
Frequency	47...63 Hz			
Current @ Iout max. (Uin 400 / 500 Vac)	0.6 A / 0.42 A			
Inrush peak current	< 50 A			
Power factor	> 0.7			
Internal protection fuse	—			
External protection on AC line	circuit breaker: 3 X 6 A C characteristic - fuse: 3 X T 1.5 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**			
Output adjustable range	24…28 Vdc			
Continuous current	**10 A** @ 50°C (3)			
Overload limit	15 A for >5 s with Uout >Un x 0.9 (4)			
Short circuit peak current	>25 A for 1.5 s (4)			
Load regulation	< 1%			
Ripple @ nominal ratings	≤ 50 mVpp			
Hold up time (Uin 400 / 500 Vac)	>20 ms / >30 ms			
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection (3)			
Status display	"DC OK" green LED / "DC OK" alarm contact			
Alarm contact threshold	–			
Parallel connection	possible			
Redundant parallel connection	possible with external ORing diode			
GENERAL TECHNICAL DATA				
Efficiency (Uin 400 / 500 Vac)	>90% / >90%			
Dissipated power (Uin 400 / 500 Vac)	27 W / 27 W			
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	2 KVac / 60 s			
Output/ground isolation	0.5 KVac / 60 s			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	4 mm² fixed screw type			
Housing material	aluminium			
Approx. weight	1 Kg (35.3 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

3-phase switching power supply 400-500 Vac output power 500 W


- Three-phase input 340...550 Vac or two-phase with derating
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- High outrush current to guarantee downstream overcurrent protections selectivity and to start-up heavy loads
- High efficiency and low dissipated power
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the DIN rail clamp.
(1) Version available upon request; for information call our sales department, local agent or representative
(2) 550 Vdc max for UL508
(3) Over 50°C (122°F) apply a derating of about 6 W/°C
(4) Overload and short circuit current depends on the total line resistance.
(5) "Triple Power" version with threshold alarm and "Overload" LED available from October


BLOCK DIAGRAM



VERSIONS	Cod. XCSG500C			Cod. XCSG500D
Output 24 Vdc 20 A	**CSG500C**			
Output 24 Vdc 20 A redundant version		—		
Output 12…15 Vdc 40 A			—	
Output 48 Vdc 10 A				**CSG500D (1)**
INPUT TECHNICAL DATA				
Input rated voltage	**400–500 Vac** (range 340…550 Vac / 507…770 Vdc) (2)			
Frequency	47...63 Hz			
Current @ Iout max. (Uin 400 / 500 Vac)	1 A / 0.6 A			
Inrush peak current	< 35 A			
Power factor	> 0.75 with PFC			
Internal protection fuse	—			
External protection on AC line	circuit breaker: 3 X 10 A C characteristic - fuse: 3 X T 3.15 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**			**48 Vdc**
Output adjustable range	24...28 Vdc			45…55 Vdc
Continuous current	**20 A** @ 50°C (3)			**10 A** @ 50°C (3)
Overload limit	>30 A for >5 s with Uout >Un x 0.9 (4)			>15 A for >5 s with Uout >Un x 0.9 (4)
Short circuit peak current	>50 A for 5 s (4)			>50 A for 5 s (4)
Load regulation	< 0.5%			< 0.5%
Ripple @ nominal ratings	≤ 50 mVpp			≤ 50 mVpp
Hold up time (Uin 400 / 500 Vac)	>12 ms / >20 ms			>15 ms / >30 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	"DC OK" green LED / "DC OK" alarm contact/ "Overload" red LED (5)			
Alarm contact threshold	<21.6 Vdc			<43.2 Vdc
Parallel connection	possible			possible
Redundant parallel connection	possible with external ORing diode			possible with external ORing diode
GENERAL TECHNICAL DATA				
Efficiency (Uin 400 / 500 Vac)	>93% / >94%			>93% / >94%
Dissipated power (Uin 400 / 500 Vac)	36 W / 30 W			36 W / 30 W
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	2 KVac / 60 s			
Output/ground isolation	0.5 KVac / 60 s			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	4 and 6 mm² fixed screw type			
Housing material	aluminium			
Approx. weight	1.3 Kg (45.89 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

3-phase switching power supply 400-500 Vac output power 720 W


- Three-phase input 340...550 Vac or two-phase with derating
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- High outrush current to guarantee downstream overcurrent protections selectivity and to start-up heavy loads
- High efficiency and low dissipated power
- Suitable for applications in SELV and PELV circuits



NOTES


The depth dimension includes the DIN rail clamp.
(1) Version available upon request; for information call our sales department, local agent or representative
(2) 550 Vdc max for UL508
(3) Over 50°C (122°F) apply a derating of about 6 W/°C
(4) Overload and short circuit current depends on the total line resistance.
(5) "Triple Power" version with threshold alarm and "Overload" LED available from October

BLOCK DIAGRAM



VERSIONS	Cod. XCSG720C			Cod. XCSG720D
Output 24 Vdc 30 A	**CSG720C**			
Output 24 Vdc 30 A redundant version		**(1)**		
Output 12…15 Vdc 60 A			**(1)**	
Output 48 Vdc 15 A				**CSG720D (1)**
INPUT TECHNICAL DATA				
Input rated voltage	**400–500 Vac** (range 340…550 Vac / 507…770 Vdc) (2)			
Frequency	47...63 Hz			
Current @ Iout max. (Uin 400 / 500 Vac)	1.4 A / 1.1 A			
Inrush peak current	< 30 A			
Power factor	> 0.75			
Internal protection fuse	—			
External protection on AC line	circuit breaker: 3 X 10 A C characteristic - fuse: 3 X T 5 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**			**48 Vdc**
Output adjustable range	24…28 Vdc			45…55 Vdc
Continuous current	**30 A** @ 50°C (3)			**15 A** @ 50°C (3)
Overload limit	45 A for >5 s with Uout >Un x 0.9 (4)			22.5 A for >5 s with Uout >Un x 0.9 (4)
Short circuit peak current	>50 A for 1.5 s (4)			>50 A for 1.5 s (4)
Load regulation	< 1%			< 1%
Ripple @ nominal ratings	≤ 200 mVpp			≤ 200 mVpp
Hold up time (Uin 400 / 500 Vac)	>10 ms / >15 ms			>10 ms / >15 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	"DC OK" green LED / "DC OK" alarm contact/ "Overload" red LED (5)			
Alarm contact threshold	<21.6 Vdc			<43.2 Vdc
Parallel connection	possible			possible
Redundant parallel connection	possible with external ORing diode			possible with external ORing diode
GENERAL TECHNICAL DATA				
Efficiency (Uin 400 / 500 Vac)	>93% / >94%			>93% / >94%
Dissipated power (Uin 400 / 500 Vac)	36 W / 30 W			36 W / 30 W
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	2 KVac / 60 s			
Output/ground isolation	0.5 KVac / 60 s			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	4 and 6 mm² fixed screw type			
Housing material	aluminium			
Approx. weight	1.3 Kg (45.86 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

3-phase switching power supply 400-500 Vac output power 960 W




- Three-phase input 340...550 Vac or two-phase with derating
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- High outrush current to guarantee downstream overcurrent protections selectivity and to start-up heavy loads
- High efficiency and low dissipated power
- Suitable for applications in SELV and PELV circuits

NOTES

The depth dimension includes the DIN rail clamp.
(1) To be replaced by model XCSG960C
(2) 550 Vdc max for UL508
(3) Over 50°C (122°F) apply a derating of about 24 W/°C
(4) Overload and short circuit current depends on the total line resistance.


BLOCK DIAGRAM



VERSIONS	Cod. XCSG42			
Output 24 Vdc 40 A	**CSG42 (1)**			
Output 24 Vdc 40 A redundant version		—		
Output 12…15 Vdc 80 A			—	
Output 48 Vdc 20 A				—
INPUT TECHNICAL DATA				
Input rated voltage	**400–500 Vac** (range 340…550 Vac / 507…770 Vdc) (2)			
Frequency	47...63 Hz			
Current @ Iout max. (Uin 400 / 500 Vac)	2,2 A / 1.1 A			
Inrush peak current	< 20 A			
Power factor	> 0.65			
Internal protection fuse	—			
External protection on AC line	circuit breaker: 3 X 10 A C characteristic - fuse: 3 X T 6.3 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**			
Output adjustable range	24…28 Vdc			
Continuous current	**40 A** @ 50°C (3)			
Overload limit	>45 A			
Short circuit peak current	—			
Load regulation	< 1%			
Ripple @ nominal ratings	≤ 250 mVpp			
Hold up time (Uin 400 / 500 Vac)	>10 ms / >15 ms			
Overload / short circuit protections	hiccup at the overload limit with auto reset / manual reset / over temperature protection			
Status display	"DC OK" green LED			
Alarm contact threshold	—			
Parallel connection	possible			
Redundant parallel connection	possible with external ORing diode			
GENERAL TECHNICAL DATA				
Efficiency (Uin 400 / 500 Vac)	>91% / >91%			
Dissipated power (Uin 400 / 500 Vac)	95 W / 95 W			
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	2 KVac / 60 s			
Output/ground isolation	0.5 KVac / 60 s			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC529, EN60529			
Connection terminal	4 and 6 mm² screw type			
Housing material	aluminium			
Approx. weight	2.2 Kg (77.60 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

3-phase switching power supply 400-500 Vac output power 960 W


- Three-phase input 340...550 Vac or two-phase with derating
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- High outrush current to guarantee downstream overcurrent protections selectivity and to start-up heavy loads
- High efficiency and low dissipated power
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the DIN rail clamp.
(1) Available from June 2009
(2) 550 Vdc max for UL508
(3) Over 50°C (122°F) apply a derating of about 18 W/°C
(4) Overload and short circuit current depends on the total line resistance.


BLOCK DIAGRAM



VERSIONS	Cod. XCSG960C			Cod. XCSG960D
Output 24 Vdc 40 A	**CSG960C (1)**			
Output 24 Vdc 40 A redundant version		—		
Output 12…15 Vdc 80 A			—	
Output 48 Vdc 20 A				**CSG960D (1)**
INPUT TECHNICAL DATA				
Input rated voltage	**400–500 Vac** (range 340…550 Vac / 507…770 Vdc) (2)			
Frequency	47...63 Hz			
Current @ Iout max. (Uin 400 / 500 Vac)	2.2 A / 1.1 A			
Inrush peak current	< 20 A			
Power factor	> 0.65			
Internal protection fuse	—			
External protection on AC line	circuit breaker: 3 X 10 A C characteristic - fuse: 3 X T 6.3 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**			**48 Vdc**
Output adjustable range	24…28 Vdc			45…55 Vdc
Continuous current	**40 A** @ 50°C (3)			**20 A** @ 50°C (3)
Overload limit	60 A for >5 s with Uout >Un x 0.9 (4)			30 A for >5 s with Uout >Un x 0.9 (4)
Short circuit peak current	>80 A for 5 s (4)			>80 A for 5 s (4)
Load regulation	< 1%			< 1%
Ripple @ nominal ratings	≤ 250 mVpp			≤ 250 mVpp
Hold up time (Uin 400 / 500 Vac)	>10 ms / >15 ms			>10 ms / >15 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	"DC OK" green LED / "DC OK" alarm contact/ "Overload" red LED			
Alarm contact threshold	<21.6 Vdc			<43.2 Vdc
Parallel connection	possible			possible
Redundant parallel connection	possible with external ORing diode			possible with external ORing diode
GENERAL TECHNICAL DATA				
Efficiency (Uin 400 / 500 Vac)	>91% / >91%			>91% / >91%
Dissipated power (Uin 400 / 500 Vac)	95 W / 95 W			95 W / 95 W
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	2 KVac / 60 s			
Output/ground isolation	0.5 KVac / 60 s			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	4 and 6 mm² fixed screw type			
Housing material	aluminium			
Approx. weight	2 Kg (70.55 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

3-phase switching power supply 400-500 Vac output power 2400 W


- Three-phase input 340...550 Vac or two-phase with derating
- Short circuit, overload, over temperature, input and ouput overvoltage protections
- High outrush current to guarantee downstream overcurrent protections selectivity and to start-up heavy loads
- High efficiency and low dissipated power
- Suitable for applications in SELV and PELV circuits



NOTES

The depth dimension includes the DIN rail clamp.
(2) 550 Vdc max for UL508
(3) Over 50°C (122°F) apply a derating of about 40 W/°C.
(4) Overload and short circuit current depends on the total line resistance.


BLOCK DIAGRAM



VERSIONS	Cod. XCSG2400C			Cod. XCSG2400D
Output 24 Vdc 100 A	**CSG2400C**			
Output 24 Vdc 100 A redundant version		—		
Output 12…15 Vdc 200 A			—	
Output 48 Vdc 50 A				**CSG2400D**
INPUT TECHNICAL DATA				
Input rated voltage	**400–500 Vac** (range 340…550 Vac / 507…770 Vdc) (2)			
Frequency	47...63 Hz			
Current @ Iout max. (Uin 400 / 500 Vac)	6 A / 5 A			
Inrush peak current	< 130 A			
Power factor	> 0.75			
Internal protection fuse	—			
External protection on AC line	circuit breaker: 3 X 20 A C characteristic - fuse: 3 X T 15 A			
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**			**48 Vdc**
Output adjustable range	24…28 Vdc			45…55 Vdc
Continuous current	**100 A** @ 45°C (3)			**50 A** @ 45°C (3)
Overload limit	110 A (4)			55 A (4)
Short circuit peak current	>150 A for 2 s (4)			>75 A for 2 s (4)
Load regulation	< 1%			< 1%
Ripple @ nominal ratings	≤ 300 mVpp			≤ 300 mVpp
Hold up time (Uin 400 / 500 Vac)	>10 ms / >15 ms			>10 ms / >15 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / manual reset / over temperature protection			
Status display	"DC OK" green LED			
Alarm contact threshold	—			—
Parallel connection	possible			possible
Redundant parallel connection	possible with external ORing diode			possible with external ORing diode
GENERAL TECHNICAL DATA				
Efficiency (Uin 400 / 500 Vac)	>92% / >92%			> 93% / >93%
Dissipated power (Uin 400 / 500 Vac)	210 W / 210 W			200 W / 200 W
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (3)			
Input/output isolation	3 KVac / 60 s SELV output			
Input/ground isolation	2 KVac / 60 s			
Output/ground isolation	0.5 KVac / 60 s			
Standard/approvals	EN50178, EN61558, EN60950, IEC950, UL508			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC529, EN60529			
Connection terminal	4 and 6 mm² screw type			
Housing material	aluminium			
Approx. weight	3.2Kg			
Mounting information	vertical on rail, allow 20 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

DC/DC Insulated converters output power 120 W


- DC wide range input
- Short circuit, overload, over temperature protection
- Compact design



NOTES

The depth dimension includes the terminal blocks and the DIN clamp.
(1) Inrush current is measured with input supplied by a battery; the current peak vary depending on the internal impedance of the current source and depending on cables and connections resistance.
(2) Over 50°C (122°F) apply a derating -3 W/°C, max 60°C
(3) According to EN60950 insulation tests on input side must be made only with DC instruments.


BLOCK DIAGRAM



VERSIONS	Cod. XCSA120BC	Cod. XCSA120CB	Cod. XCSA120CC	Cod. XCSA120DC
12 Vdc / 24 Vdc 5 A	**CSA120BC**			
24 Vdc / 12 Vdc 7 A		**CSA120CB**		
24 Vdc / 24 Vdc 5 A			**CSA120CC**	
48 Vdc / 24 Vdc 5 A				**CSA120DC**
INPUT TECHNICAL DATA				
Input rated voltage	**12 Vdc** (range 10.5…18 Vdc)	**24 Vdc** (range 18…36 Vdc)	**24 Vdc** (range 18…36 Vdc)	**48 Vdc** (range 36…72 Vdc)
Current @ Iout max.	12 A ±10%	5.1 A ±10%	5.8 A ±10%	2.8 A ±10%
Inrush peak current	< 60A / < 2ms (1)	< 100A / < 2ms (1)	< 90A /< 2ms (1)	< 120A / < 2ms (1)
Standby power	<1.5 W @ 12 Vdc	<1 W @ 24 Vdc	<1.5 W @ 24 Vdc	<2 W @ 48 Vdc
Internal protection fuse	T 20 A replaceable	T 10 A replaceable		T 5 A replaceable
External protection on AC line	≥25 A C characteristic	≥13 A C characteristic		≥6 A C characteristic
Overvoltage input protection circuit	Passive varistor and active shutdown at 19 Vdc	Passive varistor and active shutdown at 38 Vdc		Passive varistor and active shutdown at 76 Vdc
OUTPUT TECHNICAL DATA				
Output rated voltage	**24 Vdc**	**12...15 Vdc**	**24 Vdc**	**24 Vdc**
Output adjustable range	22.5...27.5 Vdc	12...15 Vdc	22.5...27.5 Vdc	22.5...27.5 Vdc
Continuous current	**5 A** @ 50°C (2)	**7 A** @ 50°C (2)	**5 A** @ 50°C (2)	**5 A** @ 50°C (2)
Overload limit	6.5 A	9.1 A	6.5 A	6.5 A
Short circuit peak current	12 A for 300 ms	15 A for 300 ms	12 A for 300 ms	13 A for 300 ms
Load regulation	<0.5%			
Ripple @ nominal ratings	≤ 100 mVpp		≤ 150 mVpp	≤ 200 mVpp
Hold up time @ In	>1 ms	>2 ms		>4.5 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection			
Status display	"DC OK" green LED			
Alarm contact threshold	—			
Parallel connection	possible			
Redundant parallel connection	possible with external ORing diode			
GENERAL TECHNICAL DATA				
Efficiency (Uin 110 Vdc)	> 83%	>87%	>87%	>90%
Dissipated power (Uin 110 Vdc)	<25 W	<16 W	<18 W	<13 W
Operating temperature range	–20...+60°C, with derating over 50°C (2)			
Input/output isolation	2.1 kVdc / 60s (3)			
Input/ground isolation	1.41 kVdc / 60s (3)			
Output/ground isolation	0.75 kVdc / 60s (3)			
Standard/approvals	IEC950, EN60950			
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-5-5, EN61000-4-6, EN61000-4-11			
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F			
Overvoltage category/Pollution degree	II / 2			
Protection degree	IP 20 IEC 529, EN60529			
Connection terminal	2.5 mm² pluggable screw type			
Housing material	aluminium			
Approx. weight	550 g (19.40 oz)			
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components			
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32	—			

DC/DC Insulated converters output power 240 W

- DC wide range input
- Short circuit, overload, over temperature protection
- Already preset with internal ORing diode for redundant connection
- Compact design



NOTES


The depth dimension includes the terminal blocks and the DIN clamp.

(1) Inrush current is measured with input supplied by a battery; the current peak vary depending on the internal impedance of the current source and depending on cables and connections resistance.

(2) Over 50°C (122°F) apply a derating -6 W/°C, max 60°C

(3) According to EN60950 insulation tests on input side must be made only with DC instruments.

BLOCK DIAGRAM



VERSIONS	Cod. XCSA240FC
110 Vdc / 24 Vdc 10 A	—
110 Vdc / 24 Vdc 10 A ridondante	**CSA240FC**

INPUT TECHNICAL DATA	
Input rated voltage	**110 Vdc** (range 90…130 Vdc)
Current @ Iout max.	2.4 A ±10%
Inrush peak current	< 150A / < 2ms (1)
Standby power	<3.4 W @ 110 Vdc
Internal protection fuse	T 5 A replaceable
External protection on AC line	≥6 A C characteristic
Overvoltage input protection circuit	Passive varistor and active shutdown at 136 Vdc


OUTPUT TECHNICAL DATA	
Output rated voltage	**24 Vdc**
Output adjustable range	22.7…27 Vdc
Continuous current	**10 A @ 50°C (2)**
Overload limit	15 A
Short circuit peak current	21 A for 300 ms
Load regulation	<1.5%
Ripple @ nominal ratings	≤ 100 mVpp
Hold up time @ In (Uin 110 Vdc)	>4 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection
Status display	"DC OK" green LED / "DC OK" alarm contact / "Overload" red LED
Alarm contact threshold	—
Parallel connection	possible
Redundant parallel connection	factory provided with internal ORing diode

GENERAL TECHNICAL DATA	
Efficiency (Uin 110 Vdc)	>89%
Dissipated power (Uin 110 Vdc)	<28 W
Operating temperature range	–20...+60°C, with derating over 50°C (2)
Input/output isolation	2.1 kVdc / 60s (3)
Input/ground isolation	1.41 kVdc / 60s (3)
Output/ground isolation	0.75 kVdc / 60s (3)
Standard/approvals	IEC950, EN60950
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-5-5, EN61000-4-6, EN61000-4-11
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F
Overvoltage category/Pollution degree	II / 2
Protection degree	IP 20 IEC 529, EN60529
Connection terminal	2.5 mm² pluggable screw type
Housing material	aluminium
Approx. weight	800 g (28.24 oz)
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components

MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—

Switching power supply input 24 Vac output power 72…120 W

- Standard input voltage 24 Vac
- Dissipated power less than 10%
- Short circuit, overload, over temperature protection
- Input protection fuse




CE

NOTES

The depth dimension includes the terminal blocks and the DIN clamp.
(1) Over 25°C (77°F) apply derating: CSE3: -0.5 W/°C; CSE5: -0.85 W/°C; max 60°C

BLOCK DIAGRAM




VERSIONS	Cod. XCSE3	Cod. XCSE5
Output 24 Vdc 3 A	**CSE3**	
Output 24 Vdc 5 A		**CSE5**
INPUT TECHNICAL DATA		
Input rated voltage	**24 Vac** (range 24…28 Vac)	
Frequency	50...60 Hz	
Current @ Iout max.	4 A	5 A
Internal protection fuse	T 8 A replaceable	
External protection on AC line	circuit breaker: 10 A C characteristic - fuse: T 10 A	
OUTPUT TECHNICAL DATA		
Output rated voltage	**24 Vdc**	**24 Vdc**
Output adjustable range	23…25 Vdc	23…25 Vdc
Continuous current	**3 A** @ 25°C (1)	**5 A** @ 25°C (1)
Overload limit	4 A	5.5 A
Short circuit peak current	—	—
Load regulation	< 1%	
Ripple @ nominal ratings	< 100 mVpp	
Hold up time @ In	>20 ms	
Overload / short circuit protections	constant current, limit current, auto reset / over temperature protection	
Status display	"DC OK" green LED	
Parallel connection	possible	
Redundant parallel connection	possible with external ORing diode	
GENERAL TECHNICAL DATA		
Efficiency	>90%	>90%
Dissipated power	< 8 W	< 13 W
Operating temperature range	–10...+60°C, with derating over 45°C / over temperature protection (1)	
Input/output isolation	not insulated	
Input/ground isolation	0.5 KVac / 60 s	
Output/ground isolation	0.5 KVac / 60 s	
Reference Standards	IEC 664-1, DIN VDE 0110.1	
EMC Standards	EN55011, EN55022	
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F	
Overvoltage category/Pollution degree	II / 2	
Protection degree	IP 20 IEC 529, EN60529	
Connection terminal	2.5 mm² fixed screw type	
Housing material	metal	
Approx. weight	500 g (17.64 oz)	550 g (19.40 oz)
Mounting information	vertical on rail, allow 20 mm spacing between adjacent components	
MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	
Mounting rail type according to IEC60715/G32	—	

APPLICATIONS

CSE power supplies are suitable for use in SELV and PELV circuits.
WARNING! In PELV circuits, in which one safety low voltage pole is connected to the ground, **a pole of the secondary of the transformer too must not be connected to ground at once**; the only one pole to be grounded is normally the negative of the 24 Vdc output of the power supply and effectively used as control voltage.
The connection to ground of one pole of the transformer Vac output together with one pole of the 24 Vdc of the power supply output damages the power supply.
Input and output of the CSE Series power supplies are not isolated. Safety isolation function is therefore assigned to the external transformer which has to comply with EN60742 Std.

Switching power supply input 24 Vac output power 240 W


- Standard input voltage 24 Vac
- Dissipated power less than 10%
- Short circuit, overload, over temperature protection
- Input protection fuse



NOTES

The depth dimension includes the terminal blocks and the DIN clamp.
(1) Over 45°C (113°F) apply a derating -4 W/°C, max 60°C.

BLOCK DIAGRAM




VERSIONS	Cod. XCSE10
Output 24 Vdc 10 A	**CSE10**
INPUT TECHNICAL DATA	
Input rated voltage	**24 Vac** (range 21…30 Vac)
Frequency	50...60 Hz
Current @ Iout max.	12 A
Internal protection fuse	T 20 A replaceable
External protection on AC line	circuit breaker: 25 A C characteristic - fuse: T 25 A
OUTPUT TECHNICAL DATA	
Output rated voltage	**24 Vdc**
Output adjustable range	22…26.5 Vdc
Continuous current	**10 A** @ 25°C (1)
Overload limit	12 A
Short circuit peak current	—
Load regulation	< 1%
Ripple @ nominal ratings	< 200 mVpp
Hold up time @ In	>10 ms
Overload / short circuit protections	hiccup at the overload limit with auto reset / over temperature protection
Status display	"DC OK" green LED
Parallel connection	possible
Redundant parallel connection	possible with external ORing diode
GENERAL TECHNICAL DATA	
Efficiency (Uin 110 Vdc)	>90%
Dissipated power (Uin 110 Vdc)	< 26 W
Operating temperature range	–10...+60°C, with derating over 45°C / over temperature protection (1)
Input/output isolation	not insulated
Input/ground isolation	0.5 KVac / 60 s
Output/ground isolation	0.5 KVac / 60 s
Reference Standards	IEC 664-1, DIN VDE 0110.1
EMC Standards	EN55011, EN55022
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F
Overvoltage category/Pollution degree	II / 2
Protection degree	IP 20 IEC 529, EN60529
Connection terminal	2.5 mm² fixed screw type
Housing material	metal
Approx. weight	600 g (21.16 oz)
Mounting information	vertical on rail, allow 20 mm spacing between adjacent components
MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—


APPLICATIONS

CSE power supplies are suitable for use in SELV and PELV circuits.
WARNING! In PELV circuits, in which one safety low voltage pole is connected to the ground, **a pole of the secondary of the transformer too must not be connected to ground at once**; the only one pole to be grounded is normally the negative of the 24 Vdc output of the power supply and effectively used as control voltage.
The connection to ground of one pole of the transformer Vac output together with one pole of the 24 Vdc of the power supply output damages the power supply.
Input and output of the CSE Series power supplies are not isolated. Safety isolation function is therefore assigned to the external transformer which has to comply with EN60742 Std.

Adjustable linear power supply input 24 Vac

- Adjustable output voltage 1.2...24 Vdc
- Output current 1.5 and 5 A
- Short circuit, overload, over temperature protection






NOTES

The depth dimension includes the terminal blocks and the DIN clamp.
(1) See “Applications”

BLOCK DIAGRAM



VERSIONS	Cod. XCL1R	Cod. XCL5R
Output 1.2 A	**CL1R**	
Output 5 A		**CL5R**
INPUT TECHNICAL DATA		
Input rated voltage	**9…26 Vac** (see Tab. 1)	
Frequency	50...60 Hz	
Current @ Iout max.	2,5 A	6 A
Internal protection fuse	T 3 A replaceable	T 10 A replaceable
External protection on AC line	MCB: 4 A C characteristic - fuse T 4 A	MCB: 10 A C characteristic - fusibilie T 10 A
OUTPUT TECHNICAL DATA		
Output rated voltage	**1.2...24 Vdc**	**1.2...24 Vdc**
Output adjustable range	(see Tab. 1)	(see Tab. 1)
Continuous current	**1.5 A** (see Tab. 2)	**5 A** (see Tab. 2)
Overload limit	—	—
Load regulation	< 1%	
Ripple @ nominal ratings	< 50 mVpp @ 24 Vac	
Hold up time @ In	>20 ms	
Overload / short circuit protections	constant current, limit current, auto reset / over temperature protection	
Status display	“DC OK” green LED	
GENERAL TECHNICAL DATA		
Operating temperature range	–20...+45°C / over temperature protection (1)	
Input/output isolation	not insulated	
Input/ground isolation	0.5 KVac / 60 s	
Output/ground isolation	0.5 KVac / 60 s	
Reference Standards	IEC 664-1, DIN VDE	
EMC Standards	EN50081-1, EN61000-6-4	
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F	
Overvoltage category/Pollution degree	II / 2	
Protection degree	IP 00 IEC 529, EN60529	
Connection terminal	2.5 mm² fixed screw type	
Housing material	UL94V-0 plastic material	aluminium
Approx. weight	120 g (4.23 oz)	350 g (12.35 oz)
Mounting information	vertical on rail, allow 20 mm spacing between adjacent components	
MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	
Mounting rail type according to IEC60715/G32	**PR/DIN/AC, PR/DIN/AS, PR/DIN/AL**	—

APPLICATIONS

The CL-R linear reguated power supply series of CABUR is provided with adjustable output and it can satisfy all those needs related to the feeding of small loads with non-standard rated voltage and at an extremely limited cost. It can be mounted on the rail in whatever position, providing that enough space for the free circulation of the air remains for the cooling; the CL1R model having an IP 00 protection degree, its use is intended inside a protected enclosure. Even if the power supply is protected from over-current it is advisable to respect the rated values shown in table 1 and 2.

(1) **CL1R** and **CL5R** give the rated performances if fed by a voltage between 24 and 27 Vac, as indicated on **Tab. 1**; with input voltage between 24 and 27 Vac, the maximum output current for output voltages lower than 24 Vdc are indicted on **Tab. 2**; to achieve a good voltage stabilization and low ripple, linear power supplies must be fed with an input voltage higher than output voltage, while if they are supplied with 24 Vac, and adjusted for 24 Vdc output, when rated current is supplied, the ripple increases and voltage stabilization decreases; input voltages higher than 27 Vac increases power dissipation and increases operating temperature of the component, and might cause thermal protection shut down.
The products are preadjusted to Vout 24 Vdc with Vin 26 Vac.

INPUT (Vac)	OUTPUT (Vdc)	Iout max (A) XCL1R	Iout max (A) XCL5R
24...27	24	1.5	5
16...18	15	1.5	5
14...16	12	1.5	5
12...14	10	1.5	5
12	9	1.5	5
9	5	1.5	5


Tab. 1


INPUT (Vac)	OUTPUT (Vdc)	Iout max (A) XCL1R	Iout max (A) XCL5R
24	24	1.5	5
24	15	0.8	2.5
24	12	0.7	2
24	10	0.5	1.5
24	9	0.45	1.3
24	5	0.3	0.8

Tab. 2

Filtered power supplies without transformer with non regulated output

- DIN rail mounting
- Suitable for rectifying 6 Vac to 20 Vac
- V output = Vac input x 1.41 (-1V)






NOTES

(2) Version available upon request; for information call our sales department, local agent or representative
(3) They can work with input from min. 6 Vac to 30 Vac max., the non regulated output voltage depends on the load and on the variations of the input voltage supplied by the transformer
(4) They are protected from overcurrent by their input fuse (except AR1 model); it is recommended to protect cables of the output line with fuses of value coordinated with the current of the load and cables.

BLOCK DIAGRAM



VERSIONS	Cod. XAR1	Cod. XAR2
Output 1 A	**AR1**	
Output 2 A (2)		**AR2 (2)**
INPUT TECHNICAL DATA		
Input rated voltage	**6…20 Vac**	
Frequency	50...60 Hz	
Current @ Iout max.	1.2 A @ 20 Vac	2.4 A @ 20 Vac
Internal protection fuse	not available	T 3.15 A replaceable
External protection on AC line	MCB: 1 A C characteristic - fuse T 1 A	MCB: 4 A C characteristic - fusibilie T 4 A
OUTPUT TECHNICAL DATA		
Output voltage (without load)	Uout = (Uin x 1.41) (3)	
Output voltage (full load)	Uout = (Uin x 1.41) -2 (3)	
Continuous current	**1 A** @ 20°C	**2 A** @ 20°C
Overload limit	1 A	3 A
Load regulation	—	
Ripple @ nominal ratings	≤ 10%	
Hold up time @ In	>20 ms	
Overload / short circuit protections	not available, insert external fuse (4)	
Status display	"DC OK" green LED	
Parallel connection	—	
Redundant parallel connection	—	
GENERAL TECHNICAL DATA		
Operating temperature range	–20...+45°C / max 60°C	
Input/output isolation	not insulated	
Input/ground isolation	0.5 KVac / 60 s	
Output/ground isolation	0.5 KVac / 60 s	
Reference Standards	IEC 664-1, DIN VDE	
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F	
Overvoltage category/Pollution degree	II / 2	
Protection degree	IP 00 IEC 529, EN60529	
Connection terminal	2.5 mm² fixed screw type	
Housing material	UL94V-0 plastic material	
Approx. weight	22 g (0.77 oz)	110 g (3.88 oz)
Mounting information	vertical on rail, allow 50 mm spacing between adjacent components	
MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	
Mounting rail type according to IEC60715/G32	**PR/DIN/AC, PR/DIN/AS, PR/DIN/AL**	


APPLICATIONS

A rectified and filtered power supply is made with a rectifier bridge and a filter capacitor, that converts the alternating voltage into a continuous voltage. Since the power supply unit is not regulated, the output voltage varies considerably according to the current required by the load and according to the ±10% mains voltage variations.
The formula indicated in the output specifications allows to calculate the output voltage with Zero load, with 50% load and full load. This allows you to choose the most suitable transformer for your needs.
These units offer a low cost and a reliable voltage source suitable for loads such as relays, contactors, solenoid valves or loads that can work with relatively high ripple and wide voltage variations; in applications where mains is unstable or troubled, **it might be not suitable to feed microprocessor devices, analog converters, encoders and electronic devices which are sensitive to voltage variations.**

INPUT (Vac)	OUTPUT without load (Vdc)	OUTPUT full load (Vdc)
20	28.7	24.2
18	25.4	21.4
15	21.2	17.2
12	17	15
9	12.7	8.7
6	8.5	4.5

Filtered power supplies without transformer with non regulated output


- DIN rail mounting
- Suitable for rectifying 6....20 Vac
- V output = Vac input x 1.41 (-1V)



NOTES

(1) They can work with input from min. 6 Vac to 30 Vac max., the non regulated output voltage depends on the load and on the variations of the input voltage supplied by the transformer
(2) They are protected from overcurrent by their input fuse (except AR1 model); it is recommended to protect cables of the output line with fuses of value coordinated with the current of the load and cables

BLOCK DIAGRAM



VERSIONS	Cod. XAR4	Cod. XAR6
Output 4 A	**AR4**	
Output 6 A		**AR6**
INPUT TECHNICAL DATA		
Input rated voltage	**6…20 Vac**	
Frequency	50...60 Hz	
Current @ Iout max.	4.8 A @ 20 Vac	7.2 A @ 20 Vac
Internal protection fuse	T 6.3 A replaceable	T 8 A replaceable
External protection on AC line	MCB: 10 A C characteristic - fuse T 7 A	MCB: 10 A C characteristic - fuse T 10 A
OUTPUT TECHNICAL DATA		
Output voltage (without load)	Uout = (Uin x 1.41) (1)	
Output voltage (full load)	Uout = (Uin x 1.41) -2 (1)	
Continuous current	**4 A** @ 20°C	**6 A** @ 20°C
Overload limit	6 A	9 A
Load regulation	—	
Ripple @ nominal ratings	£ 10%	
Hold up time @ In	>20 ms	
Overload / short circuit protections	not available, insert external fuse (2)	
Status display	"DC OK" green LED	
Parallel connection	—	
Redundant parallel connection	—	
GENERAL TECHNICAL DATA		
Operating temperature range	–20...+45°C / max 60°C	
Input/output isolation	not insulated	
Input/ground isolation	0.5 KVac / 60 s	
Output/ground isolation	0.5 KVac / 60 s	
Reference Standards	IEC 664-1, DIN VDE	
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F	
Overvoltage category/Pollution degree	II / 2	
Protection degree	IP 00 IEC 529, EN60529	
Connection terminal	2.5 mm² fixed screw type	
Housing material	UL94V-0 plastic material	
Approx. weight	115 g (4.06 oz)	140 g (4.94 oz)
Mounting information	vertical on rail, allow 50 mm spacing between adjacent components	
MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	
Mounting rail type according to IEC60715/G32	**PR/DIN/AC, PR/DIN/AS, PR/DIN/AL**	


APPLICATIONS

A rectified and filtered power supply is made with a rectifier bridge and a filter capacitor, that converts the alternating voltage into a continuous voltage. Since the power supply unit is not regulated, the output voltage varies considerably according to the current required by the load and according to the ±10% mains voltage variations.
The formula indicated in the output specifications allows to calculate the output voltage with Zero load, with 50% load and full load. This allows you to choose the most suitable transformer for your needs.
These units offer a low cost and a reliable voltage source suitable for loads such as relays, contactors, solenoid valves or loads that can work with relatively high ripple and wide voltage variations; in applications where mains is unstable or troubled, **it might be not suitable to feed microprocessor devices, analog converters, encoders and electronic devices which are sensitive to voltage variations.**

INPUT (Vac)	OUTPUT without load (Vdc)	OUTPUT full load (Vdc)
20	28.7	24.2
18	25.4	21.4
15	21.2	17.2
12	17	15
9	12.7	8.7
6	8.5	4.5

Accessory for charging buffer batteries

- Battery charger
- Allows to connect in redundant parallel two power supplies
- Suitable for power supplies up to 10 A
- Battery protection fuse
- Battery feedback protection diode
- Current charge limiting resistor




NOTES

The depth dimension includes the terminal blocks and the DIN rail clamp.

(1) The charging current is dependent on the battery type and the required level of charge

BLOCK DIAGRAM



VERSIONS	Cod. XCSBC
	CSBC
GENERAL TECHNICAL DATA	
Power supply rated voltage	6...30 Vdc
Power supply rated current	> 3 A
Load rated voltage	6...29.5 Vdc
Load max current	10 A
Charge current limitation	0.6 A (1)
Battery disconnecting voltage	not available
IN/OUT drop voltage	0.5 V
Battery protection fuse	F1 = T 6.3 A / F2 = T 1 A
Protections	battery short circuit /overload
Alarm signal	—
Operating temperature range	–10...+50°C
Reference Standards	IEC 664-1, DIN VDE
Overvoltage category/Pollution degree	II / 2
Protection degree	IP 20 IEC 529, EN60529
Connection terminal	2.5 mm² fixed screw type
Housing material	UL94V-0 plastic material
Approx. weight	80 g (2.82 oz)
Mounting information	vertical on rail, adjacent
MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	**PR/DIN/AC, PR/DIN/AS, PR/DIN/AL**

APPLICATIONS

1. Battery charger

With this module is possible to use a Cabur power supply as a battery charger while it is feeding the load.

The diode provides decoupling between the battery and the power supply; the resistance limits the current charge limiting power supply output current and assuring longer life to the battery. The F1 fuse protects the battery and its wiring against short circuit.


The next picture shows the connections.

2. Parallel connection of power supplies

It is possible to use this module also to connect two power supplies in parallel, not provided with output decoupling diode, eliminating "Fuse 2" in series to charging current limiting resistor.


The next picture shows the connections.

1. Battery charger



(A) Power supply
(B) Battery
(C) CSBC

2. Parallel connection of power supplies



(A) Power supply
(C) CSBC

Accessory for charging and controlling buffer batteries

- Suitable for power supply with adjustable output
- Suitable for lead batteries
- Suitable for charging batteries while feeding loads
- Battery protection fuse
- "Deep discharge" battery protection
- Status display LED and failure contact




CE

NOTES

The depth dimension includes the DIN rail clamp.

BLOCK DIAGRAM



VERSIONS		Cod. XCSUPS1	Cod. XCSUPS2
Output 24 Vdc		**CS-UPS1**	
Output 12 Vdc			**CS-UPS2**
GENERAL TECHNICAL DATA			
Power supply input voltage		26...28.5 Vdc	12...15 Vdc
Power supply rated current		≥ 3 A	≥ 3 A
Load rated voltage		**26...28 Vdc**	**10...15 Vdc**
Max load current		**15 A**	**15 A**
Charging current		selectable 2 A or 4 A	selectable 2 A or 4 A
Battery disconnection voltage		≤ 18 Vdc ±0.5V	≤ 9.2 Vdc ±0.5V
IN/OUT voltage drop		0.4 V	
Battery protection fuse		T 15 A 42 V blade type	
Protections		Reverse polarity, short circuit, battery overload, battery deep discharge	
Alarm signals	Power supply OK:	SPDT 24 V / 1 A	
	Battery OK	green LED	
	Battery LOW	red LED	
	Load OK	yellow LED	
	Battery reverse polarity	green LED	
Operating temperature range		–10...+50°C	
EMC Standards		IEC 664-1, DIN VDE	
Overvoltage category/Pollution degree		II / 2	
Protection degree		IP 20 IEC 529, EN60529	
Connection terminal		2.5 mm² pluggable screw type	
Housing material		aluminium	
Approx. weight		300 g (10.58 oz)	
Mounting information		vertical on rail, adjacent	
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35-7.5		**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	
Mounting rail type according to IEC60715/G32		**PR/DIN/AC, PR/DIN/AS, PR/DIN/AL**	

APPLICATIONS

All power supplies with adjustable output voltage to +15% of rated voltage can be used as lead battery chargers, suitable to be used as back up supply in case of AC line breakdown.

The CS-UPS-1 circuit regulate the current charging the battery, and it is possible to set it up to 2A or 4A charging current ; CS- UPS1 disconnects the load form the battery whenever the battery voltage drops under 19Vdc, to avoid total discharge which always shortens battery life.

The module is provided with a fuse protecting the battery and its cable to prevent fire risk in case in case of short circuit. The module is provided with the following leds diplay:

PS OK: The green LED is on when the power supply feeding the CS-UPS1 is OK and the load is supplied by the power supply while the battery is continuously charged.

LOAD OK: Yellow LED is on when CS-UPS1 feeds the load.

BATT. OK: Green LED is on when the power supply is turned OFF or disconnected and indicates that the battery is connected and can feed the load.

BATT. LOW: Red LED on when the battery is low or discharged.

REVERSE BATTERY: Red LED is on when battery is connected with reverse polarity.

Alarm contact: a relay with an SPDT contact 1A/24V switches when the load is no more supplied by the power supply and then is supplied by the battery. This contact allows to get a remote warning on the status of the system even in the case that the power supply is turned OFF or damaged, or non more supplied for any reasons.

Batteries holder module


- 12 or 24 Vdc selectable output voltage
- Suitable for sealed lead rechargeable batteries
- Suitable for CSBC, CS-UPS, CSC75
- Suitable for DIN rail installation



NOTES

The depth dimension includes the terminal blocks and the DIN rail clamp.
(1) Available from February 2009

BLOCK DIAGRAM



VERSIONS

Batteries holder module (empty)	**CSBP30Y**	**Art. No. XCSBP30Y**
Battery	**BAT12V1,2AH**	**Art. No. 911012**


GENERAL TECHNICAL DATA

Batteries type	2 sealed batteries 12 Vdc 1.2 Ah	
Internal protection fuse	15 A	
Tipo di configurazione	**parallel**	**series**
Output voltage	12 Vdc 2.4 Ah	24 Vdc 1.2 Ah
Charging current max.	0.6 A	0.3 A
Discharging current max.	5 A	3 A
Operating temperature range	–10...+50°C	
EMC Standards	IEC 664-1, DIN VDE	
Overvoltage category/Pollution degree	II / 2	
Protection degree	IP 20 IEC 529, EN60529	
Connection terminal	2.5 mm² pluggable screw type	
Housing material	aluminium	
Approx. weight	1.2 kg (42,36 oz)	
Mounting information	vertical on rail, adjacent	


MOUNTING ACCESSORIES

Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	**PR/DIN/AC, PR/DIN/AS, PR/DIN/AL**

APPLICATIONS



PARALLEL connection: jumper 2 + 3



SERIES connection: jumper 1

Switching power supply with integrated battery charger


- Suitable for 12 Vdc loads and batteries
- Suitable for lead batteries
- Suitable for charging batteries while feeding loads
- Battery protection circuit
- "Deep discharge" battery protection
- Status display LED and failure contact



NOTES

The depth dimension includes the terminal blocks and the DIN clamp.
(1) Version available upon request; for information call our sales department, local agent or representative
(2) With 100...127 Vdc input voltage, constant output power and Ta>45°C, the output current must be derated by 25%
(3) In addition to the current load, the device supplies about 0.8 A for battery charging
(4) Over 50°C (122°F) apply a derating -0.13 A/°C, max 60°C
(5) Available from February 2009

BLOCK DIAGRAM



VERSIONS	Cod. XCSC75B	Cod. XCSC75C
Output 12 Vdc 5 A	**CSC75B** (5)	
Output 24 Vdc 5 A (1)		**(1)**

APPLICATIONS

INPUT TECHNICAL DATA	
Input rated voltage	**120–230 Vac** (range 90…264 Vac / 100…370 Vdc) (2)
Frequency	47...63 Hz
Current @ nominal Iout (Uin 120 /230 Vac)	1.3 A / 0.8 A ± 10%
Inrush peak current	< 20 A
Power factor	> 0.6
Internal protection fuse	T 2 A replaceable
External protection on AC line	circuit breaker: 4 A - C characteristic - fuse: T 4 A


OUTPUT TECHNICAL DATA		
Output voltage with operating power supply	**12.8…15.2 Vdc**	**24.8…27 Vdc**
Output voltage with batteries	12…14.4 Vdc	24…26.2 Vdc
Continuous current	**5 A** @ 50°C (3)	**5 A** @ 50°C (3)
Overload limit	>8 A per >30 s	>8 A per >30 s
Short circuit peak current	—	—
Load regulation	< 1%	< 1%
Ripple @ nominal ratings	≤ 50 mVpp	≤ 50 mVpp
Hold up time @ In (Uin 120 / 230 Vac)	>15 ms / >20 ms	>15 ms / >20 ms
Overload / short circuit protections	with operating power supply: hiccup at the overload limit with auto reset with non operating power supply: auto resettable electronic fuse against battery short circuit with non operating power supply: threshold-relay against battery deep discharge	
Output voltage with operating power supply	"PSU OK" green LED / failure contact / "BATTERY" red LED	
Output voltage with operating batteries	0.8 A (suitable for sealed lead batteries up to 15 Ah)	

GENERAL TECHNICAL DATA		
Efficiency (Uin 120 / 230 Vac)	>86% / >90%	>90%
Dissipated power (Uin 120 / 230 Vac)	21 W / 13 W	< 13 W
Operating temperature range	–20...+60°C, with derating over 50°C / over temperature protection (4)	
Input/output isolation	1.5 KVac / 60 s SELV output	
Input/ground isolation	1.5 KVac / 60 s	
Output/ground isolation	0.5 KVac / 60 s	
Standard/approvals	IEC950, EN60950	
EMC Standards	EN61000-6-2, EN61000-6-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11	
MTBF @ 25°C @ nominal ratings	>500'000 h acc. to SN 29500 / >150'000 h acc. to MIL Std. HDBK 217F	
Overvoltage category/Pollution degree	II / 2	
Protection degree	IP 20 IEC 529 EN60529	
Connection terminal	2.5 mm² pluggable screw type	
Housing material	aluminium	
Approx. weight	500 g (17.65 oz)	
Mounting information	vertical on rail, allow 10 mm spacing between adjacent components	

MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	**–**

Accessory for power supplies redundant parallel connections

- Suitable for power supplies without Oring diodes
- Compact dimensions
- Three selectanle voltages 12, 24 and 48 Vdc
- 2 status/relays contacts
- Power supplied status LED






CE

NOTES

The depth dimension includes the terminal blocks and the DIN rail clamp.

BLOCK DIAGRAM



VERSIONS	Cod. XCSBD
	CSBD


GENERAL TECHNICAL DATA	
Power supply rated voltage	**12–24–48 Vdc** selectable
Power supply rated current	15 A, max 30 A
Load rated voltage	**12–24–48 Vdc** selectable
Load max current	15 A
IN/OUT drop voltage	0.7 V @ 15 A
Protections	—
Alarm signal	2 contacts NA 2A @ 230 Vac
Operating temperature range	–20...+50°C
Reference Standards	IEC 664-1, DIN VDE
Overvoltage category/Pollution degree	II / 2
Protection degree	IP 00 IEC 529, EN60529
Connection terminal	2.5 mm² fixed screw type
Housing material	UL94V-0 plastic material
Approx. weight	120 g (4.23 oz)
Mounting information	vertical on rail, adjacent

MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	**PR/DIN/AC, PR/DIN/AS, PR/DIN/AL**

APPLICATIONS

This module allows the customer to connect in redundant parallel two power supplies not provided with built in Oring diodes (output decoupling diodes); a jumper bridge allows to select 12, 15, 24 or 48 Vdc operating voltage; each channel is provided with status indication led, status relay and contact for remote failure alarm.

Block diagram



(A) Power supply
(B) CSBD

Surge Protection Devices




Surge Protection Devices

The MA3000 Series surge protection devices prevent surges and transient overvoltages conducted through AC power distribution boards from damaging electronic systems such as instrumentation control panels, telemetry substations and fire and security alarm installations. The JVS operates by limiting excess voltages to suitable lower levels for the equipment previewed for employment in Overvoltage Category II (2.5 KV), in Class C overvoltage security zone, like requested by the Standards IEC 1024, IEC 1312-1, EN 50083-1.

Where to mount the SPDs

According to actual standards, the JVS overvoltage protection device has to be installed on the AC supply line at the very input of control cabinets, to guarantee surge immunity of all the devices installed in the panel, such as PLC, power supplies, inverters etc. The conformity to EMC Standards applies also to control cabinets, and requires that the max residual overvoltage does not exceed 2.5 KV. As a consequence, it is mandatory to install overvoltage protection devices capable to reduce incoming overvoltages under 2.5 KV, and overvoltage level that the devices inside the cabinet can withstand without damage.

picture no. 1



JVS Series


The surge protection device is made of a DIN rail mounted socket equipped with double connection terminal blocks and a pluggable module containing the overvoltage protection circuitry. This feature makes it easy to remove the protection device during isolation tests and for quick replacement. The MA 3000 can withstand a 20 times 10 kA discharge current (waveform 8/20), and a single 40 kA (JVS1-C1P) and 70 kA (JVS1-E1P) peak current. As required by industry surge protection device standards, the MA3000 series is provided with a disconnection device that removes the SPD from the line in case of internal damage or short circuit, giving a visible failure display on the front panel of the unit (picture no. 2). After a great number of discharges and continued long service the module will lose protection capacity and can be replaced without disconnecting the circuit wiring.

Fuse and protection devices


The MA3000 Series surge protective devices are not designed with a built-in thermal disconnector, therefore they must be equipped with upstream protection against short-circuit currents and with a differential protection element for protection against indirect contact (generally already present in the installation). The MA3000 Series must not be installed downstream of high sensitivity differential protection devices.

Connections

The surge protection devices MA3000 series can be employed in these types of connections:



Protection takes priority




Continuity of services takes priority

Lightning protection zones


Zone 0 - Zone where items are subject to direct lightning strikes or where an unattenuated electromagnetic field occurs as a result of the strike.
Zone 1 - Zone where items are subject to low level direct lightning strikes. The conducted impulse lightning currents and/or switching surges are reduced compared with Zone 0.
Zone 2 - Remnants of lightning impulse currents and/or switching surges are reduced compared with Zone 1.
Zone 3 - Surges, caused by oscillation effects, magnetic field couplings and internal switching surges are reduced compared with Zone 2
A - Sub Station
B - Main distribution board
C - Heavy machinery
D - Local distribution board
E - Light machinery
F - Workstation
G - Equipment


picture no. 2



Surge protection devices

- Rugged contacts
- Pluggable protection
- Efficiency status indicator on front panel
- Rugged metal parallel connection bridges






CE

NOTES

BLOCK DIAGRAM



VERSIONS	cod. XJVS1C1P	cod. XJVS1E1P
With varistor	**JVS1-C1P**	**JVS1-E1P**
ELECTRICAL TECHNICAL DATA		
Rated voltage	**230 V**	**400 V**
Max. operating voltage	320 V	460 V
Frequency	50…60 Hz	
Limiting voltage	< 1500 V	< 2300 V
Nominal discharge current (20 multi shot 8/20 µs waveform)	20 kA	40 kA
Maximum discharge current (single shot 8/20 µs waveform)	40 kA	70 kA
Protection voltage level	1.5 kV	2.3 kV
Varistor rated voltage	510 V ±10%	680 V ±10%
Leakage current	< 1 mA	
Response time	<25 ns	
Energy withstand (2 ms)	640 J	1580 J
External protection devices	circuit breaker: C-10 A o B-25 A - fuse: 50...40 A	
GENERAL TECHNICAL DATA		
Efficiency status indicator	green: protection fully operational red: protection disconnected, replace the module	
Operating temperature range	-40...+80°C	
Protection degree	IP 20 IEC 529, EN60529	
Reference Standards	IEC61643-1	
EMC Standards	EN 55011	
Connection terminal	16 mm² screw type (6 AWG) / 25 mm² (rigid cable)	
Module color	light grey	red
Housing material	UL94V-0 plastic material	
Approx. weight	128 g (4.52 oz)	
Mounting information	on rail, adjacent without gap	
MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	
Replacement varistor	XJVS1C1R	XJVS1E1R
Screw type jumper 2 poles	XJGB2P	
Screw type jumper 3 poles	XJGB3P	
Screw type jumper 4 poles	XJGB4P	

APPLICATIONS

The JVS Series surge protection devices prevent surges and transient overvoltages conducted through AC power distribution boards from damaging electronic devices and electronic control systems used in process control, factory automation , machinery automation and electric systems in general.
In case of local or remote lightining strokes, JVS surge suppressors limit the residual overvoltage to volateg values co ordinated with Overvoltage Cathegory II, as used on most electronic control systems, panels and electronic devices such as PLCs, DCSs, industrial PCs, power supplies and motor drives or any other electronic devices.

Adjustable electronic overcurrent protection from 1…10 A / 24 Vdc




figure 1

According to the new EN60204-1 Std. it is **compulsory** to protect wires on SELV-PELV lines against the effects of surges. The standard requires that surge protection devices on 24Vdc cut the fault off before the 24 Vdc control drops below 21.6 V, disconnecting power to controls and preventing the starting of emergency and safety functions.
According to EN 60204-1 and EN 61131-1 and -2, surge protection devices on SELV-PELV lines must be able to disconnect shorts within 10ms and dangerous surges within 5s. The use of power supplies with high output surge capacity and precise and quick protection devices enables to cut faults off before 24V drops below 21.6V disconnecting power to controls.

Fuses and magneto-thermic switches on 24 Vdc lines do not have I /t features enabling to quickly and precisely cut faults off; moreover fuses may be replaced with different types thus altering the system's protection and safety.

The correct coordination of the circuitry into which the surge protection device is incorporated must take into account the line's total R: R connections + R wires + R protection + residual R of the damaged load. R total value must always enable that the protection device's tripping current may flow in the circuit; it is also important to avoid undersizing the protection device in order to prevent inconvenient trips due to the load's breakaway starting I, or oversizing it thus increasing t of intervention.

The whole circuitry made up of power supply, surge protection device, wires and connections must be designed so as to enable the safe interruption of surges within 5s before 24 Vdc drops below 21.6 Vdc. This condition may be met using Cabur's power supplies - series CSF and CSG - dimensioned to supply high output surge (>+50% of rat.I for >5s) and electronic surge protection devices with CEP System which are more precise and quicker than magneto-thermic switches and devices whose tripping t does not depend upon ambient T and may be reset with local or remote controls.




figure 3

Features of protection devices
Mgts have two different intervention curves: Thermal and Magnetic. The magnetic relay trips exclusively in the event of a short with different I/ t curves: thermal relays have all the same intervention curve, regardless of the mgt curve and in the event of a surge, they operate as described in figure 2: surge currents 1.13 x In are cut in >1h and with surges > 1.45 X In, the tripping takes place in a few minutes.
The disconnection of short currents is carried out by a magnetic relay whose tripping t goes from 0.01 to 0.1 sec, with very high currents which the power supply may not be able to supply; an mgt C5 used on DC has >70A safe tripping, a current that only power supplies with much higher rated I, i.e. 40A, may be able to supply (and not all of them) and that can not be supplied by 10A power supplies.
Using mgt as surge protection device, if the power supply has a surge I 1.2 times its rat. I, disconnection will take place in 20…60 min, while with 2.5 currents higher than rat.I it will take place between 25 sec. and 2 min., depending on amb.T., whose times are too long to ensure the stability of 24V, for protecting wires and the selectivity of protection devices. In the event of a failure - until the protection device trips - the power supply remains with a higher surge of In x 1.5 x 5s and 24V drops below 21.6V leaving standard functions and most of all safety functions with no power supply.




figure 4

Selectivity of protection devices
In the event of a surge or a short, only the damaged circuit is disconnected by its protection device with no repercussions on the supply of the other loads. This function is obtained with power supplies having high surge capacity and quick and precise protection devices.

CEP system - a smart system for current's control
CEP "recognizes" surges at their lowest and more precise stage and disconnects the damaged circuit as quickly as possible. For an excellent flexible use, the CEP system allows to set 10 tripping currents ranging from 1A to 10A in 1A steps and 3 intervention curves "Fast - Normal - Delayed" (see figure 3).
The protection status is displayed by two leds and by a remote alarm transistor output; the load may be activated / deactivated by pressing a button on the front (figure 5) or by the PLC remote control. The possibility of separately controlling single channels is useful during installation, because the various components may be separately activated and tested and - in big systems - the remote control may be used in order to gradually activate loads thus preventing simultaneous overloads when the system is started up. Another important features in terms of safety is the possibility of manually disconnecting the load, which means that even when protection devices are reset from the remote control, the load will remain inactive thus preventing dangerous situations.





figure 5

Programmable electronic overcurrent protection 1...10 A / 24 Vdc

- Programmable from 1 A to 10 A in 1 A steps
- 3 programmable characteristic curves
- Remote or local ON/OFF control
- Status signal with LED and remote signal
- Slide contact for the manual load disconnection
- Sealable front cover allows to protect the set up of the protection

UL pendant






1) sealable front cover
2) current selector
3) identification label
4) characteristic curve selector
5) ste/reset button

NOTES

The measures include the overall dimensions and the fixing to the guide. (1) Version available upon request; for information call our sales department, local agent or representative (2) Il comando remoto avviene tramite impulsi a 24 Vdc. La durata degli impulsi dovrà essere: ON = impulso > 1 s / OFF = impulso > 100 ms e < 800 ms (3) The three standard intervention curves are described in the grafics; the C EP-D3 Version is also provided with a curve programmable through a software

BLOCK DIAGRAM

VERSIONS	Cod. XCEPD1		Cod. XCEPD3
With overload indication	**CEP-D1**		
With status indication (ON/OFF)		**(1)**	
With one wire bus			**CEP-D3**
INPUT TECHNICAL DATA			
Rated voltage	**24 Vdc** (range 18…32 Vdc)		
Rated current	10 A dc max.		
Max system current	40 A dc with CEP-RCC copper rail		
Protection	Internal against reverse polarity		
Remote control ON/OFF	24 Vdc external pulse		24 Vdc external pulse and by software (2)
OUTPUT TECHNICAL DATA			
Rated voltage	**24 Vdc** (voltage drop <170 mV @ Un / In)		
Current min. / max.	1...10 A dc programmable in 10 step of 1 A		
Programmable characteristic curves	slow, medium, fast		slow, medium, fast and a special programmable custom curve (3)
Switch ON capacity	10.000 µF		
Status indication	green LED: fixed = ok, flashing = Iout at 90% of the nominal, red LED: fixed = output manually switched off, slow flashing = overcurrent, quick flashing = error		
Status display	open collector transistor (overcurrent status)	open collector transistor (ON/OFF status)	open collector transistor (programmable status)
GENERAL TECHNICAL DATA			
Operating temperature range	–25...+60°C, derating Imax. 8 A over 40°C		
Input/output isolation	3 KVac / 60 s SELV output		
Protection degree	IP 20 IEC 529, EN60529		
Reference Standards	EN60950-1, EN61131-1, EN61131-2, EN60898, EN60947-4-1, EN50081		
Connection terminal	0.25...2.5 mm² fixed screw type		
Housing material	PA 6.6 (UL94V-0, NFF I2, F2)		
Approx. weight	120 g (4.24 oz)		
Mounting information	vertical on rail, adjacent without gap, we recommend the use of end brackets		
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**		
Mounting rail type according to IEC60715/G32	—		
Distribution kit (terminal + end bracket)	CEP-SS	(cod. XCEPSS)	
Distribution rail (busbar)	CEP-RCC	(cod. XCEPRCC)	
Insulation cover for distribution rail	CEP-RCP	(cod. XCEPRCP)	
Plug-in jumper red	CEP-BCR	(cod. XCEPBCR)	(8 poles)
Plug-in jumper blue	CEP-BCB	(cod. XCEPBCB)	(8 poles)
Marking tag	CEP-MTW	(cod. XCEPMTW)	(table with 50 tags)



CEP-BCR and CEP-BCB





CEP-MTW




CEP-SS

Intervention curves:
1) fast
2) medium
3) slow







EMI filters quick selection table

These tables allow you to quickly select only the items, then check if all product's technical data meet your application requirements.

3-phase filter without neutral wire 400-480 Vac

Current	Common mode (L / PE) attenuation (dB)						Differential mode (L / L) attenuation (dB)						Cat. No.	Page
	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz		
7 A	20	60	60	60	50	35	25	60	65	60	55	40	XFTDV07ST2	65
16 A	15	50	55	60	50	35	25	55	60	60	55	40	XFTDV16ST2	65
30 A	15	50	55	60	50	35	25	55	60	60	55	40	XFTDV30ST2	65
42 A	55	70	70	45	35	20	45	45	45	45	45	30	XFTDV42ST2	65
55 A	15	55	55	55	50	35	25	55	60	60	50	40	XFTDV55ST2	65
75 A	15	55	55	55	50	30	20	50	50	50	55	40	XFTDV75ST2	65
100 A	35	50	45	25	15	7	30	35	35	35	30	7	XFTDV100ST2	65
150 A	20	30	40	45	40	30	30	40	40	45	40	25	XF150TDS84C	66
180 A	20	30	40	45	40	30	30	40	40	45	40	25	XF180TDS84C	66
200 A	55	60	55	30	20	–	45	30	25	10	10	5	XF200TDDS84C	67
300 A	30	30	23	10	8	5	35	30	25	14	10	5	XF300TDSS84C	68
400 A	30	30	20	10	5	2	30	30	20	10	8	2	XF400TDSS84C	68
500 A	45	25	20	10	5	2	40	30	25	10	10	5	XF500TDSS84C	68
600 A	25	25	20	10	5	2	40	30	25	10	10	5	XF600TDSS84C	68

3-phase filter with neutral wire 400-480 Vac

Current	Common mode (L / PE) attenuation (dB)						Differential mode (L / L) attenuation (dB)						Cat. No.	Page
	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz		
10 A	10	20	20	20	30	25	10	20	25	25	30	30	XF10TYG9	70
16 A	25	50	50	50	45	30	35	55	60	60	40	30	XF16TYT2	69
20 A	10	15	20	35	40	25	10	15	20	20	25	20	XF20TYS9	70
25 A	25	50	50	50	45	30	35	55	60	60	40	30	XF25TYT2	69
36 A	25	50	50	50	40	25	30	50	55	50	40	30	XF36TYT2	69
50 A	25	45	45	40	40	25	30	50	50	40	40	30	XF50TYT2	69
100 A	10	20	25	30	30	20	30	40	40	35	35	25	XF100TYT2	69

Single-cell single-phase filter 120-250 Vac


Current	Common mode (L / PE) attenuation (dB)						Differential mode (L / L) attenuation (dB)						Cat. No.	Page
	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz		
3 A	20	30	35	45	50	45	7	35	50	45	45	45	XF03DKBG5B	71
6 A	15	20	25	40	45	45	10	20	45	45	50	45	XF06DKBG5B	71
12 A	10	20	22	35	45	40	10	20	40	45	45	45	XF12DKBG5B	71
16 A	10	18	20	35	45	30	10	18	40	40	40	35	XF16DKCG5B	71
20 A	10	18	20	30	35	35	10	12	35	35	40	40	XF20DKCG5B	71
30 A	10	25	30	45	50	35	12	40	50	50	50	45	XF30DKCS5B	71

Double-cell single-phase filter 120-250 Vac

Current	Common mode (L / PE) attenuation (dB)						Differential mode (L / L) attenuation (dB)						Cat. No.	Page
	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz		
3 A	45	60	60	55	45	45	12	45	45	45	45	45	XF03DPCG5C	72
6 A	30	50	60	55	50	35	8	45	45	45	45	45	XF06DPCG5C	72
12 A	15	25	35	55	55	35	12	40	40	35	35	40	XF12DPCG5C	72
16 A	20	35	45	60	50	35	12	40	40	45	45	50	XF16DPCG5C	72
20 A	15	40	45	50	50	40	12	45	45	45	35	50	XF20DPCG5C	72
30 A	10	30	35	55	45	30	18	45	50	40	40	40	XF30DPGS5C	72

3-phase filter without neutral TDV series


- Models from 7 to 130 A
- High attenuation from 50 kHz to 30 MHz
- High attenuation also with long cables
- Minimum space on the panel



NOTES

Dimensions and diagrams are indicative, for more details see the products data sheet.
(1) According to EN60950 insulation tests on input side must be made only with DC instruments.

BLOCK DIAGRAM



VERSIONS

Rated current	Type	Cat. No.	Dimensions A	B	C	Weight (kg)
7 A	**F 07 TDV ST2**	XFTDV07ST2	42 (1,65 in)	192 (7,56 in)	72 (2,84 in)	
16 A	**F 16 TDV ST2**	XFTDV16ST2	47 (1,85 in)	252 (9,93 in)	72 (2,84 in)	
30 A	**F 30 TDV ST2**	XFTDV30ST2	52 (2,05 in)	272 (10,72 in)	87 (3,43 in)	
42 A	**F 42 TDV ST2**	XFTDV42ST2	52 (2,05 in)	312 (12,29 in)	87 (3,43 in)	
55 A	**F 55 TDV ST2**	XFTDV55ST2	87 (3,43 in)	252 (9,93 in)	92 (3,62 in)	
75 A	**F 75 TDV ST2**	XFTDV75ST2	92 (3,62 in)	272 (10,72 in)	137 (5,4 in)	
100 A	**F 100 TDV ST2**	XFTDV100ST2	90 (3,55 in)	270 (10,64 in)	150 (5,91 in)	


GENERAL TECHNICAL DATA

Rated voltage	480 Vac ± 10%	
Rated current	see versions table	
Frequency	50…60 Hz	
Leakage current at 480 Vac 60 Hz	30 mA	
Operating temperature range	–25...+85°C	
Insulation L/L	1.45 KVdc / 60 s	(1)
Insulation L/PE	2.25 KVdc / 60 s	(1)
Overvoltage category/Pollution degree	—	
Protection degree	IP 20 IEC 529, EN60529	
Connection terminal	screw terminals	
Housing material	metal	
Approx. weight	see versions table	
Mounting information	on the panel with screws	

Type	Common mode (L / PE) attenuation (dB)						Differential mode (L / L) attenuation (dB)					
	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz
F 07 TDV ST2	20	60	60	60	50	35	25	60	65	60	55	40
F 16 TDV ST2	15	50	55	60	50	35	25	55	60	60	55	40
F 30 TDV ST2	15	50	55	60	50	35	25	55	60	60	55	40
F 42 TDV ST2	55	70	70	45	35	20	45	45	45	45	45	30
F 55 TDV ST2	15	55	55	55	50	35	25	55	60	60	50	40
F 75 TDV ST2	15	55	55	55	50	30	20	50	50	50	55	40
F 100 TDV ST2	35	50	45	25	15	7	30	35	35	35	30	7

3-phase filter without neutral TDS series

- Models from 150 to 180 A
- High attenuation from 150 kHz to 30 MHz
- High attenuation also with long cables




NOTES

Dimensions and diagrams are indicative, for more details see the products data sheet.

(1) Version available upon request; for information call our sales department, local agent or representative

(2) According to EN60950 insulation tests on input side must be made only with DC instruments.

BLOCK DIAGRAM



VERSIONS

Rated current	Type	Cat. No.	Dimensions A	Dimensions B	Dimensions C	Weight (kg)
150 A	**F 150 TDS 84C**	XF150TDS84C (1)	202 (7,96 in)	390 (15,37 in)	122 (4,81 in)	
180 A	**F 180 TDS 84C**	XF180TDS84C (1)	202 (7,96 in)	390 (15,37 in)	122 (4,81 in)	


GENERAL TECHNICAL DATA

Rated voltage	480 Vac ± 10%
Rated current	see versions table
Frequency	50…60 Hz
Leakage current at 480 Vac 60 Hz	500 mA
Operating temperature range	–25...+85°C
Insulation line/line	1 KVdc / 60 s (2)
Insulation line/PE	1 KVdc / 60 s (150A) – 2.25 KVdc / 60 s (180A) (2)
Overvoltage category/Pollution degree	—
Protection degree	IP 20 IEC 529, EN60529
Connection terminal	with screw bolts
Housing material	metal
Approx. weight	see versions table
Mounting information	on the panel with screws

Type	Common mode (L / PE) attenuation (dB)						Differential mode (L / L) attenuation (dB)					
	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz
F 150 TDS 84C	20	30	40	45	40	30	30	40	40	45	40	25
F 180 TDS 84C	20	30	40	45	40	30	30	40	40	45	40	25

3-phase filter without neutral serie TDDS


- High attenuation from 150 kHz to 30 MHz
- High attenuation also with long cables



NOTES

Dimensions and diagrams are indicative, for more details see the products data sheet.
(1) Version available upon request; for information call our sales department, local agent or representative
(2) According to EN60950 insulation tests on input side must be made only with DC instruments.

BLOCK DIAGRAM



VERSIONS

Rated current	Type	Cat. No.		Dimensions A	Dimensions B	Dimensions C	Weight (kg)
200 A	**F 200 TDDS 84C**	XF200TDDS84C	(1)	240 (9,46 in)	477 (18,79 in)	140 (5,52 in)	


GENERAL TECHNICAL DATA

Rated voltage	480 Vac ± 10%
Rated current	200 A
Frequency	50…60 Hz
Leakage current at 480 Vac 60 Hz	500 mA
Operating temperature range	–25...+85°C
Insulation line/line	1 KVdc / 60 s (2)
Insulation line/PE	1.8 KVdc / 60 s (2)
Overvoltage category/Pollution degree	—
Protection degree	IP 20 IEC 529, EN60529
Connection terminal	with screw bolts
Housing material	metal
Approx. weight	see versions table
Mounting information	on the panel with screws

Type	Common mode (L / PE) attenuation (dB)						Differential mode (L / L) attenuation (dB)					
	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz
F 200 TDDS 84C	55	60	55	30	20	/	45	30	25	10	10	5

3-phase filter without neutral TDSS series

- Models from 300 to 600 A
- High attenuation from 150 kHz to 30 MHz
- High attenuation also with long cables




NOTES

Dimensions and diagrams are indicative, for more details see the products data sheet.

(1) Version available upon request; for information call our sales department, local agent or representative

(2) According to EN60950 insulation tests on input side must be made only with DC instruments.

BLOCK DIAGRAM



VERSIONS

Rated current	Type	Cat. No.	Dimensions A	Dimensions B	Dimensions C	Weight (kg)
300 A	**F 300 TDSS 84C**	XF300TDSS84C (1)	242 (9,53 in)	525 (20,69 in)	142 (5,59 in)	
400 A	**F 400 TDSS 84C**	XF400TDSS84C (1)	242 (9,53 in)	525 (20,69 in)	142 (5,59 in)	
500 A	**F 500 TDSS 84C**	XF500TDSS84C (1)	272 (10,72 in)	680 (26,79 in)	182 (7,17 in)	
600 A	**F 600 TDSS 84C**	XF600TDSS84C (1)	272 (10,72 in)	680 (26,79 in)	182 (7,17 in)	


GENERAL TECHNICAL DATA

Rated voltage	480 Vac ± 10%
Rated current	see versions table
Frequency	50…60 Hz
Leakage current at 480 Vac 60 Hz	1000 mA
Operating temperature range	–25...+85°C
Insulation line/line	0.6 KVdc / 60 s (2)
Insulation line/PE	1 KVdc / 60 s (2)
Overvoltage category/Pollution degree	—
Protection degree	IP 20 IEC 529, EN60529
Connection terminal	with flat plug
Housing material	metal
Approx. weight	see versions table
Mounting information	on the panel with screws

Type	Common mode (L / PE) attenuation (dB)						Differential mode (L / L) attenuation (dB)					
	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz
F 300 TDSS 84C	30	40	40	25	20	15	40	40	50	35	30	20
F 400 TDSS 84C	25	35	30	20	20	10	40	35	35	20	15	10
F 500 TDSS 84C	25	30	30	20	15	10	30	30	30	20	15	10
F 600 TDSS 84C	25	25	25	15	15	10	25	25	25	15	10	10

3-phase filter with neutral serie TYT


- Models from 16 to 100 A
- High attenuation from 150 kHz to 30 MHz
- High attenuation also with long cables



NOTES

Dimensions and diagrams are indicative, for more details see the products data sheet.
(1) According to EN60950 insulation tests on input side must be made only with DC instruments.

BLOCK DIAGRAM




VERSIONS			Dimensions			Weight
Rated current	Type	Cat. No.	A	B	C	(kg)
16 A	**F 16 TYT2**	XF16TYT2	107 (4,22 in)	191,5 (7,55 in)	82 (3,23 in)	
25 A	**F 25 TYT2**	XF25TYT2	107 (4,22 in)	191,5 (7,55 in)	82 (3,23 in)	
36 A	**F 36 TYT2**	XF36TYT2	107 (4,22 in)	191,5 (7,55 in)	82 (3,23 in)	
50 A	**F 50 TYT2**	XF50TYT2	124 (4,89 in)	194 (7,64 in)	104 (4,1 in)	
100 A	**F 100 TYT2**	XF100TYT2	162 (6,38 in)	252 (9,93 in)	132 (5,2 in)	

GENERAL TECHNICAL DATA		
Rated voltage	440 Vac ± 10%	
Rated current	see versions table	
Frequency	50...60Hz	
Leakage current at 480 Vac 60 Hz	3 mA	
Operating temperature range	–25...+85°C	
Insulation line/line	1.45 KVdc / 60 s	(1)
Insulation line/PE	2.25 KVdc / 60 s	(1)
Overvoltage category/Pollution degree	—	
Protection degree	IP 20 IEC 529, EN60529	
Connection terminal	screw terminals	
Housing material	metal	
Approx. weight	see versions table	
Mounting information	on the panel with screws	

Type	Common mode (L / PE) attenuation (dB)						Differential mode (L / L) attenuation (dB)					
	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz
F 16 TYT2	25	50	50	50	45	30	35	55	60	60	40	30
F 25 TYT2	25	50	50	50	45	30	35	55	60	60	40	30
F 36 TYT2	25	50	50	50	40	25	30	50	55	50	40	30
F 50 TYT2	25	45	45	40	40	25	30	50	50	40	40	30
F 100 TYT2	10	20	25	30	30	20	30	40	40	35	35	25

Compact 3-phase filter with neutral TY series


- Models from 10 to 20 A
- High attenuation from 150 kHz to 30 MHz
- High attenuation also with long cables
- Eccellent quality/price/performances ratio



NOTES

Dimensions and diagrams are indicative, for more details see the products data sheet.
(1) According to EN60950 insulation tests on input side must be made only with DC instruments.

BLOCK DIAGRAM




VERSIONS			Dimensions			Weight
Rated current	Type	Cat. No.	A	B	C	(kg)
10 A	**F 10 TYG9**	XF10TYG9	50 (1,97 in)	85 (3,35 in)	44 (1,73 in)	
20 A	**F 20 TYS9**	XF20TYS9	50 (1,97 in)	97 (3,82 in)	44 (1,73 in)	

GENERAL TECHNICAL DATA		
Rated voltage	440 Vac ± 10%	
Rated current	see versions table	
Frequency	50...60Hz	
Leakage current at 480 Vac 60 Hz	0.5 mA	
Operating temperature range	–25...+85°C	
Insulation line/line	1.45 KVdc / 60 s	(1)
Insulation line/PE	2.25 KVdc / 60 s	(1)
Overvoltage category/Pollution degree	—	
Protection degree	IP 20 IEC 529, EN60529	
Connection terminal	with flat plug (10 A) and with screw terminals (20 A)	
Housing material	metal	
Approx. weight	see versions table	
Mounting information	on the panel with screws	

Type	Common mode (L / PE) attenuation (dB)						Differential mode (L / L) attenuation (dB)					
	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz
F 10T YG9	10	20	20	20	30	25	10	20	25	25	30	30
F 20 TYS9	10	15	20	20	25	20	10	15	20	20	25	20

Single-cell single-phase filter DK series

- Models from 3 to 30 A
- High attenuation from 150 kHz to 30 MHz
- High attenuation also with long cables
- Minimum space on the panel



NOTES


Dimensions and diagrams are indicative, for more details see the products data sheet.

(1) 0.25 mA @ 115 Vac e 0.45 mA @ 250 Vac for models from 3…20 A - 1 mA @ 115 Vac e 2 mA @ 250 Vac for the model of 30 A.

(2) According to EN60950 insulation tests on input side must be made only with DC instruments.

(3) With flat plug for models from 3…20 A – with screw bolt for the model from 30 A.

BLOCK DIAGRAM




VERSIONS			Dimensions			Weight
Rated current	Type	Cat. No.	A	B	C	(kg)
3 A	**F 03 DK BG5B**	XF03DKBG5B	64,5 (2,54 in)	34 (1,34 in)	30 (1,18 in)	
6 A	**F 06 DK BG5B**	XF06DKBG5B	64,5 (2,54 in)	34 (1,34 in)	30 (1,18 in)	
12 A	**F 12 DK BG5B**	XF12DKBG5B	64,5 (2,54 in)	34 (1,34 in)	30 (1,18 in)	
16 A	**F 16 DK CG5B**	XF16DKCG5B	45,5 (1,79 in)	71,5 (2,82 in)	30 (1,18 in)	
20 A	**F 20 DK CG5B**	XF20DKCG5B	51,8 (2,04 in)	84,8 (3,34 in)	30 (1,18 in)	
30 A	**F 30 DK CS5B**	XF30DKCS5B	56,5 (2,23 in)	114 (4,49 in)	46,4 (1,83 in)	

GENERAL TECHNICAL DATA	
Rated voltage	115–250 Vac ± 10%
Rated current	see versions table
Frequency	50…60 Hz
Leakage current at 480 Vac 60 Hz	0.25…1 mA / 0.45…2 mA (1)
Operating temperature range	–25...+85°C
Insulation line/line	1.45 KVdc / 60 s (2)
Insulation line/PE	2.25 KVdc / 60 s (2)
Overvoltage category/Pollution degree	—
Protection degree	IP 20 IEC 529, EN60529
Connection terminal	with flat plug (from 3 to 20 A) / with screw bolt (30 A) (3)
Housing material	metal
Approx. weight	see versions table
Mounting information	on the panel with screws

Type	Common mode (L / PE) attenuation (dB)						Differential mode (L / L) attenuation (dB)					
	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz
F 03 DK BG5B	20	30	35	45	50	45	7	35	50	45	45	45
F 06 DK BG5B	15	20	25	40	45	45	10	20	45	45	50	45
F 12 DK BG5B	10	20	22	35	45	40	10	20	40	45	45	45
F 16 DK CG5B	10	18	20	35	45	30	10	18	40	40	40	35
F 20 DK CG5B	10	18	20	30	35	35	10	12	35	35	40	40
F 30 DK CS5B	10	25	30	45	50	35	12	40	50	50	50	45

Double-cell single-phase filter DP series

- Models from 3 to 30 A
- High attenuation from 150 kHz to 30 MHz
- High attenuation also with long cables
- Minimum space on the panel



NOTES


Dimensions and diagrams are indicative, for more details see the products data sheet.

(1) 0.25 mA @ 115 Vac e 0.45 mA @ 250 Vac for models from 3…20 A - 1 mA @ 115 Vac e 2 mA @ 250 Vac for the model of 30 A.

(2) According to EN60950 insulation tests on input side must be made only with DC instruments.

(3) With flat plug for models from 3…20 A – with screw bolt for the model from 30 A.

BLOCK DIAGRAM



VERSIONS

Rated current	Type	Cat. No.	Dimensions A	Dimensions B	Dimensions C	Weight (kg)
3 A	**F 03 DP CG5C**	XF03DPCG5C	84,8 (3,34 in)	75 (2,96 in)	52 (2,05 in)	
6 A	**F 06 DP CG5C**	XF06DPCG5C	152,9 (6,02 in)	143 (5,63 in)	51,3 (2,02 in)	
12 A	**F 12 DP CG5C**	XF12DPCG5C	84,8 (3,34 in)	75 (2,96 in)	52 (2,05 in)	
16 A	**F 16 DP CG5C**	XF16DPCG5C				
20 A	**F 20 DP CG5C**	XF20DPCG5C	56,5 (2,23 in)		46.4 (1,83 in)	
30 A	**F 30 DP GS5C**	XF30DPGS5C				


GENERAL TECHNICAL DATA

Rated voltage	115–250 Vac ± 10%
Rated current	see versions table
Frequency	50…60 Hz
Leakage current at 480 Vac 60 Hz	0.25…1 mA / 0.45…2 mA (1)
Operating temperature range	–25...+85°C
Insulation line/line	1.45 KVdc / 60 s (2)
Insulation line/PE	2.25 KVdc / 60 s (2)
Overvoltage category/Pollution degree	—
Protection degree	IP 20 IEC 529, EN60529
Connection terminal	with flat plug (from 3 to 20 A) / with screw bolt (30 A) (3)
Housing material	metal
Approx. weight	see versions table
Mounting information	on the panel with screws

Type	Common mode (L / PE) attenuation (dB)						Differential mode (L / L) attenuation (dB)					
	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz	0.15 MHz	0.5 MHz	1 MHz	5 MHz	10 MHz	30 MHz
F 03 DP CG5C	45	60	60	55	45	45	12	45	45	45	45	45
F 06 DP CG5C	30	50	60	55	50	35	8	45	45	45	45	45
F 12 DP CG5C	15	25	35	55	55	35	12	40	40	35	35	40
F 16 DP CG5C	20	35	45	60	50	35	12	40	40	45	45	50
F 20 DP CG5C	15	40	45	50	50	40	12	45	45	40	35	50
F 30 DP GS5C	10	30	35	55	45	30	18	45	50	40	40	40

Applications of analog converters and galvanic isolation

These convert electric signals generated by sensors for measuring physical quantities such as: temperature (RTD thermocouples and PT100 thermal resistors), frequency (proximity, contacts, photoelectric cells), current (HV, Hall sensors), resistance (potentiometers), voltage, pressure, level etc., into standardised electrical signals, adapting them to the I/O of industrial PLC's, DCS's, and PC's (control), or they convert a given analog signal into a different one, adapting it to the inputs/outputs of the control, or allow remote transmission of the signal without interference via galvanic isolation (Fig. 1).



ADAPTATION OF THE SIGNAL


fig. 1

Adaptation between sensor output signal and control input signal:

physical quantity measured	sensor output	converter input		converter output	
Temperature	Normally one of the signals indicated in the next column	0 – 60 mV	±60 mV	0 – 5 V	±5 V
Frequency		0 – 100 mV	±100 mV	0 – 10 V	±10 V
Current		0 – 500 mV	±500 mV	0 – 20 mA	±20 mA
Resistance		0 – 1 V	±1 V	4 – 20 mA	
Voltage		0 – 5 V	±5 V		
Pressure		0 – 10 V	±10 V		
Level measurement		0 – 5 mA	±5 mA		
		0 – 10 mA	±10 mA		
		0 – 20 mA	±20 mA		
		0 – 20 mA			

Remote transmission of the signal:

The voltage signals reach a max. distance of 10-20 m, beyond this they lose reliability and become very sensitive to earth and induced interference (to transmit at a distance > 20 m a voltage signal must be converted into a current signal and galvanically isolated) (Fig. 2).



BLOCK DIAGRAM OF AN AMPLIFIER WITH GALVANIC ISOLATION


fig. 2

- current signals exceed 300 m of transmission distance and are less sensitive to induced interference. In order to transmit a current signal at a distance galvanic isolation is required.

① Input amplifier
② Opto-isolator
③ Signal adapter
④ Output amplifier
⑤ DC/DC converter


Galvanic isolation of the signal:

- electrically isolates and separates the circuit of the sensor from the control and power supply circuits. Thus each circuit operates with reference to its own zero potential which, being isolated from other circuits, cannot be altered by differences in potential always present between different earth references (Figs. 3 and 4).



NON-ISOLATED THERMOCOUPLE AND DIFFERENT ZERO POTENTIALS

fig. 3




Earthing through the resistance of the conductors. Consequently on the computer side potential combinations and equalising currents are created which lead to a measurement error.

CIRCUIT WITH EARTH REFERENCE

fig. 4

- isolates and separates the various zero potentials between power supply, control and sensors/actuators;
- allows transmission of the signal without errors or interference and with greater reliability;
- the higher the isolation (in KV), the greater the security of transmission where there are zero potentials, electromagnetic interference, transients (lightning, discharges etc.) (Fig. 5).




POTENTIAL DIFFERENCE AND EARTH CIRCUITS

fig. 5

Galvanic isolation is necessary when:

- the distance between control and sensor/actuator is more than 20 m;
- the earth references are different;
- the zero potentials are high, or potentially high in the case of discharges or earth dispersed currents;
- electromagnetic interference is present;
- the signal cables are wired in conduits with power cables (Fig. 6).



INTERFERENCE

fig. 6

Analog converters selection table

These tables allow you to quickly select only the items, then check if all product's technical data meet your application requirements.

Analog converters and isolators

Input	Output	Isolation	Power supply	Notes	Type	Cat. No.	Page
0...60 / 0...100 / 0...500 mV ±60 / ±100 / ±500 mV 0...1 / 0...2 / 0...5 / 0...10 V ±1 / ±2 / ±5 / ±10 V 0...5 / 0...10 / 0...20 / 4...20 mA ±5 / ±10 / ±20 mA	0...5 / 0...10 / ±5 / ±10 V 0...20 / 4...20 / ±20 mA	3 ways	24 Vdc	(1) (4)	CA-PI/PO1	XSSAPIPO1	78
0...60 / 0...100 / 0...300 / 0...500 mV 0...1 / 0...10 / 0...20 / 2...20 V 0...5 / 0...10 / 0...20 / 4...20 / ±5 / ±20 mA	0...10 V 0...20 / 4...20 mA	3 ways	24 Vac/dc	(1) (4)	CWUAA 6-0516	X756516	79
0...60 / 0...100 / 0...300 / 0...500 mV 0...1 / 0...10 / 0...20 / 2...20 V 0...5 / 0...10 / 0...20 / 4...20 / ±5 / ±20 mA	0...10 V 0...20 / 4...20 mA	3 ways	24...240 Vac/dc	(1) (5)	CWUAA 6-0517	X756517	79
0...10 V 0...20 / 4...20 mA	0...10 V 0...20 / 4...20 mA	3 ways	24 Vac/dc	(1) (4)	CWNAA 7-0539	X756539	80
0...10 V 0...20 / 4...20 mA	0...10 V 0...20 / 4...20 mA	3 ways	24...240 Vac/dc	(1) (5)	CWNAA 6-0510	X756510	80
0...10 V 0...20 / 4...20 mA	0...10 V 0...20 / 4...20 mA	2 ways	24 Vac/dc	(1) (4)	CWNAA 6-0509	X756509	81
0...10 V	0...10 V	3 ways	24 Vac/dc	(2) (4)	CWAA 6-0530	X756530	82
0...10 V	0...20 mA	3 ways	24 Vac/dc	(2) (4)	CWAA 6-0531	X756531	82
0...10 V	4...20 mA	3 ways	24 Vac/dc	(2) (4)	CWAA 6-0532	X756532	82
0...20 mA	0...10 V	3 ways	24 Vac/dc	(2) (4)	CWAA 6-0533	X756533	83
0...20 mA	0...20 mA	3 ways	24 Vac/dc	(2) (4)	CWAA 6-0534	X756534	83
0...20 mA	4...20 mA	3 ways	24 Vac/dc	(2) (4)	CWAA 6-0535	X756535	83
4...20 mA	0...10 V	3 ways	24 Vac/dc	(2) (4)	CWAA 6-0536	X756536	84
4...20 mA	0...20 mA	3 ways	24 Vac/dc	(2) (4)	CWAA 6-0537	X756537	84
4...20 mA	4...20 mA	3 ways	24 Vac/dc	(2) (4)	CWAA 6-0538	X756538	84
0...10 V	0...10 V	2 ways	24 Vac/dc	(2) (4)	CWAA 6-0500	X756500	85
0...10 V	0...20 mA	2 ways	24 Vac/dc	(2) (4)	CWAA 6-0501	X756501	85
0...10 V	4...20 mA	2 ways	24 Vac/dc	(2) (4)	CWAA 6-0502	X756502	85
0...20 mA	0...10 V	2 ways	24 Vac/dc	(2) (4)	CWAA 6-0503	X756503	86
0...20 mA	0...20 mA	2 ways	24 Vac/dc	(2) (4)	CWAA 6-0504	X756504	86
0...20 mA	4...20 mA	2 ways	24 Vac/dc	(2) (4)	CWAA 6-0505	X756505	86
4...20 mA	0...10 V	2 ways	24 Vac/dc	(2) (4)	CWAA 6-0506	X756506	87
4...20 mA	0...20 mA	2 ways	24 Vac/dc	(2) (4)	CWAA 6-0507	X756507	87
4...20 mA	4...20 mA	2 ways	24 Vac/dc	(2) (4)	CWAA 6-0508	X756508	87
0...20 / 4...20 mA	0...20 / 4...20 mA	2 ways	—	(4)	CWPAA 7-0526	X756526	88
0...20 / 4...20 mA	0...20 / 4...20 mA	2 ways	—	(3) (4)	CWPAA 7-0527	X756527	88
0...10 V	0...50 / 0...100 Hz	2 ways	24 Vac/dc	(1)	CWNAF 6-0511	X756511	89
0...20 / 4...20 mA	0...1 / 0...10 kHz						
0...10 V 0...20 / 4...20 mA	0...50 / 0...100 Hz 0...1 / 0...10 kHz	3 ways	24...240 Vac/dc	(1)	CWNAF 6-0512	X756512	89

Notes

(1) programmable input and output signal via DIP switches
(2) single range input and output signal (not programmable), articles generally not in stock but available upon request, for info please contact our sales department
(3) two channels version
(4) 1.5 KVac / 60 s two way isolation (input / output) or 1.5 KVac / 60 s three way isolation (input / output / supply)
(5) 4 KVac / 60 s three way isolation (input / output / supply)
(6) 0.5 KVac / 60 s two way isolation (input / output)

Analog / digital and digital / analog converters

Input	Output	Isolation	Power supply	Notes	Type	Cat. No.	Page
0...10 V	8 BIT		24 Vdc		ADC08V10	XW000933	98
0...20 mA	8 BIT		24 Vdc		ADC08A0	XW000934	98
4...20 mA	8 BIT		24 Vdc		ADC08A4	XW000935	98
8 BIT	0...10 V		24 Vdc		DAC08V10	XW000936	99
8 BIT	0...20 mA		24 Vdc		DAC08A0	XW000937	99
8 BIT	4...20 mA		24 Vdc		DAC08A4	XW000938	99

Analog converters selection table

These tables allow you to quickly select only the items, then check if all product's technical data meet your application requirements.

Current converter

Input	Output	Isolation	Power supply	Notes	Type	Cat. No.	Page
0…50 A ac	adjustable threshold 1…30 A	2 ways	24 Vdc	(3)	CCIS-1	XCCIS1	94
0…50 A ac	adjustable threshold 2…40 A	2 ways	24 Vdc	(4)	CCIS-R	XCCISR	94
0…1 A ac/dc	0...10 V 0...20 / 4...20 mA	2 ways	24 Vdc	(2)	SW01VA	XW000928	95
0…5 A ac/dc	0...10 V 0...20 / 4...20 mA	2 ways	24 Vdc	(2)	SW05VA	XW000929	95
0…10 A ac/dc	0...10 V 0...20 / 4...20 mA	2 ways	24 Vdc	(2)	SW10VA	XW000930	95
0…20 A ac/dc	0...10 V 0...20 / 4...20 mA	2 ways	24 Vdc	(2)	SW20VA	XW000931	96
0…50 A ac/dc	0...10 V 0...20 / 4...20 mA	2 ways	24 Vdc	(2)	SW50VA	XW000932	96

Notes

(1) single I/O version
(2) three programmable output signals
(3) open collector threshold output
(4) threshold output with one changeover relay

Programmable frequency to analog signal converters

Input	Output	Isolation	Power supply	Notes	Type	Cat. No.	Page
0…28.8 kHz	0...10 V 0...20 / 4...20 mA	2 ways	24 Vac/dc	(1)	CWNFA 6-0524	X756524	96

Notes

(1) 21 input signals and 3 programmable output signals
(2) 3 input signals and 3 programmable output signal

Analog to threshold signal converters

Input	Output	Isolation	Power supply	Notes	Type	Cat. No.	Page
0...10 V	relé 1 exchange	2 ways	24 Vdc	(1)	GWMV10	XW000926	100
0...20 mA	relé 1 exchange	2 ways	24 Vdc	(2)	GWMA0	XW000927	100

Notes

(1) programmable threshold output 0.3…10 V and 0.1…10 V hysteresis
(2) programmable threshold output 0.6…20 mA and 0.2…20 mA hysteresis

Load cells converters

Input	Output	Isolation	Power supply	Notes	Type	Cat. No.	Page
Measuring bridge	0...10 V 0...20 / 4...20 mA		24 Vac/dc		CWBRA 6-0522	X756522	101

Analog converters selection table

These tables allow you to quickly select only the items, then check if all product's technical data meet your application requirements.

Converters for temperature sensors

Sensor Type	Input	Output	Isolation	Power supply	Notes	Type	Cat. No.	Page
PT100, PT500, PT1000 Ni100, Ni1000 PTC, KTY Potentiometers 0…5 kOhm Thermocouples B, C, D, E, J, K, L, N, R, S, T, U	Programmable -200…+2400°C (-328…+4.352°F) according to sensor type	0...10 / 2...10 V 0...20 / 4...20 mA	3 ways	24 Vac/dc	(1)	CWTPR 7-0890	X756890	90
PT100 3 wires (RTD)	-50…+50°C (-58…+122°F) -50…+100°C (-58…+212°F) -50…+150°C (-58…+302°F) 0…+100°C (+32…+212°F) 0…+150°C (+32…+302°F) 0…+200°C (+32…+392°F) 0…+300°C (+32…+572°F) 0…+400°C (+32…+752°F)	0...10 V 0...20 / 4...20 mA	3 ways	24 Vac/dc	(2)	CWPT 6-0816	X756816	91
PT100 3 wires (RTD)	-50…+50°C (-58…+122°F) -50…+100°C (-58…+212°F) -50…+150°C (-58…+302°F) 0…+100°C (+32…+212°F) 0…+150°C (+32…+302°F) 0…+200°C (+32…+392°F) 0…+300°C (+32…+572°F) 0…+400°C (+32…+752°F)	0...10 V 0...20 / 4...20 mA	3 ways	24...240 Vac/dc	(2)	CWPT 6-0817	X756817	91
Thermocouples J (FeCuNi) and K (NiCrNi)	-50…+200°C (-58…+392°F) -50…+350°C (-58 …+662°F) 0…+200°C (+32…+392°F) 0…+400°C (+32…+752°F) 0…+600°C (+32…+1112°F) 0…+800°C (+32…+1472°F) 0…+1000°C (+32…+1832°F) 0…+1200°C (+32…+2192°F)	0...10 V 0...20 / 4...20 mA	3 ways	24 Vac/dc	(2)	CWTH 6-0844	X756844	92
Thermocouples J (FeCuNi) and K (NiCrNi)	-50…+200°C (-58…+392°F) -50…+350°C (-58 …+662°F) 0…+200°C (+32…+392°F) 0…+400°C (+32…+752°F) 0…+600°C (+32…+1112°F) 0…+800°C (+32…+1472°F) 0…+1000°C (+32…+1832°F) 0…+1200°C (+32…+2192°F)	0...10 V 0...20 / 4...20 mA	3 ways	24...240 Vac/dc	(2)	CWTH 6-0847	X756847	92
PT100 2 wires (RTD)	-50…+150°C (-58…+302°F) 0…+200°C (+32…+392°F) 0…+400°C (+32…+752°F)	0...50 / 0...100 Hz 0...1 / 0...10 kHz	3 ways	24 Vac/dc	(2)	CWPTF 7-0811	X756811	93
Thermocouples J (FeCuNi)	0…+200°C (+32…+392°F) 0…+400°C (+32…+752°F) 0…+600°C (+32…+1112°F)	0...50 / 0...100 Hz 0...1 / 0...10 kHz	3 ways	24 Vac/dc	(2)	CWTHF 7-0831	X756831	93
Thermocouples K (NiCrNi)	0…+200°C (+32…+392°F) 0…+400°C (+32…+752°F) 0…+600°C (+32…+1112°F)	0...50 / 0...100 Hz 0...1 / 0...10 kHz	3 ways	24 Vac/dc	(2)	CWTHF 7-0871	X756871	93

Notes

(1) programmable input and output signals via software

(2) programmable input and output signals via dip-switch

Auxiliary power supply for sensors and potentiometers


Input	Output	Isolation	Power supply	Notes	Type	Cat. No.	Page
24 Vdc	10 Vdc	2 Vie			CWCV 7-6184	X766184	102

NPN and PNP signal polarity inverter

Input	Output	Isolation	Power supply	Notes	Type	Cat. No.	Page
NPN (17…30 Vdc)	PNP				CI-NPN/PNP	XNPNPNP	103
PNP (17…30 Vdc)	NPN				CI-NPN/PNP	XNPNPNP	103

Programmable analog signal converter

- 19 input scales
- 7 output scales
- 1 SPST (NO) alarm contact
- IN/OUT isolation >3 KVac
- Auxiliary supply output for loop-powered sensors
- Input for potentiometer



CE


TAB.1 - INPUT SELECTION TABLE

INPUT RANGE		SW1 (INPUT)							
UNIPOLAR	BIPOLAR	1	2	3	4	5	6	7	8
0 – 60 mV	± 60 mV								
0 – 100 mV	± 100 mV		●						
0 – 500 mV	± 500 mV			●					
0 – 1 V	± 1 V				●				
0 – 2 V	± 2 V						●		
0 – 5 V	± 5 V			●	●	●	●		
0 – 10 V	± 10 V							●	
0 – 5 mA	± 5 mA	●		●					
0 – 10 mA	± 10 mA	●			●				
0 – 20 mA	± 20 mA	●					●		
4 – 20 mA	—	●				●			●

NOTES

The dimensions include the terminal blocks and the DIN clamp.
(1) The modules in stock are programmed and calibrated with 0 – 10 V and 0 – 15 V output. Modules programmed and calibrated for all other possible configurations can be supplied on request.

BLOCK DIAGRAM



TAB.2 - OUTPUT SELECTION TABLE

OUTPUT RANGE	INPUT TYPE	SW2 (OUTPUT)								SW3
		1	2	3	4	5	6	7	8	
0 – 5 V	UNIP.	X		●				●		U
	BIP.	X	●	●				●	●	U
± 5 V	UNIP.	X			●			●		U
	BIP.	X		●				●		U
0 – 10 V	UNIP.	X		●						U
	BIP.	X	●	●					●	U
± 10 V	UNIP.	X			●					U
	BIP.	X		●						U
0 – 20 mA	UNIP.	X		●				X		I
	BIP.	X	●	●				X	●	I
± 20 mA	UNIP.	X			●			X		I
	BIP.	X		●				X		I
4 – 20 mA	UNIP.	X				●	●	X		I
	BIP.	X	●			●	●	X	●	I

● = ON
= OFF
X = ANY

VERSIONS	Cat. No. XSSAPIP01
	CA-PI/P01
INPUT TECHNICAL DATA	
Input signal (1)	19 programmable ranges (see Table 1)
Impedance voltage / current mode	1 MΩ / 50 Ω
Max. input voltage	15 V
Max. input current	30 mA
OUTPUT TECHNICAL DATA	
Output signal (1)	7 programmable ranges (see Table 2)
Applicable load (voltage / current model)	≥ 10 KΩ / ≤ 500 Ω
Max. output voltage	12 V
Max. output current	25 mA
GENERAL TECHNICAL DATA	
Supply voltage	15...36 Vdc
Rated current	100 mA max. @ 24 Vdc
Auxiliary DC feed output max. current	5 mA @ 5 Vdc / 30mA @ 15 Vdc
Gain error	< 0.1% FS
Offset error	< 0.05 % FS
Linearity error	< 0.1% FS
Zero adjustment / Span adjustment	± 10% FS
Transmission frequency	400Hz...1kHz according to full-scale
Rise time	150 mV / µs
Bandwidth	1 kHz @ -6 dB
Phase delay	< 10 µs
I/O / supply isolation	> 3 KVac / 60 s
Continuous voltage isolation	800 Vac max.
Reference Standard	IEC 664-1, DIN VDE0110.1
Overvoltage category/Pollution degree	III / 2
Operating temperature range	-10... +65°C
Δ T	5°C
Protection degree	IP 20 IEC 529, EN60529
ECM standards	EN 50081-2 , EN 50082-2
Connection terminal	2.5 mm² pluggable screw type (14 AWG)
Housing material	polyamide UL94V-0
Approx. weight	150 g (5.29 oz)
Mounting information	vertical on rail, allow 5 mm spacing between adjacent component
MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—
Plug-in jumper red	—
white	—
blue	—


INPUT STAGE

The module can manage single-pole and two-pole inputs, choosing from among the ranges (see Table 1):

- 0…60 mV ± 60 mV
- 0…100 mV ± 100 mV
- 0…500 mV ± 500 mV
- 0…1 V ± 1 V
- 0…5 V ± 5 V
- 0…10 V ± 10 V
- 0…5 mA ± 5 mA
- 0…10 mA ± 10 mA
- 0…20 mA ± 20 mA
- 4…20 mA

The input stage provides two auxiliary supply outputs, for feeding loop powered sensor and potentiometer directly from the module (5 V and 15 V).

Example of connection:




OUTPUT STAGE

The module supplies in output single-pole and two-pole signals with the following ranges (see Table 2):

- 0…5 V ± 5 V
- 0…10 V ± 10 V
- 0…20 mA ± 20 mA
- 4…20 mA

Programmable analog signal converters


- 3 ways galvanic isolation
- 14 programmable input range
- 3 programmable output range
- Simple programming
- Available version with 24-240 Vac/dc supply voltage



NOTES

The dimensions include the DIN clamp.
(1) Adjustable via rotary-switch
(2) Adjustable via dip-switch
(3) range 16.8…30 Vdc / 19.2…28.8 Vac
(4) range 16.8…264 Vdc / 19.2…264 Vac
(5) 3-way isolation: IN/OUT/power supply

BLOCK DIAGRAM



VERSIONS	Cat. No. X756516	Cat. No. X756517
24 Vac/dc supply voltage	**CWUAA 6-0516**	
24-240 Vac/dc supply voltage		**CWUAA 6-0517**
INPUT TECHNICAL DATA		
Input signal (1)	**0...60 / 0...100 / 0...300 / 0…500 mV** **0…1 / 0…10 / 0…20 / 2…20 V** **0…5 / 0…10 / 0…20 / 4…20 / ±5 / ±20 mA**	**0...60 / 0...100 / 0...300 / 0…500 mV** **0…1 / 0…10 / 0…20 / 2…20 V** **0…5 / 0…10 / 0…20 / 4…20 / ±5 / ±20 mA**
Input resistance	330 KΩ with input voltage 100 Ω with input current	330 KΩ with input voltage 100 Ω with input current
OUTPUT TECHNICAL DATA		
Output signal (2)	**0…10 V** **0…20 / 4…20 mA**	**0…10 V** **0…20 / 4…20 mA**
Applicable load	>1 KΩ with output voltage <400 Ω with output current	>1 KΩ with output voltage <400 Ω with output current
GENERAL TECHNICAL DATA		
Supply voltage	**24 Vac/dc** (3)	**24-240 Vac/dc** (4)
Rated current	≤ 35 mA ± 10% @ 24 Vdc	≤ 35 mA ± 10% @ 24 Vdc
Accuracy	0.1% @ 23°C FS	0.1% @ 23°C FS
Trasmission frequency	< 30 Hz	< 30 Hz
Temperature coefficient	0.02% / K FS	0.02% / K FS
Isolation	1.5 KVac / 60 s (5)	4 KVac / 60 s (5)
ECM standards	EN 50081-2, EN 50082-2	EN 50081-2, EN 50082-2
Reference Standard	IEC 664-1, DIN VDE	IEC 664-1, DIN VDE
Overvoltage category/Pollution degree	III / 2	III / 2
Protection degree	IP 20 IEC 529, EN60529	IP 20 IEC 529, EN60529
Operating temperature range	-25…+60°C	-25…+60°C
Connection terminal	2.5 mm² fixed screw type	2.5 mm² fixed screw type
Housing material	Noryl UL94V-0	Noryl UL94V-0
Approx. weight	65 g (2.29 oz)	75 g (2.65 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap


MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35-7.5		**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32		—
Plug-in jumper	red	—
(16 poles, 16 A)	white	—
	blue	—


APPLICATIONS

Multifunction converters can be used to convert and isolate the most common standard analog signals; the input of the modules can be set up into 14 signal ranges and the output can be set for up to 3 most important analog ranges. The set up is possible by simply switching the position of a dip switch on the side of the module.
The many different input / output combinations offered by multifunctions modules allows to reduce inventory for both new and replacement products and provides many signal conversion solutions.
The “3 ways” galvanic isolation assures total isolation between input, output and supply input; this feature, and the “self calibrating signal circuitry”, gives excellent accuracy without any manual adjustment.
If a single signal must provide several output channels it is possible to use many modules connecting their inputs in parallel as long as the signal is voltage, or in series when signal is current.

Programmable analog signal converters

- 1.5 KV, 3 ways, IN/OUT/supply voltage isolation
- 3 programmable input range
- 3 programmable output range
- Simple programming and self calibrating
- Available version with 24-240 Vac/dc supply voltage







NOTES

The dimensions include the DIN clamp.
(1) range 16.8…30 Vdc / 19.2…28.8 Vac
(2) range 16.8…264 Vdc / 19.2…264 Vac
(3) 3-way isolation: IN/OUT/power supply

BLOCK DIAGRAM



Power supply
24 Vac/dc



Power supply
24...240 Vac/dc

VERSIONS	Cat. No. X756539	Cat. No. X756510
24 Vac/dc supply voltage	**CWNAA-7-0539**	
24-240 Vac/dc supply voltage		**CWNAA-6-0510**
INPUT TECHNICAL DATA		
Input signal	**0…10 V** **0…20 / 4…20 mA**	**0…10 V** **0…20 / 4…20 mA**
Input resistance	330 KΩ with input voltage 100 Ω with input current	330 KΩ with input voltage 100 Ω with input current
OUTPUT TECHNICAL DATA		
Output signal	**0…10 V** **0…20 / 4…20 mA**	**0…10 V** **0…20 / 4…20 mA**
Applicable load	>1 KΩ with output voltage <400 Ω with output current	>1 KΩ with output voltage <400 Ω with output current
GENERAL TECHNICAL DATA		
Supply voltage	**24 Vac/dc** (1)	**24-240 Vac/dc** (2)
Rated current	≤ 35 mA ± 10% @ 24 Vdc	≤ 35 mA ± 10% @ 24 Vdc
Accuracy	0.1% @ 23°C FS	0.1% @ 23°C FS
Trasmission frequency	< 30 Hz	< 30 Hz
Temperature coefficient	0.02% / K FS	0.02% / K FS
Isolation	1.5 KVac / 60 s (3)	4 KVac / 60 s (3)
ECM standards	EN 61000-6-2, EN 61000-6-4	EN 50081-2, EN 50082-2
Reference Standard	IEC 664-1, DIN VDE	IEC 664-1, DIN VDE
Overvoltage category/Pollution degree	III / 2	III / 2
Protection degree	IP 20 IEC 529, EN60529	IP 20 IEC 529, EN60529
Operating temperature range	-25…+60°C	-25…+60°C
Connection terminal	2.5 mm² fixed screw type	2.5 mm² fixed screw type
Housing material	Noryl UL94V-0	Noryl UL94V-0
Approx. weight	40 g (1.41 oz)	75 g (2.65 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap


MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35-7.5		**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	
Mounting rail type according to IEC60715/G32		—	
Plug-in jumper	red	CWBK 7-0802 Cat. No. X766802	—
(16 poles, 16 A)	white	CWBK 7-0803 Cat. No. X766803	—
	blue	CWBK 7-0804 Cat. No. X766804	—

APPLICATIONS

Multi-function converters can be used to convert and isolate the most common standard analog signals; the input and the output can be set up into 3 different signal ranges. The set up is possible by simply switching the position of a dip switch on the side of the module.
The input / output combinations offered by these modules provide the most common input/output configurations more economically when compared to 14 input / 3 output modules and reduces inventory.
If a single signal must provide several output channels it is possible to use many modules connecting their inputs in parallel as long as the signal is voltage, or in series when signal is current.

Programmable analog signal converters


- 2 ways galvanic isolation
- 3 programmable input range
- 3 programmable output range
- Simple programming
- Available version with 24-240 Vac/dc supply voltage



NOTES

The dimensions include the DIN clamp.
(1) Adjustable via dip-switch in model CWNAA 6-0509 and via rotary-switch in model CWNAA 6-0510
(2) range 16.8…30 Vdc / 19.2…28.8 Vac
(3) 2-way isolation: IN/OUT

BLOCK DIAGRAM




VERSIONS	Cat. No. X756509
24 Vac/dc supply voltage	**CWNAA 6-0509**
24-240 Vac/dc supply voltage	
INPUT TECHNICAL DATA	
Input signal (1)	**0…10 V** **0…20 / 4…20 mA**
Input resistance	330 KΩ with input voltage 100 Ω with input current
OUTPUT TECHNICAL DATA	
Output signal (2)	**0…10 V** **0…20 / 4…20 mA**
Applicable load	>1 KΩ with output voltage <400 Ω with output current
GENERAL TECHNICAL DATA	
Supply voltage	**24 Vac/dc** (2)
Rated current	≤ 35 mA ± 10% @ 24 Vdc
Accuracy	0.1% @ 23°C FS
Trasmission frequency	< 30 Hz
Temperature coefficient	0.02% / K FS
Isolation	1.5 KVac / 60 s (3)
ECM standards	EN 50081-2, EN 50082-2
Reference Standard	IEC 664-1, DIN VDE
Overvoltage category/Pollution degree	III / 2
Protection degree	IP 20 IEC 529, EN60529
Operating temperature range	-25…+60°C
Connection terminal	2.5 mm² fixed screw type
Housing material	Noryl UL94V-0
Approx. weight	35 g (1.24 oz)
Mounting information	vertical on rail adjacent without gap
MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—
Plug-in jumper red	—
(16 poles, 16 A) white	—
blue	—

APPLICATIONS

Multi-function converters can be used to convert and isolate the most common standard analog signals; the input and the output can be set up into 3 different signal ranges. The set up is possible by simply switching the position of a dip switch on the side of the module.
The input / output combinations offered by these modules provide the most common input/output configurations more economically when compared to 14 input / 3 output modules and reduces inventory.
The “2 way” galvanic isolation assures isolation only between input and output signal, the supply input has the negative pole in common with the output signal; this feature, and the “self calibrating signal circuitry”, gives excellent accuracy without any manual adjustment.
These modules are the right solution in applications where analog converter are mounted in the same cabinet with PLC, DCS and CN, and when they are powered by the same supply; in this case they allow a cost reduction compared with 3 way fully isolated modules.
If a single signal must provide several output channels it is possible to use many modules connecting their inputs in parallel as long as the signal is voltage, or in series when the signal is current.

Analog signal converters


- 1.5 KV, 3 ways, IN/OUT/supply voltage isolation
- Fixed value
- Compact dimension, 6.2 mm pitch



NOTES

The dimensions include the DIN clamp.
(1) range 16.8…30 Vdc / 19.2…28.8 Vac
(2) 3-way isolation: IN/OUT/power supply

BLOCK DIAGRAM



VERSIONS	Cat. No. X756530	Cat. No. X756531	Cat. No. X756532
IN: 0...10 V / OUT: 0...10 V	**CWAA 7-0530**		
IN: 0...10 V / OUT: 0...20 mA		**CWAA 7-0531**	
IN: 0...10 V / OUT: 4...20 mA			**CWAA 7-0532**
INPUT TECHNICAL DATA			
Input signal	**0…10 V**	**0…10 V**	**0…10 V**
Input resistance	330 KΩ	330 KΩ	330 KΩ
OUTPUT TECHNICAL DATA			
Output signal	**0...10 V**	**0...20 mA**	**4...20 mA**
Applicable load	>1 KΩ	<400 Ω	<400 Ω
GENERAL TECHNICAL DATA			
Supply voltage	24 Vac/dc (1)	24 Vac/dc (1)	24 Vac/dc (1)
Rated current	≤ 13 mA ± 10%	≤ 13 mA ± 10%	≤ 13 mA ± 10%
Accuracy	0.1% @ 23°C FS	0.1% @ 23°C FS	0.1% @ 23°C FS
Trasmission frequency	< 30 Hz	< 30 Hz	< 30 Hz
Temperature coefficient	0.02% / K FS	0.02% / K FS	0.02% / K FS
Isolation	1.5 KVac / 60 s (2)	1.5 KVac / 60 s (2)	1.5 KVac / 60 s (2)
ECM standards	EN 61000-6-2, EN 61000-6-4	EN 61000-6-2, EN 61000-6-4	EN 61000-6-2, EN 61000-6-4
Reference Standard	IEC 664-1, DIN VDE	IEC 664-1, DIN VDE	IEC 664-1, DIN VDE
Overvoltage category/Pollution degree	III / 2	III / 2	III / 2
Protection degree	IP 20 IEC 529, EN60529	IP 20 IEC 529, EN60529	IP 20 IEC 529, EN60529
Operating temperature range	-25…+60°C	-25…+60°C	-25…+60°C
Connection terminal	2.5 mm² fixed screw type	2.5 mm² fixed screw type	2.5 mm² fixed screw type
Housing material	PPE	PPE	PPE
Approx. weight	40 g (1.41 oz)	40 g (1.41 oz)	40 g (1.41 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap	vertical on rail adjacent without gap


MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—
Plug-in jumper red	CWBK 7-0802 Cat. No. X766802
(16 poles, 16 A) white	CWBK 7-0803 Cat. No. X766803
blue	CWBK 7-0804 Cat. No. X766804

APPLICATIONS

These converters can be used to convert and isolate the most common standard analog signals; each model is designed for a single input output signal function, and they are the right solution in applications where many modules handling the same signal are used, where they allow a large cost reduction compared with multi function modules. These modules are provided with 3 ways galvanic isolation between input output and supply voltage. If a single signal must provide several output channels it is possible to use many modules connecting their inputs in parallel as long as the signal is voltage, or in series when the signal is current.

Analog signal converters


- 1.5 KV, 3 ways, IN/OUT/supply voltage isolation
- Fixed value
- Compact dimension, 6.2 mm pitch



NOTES

The dimensions include the DIN clamp.
(1) range 16.8…30 Vdc / 19.2…28.8 Vac
(2) 3-way isolation: IN/OUT/power supply

BLOCK DIAGRAM




VERSIONS	Cat. No. X756533	Cat. No. X756534	Cat. No. X756535
IN: 0...20 mA / OUT: 0...10 V	**CWAA 7-0533**		
IN: 0...20 mA / OUT: 0...20 mA		**CWAA 7-0534**	
IN: 0...20 mA / OUT: 4...20 mA			**CWAA 7-0535**
INPUT TECHNICAL DATA			
Input signal	**0...20 mA**	**0...20 mA**	**0...20 mA**
Input resistance	100 Ω	100 Ω	100 Ω
OUTPUT TECHNICAL DATA			
Output signal	**0...10 V**	**0...20 mA**	**4...20 mA**
Applicable load	>1 KΩ	<400 Ω	<400 Ω
GENERAL TECHNICAL DATA			
Supply voltage	**24 Vac/dc** (1)	**24 Vac/dc** (1)	**24 Vac/dc** (1)
Rated current	≤ 13 mA ± 10%	≤ 13 mA ± 10%	≤ 13 mA ± 10%
Accuracy	0.1% @ 23°C FS	0.1% @ 23°C FS	0.1% @ 23°C FS
Trasmission frequency	< 30 Hz	< 30 Hz	< 30 Hz
Temperature coefficient	0.02% / K FS	0.02% / K FS	0.02% / K FS
Isolation	1.5 KVac / 60 s (2)	1.5 KVac / 60 s (2)	1.5 KVac / 60 s (2)
ECM standards	EN 61000-6-2, EN 61000-6-4	EN 61000-6-2, EN 61000-6-4	EN 61000-6-2, EN 61000-6-4
Reference Standard	IEC 664-1, DIN VDE	IEC 664-1, DIN VDE	IEC 664-1, DIN VDE
Overvoltage category/Pollution degree	III / 2	III / 2	III / 2
Protection degree	IP 20 IEC 529, EN60529	IP 20 IEC 529, EN60529	IP 20 IEC 529, EN60529
Operating temperature range	-25…+60°C	-25…+60°C	-25…+60°C
Connection terminal	2.5 mm² fixed screw type	2.5 mm² fixed screw type	2.5 mm² fixed screw type
Housing material	PPE	PPE	PPE
Approx. weight	40 g (1.41 oz)	40 g (1.41 oz)	40 g (1.41 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap	vertical on rail adjacent without gap
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**		
Mounting rail type according to IEC60715/G32	—		
Plug-in jumper red	CWBK 7-0802 Cat. No. X766802		
(16 poles, 16 A) white	CWBK 7-0803 Cat. No. X766803		
blue	CWBK 7-0804 Cat. No. X766804		

APPLICATIONS

These converters can be used to convert and isolate the most common standard analog signals; each model is designed for a single input output signal function, and they are the right solution in applications where many modules handling the same signal are used, where they allow a large cost reduction compared with multi function modules. These modules are provided with 3 ways galvanic isolation between input output and supply voltage. If a single signal must provide several output channels it is possible to use many modules connecting their inputs in parallel as long as the signal is voltage, or in series when the signal is current.

Analog signal converters


- 1.5 KV, 3 ways, IN/OUT/supply voltage isolation
- Fixed value
- Compact dimension, 6.2 mm pitch



NOTES

The dimensions include the DIN clamp.
(1) range 16.8…30 Vdc / 19.2…28.8 Vac
(2) 3-way isolation: IN/OUT/power supply

BLOCK DIAGRAM



VERSIONS	Cat. No. X756536	Cat. No. X756537	Cat. No. X756538
IN: 4...20 mA / OUT: 0...10 V	**CWAA 7-0536**		
IN: 4...20 mA / OUT: 0...20 mA		**CWAA 7-0537**	
IN: 4...20 mA / OUT: 4...20 mA			**CWAA 7-0538**
INPUT TECHNICAL DATA			
Input signal	**4...20 mA**	**4...20 mA**	**4...20 mA**
Input resistance	100 Ω	100 Ω	100 Ω
OUTPUT TECHNICAL DATA			
Output signal	**0...10 V**	**0...20 mA**	**4...20 mA**
Applicable load	>1 KΩ	<400 Ω	<400 Ω
GENERAL TECHNICAL DATA			
Supply voltage	24 Vac/dc (1)	24 Vac/dc (1)	24 Vac/dc (1)
Rated current	≤ 13 mA ± 10%	≤ 13 mA ± 10%	≤ 13 mA ± 10%
Accuracy	0.1% @ 23°C FS	0.1% @ 23°C FS	0.1% @ 23°C FS
Trasmission frequency	< 30 Hz	< 30 Hz	< 30 Hz
Temperature coefficient	0.02% / K FS	0.02% / K FS	0.02% / K FS
Isolation	1.5 KVac / 60 s (2)	1.5 KVac / 60 s (2)	1.5 KVac / 60 s (2)
ECM standards	EN 61000-6-2, EN 61000-6-4	EN 61000-6-2, EN 61000-6-4	EN 61000-6-2, EN 61000-6-4
Reference Standard	IEC 664-1, DIN VDE	IEC 664-1, DIN VDE	IEC 664-1, DIN VDE
Overvoltage category/Pollution degree	III / 2	III / 2	III / 2
Protection degree	IP 20 IEC 529, EN60529	IP 20 IEC 529, EN60529	IP 20 IEC 529, EN60529
Operating temperature range	-25…+60°C	-25…+60°C	-25…+60°C
Connection terminal	2.5 mm² fixed screw type	2.5 mm² fixed screw type	2.5 mm² fixed screw type
Housing material	PPE	PPE	PPE
Approx. weight	40 g (1.41 oz)	40 g (1.41 oz)	40 g (1.41 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap	vertical on rail adjacent without gap


MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—
Plug-in jumper red	CWBK 7-0802 Cat. No. X766802
(16 poles, 16 A) white	CWBK 7-0803 Cat. No. X766803
blue	CWBK 7-0804 Cat. No. X766804

APPLICATIONS

These converters can be used to convert and isolate the most common standard analog signals; each model is designed for a single input output signal function, and they are the right solution in applications where many modules handling the same signal are used, where they allow a large cost reduction compared with multi function modules. These modules are provided with 3 ways galvanic isolation between input output and supply voltage. If a single signal must provide several output channels it is possible to use many modules connecting their inputs in parallel as long as the signal is voltage, or in series when the signal is current

Analog signal converters


- 2 ways galvanic isolation
- Single signal range
- 6.2 mm pitch



NOTES

The dimensions include the DIN clamp.
(1) range 16.8…30 Vdc / 19.2…28.8 Vac
(2) 2-way isolation: IN/OUT

BLOCK DIAGRAM



VERSIONS	Cat. No. X756500	Cat. No. X756501	Cat. No. X756502
IN: 0... 10 V / OUT: 0...10 V	**CWAA 6-0500**		
IN: 0... 10 V / OUT: 0...20 mA		**CWAA 6-0501**	
IN: 0... 10 V / OUT: 4...20 mA			**CWAA 6-0502**
INPUT TECHNICAL DATA			
Input signal	**0...10 V**	**0...10 V**	**0...10 V**
Input resistance	330 KΩ	330 KΩ	330 KΩ
OUTPUT TECHNICAL DATA			
Output signal	**0...10 V**	**0...20 mA**	**4...20 mA**
Applicable load	>1 KΩ	<400 Ω	<400 Ω
GENERAL TECHNICAL DATA			
Supply voltage	24 Vac/dc (1)	24 Vac/dc (1)	24 Vac/dc (1)
Rated current	≤ 35 mA ± 10% @ 24 Vdc	≤ 35 mA ± 10% @ 24 Vdc	≤ 35 mA ± 10% @ 24 Vdc
Accuracy	0.1% @ 23°C FS	0.1% @ 23°C FS	0.1% @ 23°C FS
Trasmission frequency	< 30 Hz	< 30 Hz	< 30 Hz
Temperature coefficient	0.02% / K FS	0.02% / K FS	0.02% / K FS
Isolation	1.5 KVac / 60 s (2)	1.5 KVac / 60 s (2)	1.5 KVac / 60 s (2)
ECM standards	EN 50081-2, EN 50082-2	EN 50081-2, EN 50082-2	EN 50081-2, EN 50082-2
Reference Standard	IEC 664-1, DIN VDE	IEC 664-1, DIN VDE	IEC 664-1, DIN VDE
Overvoltage category/Pollution degree	III / 2	III / 2	III / 2
Protection degree	IP 20 IEC 529, EN60529	IP 20 IEC 529, EN60529	IP 20 IEC 529, EN60529
Operating temperature range	-25…+60°C	-25…+60°C	-25…+60°C
Connection terminal	2.5 mm² fixed screw type	2.5 mm² fixed screw type	2.5 mm² fixed screw type
Housing material	PPE	PPE	PPE
Approx. weight	35 g (1.24 oz)	35 g (1.24 oz)	35 g (1.24 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap	vertical on rail adjacent without gap


MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35-7.5		**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32		—
Plug-in jumper	red	—
(16 poles, 16 A)	white	—
	blue	—

APPLICATIONS

These converters can be used to convert and isolate the most common standard analog signals; each model is designed for a single input output signal function, and they are the right solution in applications where many modules handling the same signal are used, where they allow a large cost reduction compared with multi function modules. These modules are provided with 3 ways galvanic isolation between input output and supply voltage. If a single signal must provide several output channels it is possible to use many modules connecting their inputs in parallel as long as the signal is voltage, or in series when the signal is current

Analog signal converters


- 2 ways galvanic isolation
- Single signal range
- 6.2 mm pitch



NOTES

The dimensions include the DIN clamp.
(1) range 16.8…30 Vdc / 19.2…28.8 Vac
(2) 2-way isolation: IN/OUT

BLOCK DIAGRAM



VERSIONS	Cat. No. X756503	Cat. No. X756504	Cat. No. X756505
IN: 0...20 mA / OUT: 0...10 V	**CWAA 6-0503**		
IN: 0...20 mA / OUT: 0...20 mA		**CWAA 6-0504**	
IN: 0...20 mA / OUT: 4...20 mA			**CWAA 6-0505**
INPUT TECHNICAL DATA			
Input signal	**0...20 mA**	**0...20 mA**	**0...20 mA**
Input resistance	100 Ω	100 Ω	100 Ω
OUTPUT TECHNICAL DATA			
Output signal	**0...10 V**	**0...20 mA**	**4...20 mA**
Applicable load	>1 KΩ	<400 Ω	<400 Ω
GENERAL TECHNICAL DATA			
Supply voltage	24 Vac/dc (1)	24 Vac/dc (1)	24 Vac/dc (1)
Rated current	≤ 35 mA ± 10% @ 24 Vdc	≤ 35 mA ± 10% @ 24 Vdc	≤ 35 mA ± 10% @ 24 Vdc
Accuracy	0.1% @ 23°C FS	0.1% @ 23°C FS	0.1% @ 23°C FS
Trasmission frequency	< 30 Hz	< 30 Hz	< 30 Hz
Temperature coefficient	0.02% / K FS	0.02% / K FS	0.02% / K FS
Isolation	1.5 KVac / 60 s (2)	1.5 KVac / 60 s (2)	1.5 KVac / 60 s (2)
ECM standards	EN 50081-2, EN 50082-2	EN 50081-2, EN 50082-2	EN 50081-2, EN 50082-2
Reference Standard	IEC 664-1, DIN VDE	IEC 664-1, DIN VDE	IEC 664-1, DIN VDE
Overvoltage category/Pollution degree	III / 2	III / 2	III / 2
Protection degree	IP 20 IEC 529, EN60529	IP 20 IEC 529, EN60529	IP 20 IEC 529, EN60529
Operating temperature range	-25…+60°C	-25…+60°C	-25…+60°C
Connection terminal	2.5 mm² fixed screw type	2.5 mm² fixed screw type	2.5 mm² fixed screw type
Housing material	Noryl UL94V-0	Noryl UL94V-0	Noryl UL94V-0
Approx. weight	35 g (1.24 oz)	35 g (1.24 oz)	35 g (1.24 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap	vertical on rail adjacent without gap


MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	
Mounting rail type according to IEC60715/G32	—	
Plug-in jumper	red	—
(16 poles, 16 A)	white	—
	blue	—

APPLICATIONS

These converters can be used to convert and isolate the most common standard analog signals; each model is designed for a single input output signal function, and they are the right solution in applications where many modules handling the same signal are used, where they allow a large cost reduction compared with multi function modules. These modules are provided with 3 ways galvanic isolation between input output and supply voltage. If a single signal must provide several output channels it is possible to use many modules connecting their inputs in parallel as long as the signal is voltage, or in series when the signal is current

Analog signal converters


- 2 ways galvanic isolation
- Single signal range
- 6.2 mm pitch



NOTES

The dimensions include the DIN clamp.
(1) range 16.8…30 Vdc / 19.2…28.8 Vac
(2) 2-way isolation: IN/OUT

BLOCK DIAGRAM



VERSIONS	Cat. No. X756506	Cat. No. X756507	Cat. No. X756508
IN: 4...20 mA / OUT: 0...10 V	**CWAA 6-0506**		
IN: 4...20 mA / OUT: 0...20 mA		**CWAA 6-0507**	
IN: 4...20 mA / OUT: 4...20 mA			**CWAA 6-0508**
INPUT TECHNICAL DATA			
Input signal	**4…20 mA**	**4…20 mA**	**4…20 mA**
Input resistance	100 Ω	100 Ω	100 Ω
OUTPUT TECHNICAL DATA			
Output signal	**0...10 V**	**0...20 mA**	**4...20 mA**
Applicable load	>1 KΩ	<400 Ω	<400 Ω
GENERAL TECHNICAL DATA			
Supply voltage	24 Vac/dc (1)	24 Vac/dc (1)	24 Vac/dc (1)
Rated current	≤ 35 mA ± 10% @ 24 Vdc	≤ 35 mA ± 10% @ 24 Vdc	≤ 35 mA ± 10% @ 24 Vdc
Accuracy	0.1% @ 23°C FS	0.1% @ 23°C FS	0.1% @ 23°C FS
Trasmission frequency	< 30 Hz	< 30 Hz	< 30 Hz
Temperature coefficient	0.02% / K FS	0.02% / K FS	0.02% / K FS
Isolation	1.5 KVac / 60 s (2)	1.5 KVac / 60 s (2)	1.5 KVac / 60 s (2)
ECM standards	EN 50081-2, EN 50082-2	EN 50081-2, EN 50082-2	EN 50081-2, EN 50082-2
Reference Standard	IEC 664-1, DIN VDE	IEC 664-1, DIN VDE	IEC 664-1, DIN VDE
Overvoltage category/Pollution degree	III / 2	III / 2	III / 2
Protection degree	IP 20 IEC 529, EN60529	IP 20 IEC 529, EN60529	IP 20 IEC 529, EN60529
Operating temperature range	-25…+60°C	-25…+60°C	-25…+60°C
Connection terminal	2.5 mm² fixed screw type	2.5 mm² fixed screw type	2.5 mm² fixed screw type
Housing material	Noryl UL94V-0	Noryl UL94V-0	Noryl UL94V-0
Approx. weight	35 g (1.24 oz)	35 g (1.24 oz)	35 g (1.24 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap	vertical on rail adjacent without gap


MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—
Plug-in jumper red	—
(16 poles, 16 A) white	—
blue	—


APPLICATIONS

These converters can be used to convert and isolate the most common standard analog signals; each model is designed for a single input output signal function, and they are the right solution in applications where many modules handling the same signal are used, where they allow a large cost reduction compared with multi function modules. These modules are provided with 3 ways galvanic isolation between input output and supply voltage. If a single signal must provide several output channels it is possible to use many modules connecting their inputs in parallel as long as the signal is voltage, or in series when the signal is current

Passive galvanic isolators

- Do not require power supply
- Suitable for loop powered sensors
- 2 Ways I/O 500 V isolation
- Single and double channel version
- Compact dimension, 6.2 mm pitch







NOTES

The dimensions include the DIN clamp.
(1) Input voltage must have a value higher than the value calculated with this formula, where Rb is load resistance (see pic.1); for calculation refer to the diagram comparing minimum input voltage with output load and wires resistance values; refer to the diagram (see pic. 2) to define if application conditions allow to get full 20 mA output signal
(2) 2-way isolation: IN/OUT

BLOCK DIAGRAM





Item available till sell-out

VERSIONS	Cat. No. X756526	Cat. No. X756527
Single channel	**CWPAA 7-0526**	
Double channel		**CWPAA 7-0527**
INPUT TECHNICAL DATA		
Input signal	1 channel 0…20 mA, 4…20 mA	2 channels 0…20 mA, 4…20 mA
Input current	—	—
Input voltage (1)	2.7 + (20 mA x Rb)	2.7 + (20 mA x Rb)
Input resistance	100 Ω	100 Ω
OUTPUT TECHNICAL DATA		
Output signal	1 channel 0…20 / 4…20 mA, (max 21 mA)	2 channels 0…20 / 4…20 mA, (max 21 mA)
Applicable load	<400 Ω with output current	<400 Ω with output current
GENERAL TECHNICAL DATA		
Supply voltage	—	—
Rated current	12 mA	12 mA
Accuracy	0.1 FS (23°C)	0.1 FS (23°C)
Rise time (10..90%)	10 ms	10 ms
Trasmission frequency	30 Hz @ 3 dB	30 Hz @ 3 dB
Temperature coefficient	0.02% FS	0.02% FS
Isolation	1.5 KVac / 60 s (2)	1.5 KVac / 60 s (2)
ECM standards	EN 61000-6-2, EN 61000-6-4	EN 61000-6-2, EN 61000-6-4
Reference Standard	IED 664-1, DIN VDE	IED 664-1, DIN VDE
Overvoltage category/Pollution degree	III / 2	III / 2
Protection degree	IP 20 IEC 529 EN60529	IP 20 IEC 529 EN60529
Operating temperature range	-25…+60°C	-25…+60°C
Connection terminal	1.5 mm² fixed screw type	1.5 mm² fixed screw type
Housing material	Luranyl	Luranyl
Approx. weight	35 g (1.24 oz)	35 g (1.24 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap
MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	
Mounting rail type according to IEC60715/G32	—	
Plug-in jumper red	CWBK 7-0802 Cat. No. X766802	
(16 poles, 16 A) white	CWBK 7-0803 Cat. No. X766803	
blue	CWBK 7-0804 Cat. No. X766804	

APPLICATIONS

The passive galvanic isolators can isolate the signal generated by loop powered sensors, where the applied load must have a resistance lower than 400 Ω 20 mA, including the cable resistance; the applied input voltage has to be higher than 2.7 V compared with output voltage (see note 2). If above conditions are satisfied, passive isolators reduce cabling costs and eliminate power supplies thereby saving costs. If above conditions are not satisfied, passive module introduces a signal attenuation.

figure 1







figure 2



Analog signal to frequency converters

- 2 and 3 ways galvanic isolation
- 3 programmable analog signals input ranges
- 4 programmable frequency output ranges
- Simple programming
- Version with 24-240 Vac/dc supply voltage







NOTES

The dimensions include the DIN clamp.
(1) Adjustable via dip-switch in model CWNAF 6-0511 and via rotary-switch in model CWNAF 6-0512
(2) range 16.8…30 Vdc / 19.2…28.8 Vac
(3) range 16.8…264 Vdc / 19.2…264 Vac
(4) 2-way isolation: IN/OUT
(5) 3-way isolation: IN/OUT/power supply

BLOCK DIAGRAM





VERSIONS	Cat. No. X756511	Cat. No. X756512
24 Vac/dc supply voltage	**CWNAF 6-0511**	
24-240 Vac/dc supply voltage		**CWNAF 6-0512**
INPUT TECHNICAL DATA		
Input signal	0…10 V 0…20 / 4…20 mA	0…10 V 0…20 / 4…20 mA
Input current	—	—
Input voltage (1)	—	—
Input resistance	330 KΩ with input voltage 100 Ω with input current	330 KΩ with input voltage 100 Ω with input current
OUTPUT TECHNICAL DATA		
Output signal	0…50 / 0…100 / 0…1000 / 0…10000 Hz	0…50 / 0…100 / 0…1000 / 0…10000 Hz
Applicable load	20.9 V / 10 mA with 24 Vdc supply voltage	20.9 V / 10 mA with 24 Vdc supply voltage
GENERAL TECHNICAL DATA		
Supply voltage	24 Vac/dc (2)	24-240 Vac/dc (3)
Rated current	≤ 43mA ± 10% @ 24 Vdc	≤ 43 mA ± 10% @ 24 Vdc
Accuracy	0.1% @ 23°C FS	0.1% @ 23°C FS
Trasmission frequency	<30 Hz	<30 Hz
Temperature coefficient	0.015% / K FS	0.015% / K FS
Isolation	1.5 KVac / 60 s (4)	4 KVac / 60 s (5)
ECM standards	EN 50081-2, EN 50082-2	EN 50081-2, EN 50082-2
Reference Standard	IEC 664-1, DIN VDE	IEC 664-1, DIN VDE
Overvoltage category/Pollution degree	III / 2	III / 2
Protection degree	IP20	IP20
Operating temperature range	-20…+60°C	-20…+60°C
Connection terminal	2.5 mm² fixed screw type	2.5 mm² fixed screw type
Housing material	Noryl UL94V-0	Noryl UL94V-0
Approx. weight	35 g (1.24 oz)	50 g (1.77 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap

MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35-7.5		**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32		—
Plug-in jumper	red	—
(16 poles, 16 A)	white	—
	blue	—

APPLICATIONS

These modules converts an analog signal into a 24V square wave frequency signal. They can be used to control motor drives, speed counters and in all those cases where an analog signal must be converted into a frequency. High input sensitivity and high accuracy conversion make it possible to convert into a stable and accurate frequency, the lowest input signals of few mV.

Programmable converters for temperature sensors

- For PT100, PT500, PT1000, Ni100, Ni1000, PTC, KTY sensors, thermocouples, potentiometers
- 3 ways I/O 2.5 KV isolation
- 3 programmable output signals
- Simple programming, self-adjusting zero and span
- Compact dimension, 6.2 mm pitch







CE

NOTES

The dimensions include the DIN clamp.
(1) Version with spring-clamp terminals available on request
(2) 3-way isolation: IN/OUT/power supply

BLOCK DIAGRAM





VERSIONS

	Cat. No. X756890	Cat. No. X756891
With screw terminals (standard)	**CWTPR 7-0890**	
With spring terminals	**(1)**	
Programming tool		**CWPZB 7-0891**

INPUT TECHNICAL DATA

Input signal	PT100, PT500, PT1000, Ni100, Ni1000, PTC, KTY, potentiometers 0…5 KΩ thermocouples tipo B, C, D, E, J, K, L, N, R, S, T, U
Temperature range	-200…+2400°C, according to sensor (see table)

OUTPUT TECHNICAL DATA

Output signal	0…10 / 2…10 V, (max. 10.6 V) 0…20 / 4…20 mA, (max 21.2 mA)
Applicable load	>2 KΩ with output voltage <400 Ω with output current
Display signals	green LED = OK , flashing LED = error

GENERAL TECHNICAL DATA

Supply voltage	15...36 Vdc	
Rated current	100 mA max. @ 24 Vdc	
	PT, Ni, PTC, KTY, potentiometers	**Thermocouples**
Linearity error	±0.03% over FS	—
Temperature coefficient	<30 ppm/°C	—
Resolution	0.1°C, 16 bit	—
Connection terminals	PT2, 3, 4-wire; with 2-wire offset correction measurement	—
Input resistance	—	1 MΩ approx.
Transmission frequency	—	0.5 Hz
Isolation	2.5 KVac / 60 s (2)	
ECM standards	EN 61000-6-2, EN 61000-6-4	
Reference Standard	IEC 664-1, DIN VDE	
Overvoltage category	III	
Pollution degree	2	
Protection degree	IP 20 IEC 529 EN60529	
Operating temperature	-25…+60°C	
Connection terminal	1.5 mm² fixed screw type	
Housing material	PPE	
Approx. weight	40 g (1.41 oz)	
Mounting information	vertical on rail adjacent without gap	

MOUNTING ACCESSORIES

Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—
Plug-in jumper red	CWBK 7-0802 Cat. No. X766802
white	CWBK 7-0803 Cat. No. X766803
blue	CWBK 7-0804 Cat. No. X766804

APPLICATIONS


CSWTPR 7-0890 is a temperature to analog signal conversion module that provides high accuracy measurement and that can be connected to a really wide range of temperature sensors. The module can be used for a temperature range from -200 to + 2.400°C. In case of failure of the sensor or short circuits on the cable, the module generates a signal that allows to get a back up safety function.
With resistive sensors it is possible to select among 2, 3, 4 wire connections. With 3 or 4 wires sensors it assures the "broken wire" function and a short circuit on sensor cables. It is also possible the redundant connection of thermocouples to the module, to increase reliability of the measurement system. Input and output are provided with over voltage protections.

TABLE 1 - Temperature range

B type	0…+1820°C
C type	0…+2300°C
D type	0…+2400°C
E type	-200…+1000°C
J type	-200…+1200°C
K type	-200…+1372°C
L type	-200…+900°C
N type	-200…+1300°C
R type	-50…+1760°C
S type	-50…+1760°C
T type	-200…+400°C
U type	-200…+400°C
PT100	-200…+850°C
PT500	-200…+850°C
PT1000	-200…+850°C
Ni1000	-58…+208°C
KTY 81-110	-58…+150°C
KTY 81-120	-58…+150°C
KTY 81-121	-58…+150°C
KTY 82-122	-58…+150°C
KTY 82-150	-58…+150°C
KTY 82-151	-58…+150°C
KTY 82-152	-58…+150°C
KTY 83-110	-58…+150°C
KTY 83-120	-58…+150°C
KTY 83-121	-58…+150°C
KTY 83-122	-58…+150°C
KTY 83-150	-58…+150°C
KTY 83-151	-58…+150°C
KTY 83-152	-58…+150°C
KTY 84-130	-40…+300°C
KTY 84-150	-40…+300°C
KTY 84-151	-40…+300°C
KTY 84-152	-40…+300°C

Programmable converters for RTD sensors


- Converters for PT100 sensors
- 3 ways galvanic isolation
- 8 programmable input range
- 3 programmable output range
- Simple programming
- Version with 24-240 Vac/dc supply voltage



NOTES

The dimensions include the DIN clamp.
(1) Adjustable via rotary-switch
(2) Adjustable via dip-switch
(3) They can also be used with 2 wire PT100 sensor, connecting the terminals 1 and 4
(4) range 16.8…30 Vdc / 19.2…28.8 Vac
(5) range 16.8…264 Vdc / 19.2…264 Vac
(6) 3-way isolation: IN/OUT/power supply

BLOCK DIAGRAM




VERSIONS	Cat. No. X756816	Cat. No. X756817
24 Vac/dc supply voltage	**CWPT 6-0816**	
24-240 Vac/dc supply voltage		**CWPT 6-0817**
INPUT TECHNICAL DATA		
Input signal	PT100 3 wires (3)	PT100 3 wires (3)
Temperature range (1)	-50…+50°C (-58…+122°F) -50…+100°C (-58…+212°F) -50…+150°C (-58…+302°F) 0…+100°C (+32…+212°F) 0…+150°C (+32…+302°F) 0…+200°C (+32…+392°F) 0…+300°C (+32…+572°F) 0…+400°C (+32…+752°F)	-50…+50°C (-58…+122°F) -50…+100°C (-58…+212°F) -50…+150°C (-58…+302°F) 0…+100°C (+32…+212°F) 0…+150°C (+32…+302°F) 0…+200°C (+32…+392°F) 0…+300°C (+32…+572°F) 0…+400°C (+32…+752°F)
Supply current	0.5 mA	0.5 mA
OUTPUT TECHNICAL DATA		
Output signal (2)	0…10 V 0…20 / 4…20 mA	0…10 V 0…20 / 4…20 mA
Applicable load	>1 KΩ with output voltage, <400 Ω with output current	>1 KΩ with output voltage, <400 Ω with output current
GENERAL TECHNICAL DATA		
Supply voltage	24 Vac/dc (2)	24-240 Vac/dc (3)
Rated current	≤ 35 mA ± 10% @ 24 Vdc	≤ 35 mA ± 10% @ 24 Vdc
Accuracy	<0.3% FS	<0.3% FS
Trasmission frequency	<30 Hz	<30 Hz
Temperature coefficient	0.015% / K FS	0.015% / K FS
Isolation	1.5 KVac / 60 s (6)	4 KVac / 60 s (6)
ECM standards	EN 50081-2, EN 50082-2	EN 50081-2, EN 50082-2
Reference Standard	IEC 664-1, DIN VDE	IEC 664-1, DIN VDE
Overvoltage category/Pollution degree	III / 2	III / 2
Protection degree	IP20	IP20
Operating temperature range	-20…+60°C	-20…+60°C
Connection terminal	2.5 mm² fixed screw type	2.5 mm² fixed screw type
Housing material	Noryl UL94V-0	Noryl UL94V-0
Approx. weight	75 g (2.65 oz)	85 g (3.00 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap
MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	
Mounting rail type according to IEC60715/G32	—	
Plug-in jumper red	—	
(16 poles, 16 A) white	—	
blue	—	

APPLICATIONS

The modules convert and isolate signals generated by 3 wire / 2 wire PT100 (RTD) sensors into analog signals; the module can be set into 8 temperature ranges and for up to 3 most important analog ranges.
Set up is easily achieved by setting a dip-switch on one side of the module.
The modules provide input and output isolation, assuring high signal accuracy, and can be used with isolated and not isolated sensors.
Two wire sensors can be used by connecting a jumper wire between 1 and 4 terminal blocks.

Programmable converters for thermocouples


- Converters for sensors with thermocouples J and K type
- 3 ways galvanic isolation
- 8 programmable input range
- 3 programmable output range
- Simple programming
- Version with 24-240 Vac/dc supply voltage




NOTES

The dimensions include the DIN clamp.
(1) Adjustable via rotary-switch
(2) Adjustable via dip-switch
(3) range 16.8…30 Vdc / 19.2…28.8 Vac
(4) range 16.8…264 Vdc / 19.2…264 Vac
(5) "3-way isolation: IN/OUT/power supply

BLOCK DIAGRAM



Supply voltage
24 Vac/dc



Supply voltage
24…240 Vac/dc

VERSIONS	Cat. No. X756844	Cat. No. X756847
24 Vac/dc supply voltage	**CWTH 6-0844**	
24-240 Vac/dc supply voltage		**CWTH 6-0847**
INPUT TECHNICAL DATA		
Input signal	thermocouples FeCuNi (J type) e NiCrNi (K type) according to DIN/IEC584-1	thermocouples FeCuNi (J type) e NiCrNi (K type) according to DIN/IEC584-1
Temperature range (1)	-50…+200°C (-58…+392°F) -50…+350°C (-58 …+662°F) 0…+200°C (+32…+392°F) 0…+400°C (+32…+752°F) 0…+600°C (+32…+1112°F) 0…+800°C (+32…+1472°F) 0…+1000°C (+32…+1832°F) 0…+1200°C (+32…+2192°F)	-50…+200°C (-58…+392°F) -50…+350°C (-58 …+662°F) 0…+200°C (+32…+392°F) 0…+400°C (+32…+752°F) 0…+600°C (+32…+1112°F) 0…+800°C (+32…+1472°F) 0…+1000°C (+32…+1832°F) 0…+1200°C (+32…+2192°F)
Supply current	—	—
OUTPUT TECHNICAL DATA		
Output signal (2)	0…10 V 0…20 / 4…20 mA	0…10 V 0…20 / 4…20 mA
Applicable load	>1 KΩ with output voltage, <400 Ω with output current	>1 KΩ with output voltage, <400 Ω with output current
GENERAL TECHNICAL DATA		
Supply voltage	24 Vac/dc (3)	24-240 Vac/dc (4)
Rated current	≤ 35 mA ± 10% @ 24 Vdc	≤ 35 mA ± 10% @ 24 Vdc
Accuracy	<0.5% FS	<0.5% FS
Trasmission frequency	<30 Hz	<30 Hz
Temperature coefficient	0.015% / K FS	0.015% / K FS
Isolation	1.5 KVac / 60 s (5)	4 KVac / 60 s (5)
ECM standards	EN 50081-2, EN 50082-2	EN 50081-2, EN 50082-2
Reference Standard	IEC 664-1, DIN VDE	IEC 664-1, DIN VDE
Overvoltage category/Pollution degree	III / 2	III / 2
Protection degree	IP20	IP20
Operating temperature range	-20…+60°C	-20…+60°C
Connection terminal	2.5 mm² fixed screw type	2.5 mm² fixed screw type
Housing material	Noryl UL94V-0	Noryl UL94V-0
Approx. weight	65 g (2.29 oz)	75 g (2.65 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap
MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	
Mounting rail type according to IEC60715/G32	—	
Plug-in jumper red	—	
(16 poles, 16 A) white	—	
blue	—	

APPLICATIONS

The modules convert and isolate signals generated by thermocouples type J (FeCuNi) or K (NiCrNi) into an analog signal; can be set into 8 temperature input ranges, and can be set for up to 3 most important analog ranges. The set up is possible by setting a dip-witch on one side of the module.
The modules provide input and output isolation, assuring high signal accuracy, and can be used with isolated and not isolated sensors.

Temperature / frequency converters


- Available for PT100 sensors, and thermocouples J or K
- 3 ways I/O 1.5 KV isolation
- 3 programmable temperature input range
- 4 programmable frequency output range
- Simple programming, self-adjusting zero and span
- Compact dimension, 6.2 mm pitch



NOTES

The dimensions include the DIN clamp.
(1) range 20…30 Vdc
(2) 3-way isolation: IN/OUT/power supply

BLOCK DIAGRAM



Supply voltage 24 Vac/dc | Supply voltage 24 Vac/dc | Supply voltage 24 Vac/dc


VERSIONS	Cat. No. X756811	Cat. No. X756831	Cat. No. X756871
PT100 / Frequency	**CWTHF 7-0811**		
Termocoppia J / Frequency		**CWTHF 7-0831**	
Termocoppia K / Frequency			**CWTHF 7-0871**
INPUT TECHNICAL DATA			
Input signal	PT100 (2 wire)	Thermocouples J type	Thermocouples K type
Temperature range	-50…+150°C 0…+200°C 0…+400°C	0…+200°C 0…+400°C 0…+600°C	0…+200°C 0…+400°C 0…+600°C
Input current	0.5 mA	—	—
OUTPUT TECHNICAL DATA			
Output signal	0…50 Hz / 0…100 Hz / 0…1 KHz / 0…10 KHz	0…50 Hz / 0…100 Hz / 0…1 KHz / 0…10 KHz	0…50 Hz / 0…100 Hz / 0…1 KHz / 0…10 KHz
Applicable load	>2.5 KΩ (amplitude approx. 10 V)	>2.5 KΩ (amplitude approx. 10 V)	>2.5 KΩ (amplitude approx. 10 V)
GENERAL TECHNICAL DATA			
Supply voltage	24 Vac/dc (1)	24 Vac/dc (1)	24 Vac/dc (1)
Rated current	30 mA max	30 mA max	30 mA max
Accuracy	75x811: 0.3% FS; 75x831/871: 0.5% +2 K FS	75x811: 0.3% FS; 75x831/871: 0.5% +2 K FS	75x811: 0.3% FS; 75x831/871: 0.5% +2 K FS
Linearity error	0.1% FS	0.1% FS	0.1% FS
Rise time (10…90%)	depends on frequency	depends on frequency	depends on frequency
Setting time to accuracy 1%	depends on frequency	depends on frequency	depends on frequency
Trasmission frequency	<30 Hz	<30 Hz	<30 Hz
Temperature coefficient	150 ppm/K FS	150 ppm/K FS	150 ppm/K FS
Isolation	1.5 KVac / 60 s (2)	1.5 KVac / 60 s (2)	1.5 KVac / 60 s (2)
ECM standards	EN 60721-3-3; EN 55011; EN 61000-4-2/6; EN 50178	EN 60721-3-3; EN 55011; EN 61000-4-2/6; EN 50178	EN 60721-3-3; EN 55011; EN 61000-4-2/6; EN 50178
Reference Standard	IED 664-1, DIN VDE	IED 664-1, DIN VDE	IED 664-1, DIN VDE
Overvoltage category/Pollution degree	III / 2	III / 2	III / 2
Protection degree	IP 20 IEC 529 EN60529	IP 20 IEC 529 EN60529	IP 20 IEC 529 EN60529
Operating temperature range	-25…+60°C	-25…+60°C	-25…+60°C
Connection terminal	1.5 mm² fixed screw type	1.5 mm² fixed screw type	1.5 mm² fixed screw type
Housing material	PPE	PPE	PPE
Approx. weight	40 g (1.41 oz)	40 g (1.41 oz)	40 g (1.41 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap	vertical on rail adjacent without gap
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**		
Mounting rail type according to IEC60715/G32	—		
Plug-in jumper (16 poles, 16 A) red	CWBK 7-0802 Cat. No. X766802		
white	CWBK 7-0803 Cat. No. X766803		
blue	CWBK 7-0804 Cat. No. X766804		


APPLICATIONS

Small control systems are used in simple applications. For economical reasons they often integrate digital inputs instead of analog inputs
The Temperature/Frequency converters offer a simple and economical solution to measure and convert temperatures, exploiting the digital inputs of the small control systems

Current to threshold converters

- For AC current measure
- Adjustable threshold value
- Versions with transistor or relay output
- IN/OUT 3 KV isolation







NOTES

The dimensions include the terminal blocks and the DIN clamp.

BLOCK DIAGRAM






VERSIONS	Cat. No. XCCIS1	Cat. No. XCCIS-R
Transistor output	**CCIS-1**	
Relay output		**CCIS-R**
INPUT TECHNICAL DATA		
Max. measured current	50 A (AC)	50 A (AC)
Max. measured voltage	600 Vac	600 Vac
Frequency	50…60 Hz	50…60 Hz
Sensor's hole diameter	Ø 13 mm	Ø 13 mm
OUTPUT TECHNICAL DATA		
Threshold regulation	1…30 A	1…30 A
Threshold hysteresis	± 10%	± 10%
Max. output current	100 mA open collector PNP	100 mA open collector PNP
Output status	"high" 24 V (closed) with I < threshold "low" 0 V (open) with I > threshold	"high" 24 V (closed) with I < threshold "low" 0 V (open) with I > threshold
Response time	20 ms	20 ms
GENERAL TECHNICAL DATA		
Supply voltage	24 Vdc ± 10%	24 Vdc ± 10%
Max rated current	100 mA	100 mA
Operating temperature range	0…60°C	0…60°C
Input/output isolation	> 3 KVac /60 s	> 3 KVac /60 s
Connection terminal	2.5 mm^2 fixed screw type (14 AWG)	2.5 mm^2 fixed screw type (14 AWG)
Housing material	polyamide UL94V-03	polyamide UL94V-03
Approx. weight	100 g (3.53 oz)	100 g (3.53 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap
MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35	**PR/3/AC, PR/3/AS**	
Mounting rail type according to IEC60715/G32	**PR/DIN/AC, PR/DIN/AS, PR/DIN/AL**	
Plug-in jumper red	—	
(16 poles, 16 A) white	—	
blue	—	

APPLICATIONS

This module converts a current flowing through circuit into a threshold that can be adjusted by the potentiometer; when the current reaches the threshold value, the relay (or the transistor in the CCIS model) switches; the wire must be feed through the hole of the current sensor for current detection.
In model CCIS-1 the output will have "high" value (24 Vdc) for current higher than the threshold and "low" value (0 Vdc) for current lower than the threshold. The output is internally re-hooked to ground through a 10 k resistor, besides it is protected against overloads.
In model CCIS-R the relay will be turned on for current below the threshold, turned off for current over the threshold.
The output has all the contacts of an SPDT relay, the relay is also pluggable to allow its substitution in case of wear of the contacts.

Current to analog converters

- For AC/DC current measurements
- Protected against transients
- Power supplied LED
- 3 output signals available




CE

NOTES

The dimensions include the terminal blocks and the DIN clamp.

BLOCK DIAGRAM



VERSIONS	Cat. No. XW000928	Cat. No. XW000929	Cat. No. XW000930
0…1 A input	**SW01VA**		
0…5 A input		**SW05VA**	
0…10 A input			**SW10VA**
INPUT TECHNICAL DATA			
Input signal	0…1 A AC/DC	0…5 A AC/DC	0…10 A AC/DC
Max. input voltage	380 V	380 V	380 V
Current wire connection	2.5 mm² pluggable screw type	2.5 mm² pluggable screw type	2.5 mm² pluggable screw type
OUTPUT TECHNICAL DATA	**VOLTAGE**	**CURRENT**	
Output signal	0…10 V	0…20 mA / 4…20 mA	
Max. output signal	11 V	22 mA	
Applicable load	>2 KΩ	<500 Ω	
GENERAL TECHNICAL DATA			
Supply voltage	24 Vdc ± 10%	24 Vdc ± 10%	24 Vdc ± 10%
Rated current	60 mA	60 mA	60 mA
Operating temperature	0…55°C	0…55°C	0…55°C
Linearity error	< 0.5%	< 0.5%	< 0.5%
Offset error	< 0.5%	< 0.5%	< 0.5%
Amplification error	< 0.2%	< 0.2%	< 0.2%
Temperature coefficient	< 0.02%/K	< 0.02%/K	< 0.02%/K
Surge immunity	200 V	200 V	200 V
Response time	10 mS	10 mS	10 mS
Protection degree	IP20	IP20	IP20
Connection terminal	2.5 mm² pluggable screw type	2.5 mm² pluggable screw type	2.5 mm² pluggable screw type
Approx. weight	100 g (3.53 oz)	100 g (3.53 oz)	100 g (3.53 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap	vertical on rail adjacent without gap


MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35-7.5		**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32		—
Plug-in jumper	red	—
(16 poles, 16 A)	white	—
	blue	—

APPLICATIONS

In 99 mm depth measure is included the space occupied by the terminal block provided with the product. Through a "HALL" sensor they grant AC/DC current measurements.
The presence of current in a circuit indicates not only that power is supplied but also that the circuit is closed and the load connected and active.
It's also possible to know the work conditions of the circuit.
The module guarantees galvanic isolation between the current conductor and the analog output and, if not connected in series to the controlled current, cannot be damaged by power surges or short circuits.

Current to analog converters

- For AC/DC current measurements
- Protected against transients
- Power supplied LED
- 3 output signals available




CE

NOTES

The dimensions include the terminal blocks and the DIN clamp.

BLOCK DIAGRAM



VERSIONS	Cat. No. XW000931	Cat. No. XW000932
0…20 A input	**SW20VA**	
0…50 A input		**SW50VA**
INPUT TECHNICAL DATA		
Input signal	0…20 A AC/DC	0…50 A AC/DC
Max. input voltage	380 V	380 V
Current wire connection	Ø 8 mm	Ø 8 mm

OUTPUT TECHNICAL DATA	VOLTAGE	CURRENT
Output signal	0…10 V	0…20 mA / 4…20 mA
Max. output signal	11 V	22 mA
Applicable load	>2 KΩ	<500 Ω

GENERAL TECHNICAL DATA		
Supply voltage	24 Vdc ± 10%	24 Vdc ± 10%
Rated current	60 mA	60 mA
Operating temperature	0…55°C	0…55°C
Linearity error	< 0.5%	< 0.5%
Offset error	< 0.5%	< 0.5%
Amplification error	< 0.2%	< 0.2%
Temperature coefficient	< 0.02%/K	< 0.02%/K
Surge immunity	200 V	200 V
Response time	10 mS	10 mS
Protection degree	IP20	IP20
Connection terminal	2.5 mm² pluggable screw type (14 AWG)	2.5 mm² pluggable screw type (14 AWG)
Approx. weight	100 g (3.53 oz)	100 g (3.53 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap


MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35		**PR/3/AC, PR/3/AS**
Mounting rail type according to IEC60715/G32		**PR/DIN/AC, PR/DIN/AS, PR/DIN/AL**
Plug-in jumper	red	—
(16 poles, 16 A)	white	—
	blue	—

APPLICATIONS

In 99 mm depth measure is included the space occupied by the terminal block provided with the product.
They allow the user to measure AC/DC currents by an “HALL” sensor.
The presence of current in a circuit indicates not only that power is supplied but also that the circuit is closed and the load connected and active. It is also possible to know the working conditions of the controlled circuit.
The module guarantees galvanic isolation between the current conductor and the analog output and, if not connected in series to the controlled current, cannot be damaged by power surges or short circuits.

Frequency to analog signal converters

- Adjustable frequency range 0...28.8 Khz
- 3 programmable analog signal output ranges
- 3 ways I/O 2.5 KV isolation




CE

NOTES

The dimensions include the terminal blocks and the DIN clamp.
(1) range 16.8…30 Vdc / 19.2…28.8 Vac
(2) 3-way isolation: IN/OUT

BLOCK DIAGRAM



Voltage supply
24…240 Vac/dc


VERSIONS	Cat. No. X756524
	CWNFA 6-0524
INPUT TECHNICAL DATA	
Input signal (range)	0…28.8 KHz adjustable via DIP switch
Input signal (type)	AC/DC 0.6…30 Vpp
Input resistance	50 KΩ
Hysteresis	0.5 Vpp o 5 Vpp adjustable via DIP switch
OUTPUT TECHNICAL DATA	
Output signal	0…10 V, (max. 10.6 V) 0…20 / 4…20 mA, (max 21 mA)
Applicable load	>1 KΩ with output voltage <400 Ω with output current
Ripple	< 5 mVeff
GENERAL TECHNICAL DATA	
Supply voltage	24 Vac/dc (1)
Rated current	20 mA
Accuracy	0.1 FS (23°C)
Linearity error	0.02%
Ripple	0.1%
Setting time (accuracy 1%)	200 ms
Temperature coefficient	70 ppm/K
Isolation	1.5 KVac / 60 s (2)
ECM standards	EN 61000-6-2, EN 61000-6-4
Reference Standard	IED 664-1, DIN VDE
Overvoltage category	III
Pollution degree	2
Protection degree	IP 20 IEC 529 EN60529
Operating temperature range	-25…+60°C
Connection terminal	1.5 mm² fixed screw type
Housing material	PPE
Peso approssmativo	70 g (2.47 oz)
Mounting information	vertical on rail adjacent without gap
MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail type according to IEC60715/G32	—
Plug-in jumper red	—
white	—
blue	—

APPLICATIONS

This module is used to convert a frequancy signal, with either sinusoidal or square waveform, into a standard analog signal (eg. 0…10 V, 0..20 mA, 4…20 mA). A microprocessor provides a high resolution, high stability and accuracy output signal and a dip switch gives the possibility to select a calibrated range of frequency measurement from 0 … 100 Hz up to 0…28.8 kHz.

Analog to digital signal converters

- 8 bit resolution
- Possibility of connection in parallel
- Protected against transients
- Power supplied LED
- Pluggable terminals




Item available till sell-out

NOTES

The dimensions include the terminal blocks and the DIN clamp.

BLOCK DIAGRAM




VERSIONS	Cat. No. XW000933	Cat. No. XW000934	Cat. No. XW000935
IN: 0... 10 V / OUT: 8 bit	**ADC08V10**		
IN: 0...20 mA / OUT: 8 bit		**ADC08A0**	
IN: 4...20 mA / OUT: 8 bit			**ADC08A4**
INPUT TECHNICAL DATA			
Input signal	0…10 V	0…20 mA	4…20 mA
Resistance	400 KΩ	400 KΩ	400 KΩ
OUTPUT TECHNICAL DATA			
Output signal	8 bit	8 bit	8 bit
Max. output signal	25 mA	25 mA	25 mA
Signal level	"L" = 0, "H" = V_{IN} - 2 V	"L" = 0, "H" = V_{IN} - 2 V	"L" = 0, "H" = V_{IN} - 2 V
GENERAL TECHNICAL DATA			
Supply voltage	24 Vdc ± 10%	24 Vdc ± 10%	24 Vdc ± 10%
Rated current	25 mA	25 mA	25 mA
Operating temperature	0…55°C	0…55°C	0…55°C
Trasmission error	±1 LSB	±1 LSB	±1 LSB
Hold signal	enabled > 5 V	enabled > 5 V	enabled > 5 V
Bus signal	enabled > 5 V	enabled > 5 V	enabled > 5 V
Conversion time	1.5 ms	1.5 ms	1.5 ms
Resolution	39 mV	78 µA	63 µA
Temperature coefficient	0.01% k	0.01% k	0.01% k
Surge immunity	200 V	200 V	200 V
Protection degree	IP20	IP20	IP20
Connection terminal	2.5 mm² pluggable screw type	2.5 mm² pluggable screw type	2.5 mm² pluggable screw type
Peso apprssimativo	103 g (3.64 oz)	103 g (3.64 oz)	103 g (3.64 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap	vertical on rail adjacent without gap
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AS**		
Mounting rail type according to IEC60715/G32	**PR/DIN/AC, PR/DIN/AS, PR/DIN/AL**		
Plug-in jumper red	—		
white	—		
blue	—		

APPLICATIONS

It allows to convert analog input signals into digital 8 bit output signal, suitable to be used with the less expensive digital inputs of any PLC. The 8 bit signal stored in the LATCH memory is controlled by HOLD signal input. If HOLD is active, the memory does not convert any new signal from the input, and keeps the last stored signal which can be supplied to the output when the module receives a control signal on the bus, allowing connection in parallel of more modules.

Digital to analog signal converters

- 8 bit resolution
- START/STOP function
- Protected against transients
- Pluggable terminals




Item available till sell-out

NOTES

The dimensions include the terminal blocks and the DIN clamp.

BLOCK DIAGRAM



VERSIONS	Cat. No. XW000936	Cat. No. XW000937	Cat. No. XW000938
IN: 8 bit / OUT: 0... 10 V	**DAC08V10**		
IN: 8 bit / OUT: 0...20 mA		**DAC08A0**	
IN: 8 bit / OUT: 4...20 mA			**DAC08A4**
INPUT TECHNICAL DATA			
Input signal	8 bit	8 bit	8 bit
Max. input current	25 mA	25 mA	25 mA
Signal level	"L" < 2.5 V, "H"> 15 V	"L" < 2.5 V, "H"> 15 V	"L" < 2.5 V, "H"> 15 V
OUTPUT TECHNICAL DATA			
Output signal	0…10 V	0…20 mA	4…20 mA
Max. output signal	11 V	25 mA	25 mA
Applicable load	> 2 KΩ	<500 KΩ	<500 KΩ
GENERAL TECHNICAL DATA			
Supply voltage	24 Vdc ± 10%	24 Vdc ± 10%	24 Vdc ± 10%
Rated current	40 mA	40 mA	40 mA
Operating temperature	0…55°C	0…55°C	0…55°C
Transmission error	±1 LSB	±1 LSB	±1 LSB
Hold signal	enabled > 5 V	enabled > 5 V	enabled > 5 V
Conversion time	100 µs	100 µs	100 µs
Resolution	39 mV	78 µA	63 µA
Temperature coefficient	0.01% k	0.01% k	0.01% k
Surge immunity	200 V	200 V	200 V
Protection degree	IP20	IP20	IP20
Connection terminal	2.5 mm² pluggable screw type	2.5 mm² pluggable screw type	2.5 mm² pluggable screw type
Peso approsimativo	103 g (3.64 oz)	103 g (3.64 oz)	103 g (3.64 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap	vertical on rail adjacent without gap


MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35-7.5		**PR/3/AC, PR/3/AS**
Mounting rail type according to IEC60715/G32		**PR/DIN/AC, PR/DIN/AS, PR/DIN/AL**
Plug-in jumper	red	—
	white	—
	blue	—

APPLICATIONS

This module allows to convert analog input signals into a digital 8 bit output signal, suitable to be used with the less expensive digital inputs of any PLC. The 8 bit signal stored in the LATCH memory is controlled by HOLD signal input. If HOLD is active, the memory does not convert any new signal from the input, and keeps the last stored signal which can be supplied to the output when the module receives a control signal on the bus, allowing connection in parallel of more modules.

Analog signal to threshold converters

- Adjustable threshold and hysteresis
- Monitorable threshold value
- Programmable min./max. function




CE

NOTES

The dimensions include the terminal blocks and the DIN clamp.
S1=OFF/S2=ON Relay is turned ON below the threshold (minimum function)
S1=OFF/S2=OFF Relay is turned ON above the threshold (minimum function)
S1=ON/S2=ON Relay is turned ON inside the hysteresis range
S1=ON/S2=OFF Relay is turned ON outside the hysteresis range

BLOCK DIAGRAM



VERSIONS	Cat. No. XW000926	Cat. No. XW000927
IN: 0... 10 V / OUT: 1 threshold	**GWMV10**	
IN: 0...20 mA / OUT: 1 threshold		**GWMA0**
INPUT TECHNICAL DATA		
Input signal	0…10 V	0…20 mA
Max input signal	11 V	22 mA
Surge immunity	200 V	200 V
Resistance	> 100 KΩ	50 Ω
OUTPUT TECHNICAL DATA		
Relay contact	SPDT AgCdO	SPDT AgCdO
Rated voltage	250 Vdc, 230 Vac	250 Vdc, 230 Vac
Rated current	5 A	5 A
Max. continuous current	2 A	2 A
Min. contact current	—	—
Threshold value	100% contact ratio	100% contact ratio
Response time	20 ms	20 ms
GENERAL TECHNICAL DATA		
Supply voltage	24 Vdc ± 10%	24 Vdc ± 10%
Rated current	40 mA	40 mA
Surge immunity	200 V	200 V
Setpoint setting range	0.3…10 V	0.6…20 V
Hysteresis setting range	0.1…10 V	0.2…20 V
Max. hysteresis offset	±30 mV	±60 µA
Transmission error	0.5%	0.5%
Operating temperature range	0…55°C	0…55°C
Connection terminal	2.5 mm² pluggable screw type	2.5 mm² pluggable screw type
Approx. weight	110 g (3.88 oz)	110 g (3.88 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap
MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35	**PR/3/AC, PR/3/AS**	
Mounting rail type according to IEC60715/G32	**PR/DIN/AC, PR/DIN/AS, PR/DIN/AL**	
Plug-in jumper red	—	
(16 poles, 16 A) white	—	
blue	—	

APPLICATIONS

The modules were designed above all for two examples of application:

1. Threshold value signal


With the aid of a trimmer integrated in the module, a threshold value is set. The base is represented by the input signal of the connected sensor.
If the input signal reaches the nominal value set, a relay is enabled in the output stage. By means of a dip-switch, energisation or de-energisation of the relay can be selected on reaching the nominal value.

2. Minimum/maximum function

Having regulated the threshold, regulation of the hysteresis allows a non-intervention zone to be set between the minimum and maximum, of variable extent.
The relay does not operate on a threshold as constant on/off, but only if the upper and lower limits defined by the hysteresis set are exceeded.
On the THRESHOLD VALUE and HYSTERESIS terminals the limit value set can be displayed with the aid of an external voltmeter. The indication of this measuring instrument also allows the value to be read when setting the threshold and hysteresis values. If several switching points are required, there is the possibility of connecting the appliances with current input (in series).

Load cells converter

- Suitable for pressure sensors, for load cells, strain gauges and other measuring bridges
- High impedance differential input, bipolar input and output
- 3 programmable analog signal output ranges




CE

NOTES

The dimensions include the DIN clamp.
(1) range 20.4…28.8 Vdc

BLOCK DIAGRAM



Supply voltage
24 Vac/dc


VERSIONS	Cat. No. X756522
	CWBRA 6-0522
INPUT TECHNICAL DATA	
Input current	1 nA (typical)
Noise	1 mV (0.1…10 Hz, pp RTI, typical)
Range changeover error	0.5%
Common mode range	-7 to +7 V
OUTPUT TECHNICAL DATA	
Output signal	0…10 V 0…20 / 4…20 mA
Output current	<5 mA with output voltage <21 mA with output current
Output voltage	min.: -10.2 V / max.: 10.5 V
Applicable load	>2 KΩ with output voltage <400 Ω with output current
Residual ripple	< 5 mV_{eff}
GENERAL TECHNICAL DATA	
Supply voltage	24 Vac/dc (1)
Rated current	<30 mA
Accuracy	0.1 FS (23°C)
Linearity error	0.02%
Transmission frequency	range 30 mV: 25 Hz/6 Hz; range 1 mV: 2 Hz/1.5 Hz; reversibile
Setting time to accuracy 1%	25 Hz: 50 ms; 6 Hz: 200 ms; 2 Hz: 600 ms; 1.5 Hz: 800 ms
Operating voltage influence	0.005 %/V
Isolation	—
ECM standards	EN 60721-3-3; EN 55011; EN 61000-4-2/6; EN 50178
Reference standards	IED 664-1; DIN VDE
Overvoltage category/Pollution degree	III / 2
Protection degree	IP 20 IEC 529 EN60529
Operating temperature range	-25…+60°C
Connection terminal	1.5 mm² fixed screw type
Housing material	PPE
Approx. weight	70 g (2.47 oz)
Mounting information	vertical on rail adjacent without gap
MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail type according to IEC60715/G32	—
Plug-in jumper red	—
white	—
blue	—

APPLICATIONS

These devices amplify the output signal of a measuring bridge and convert it in a standard analog signal (for example, 0...10 V, 0..20 mA, 4...20 mA). Suitable for pressure sensors, for load cells, strain gauges and other measuring bridges.
They have a high impedance differential input, bipolar I/O, and they supply the measuring bridge with an accurate auxiliary voltage. Moreover they are protected from short circuit, polarity inversion and from overvoltage up to 40 Vdc.

Auxiliary supply output for sensors and potentiometers

- Stabilized switching converter
- IN 16.8…20 Vdc / 9…11 Vdc 60 mA
- Suitable to feed potentiometers and sensors




CE


NOTES

The dimensions include the DIN clamp.
(1) range 16.8…30 Vdc

BLOCK DIAGRAM



EXAMPLE




VERSIONS	Cat. No. X766184
With screw connection (standard)	**CWCV 7-6184**
With spring connection	
INPUT TECHNICAL DATA	
Rated voltage	24 Vdc (1)
Current @ Iout max.	30 mA @ 10 Vdc
Protection fuse	T 1 A (external)
OUTPUT TECHNICAL DATA	
Voltage	10 Vdc (9…11 Vdc adjustable)
Maximum current	60 mA
Continuous current	60 mA
Load regulation	< 1%
Ripple @ rated U-I output	≤ 50 mVpp
Overload / short circuit protection	sì
Output signal	yellow LED Power OK
Parallel connection	possible with external diode
GENERAL TECHNICAL DATA	
Operating temperature range	-25...+60°C
Input/output isolation	50 Vac / 60 s
Protection degree	IP 20 IEC529, EN60529
EMC Standards	EN 50081-1, EN 50082-2, EN 61000-3-2
Surge immunity	EN61000-4-2, EN61000-4-4
Connection terminal	1.5 mm² screw type / 1.5 mm² spring type (16 AWG)
Housing material	Noryl UL94V-0
Approx. weight	35 g (1.24 oz)
Mounting information	vertical on rail adjacent without gap
MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—
Plug-in jumper red	CWBK 7-0802 Cat. No. X766802
white	CWBK 7-0803 Cat. No. X766803
blue	CWBK 7-0804 Cat. No. X766804

APPLICATIONS

For the highest accuracy of electronic measurements in process control and automation systems, a stable supply source is required to feed reference voltages. Accuracy of position sensors, such as linear or rotary potentiometers, depends greatly on the stability and accuracy of the DC supply of the sensor. For this reason our modules are provided with a calibrated DC output dedicated to feed the sensor for the highest accuracy, and this feature also helps to save space and the cost of an external DC supply source.

NPN and PNP signal polarity inverter

- Converts a NPN sensor in a PNP sensor and vice versa
- Compact design




CE

NOTES

The dimensions include the terminal blocks and the DIN clamp.
(1) range 17...30 Vdc

BLOCK DIAGRAM




VERSIONS	Cat. No. XNPNPNP
	CI-NPN/PNP
INPUT TECHNICAL DATA	
Input voltage	24 Vdc (1)
Max. current	200 mA
Max. frequency	120 KHz
GENERAL TECHNICAL DATA	
OFF state current	—
ECM standards	EN 61000-6-2, EN 61000-6-4
Reference Standard	IEC 664-1, DIN VDE
Overvoltage category	II
Pollution degree	2
Protection degree	IP 20 IEC 529 EN60529
Operating temperature range	0...55°C
Connection terminal	morsetti a vite 2.5 mm2 fissi
Housing material	Poliammide UL94V-0
Approx. weight	20 g (0.71 oz)
Mounting information	vertical on rail adjacent without gap
MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	PR/3/AC, PR/3/AS
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL
Plug-in jumper red	—
white	—
blue	—

APPLICATIONS


It converts signal form PNP sensors into NPN signal and vice versa. It allows to adapt the PLC inputs to all sensors on the market, regardless of their output polarity, and it is a great help for maintenance and allows in any case a quick replacement of failed sensors when you need a PNP sensor but you have a NPN type.

EXAMPLE

Conversion from PNP to NPN



Conversion from NPN to PNP



Single relay modules quick selection table


These tables allow you to quickly select only the items, then check if all product's technical data meet your application requirements.


Number of relays	Input rated voltage	Output		Notes	Type	Cat. No.	Page
		type / no. of contacts	rated current				
1	12 Vdc	SPDT	16A	(2)	RF1012D	XRF1012D	106
1	12 Vdc	SPDT	10A	(1)	CM1C012	XCM1C012	107
1	12 Vdc	DPDT	5A	(1)	CM2C012	XCM2C012	108
1	12 Vdc	4PDT	3A	(1)	CM4C012	XCM4C012	109
1	12 Vac	SPDT	10A	(1)	CM1A012	XCM1A012	110
1	12 Vac	DPDT	5A	(1)	CM2A012	XCM2A012	111
1	12 Vac/dc	SPDT	6A	(1)	CWRE7-0848	X766848	115
1	24 Vdc	SPST(NO)	5A	(2)	RFA024D	XRFA024D	105
1	24 Vdc	SPDT	16A	(1)	RE1024D	XRE1024D	105
1	24 Vdc	SPDT	16A	(2)	RF1024D	XRF1024D	105
1	24 Vdc	SPDT	12A	(1)	CM1C024	XCM1C024	107
1	24 Vdc	SPDT	12A	(1)	RE1824D	XRE1824D	105
1	24 Vdc	SPDT	12A	(2)	RF1824D	XRF1824D	105
1	24 Vdc	DPDT	8A	(1)	CM2C024	XCM2C024	108
1	24 Vdc	4PDT	3A	(1)	CM4C024	XCM4C024	109
1	24 Vac/dc	SPDT	6A	(1)	CWRE7-0842	X766842	115
1	24 Vac/dc	SPDT	6A	(2) (3)	CKR16	XCKR16	114
1	24 Vac/dc	DPDT	8A	(1)	RE2024D	XRE2024D	106
2	24 Vac/dc	DPST(NO)	5A	(2)	CKR25	XCKR25	114
1	24 Vac	SPDT	12A	(1)	CM1A024	XCM1A024	110
1	24 Vac	DPDT	8A	(1)	CM2A024	XCM2A024	111
1	24 Vac	4PDT	3A	(1)	CM4A024	XCM4A024	112
1	48 Vdc	SPDT	10A	(1)	CM1C048	XCM1C048	107
1	48 Vdc	DPDT	5A	(1)	CM2C048	XCM2C048	108
1	48 Vac/dc	SPDT	6A	(1)	CWRE7-0845	X766845	115
1	110 Vdc	SPDT	10A	(1)	CM1C110	XCM1C110	107
1	110 Vdc	DPDT	5A	(1)	CM2C110	XCM2C110	108
1	110...120 Vac/dc	SPDT	6A	(1)	CWRE7-0846	X766846	115
1	120 Vac	SPDT	10A	(1)	CM1A120	XCM1A120	110
1	120 Vac	DPDT	5A	(1)	CM2A120	XCM2A120	111
1	230 Vac	SPDT	6A	(1)	CWRE7-0847	X766847	115
1	230 Vac	SPDT	10A	(1)	CM1A230	XCM1A230	110
1	230 Vac	DPDT	5A	(1)	CM2A230	XCM2A230	111


Notes

(1) version with pluggable relay
(2) version with fixed relay
(3) protection fuse on the contact
(4) without LED and protection diode

24 Vdc SPDT single relay
R series









NOTES


(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical

(2) Version available upon request

BLOCK DIAGRAM








VERSIONS	Cat. No. XRFA024D	Cat. No. XR?1824D	Cat. No. XR?1024D
Pluggable relay	**–**	**RE1824D**	**RE1024D**
Fixed relay	**RFA024D**	**RF1824D**	**RF1024D**
INPUT TECHNICAL DATA			
Rated voltage	**24 Vdc ± 10%**	**24 Vdc ± 10%**	**24 Vdc ± 10%**
Rated current (1 channel)	22 mA ± 10%	22 mA ± 10%	22 mA ± 10%
Turn ON time	15 ms	15 ms	15 ms
Turn OFF time	5 ms	5 ms	5 ms
Protection circuit	damping & polarity protection diode	damping & polarity protection diode	damping & polarity protection diode
OUTPUT TECHNICAL DATA			
Type and number of contacts	SPST(NO) $AgSnO_2$	SPDT $AgSnO_2$	SPDT $AgSnO_2$
Nominal current (resistive load)	5 A / 250 Vac	12 A / 250 Vac	12 A / 250 Vac
Current breaking power	**5 A**	**12 A**	**12 A**
Current of the fuse max.	—	—	—
GENERAL TECHNICAL DATA			
Operating temperature	–10...+50°C	–10...+50°C	–10...+50°C
Coil/contact isolation	2.5 KVac / 60 s	2.5 KVac / 60 s	2.5 KVac / 60 s
Isolation between output terminals	0,5 kVac / 60 s (between open contact)	0,5 kVac / 60 s (between open contact)	0,5 kVac / 60 s (between open contact)
Protection degree	IP 00 IEC529, EN60529	IP 00 IEC529, EN60529	IP 00 IEC529, EN60529
Overvoltage category / pollution degree	III / 2	III / 2	III / 2
Reference Standard	IEC 664-1, DIN VDE 0110.1	IEC 664-1, DIN VDE 0110.1	IEC 664-1, DIN VDE 0110.1
Status display	green LED	green LED	green LED
Connection terminals	2.5 mm² fixed screw type AWG26-14	2.5 mm² fixed screw type AWG26-14	2.5 mm² fixed screw type AWG26-14
Housing material	UL94V-0 plastic material	UL94V-0 plastic material	UL94V-0 plastic material
Approx. weight	30 g (1.07 oz)	44 g (1.55 oz)	44 g (1.55 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap	vertical on rail adjacent without gap
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**		
Mounting rail type according to IEC60715/G32	**PR/DIN/AC - PR/DIN/AS - PR/DIN/AL**		
Replacement relay (1)	Cat. No. 8904000	Cat. No. 8904001	Cat. No. 89040
Screw type jumper black	—	—	—

24 Vdc SPDT single relay
R series




NOTES

(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical

(2) Version available upon request


BLOCK DIAGRAM



VERSIONS	Cat. No. XRF1012D	Cat. No. XRE2024D
Pluggable relay	**–**	**RE2024D**
Fixed relay	**RF1012D**	**–**
INPUT TECHNICAL DATA		
Rated voltage	**12 Vdc ± 10%**	**24 Vac / dc ± 10%**
Rated current (1 channel)	44 mA ± 10%	22 mA ± 10%
Turn ON time	15 ms	15 ms
Turn OFF time	5 ms	5 ms
Protection circuit	damping & polarity protection diode	damping & polarity protection diode
OUTPUT TECHNICAL DATA		
Type and number of contacts	SPDT $AgSnO_2$	DPDT $AgSnO_2$
Nominal current (resistive load)	16 A / 250 Vac	8 A / 250 Vac
Current breaking power	**16 A**	**8 A**
Current of the fuse max.	—	—
GENERAL TECHNICAL DATA		
Operating temperature	–10...+50°C	–10...+50°C
Coil/contact isolation	2.5 KVac / 60 s	2.5 KVac / 60 s
Isolation between output terminals	0,5 kVac / 60 s (between open contact)	0,5 kVac / 60 s (between open contact)
Protection degree	IP 20 IEC529, EN60529	IP 00 IEC529, EN60529
Overvoltage category / pollution degree	III / 2	III / 2
Reference Standard	IEC 664-1, DIN VDE 0110.1	IEC 664-1, DIN VDE 0110.1
Status display	green LED	green LED
Connection terminals	2.5 mm² fixed screw type AWG26-14	2.5 mm² fixed screw type AWG26-14
Housing material	UL94V-0 plastic material	UL94V-0 plastic material
Approx. weight	44 g (1.55 oz)	76 g (2.68 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap
MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	
Mounting rail type according to IEC60715/G32	**PR/DIN/AC - PR/DIN/AS - PR/DIN/AL**	
Replacement relay (1)	Cat. No. 8904032	Cat. No. 8904002
Screw type jumper black	—	—

Single relay DC input series CM

- Pluggable relay
- Mounting on DIN rail or panel through central screw
- Compact dimensions
- Cross and slotted screws
- Screw type jumper available



NOTES


The height dimension includes 35 mm DIN rail.

(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.

(2) On request, there are available versions without signalling and protection circuit; for the order, please add the suffix "Z" to the item code (for example: XCM1C024Z).

(3) On request, there are available versions with gold-plated contact; for the order, please add the suffix "U" to the item code (for example: XCM1C024U).

BLOCK DIAGRAM




VERSIONS	Cat. No. XCM1C012	Cat. No. XCM1C024	Cat. No. XCM1C048	Cat. No. XCM1C110
12 Vdc	**CM1C012**			
24 Vdc		**CM1C024**		
48 Vdc			**CM1C048**	
110 Vdc				**CM1C110**
INPUT TECHNICAL DATA				
Rated voltage	**12 Vdc** ±10%	**24 Vdc** ±10%	**48 Vdc** ±10%	**110 Vdc** ±10%
Rated current (1 channel)	44 mA ±10%	22 mA ±10%	12 mA ±10%	11 mA ±10%
Turn ON time	15 ms	15 ms	15 ms	15 ms
Turn OFF time	5 ms	5 ms	5 ms	20 ms
Protection circuit	damping diode (2)			
OUTPUT TECHNICAL DATA				
Type and number of contacts	SPDT $AgSnO_2$ (3)			
Nominal current (resistive load)	12 A / 250 Vac			
Current breaking power	**12 A**			
Current of the fuse max.	—			
GENERAL TECHNICAL DATA				
Operating temperature range	–10...+50°C			
Coil/contact isolation	4 kVac / 60 s			
Isolation between output terminals	1 kVac / 60 s (between open contact)			
Protection degree	IP 20 IEC 529, EN60529			
Overvoltage category/Pollution degree	III / 2			
Reference Standard	IEC 664-1, DIN VDE 0110.1			
Status display	green LED (2)			
Connection terminal	2.5 mm² fixed screw type AWG26-14			
Housing material	UL94V-0 plastic material			
Approx. weight	54 g (1.90 oz)			
Mounting information	vertical on rail adjacent without gap or panel with screw			

MOUNTING ACCESSORIES					
Mounting rail type according to IEC60715/TH35-7.5		**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32		—			
Replacement relay	(1)	Cat. No. 8904039	Cat. No. 8904001	Cat. No. 8904008	Cat. No. 8904047
Screw type jumper	black	Cat. No. XCMB16B			
	white	—			
	blue	—			

DPDT single relay DC input series CM

- Pluggable relay
- Mounting on DIN rail or panel through central screw
- Compact dimensions
- Cross and slotted screws
- Screw type jumper available




NOTES

The height dimension includes 35 mm DIN rail.

(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.

BLOCK DIAGRAM




VERSIONS	Cat. No. XCM2C012	Cat. No. XCM2C024	Cat. No. XCM2C048	Cat. No. XCM2C110
12 Vdc	**CM2C012**			
24 Vdc		**CM2C024**		
48 Vdc			**CM2C048**	
110 Vdc				**CM2C110**
INPUT TECHNICAL DATA				
Rated voltage	**12 Vdc ±10%**	**24 Vdc ±10%**	**48 Vdc ±10%**	**110 Vdc ±10%**
Rated current (1 channel)	44 mA ±10%	22 mA ±10%	24 mA ±10%	11 mA ±10%
Turn ON time	15 ms	15 ms	15 ms	15 ms
Turn OFF time	5 ms	5 ms	5 ms	20 ms
Protection circuit	damping diode			
OUTPUT TECHNICAL DATA				
Type and number of contacts	DPDT $AgSnO_2$			
Nominal current (resistive load)	8 A / 250 Vac			
Current breaking power	**8 A**			
Current of the fuse max.	—			
GENERAL TECHNICAL DATA				
Operating temperature range	–10...+50°C			
Coil/contact isolation	4 kVac / 60 s			
Isolation between output terminals	1 kVac / 60 s (between open contact)			
Protection degree	IP 20 IEC 529, EN60529			
Overvoltage category/Pollution degree	III / 2			
Reference Standard	IEC 664-1, DIN VDE 0110.1			
Status display	green LED			
Connection terminal	2.5 mm² fixed screw type AWG26-14			
Housing material	UL94V-0 plastic material			
Approx. weight	67 g (2.37 oz)			
Mounting information	vertical on rail adjacent without gap or panel with screw			

MOUNTING ACCESSORIES					
Mounting rail type according to IEC60715/TH35-7.5		**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32		—			
Replacement relay	(1)	Cat. No. 8904040	Cat. No. 8904002	Cat. No. 8904009	Cat. No. 8904054
Screw type jumper	black	Cat. No. XCMB16B			
	white	—			
	blue	—			

4PDT single relay DC input series CM

- Pluggable relay
- Mounting on DIN rail or panel through central screw
- Compact dimensions
- Cross and slotted screws
- Screw type jumper available




NOTES

The height dimension includes 35 mm DIN rail.

(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.

BLOCK DIAGRAM




VERSIONS	Cat. No. XCM4C012	Cat. No. XCM4C024	Cat. No. XCM1C048	Cat. No. XCM1C110
12 Vdc	**CM4C012**			
24 Vdc		**CM4C024**		
48 Vdc			—	
110 Vdc				—
INPUT TECHNICAL DATA				
Rated voltage	**12 Vdc ±10%**	**24 Vdc ±10%**		
Rated current (1 channel)	75 mA ±10%	38 mA ±10%		
Turn ON time	20 ms	20 ms		
Turn OFF time	20 ms	20 ms		
Protection circuit	damping diode			
OUTPUT TECHNICAL DATA				
Type and number of contacts	4PDT $AgSnO_2$			
Nominal current (resistive load)	3 A / 250 Vac			
Current breaking power	**3 A**			
Current of the fuse max.	—			
GENERAL TECHNICAL DATA				
Operating temperature range	–10...+50°C			
Coil/contact isolation	4 kVac / 60 s			
Isolation between output terminals	1 kVac / 60 s (between open contact)			
Protection degree	IP 20 IEC 529, EN60529			
Overvoltage category/Pollution degree	III / 2			
Reference Standard	IEC 664-1, DIN VDE 0110.1			
Status display	green LED			
Connection terminal	2.5 mm² fixed screw type AWG26-14			
Housing material	UL94V-0 plastic material			
Approx. weight				
Mounting information	vertical on rail adjacent without gap or panel with screw			

MOUNTING ACCESSORIES					
Mounting rail type according to IEC60715/TH35-7.5		**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32		—			
Replacement relay	(1)	Cat. No. 8904018	Cat. No. 8904030		
Screw type jumper	black	Cat. No. XCMB27B			
	white	—			
	blue	—			

Single relay AC input series CM

- Pluggable relay
- Mounting on DIN rail or panel through central screw
- Compact dimensions
- Cross and slotted screws
- Screw type jumper available




NOTES

The height dimension includes 35 mm DIN rail.

(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.

BLOCK DIAGRAM




VERSIONS	Cat. No. XCM1A012	Cat. No. XCM1A024	Cat. No. XCM1A120	Cat. No. XCM1A230
12 Vdc	**CM1A012**			
24 Vdc		**CM1A024**		
120 Vdc			**CM1A120**	
230 Vdc				**CM1A230**
INPUT TECHNICAL DATA				
Rated voltage	**12 Vac ±10%**	**24 Vac ±10%**	**120 Vac ±10%**	**230 Vac ±10%**
Rated current (1 channel)	95 mA ±10%	48 mA ±10%	10.5 mA ±10%	6 mA ±10%
Turn ON time	15 ms	15 ms	15 ms	15 ms
Turn OFF time	10 ms	10 ms	10 ms	10 ms
Protection circuit	—			
OUTPUT TECHNICAL DATA				
Type and number of contacts	$SPDT\ AgSnO_2$			
Nominal current (resistive load)	12 A / 250 Vac			
Current breaking power	**12 A**			
Current of the fuse max.	—			
GENERAL TECHNICAL DATA				
Operating temperature range	–10...+50°C			
Coil/contact isolation	4 kVac / 60 s			
Isolation between output terminals	1 kVac / 60 s (between open contact)			
Protection degree	IP 20 IEC 529, EN60529			
Overvoltage category/Pollution degree	III / 2			
Reference Standard	IEC 664-1, DIN VDE 0110.1			
Status display	green LED			
Connection terminal	2.5 mm² fixed screw type AWG26-14			
Housing material	UL94V-0 plastic material			
Approx. weight	54 g (1.91 oz)			
Mounting information	vertical on rail adjacent without gap or panel with screw			

MOUNTING ACCESSORIES					
Mounting rail type according to IEC60715/TH35-7.5		**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32		—			
Replacement relay	(1)	Cat. No. 8904016	Cat. No. 8904048	Cat. No. 8904056	Cat. No. 8904050
Screw type jumper	black	XCMB16B			
	white	—			
	blue	—			

DPDT single relay AC input series CM

- Pluggable relay
- Mounting on DIN rail or panel through central screw
- Compact dimensions
- Cross and slotted screws
- Screw type jumper available




CE

NOTES

The height dimension includes 35 mm DIN rail.

(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.

BLOCK DIAGRAM




VERSIONS	Cat. No. XCM2A012	Cat. No. XCM2A024	Cat. No. XCM2A120	Cat. No. XCM2A230
12 Vac	**CM2A012**			
24 Vac		**CM2A024**		
120 Vac			**CM2A120**	
230 Vac				**CM2A230**
INPUT TECHNICAL DATA				
Rated voltage	**12 Vac ±10%**	**24 Vac ±10%**	120 Vac ±10%	230 Vac ±10%
Rated current (1 channel)	95 mA ±10%	48 mA ±10%	10.5 mA ±10%	6 mA ±10%
Turn ON time	15 ms	15 ms	15 ms	15 ms
Turn OFF time	10 ms	10 ms	10 ms	10 ms
Protection circuit	—			
OUTPUT TECHNICAL DATA				
Type and number of contacts	DPDT $AgSnO_2$			
Nominal current (resistive load)	8 A / 250 Vac			
Current breaking power	**8 A**			
Current of the fuse max.	—			
GENERAL TECHNICAL DATA				
Operating temperature range	–10...+50°C			
Coil/contact isolation	4 kVac / 60 s			
Isolation between output terminals	1 kVac / 60 s (between open contact)			
Protection degree	IP 20 IEC 529, EN60529			
Overvoltage category/Pollution degree	III / 2			
Reference Standard	IEC 664-1, DIN VDE 0110.1			
Status display	green LED			
Connection terminal	2.5 mm² fixed screw type AWG26-14			
Housing material	UL94V-0 plastic material			
Approx. weight	67 g (2.37 oz)			
Mounting information	vertical on rail adjacent without gap or panel with screw			

MOUNTING ACCESSORIES					
Mounting rail type according to IEC60715/TH35-7.5		**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**			
Mounting rail type according to IEC60715/G32		—			
Replacement relay	(1)	Cat. No. 8904017	Cat. No. 8904055	Cat. No. 8904056	Cat. No. 8904057
Screw type jumper	black	Cat. No. XCMB16B			
	white	—			
	blue	—			

4PDT single relay AC input series CM

- Pluggable relay
- Mounting on DIN rail or panel through central screw
- Compact dimensions
- Cross and slotted screws
- Screw type jumper available




NOTES

The height dimension includes 35 mm DIN rail.

(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.


BLOCK DIAGRAM



VERSIONS	Cat. No. XCM4A024			
12 Vdc	—			
24 Vdc		**CM4A024**		
120 Vdc			—	
230 Vdc				—
INPUT TECHNICAL DATA				
Rated voltage		**24 Vac ±10%**		
Rated current (1 channel)		38 mA ±10%		
Turn ON time		20 ms		
Turn OFF time		20 ms		
Protection circuit		—		
OUTPUT TECHNICAL DATA				
Type and number of contacts		DPDT $AgSnO_2$		
Nominal current (resistive load)		3 A / 250 Vac		
Current breaking power		**3 A**		
Current of the fuse max.		—		
GENERAL TECHNICAL DATA				
Operating temperature range		–10...+50°C		
Coil/contact isolation		4 kVac / 60 s		
Isolation between output terminals		1 kVac / 60 s (between open contact)		
Protection degree		IP 20 IEC 529, EN60529		
Overvoltage category/Pollution degree		III / 2		
Reference Standard		IEC 664-1, DIN VDE 0110.1		
Status display		green LED		
Connection terminal		2.5 mm² fixed screw type AWG26-14		
Housing material		UL94V-0 plastic material		
Approx. weight				
Mounting information		vertical on rail adjacent without gap or panel with screw		

MOUNTING ACCESSORIES					
Mounting rail type according to IEC60715/TH35-7.5			**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**		
Mounting rail type according to IEC60715/G32			—		
Replacement relay	(1)	Cat. No. 8904033			
Screw type jumper	black		—		
	white		—		
	blue		—		


CK system interface



The CK series is a collection of interfaces for sensors and actuators, is composed by a wide range of electromechanical relay and solid state relay modules and passive interfaces in modular housings, which are only 6 mm wide thus saving valuable space. All products are mounted inside the CK housing, which is also available for use as a housing for custom. The CK housing can be equipped with six 2.5 mm spring-clamp terminals and four contacts for the insertion of a PTC parallel connection bridge, which provides for quick and easy circuit bridging and saves space and harness time.

The product range is currently composed by:


- Single electromechanical relay with 6 A/250 Vac SPDT protected with replaceable fuse, status Led display on front panel, AC/DC input and positive or negative common on relay coil.
- Double electromechanical relay with 5 A/250 Vac SPST (NO), two status LED displays on front panel, AC/DC input and positive or negative common on relay coil.
- Single solid state relay for common negative load, 5 A /48 Vdc output current, protected with replaceable fuse, status LED display on front panel and positive or negative common on input.
- Double solid state relay suitable for 12-24 Vdc 2.5 A loads, status LED display on front panel and positive or negative common of the input and output as well.
- Diode-holder modules with common anode (CK…AC) or common cathode (CK…CC).
- Lamp and LED test modules.
- Supply connection and distribution modules with LED display.




1

Composition of an interface with the CK System:

- The required modules must be selected and mounted on the DIN rail.
- The common poles of inputs and outputs can be connected in parallel using the fast connection bridges **PTC/CK/42**.
- For the connection of inputs and outputs of the relay module interface, we recommend to use the **CKF** supply distribution module: it allows to connect and distribute the feeding potential to inputs and outputs on all adjacent modules; the CKF module can be mounted as first module, or even better, in the middle position of the interfaces assembly, to divide 50+50% the current on the bridge and to reduce voltage drop and heating; the CKF- - is available with LED for ON display, and is equipped with four 2.5 mm / AWG 26 ÷ 14 / 24 A rated spring-clamp terminals - input and output.
- In order to assure the IP XXB protection degree, the last module must be protected and insulated using the **CK/PT** end section.
- Main technical data and BLOCK DIAGRAM are printed on one side of each module; for individual terminal block marking, CNU/8 marking tags are available; CNU/8 marking tags are available in blank format for plotter or pen marking, or in CK dedicated series bearing numbers and/or symbols and allow to have 4, 8, 16 relay interface modules, each one individually marked on all poles.
- If the input and output power supply cables of the interface assembly are directly connected to eg. the first module, two cables must be connected on a single terminal block (feeding wire and load wire) forcing to reduce the cross-section of each conductor to less than 2,5 mm; 2consequently, this means a current and a reduction of the total number of relay modules that can be fed; the problem can be solved by using the CKF feeder distribution module as described in the third point.



2


3



4

Easy Bridge system

The fast connection bridge **PTC/CK/42** has 42 poles, and a rated current of 32 A; WARNING: the total current is limited by the rated current of the spring-clamp terminal block (24 A): if a PTC/CK serves 10 relays, a rated current of 2,4 A can be distributed on to each relay.
The use of PTC/CK bridges is simple and cost effective; the following instructions must be followed:


- after having cut the PTC/CK/42-pole bar according to required number of poles, in order to maintain the IPXXB protection degree the bar must be sheared in proximity of the end poles (see pictures 1 and 2);
- insert the jumper in the slot of the CK terminals (see picture 3);
- by using the blade of a screwdriver, the PTC bridge must be pushed down until it snaps into the female contacts; in case of long jumpers, the operation shall be started by pushing the bridge in the middle, then gradually on left / right sides; the jumper will then result completely IPXXB insulated (see picture 4);
- to remove the jumper, the blade of a screwdriver shall be inserted into the slot provided in the upper side of the PTC bridge, then lifted up and finally extracted; in case of long jumpers, the bridge shall be lifted in the middle, then gradually on left / right sides (pictures 5 and 6).


5


6

24 Vdc relay modules
CKR series

- Built-in replaceable contact protection fuse
- AC/DC common negative or positive input
- Status LED display, reverse polarity protection, crow-bar diode
- 6 mm wide
- Plug-in jumper available




CE CE

NOTES

(1) The contact rated voltage is 250 Vac; max operating voltage of the contact of the module is 50 Vac-Vdc, limited by the voltage ratings of the adopted type of fuse, which is rated for ≤50 Vac-75 Vdc SELV voltages; WARNING: if used with higher voltage, it does not guarantee breaking power and thus safety, and IP protection degree is lowered to IP 00; fuses with higher current ratings are not allowed and do not protect the contact against short circuit and overcurrents
(2) Version available upon request.
(3) In order to assure the IP20 protection degree, the last module must be protected and insulated using the CK/PT end section.


BLOCK DIAGRAM



VERSIONS	Cat. No. XCKR16	Cat. No. XCKR25
1 channel	**CKR16**	**—**
2 channels	**—**	**CKR25**
INPUT TECHNICAL DATA		
Rated voltage	**24 Vac/dc ± 10%**	**24 Vac/dc ±10%**
Rated current (1 channel)	≤15 mA ± 10% @ 24 Vdc	≤13 mA ±10% @ 24 Vdc
Turn ON time	5 ms	5 ms
Turn OFF time	10 ms	10 ms
Protection circuit	bridge rectifier	bridge rectifier
OUTPUT TECHNICAL DATA		
Type and number of contacts	SPDT $AgSnO_2$	2PST (NO) $AgSnO_2$
Nominal current (resistive load)	6 A / 250 Vac	5 A / 250 Vac
Current breaking power	**30 A**	**30 A**
Current of the fuse max.	—	—
GENERAL TECHNICAL DATA		
Operating temperature	-20…+60°C	-20…+60°C
Coil/contact isolation	3 KVac / 60 s	3 KVac / 60 s
Isolation between output terminals		
Protection degree	IP 20 IEC529, EN60529	IP 00 IEC529, EN60529
Overvoltage category / pollution degree	II / 2	II / 2
Reference Standard	IEC 664-1, DIN VDE 0110.1	IEC 664-1, DIN VDE 0110.1
Status display	green LED	green LED
Connection terminals	2.5 mm² AWG26-14 fixed spring type	2.5 mm² AWG26-14 fixed spring type
Housing material	polyamide UL94V-0	polyamide UL94V-0
Approx. weight	40 g (1.41 oz)	43 g (1,52 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap
MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	
Mounting rail type according to IEC60715/G32	**PR/DIN/AC - PR/DIN/AS - PR/DIN/AL**	
Replacement relay (1)	—	—
Plug-in jumper —	Cat. No. PTCCK42 (42 poles)	Cat. No. XCKPT
Marking tags blank	Cat. No. NU008	Cat. No. NU008
printed	Cat. No. N8CK1610	Cat. No. N8CK2518
printed	Cat. No. N8CK1620	
End plate		

Relay modules AC/DC input series CWRE

- Pluggable relay
- Status LED display
- 6.2 mm wide
- Plug-in jumper available



NOTES

The height dimension includes 35 mm DIN rail.


(1) Version available upon request; for information call our sales department, local agent or representative.

(2) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.

APPLICAZIONI

The CWRE series is suitable for the commutation of signals and is equipped with a pull-out relay to make the maintenance operations easy. Furthermore this series offers the possibility to execute the parallel on both the input and output side by the means of a proper comb jumper.

BLOCK DIAGRAM



VERSIONS	Cat. No. X766848	Cat. No. X766842	Cat. No. X766845	Cat. No. X766846	Cat. No. X766847
12 Vac/dc	CWRE7-0848				
24Vac/dc		CWRE7-0842			
48 Vac/dc (1)			CWRE7-0845 (1)		
115 Vac/dc				CWRE7-0846	
230 Vac/dc					CWRE7-0847
INPUT TECHNICAL DATA					
Rated voltage	**12 Vac/dc ±10%**	**24 Vac/dc ±10%**	**48 Vac/dc ±10%**	**115 Vac/dc ±10%**	**230 Vac/dc ±10%**
Rated current (1 channel)	10 mA ±10%	7 mA ±10%	5 mA ±10%	4 mA ±10%	4 mA ±10%
Turn ON time	8 ms	8 ms	7 ms	8 ms	8 ms
Turn OFF time	5 ms	5 ms	7 ms	13 ms	13 ms
Protection circuit	bridge rectifier				
OUTPUT TECHNICAL DATA					
Type and number of contacts	SPDT $AgSnO_2$ (3)				
Nominal current (resistive load)	6 A / 250 Vac ; 6 A / 30 Vdc				
Current breaking power	**DC 13: 24 V / 1A; 115V / 200 mA; 230 V / 100 mA**				
Current of the fuse max.	—				
GENERAL TECHNICAL DATA					
Operating temperature	–40...+70°C				
Coil/contact isolation	4 kVac / 60 s				
Isolation between output terminals	1 kVac / 60 s (between open contact)				
Protection degree	IP 20 IEC 529, EN60529				
Overvoltage category / pollution degree	III / 2				
Reference Standard	IEC 664.1, DIN VDE 0110.1				
Status display	green LED				
Connection terminals	2.5 mm² fixed screw type AWG26-14				
Housing material	UL94V-0 plastic material				
Approx. weight	35 g (1.23 oz)				
Mounting information	vertical on rail adjacent without gap				
MOUNTING ACCESSORIES					
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**				
Mounting rail type according to IEC60715/G32	—				
Replacement relay (2)		Cat. No. 8904027			
Plug-in jumper black	—				
white	—				
blue	CWBK7-0813 (Cat. No. X766813) (20 poli)				

Multiple relay modules quick selection table

These tables allow you to quickly select only the items, then check if all product's technical data meet your application requirements.


Number of relays	Input rated voltage	Output		Notes	Type	Cat. No.	Page
		type / no. of contacts	rated current				
4	12 Vdc	SPDT	10 A	(1) (4)	R41E12	XR041E12	125
4	12 Vdc	DPDT	5 A	(1) (4)	R42E12	XR042E12	126
4	24 Vdc	SPDT	12 A	(1) (4)	R41E24	XR041E24	117
4	24 Vdc	SPDT	12 A	(1) (5)	R41E24P	XR041E24P	118
4	24 Vdc	SPDT	12 A	(3) (4)	Z4124D	XZ04124D	130
4	24 Vdc	DPDT	8 A	(1) (4)	R42E24	XR042E24	121
4	24 Vdc	DPDT	8 A	(1) (5)	R42E24P	XR042E24P	122
4	24 Vdc	DPDT	8 A	(3) (4)	Z4224D	XZ04224D	131
4	24 Vac/dc	SPDT	8 A	(2) (6)	CR4-1	XCR41	132
4	24 Vac/dc	SPDT	8 A	(2) (6)	CR4-2	XCR42	132
4	24 Vac/dc	SPDT	8 A	(1) (6)	CRE4-1	XCRE41	132
4	24 Vac/dc	SPDT	12 A	(1) (6)	R41EAD	XR041EAD	119
4	24 Vac/dc	SPDT	12 A	(1) (6) (8)	R41U24F	XR041U24F	120
4	24 Vac/dc	DPDT	8 A	(1) (6)	R42EAD	XR042EAD	123
4	24 Vac/dc	DPDT	8 A	(2) (6)	CR4-2SC	XCR42SC	134
4	24 Vac/dc	DPDT	8 A	(1) (6)	CRE4-2SC	XCRE42SC	134
4	110 Vdc/120 Vac ±10%	SPDT	10 A	(1) (6)	R41E11A	XR041E1A	128
4	230 Vac	SPDT	10 A	(1) (6)	R41E22A	XR041E2A	129
8	12 Vdc	SPDT	10 A	(1) (4)	R81E12	XR081E12	125
8	12 Vdc	DPDT	5 A	(1) (4)	R82E12	XR082E12	126
8	24 Vdc	SPDT	12 A	(1) (4)	R81E24	XR081E24	117
8	24 Vdc	SPDT	12 A	(1) (5)	R81E24P	XR081E24P	118
8	24 Vdc	SPDT	12 A	(3) (4)	Z8124D	XZ08124D	130
8	24 Vdc	DPDT	8 A	(1) (4)	R82E24	XR082E24	121
8	24 Vdc	DPDT	8 A	(1) (5)	R82E24P	XR082E24P	121
8	24 Vdc	DPDT	8 A	(3) (4)	Z8224D	XZ08224D	131
8	24 Vac/dc	SPST(NO)	8 A	(2) (6)	CR8-2	XCR82	133
8	24 Vac/dc	SPST(NO)	8 A	(1) (6) (7)	CR8-3	XCR83	137
8	24 Vac/dc	SPST(NO)	8 A	(1) (6)	CRE8-1	XCRE81	133
8	24 Vac/dc	SPST(NO)	8 A	(1) (6) (7)	CRE8-3	XCRE83	137
8	24 Vac/dc	SPDT	12 A	(1) (6)	R81EAD	XR081EAD	119
8	24 Vac/dc	SPDT	12 A	(1) (6) (8)	R81U24F	XR081U24F	120
8	24 Vac/dc	SPDT	12 A	1) (6) (9) (10)	RMP081CM	XRMP081CM	124
8	24 Vac/dc	SPST(NO)	8 A	(2) (6)	CR8-1	XCR81	133
8	24 Vac/dc	DPDT	8 A	(1) (6)	R82EAD	XR082EAD	123
8	48 Vdc	DPDT	8 A	(1) (4)	R82E48	XR082E48	127
8	110 Vdc/120 Vac ±10%	SPDT	10 A	(1) (6)	R81E11A	XR081E1A	128
8	230 Vac	SPDT	10 A	(1) (6)	R81E22A	XR081E2A	129
16	12 Vdc	SPDT	10 A	(1) (4)	R161E12	XR161E12	125
16	12 Vdc	DPDT	5 A	(1) (4)	R162E12	XR162E12	126
16	24 Vdc	SPDT	12 A	(1) (4)	R161E24	XR161E24	117
16	24 Vdc	SPDT	12 A	(1) (5)	R161E24P	XR161E24P	118
16	24 Vdc	SPDT	12 A	(3) (4)	Z16124D	XZ16124D	130
16	24 Vdc	DPDT	8 A	(1) (4)	R162E24	XR162E24	121
16	24 Vdc	DPDT	8 A	(1) (5)	R162E24P	XR162E24P	121
16	24 Vdc	DPDT	8 A	(3) (4)	Z16224D	XZ16224D	131
16	24 Vac/dc	SPDT	12 A	(1) (6)	R161EAD	XR161EAD	119
16	24 Vac/dc	SPDT	12 A	(1) (6) (8)	R161U24F	XR161U24F	120
16	24 Vac/dc	DPDT	8 A	(1) (6)	R162EAD	XR162EAD	123
16	48 Vdc	DPDT	5 A	(1) (4)	R162E48	XR162E48	127
16	110 Vdc/120 Vac ±10%	SPDT	10 A	(1) (6)	R161E11A	XR161E1A	128
16	230 Vac	SPDT	10 A	(1) (6)	R161E22A	XR161E2A	129

Note

(1) version with pluggable relay
(2) version with fixed relay
(3) with socket but without relay
(4) negative common, positive command
(5) positive common, negative command
(6) universal control voltage, negative DC command, positive DC, AC
(7) with connector input command
(8) with protection fuse on the relay contact
(9) with test push button
(10) with test switch

24 Vdc SPDT relay modules negative common


- DC control voltage
- Negative control voltage
- Status LED display
- Pluggable relay




NOTES

The height dimension includes 35 mm DIN rail.
(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical


BLOCK DIAGRAM



4 relay module



8 relay module




16 relay module

VERSIONS	Cat. No. XR041E24	Cat. No. XR081E24	Cat. No. XR161E24
4 relay module	**R41E24**		
8 relay module		**R81E24**	
16 relay module			**R161E24**
INPUT TECHNICAL DATA			
Rated voltage	24 Vdc ± 10%		
Rated current (1 channel)	22 mA ± 10%		
Turn ON time	15 ms		
Turn OFF time	5 ms		
Protection circuit	damping & polarity protection diode		
OUTPUT TECHNICAL DATA			
Type and number of contacts	SPDT $AgSnO_2$		
Nominal load (resistive)	12 A / 250 Vac		
Current breaking power	12 A		
Current of the fuse max.	—		
GENERAL TECHNICAL DATA			
Operating temperature range	-10...+50°C		
Coil/contact isolation	2.5 KVac / 60 s		
Isolation between output terminals	1 KVac / 60 s (between open contact)		
Protection degree	IP 20 IEC 529, EN60529		
Overvoltage category / Pollution degree	III / 2		
Reference Standard	IEC 664-1, DIN VDE 0110.1		
Status display	green LED / yellow LED		
Connection terminal	2.5 mm² fixed screw type		
Housing material	UL94V-0 plastic material		
Approx. weight	188 g (6.63 oz)	342 g (12.06 oz)	657 g (23,17 oz)
Mounting information	vertical on rail adjacent without gap		
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB		
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL		
Replacement relay (1)	Cat. No. 8904001		
Screw type jumper red	—		
white	—		
blue	—		

24 Vdc SPDT relay modules positive common


- DC control voltage
- Positive control voltage
- Status LED display
- Pluggable relay




NOTES

The height dimension includes 35 mm DIN rail.
(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical


BLOCK DIAGRAM



4 relay module



8 relay module




16 relay module

VERSIONS	Cat. No. XR041E24P	Cat. No. XR081E24P	Cat. No. XR161E24P
4 relay module	**R41E24P**		
8 relay module		**R81E24P**	
16 relay module			**R161E24P**
INPUT TECHNICAL DATA			
Rated voltage	24 Vdc ± 10%		
Rated current (1 channel)	22 mA ± 10%		
Turn ON time	15 ms		
Turn OFF time	5 ms		
Protection circuit	damping & polarity protection diode		
OUTPUT TECHNICAL DATA			
Type and number of contacts	SPDT $AgSnO_2$		
Nominal load (resistive)	12 A / 250 Vac		
Current breaking power	12 A		
Current of the fuse max.	—		
GENERAL TECHNICAL DATA			
Operating temperature range	-10...+50°C		
Coil/contact isolation	2.5 KVac / 60 s		
Isolation between output terminals	1 KVac / 60 s (between open contact)		
Protection degree	IP 00 IEC 529, EN60529		
Overvoltage category / Pollution degree	III / 2		
Reference Standard	IEC 664-1, DIN VDE 0110.1		
Status display	green LED / yellow LED		
Connection terminal	2.5 mm² fixed screw type		
Housing material	UL94V-0 plastic material		
Approx. weight	188 g (6.63 oz)	342 g (12.06 oz)	657 g (23,17 oz)
Mounting information	vertical on rail adjacent without gap		
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB		
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL		
Replacement relay (1)	Cat. No. 8904001		
Screw type jumper red	—		
white	—		
blue	—		

24 Vac/dc SPDT relay modules universal control voltage

- DC and AC control voltage
- Positive or negative control voltage
- Status LED display
- Pluggable relay




NOTES

The height dimension includes 35 mm DIN rail.
(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical
(2) Version available upon request.


POWER SUPPLY

A1 = +	A2 = –	negative common
A1 = –	A2 = +	positive common
A1 = ~	A2 = ~	AC power supply


BLOCK DIAGRAM



4 relay module



8 relay module




16 relay module

VERSIONS	Cat. No. XR041EAD	Cat. No. XR081EAD	Cat. No. XR161EAD
4 relay module	**R41EAD**		
8 relay module		**R81EAD**	
16 relay module			**R161EAD**
INPUT TECHNICAL DATA			
Rated voltage	24 Vac/dc ± 10%		
Rated current (1 channel)	22 mA ± 10%		
Turn ON time	15 ms		
Turn OFF time	5 ms		
Protection circuit	bridge rectifier		
OUTPUT TECHNICAL DATA			
Type and number of contacts	SPDT $AgSnO_2$		
Nominal load (resistive)	12 A / 250 Vac		
Current breaking power	12 A		
Current of the fuse max.	—		
GENERAL TECHNICAL DATA			
Operating temperature range	-10...+50°C		
Coil/contact isolation	2.5 KVac / 60 s		
Isolation between output terminals	1 KVac / 60 s (between open contact)		
Protection degree	IP 00 IEC 529, EN60529		
Overvoltage category / Pollution degree	III / 2		
Reference Standard	IEC 664-1, DIN VDE 0110.1		
Status display	green LED / yellow LED		
Connection terminal	2.5 mm² fixed screw type		
Housing material	UL94V-0 plastic material		
Approx. weight	192 g (6.76 oz)	345 g (12.18 oz)	688 g (24.29 oz)
Mounting information	vertical on rail adjacent without gap		
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB		
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL		
Replacement relay (1)	Cat. No. 8904001		
Screw type jumper red	—		
white	—		
blue	—		

24 Vac/dc SPDT relay modules universal control voltage with fuse

- DC and AC control voltage
- Positive or negative control voltage
- Status LED display
- Pluggable relay
- Output contact with protection fuse




NOTES

The height dimension includes 35 mm DIN rail. (1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical. (2) The interface is supplied without a fuse and the screw plug of the fuse-holder is provided in a bag inside the packaging. The fuse must be dimensioned according to load. The max. value of 6.3 A is referred to EN60127-complying fuses and the homologation rated current of the fuseholder. Fuses of a higher value may damage the fuse-holder and module.


POWER SUPPLY

A1 = +	A2 = –	negative common
A1 = –	A2 = +	positive common
A1 = ~	A2 = ~	AC power supply


BLOCK DIAGRAM



4 relay module



8 relay module




16 relay module

VERSIONS	Cat. No. XR041U24F	Cat. No. XR081U24F	Cat. No. XR161U24F
4 relay module	**R41U24F**		
8 relay module		**R81U24F**	
16 relay module			**R161U24F**
INPUT TECHNICAL DATA			
Rated voltage	24 Vac/dc ± 10%		
Rated current (1 channel)	22 mA ± 10%		
Turn ON time	15 ms		
Turn OFF time	10 ms		
Protection circuit	bridge rectifier		
OUTPUT TECHNICAL DATA			
Type and number of contacts	SPDT $AgSnO_2$ per 4 relé		
Nominal load (resistive)	12 A / 250 Vac		
Current breaking power	12 A		
Current of the fuse max.	6,3 A (2)		
GENERAL TECHNICAL DATA			
Operating temperature range	-10...+50°C		
Coil/contact isolation	2.5 KVac / 60 s		
Isolation between output terminals	1 KVac / 60 s (between open contact)		
Protection degree	IP 00 IEC 529, EN60529		
Overvoltage category / Pollution degree	III / 2		
Reference Standard	IEC 664-1, DIN VDE 0110.1		
Status display	green LED / yellow LED		
Connection terminal	2.5 mm² fixed screw type		
Housing material	UL94V-0 plastic material		
Approx. weight	210 g (7.41 oz)	326 g (11.51 oz)	770 g (27.18 oz)
Mounting information	vertical on rail adjacent without gap		
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB		
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL		
Replacement relay (1)	Cat. No. 8904001		
Screw type jumper red	—		
white	—		
blue	—		

24 Vdc DPDT relay modules negative common


- DC control voltage
- Negative control voltage
- Status LED display
- Pluggable relay




NOTES

The height dimension includes 35 mm DIN rail.
(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.


BLOCK DIAGRAM



4 relay module



8 relay module



16 relay module

VERSIONS	Cat. No. XR042E24	Cat. No. XR082E24	Cat. No. XR162E24
4 relay module	**R42E24**		
8 relay module		**R82E24**	
16 relay module			**R162E24**

INPUT TECHNICAL DATA	
Rated voltage	24 Vdc ± 10%
Rated current (1 channel)	22 mA ± 10%
Turn ON time	15 ms
Turn OFF time	10 ms
Protection circuit	damping & polarity protection diode


OUTPUT TECHNICAL DATA	
Type and number of contacts	DPDT AgNi
Nominal load (resistive)	8 A / 250 Vac
Current breaking power	8 A
Current of the fuse max.	—

GENERAL TECHNICAL DATA			
Operating temperature range	-10...+50°C		
Coil/contact isolation	2.5 KVac / 60 s		
Isolation between output terminals	1 KVac / 60 s (between open contact)		
Protection degree	IP 00 IEC 529, EN60529		
Overvoltage category / Pollution degree	III / 2		
Reference Standard	IEC 664-1, DIN VDE 0110.1		
Status display	green LED / yellow LED		
Connection terminal	2.5 mm² fixed screw type		
Housing material	UL94V-0 plastic material		
Approx. weight	225 g (7.94 oz)	419 g (14.78 oz)	811 g (28.60 oz)
Mounting information	vertical on rail adjacent without gap		

MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35		PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail type according to IEC60715/G32		PR/DIN/AC - PR/DIN/AS - PR/DIN/AL
Replacement relay (1)		Cat. No. 8904002
Screw type jumper	red	—
	white	—
	blue	—

24 Vdc DPDT relay modules positive common


- DC control voltage
- Positive control voltage
- Status LED display
- Pluggable relay




NOTES

The height dimension includes 35 mm DIN rail.
(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.


BLOCK DIAGRAM



4 relay module



8 relay module



16 relay module

VERSIONS	Cat. No. XR042E24P	Cat. No. XR082E24P	Cat. No. XR162E24P
4 relay module	**R42E24P**		
8 relay module		**R82E24P**	
16 relay module			**R162E24P**

INPUT TECHNICAL DATA	
Rated voltage	24 Vdc ± 10%
Rated current (1 channel)	22 mA ± 10%
Turn ON time	15 ms
Turn OFF time	5 ms
Protection circuit	damping & polarity protection diode


OUTPUT TECHNICAL DATA	
Type and number of contacts	DPDT AgNi
Nominal load (resistive)	8 A / 250 Vac
Current breaking power	8 A
Current of the fuse max.	—

GENERAL TECHNICAL DATA			
Operating temperature range	-10...+50°C		
Coil/contact isolation	2.5 KVac / 60 s		
Isolation between output terminals	1 KVac / 60 s (between open contact)		
Protection degree	IP 00 IEC 529, EN60529		
Overvoltage category / Pollution degree	III / 2		
Reference Standard	IEC 664-1, DIN VDE 0110.1		
Status display	green LED / yellow LED		
Connection terminal	2.5 mm² fixed screw type		
Housing material	UL94V-0 plastic material		
Approx. weight	225 g (7.94 oz)	419 g (14.78 oz)	811 g (28.60 oz)
Mounting information	vertical on rail adjacent without gap		

MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35		PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail type according to IEC60715/G32		PR/DIN/AC - PR/DIN/AS - PR/DIN/AL
Replacement relay (1)		Cat. No. 8904002
Screw type jumper	red	—
	white	—
	blue	—

24 Vac/dc DPDT relay modules universal control voltage

- DC and AC control voltage
- Positive or negative control voltage
- Status LED display
- Pluggable relay




NOTES

The height dimension includes 35 mm DIN rail.
(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.
(2) Version available upon request.


POWER SUPPLY

A1 = +	A2 = –	negative common
A1 = –	A2 = +	positive common
A1 = ~	A2 = ~	AC power supply


BLOCK DIAGRAM



4 relay module



8 relay module




16 relay module

VERSIONS	Cat. No. XR042EAD	Cat. No. XR082EAD	Cat. No. XR162EAD
4 relay module	**R42EAD**		
8 relay module		**R82EAD**	
16 relay module			**R162EAD**
INPUT TECHNICAL DATA			
Rated voltage	24 Vac/dc ± 10%		
Rated current (1 channel)	22 mA ± 10%		
Turn ON time	15 ms		
Turn OFF time	5 ms		
Protection circuit	bridge rectifier		
OUTPUT TECHNICAL DATA			
Type and number of contacts	DPDT AgNi		
Nominal load (resistive)	8 A / 250 Vac		
Current breaking power	8 A		
Current of the fuse max.	—		
GENERAL TECHNICAL DATA			
Operating temperature range	-10...+50°C		
Coil/contact isolation	2.5 KVac / 60 s		
Isolation between output terminals	1 KVac / 60 s (between open contact)		
Protection degree	IP 00 IEC 529, EN60529		
Overvoltage category / Pollution degree	III / 2		
Reference Standard	IEC 664-1, DIN VDE 0110.1		
Status display	green LED / yellow LED		
Connection terminal	2.5 mm² fixed screw type		
Housing material	UL94V-0 plastic material		
Approx. weight	227 g (8.01 oz)	427 g (15.07 oz)	835 g (29.48 oz)
Mounting information	vertical on rail adjacent without gap		
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/ TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB		
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL		
Replacement relay (1)	Cat. No. 8904002		
Screw type jumper red	—		
white	—		
blue	—		

24 Vac/dc relay modules universal control voltage with test push button

- DC control voltage
- Positive or negative control voltage
- Status LED display
- Pluggable relay
- Test with push button and micro switch




NOTES

The height dimension includes 35 mm DIN rail.
(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.
(2) They replace XRP08124 and XRD08124 models.

POWER SUPPLY

A1 = +	A2 = –	negative common
A1 = –	A2 = +	positive common
A1 = ~	A2 = ~	AC power supply

BLOCK DIAGRAM



P = test button
D = dip-switch
IG = master switch (disable the push button and dip-switch)

VERSIONS	Cat. No. XRMP081CM (2)
With test push button and dip switch	**RMP081CM**


INPUT TECHNICAL DATA	
Rated voltage	24 Vac/dc ± 10%
Rated current (1 channel)	22 mA ± 10%
Turn ON time	15 ms
Turn OFF time	5 ms
Protection circuit	bridge rectifier

OUTPUT TECHNICAL DATA	
Type and number of contacts	SPDT $AgSnO_2$ per 8 relé
Nominal load (resistive)	12 A / 250 Vac
Current breaking power	12 A
Current of the fuse max.	—

GENERAL TECHNICAL DATA	
Operating temperature range	-10...+50°C
Coil/contact isolation	2.5 KVac / 60 s
Isolation between output terminals	1 KVac / 60 s (between open contact)
Protection degree	IP 00 IEC 529, EN60529
Overvoltage category / Pollution degree	III / 2
Reference Standard	IEC 664-1, DIN VDE 0110.1
Status display	green LED / yellow LED
Connection terminal	2.5 mm² fixed screw type
Housing material	UL94V-0 plastic material
Approx. weight	350 g (12.36 oz)
Mounting information	vertical on rail adjacent without gap


MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35		PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail type according to IEC60715/G32		PR/DIN/AC - PR/DIN/AS - PR/DIN/AL
Replacement relay (1)		Cat. No. 8904001
Screw type jumper	red	—
	white	—
	blue	—

This series of products allows piloting with alternating and direct current, in which case only positive control is possible. We also recommend cutting JP jumpers if piloting takes place via low-current devices (e.g. proximity sensors).
On both versions it is possible the temporary turn on of the relay by pushing the relative button.
On model RD08124 it is possible to switch on the relays permanently with a Dip-Switch.



12 Vdc SPDT relay modules negative common


- DC control voltage
- Negative control voltage
- Status LED display
- Pluggable relay




NOTES

The height dimension includes 35 mm DIN rail.
(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.


BLOCK DIAGRAM



4 relay module



8 relay module




16 relay module

VERSIONS	Cat. No. XR041E12	Cat. No. XR081E12	Cat. No. XR161E12
4 relay module	**R41E12**		
8 relay module		**R81E12**	
16 relay module			**R161E12**
INPUT TECHNICAL DATA			
Rated voltage	12 Vdc ± 10%		
Rated current (1 channel)	22 mA ± 10%		
Turn ON time	15 ms		
Turn OFF time	5 ms		
Protection circuit	damping & polarity protection diode		
OUTPUT TECHNICAL DATA			
Type and number of contacts	SPDT $AgSnO_2$		
Nominal load (resistive)	12 A / 250 Vac		
Current breaking power	12 A		
Current of the fuse max.	—		
GENERAL TECHNICAL DATA			
Operating temperature range	-10...+50°C		
Coil/contact isolation	2.5 KVac / 60 s		
Isolation between output terminals	1 KVac / 60 s (between open contact)		
Protection degree	IP 00 IEC 529, EN60529		
Overvoltage category / Pollution degree	III / 2		
Reference Standard	IEC 664-1, DIN VDE 0110.1		
Status display	green LED / yellow LED		
Connection terminal	2.5 mm² fixed screw type		
Housing material	UL94V-0 plastic material		
Approx. weight	188 g (6.63 oz)	342 g (12.06 oz)	657 g (23,17 oz)
Mounting information	vertical on rail adjacent without gap		
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB		
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL		
Replacement relay (1)	Cat. No. 8904001		
Screw type jumper red	—		
white	—		
blue	—		

12 Vdc DPDT relay modules negative common


- DC control voltage
- Negative control voltage
- Status LED display
- Pluggable relay




NOTES

The height dimension includes 35 mm DIN rail.
(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.


BLOCK DIAGRAM



4 relay module



8 relay module



16 relay module

VERSIONS	Cat. No. XR042E12	Cat. No. XR082E12	Cat. No. XR162E12
4 relay module	**R42E12**		
8 relay module		**R82E12**	
16 relay module			**R162E12**

INPUT TECHNICAL DATA	
Rated voltage	12 Vdc ± 10%
Rated current (1 channel)	22 mA ± 10%
Turn ON time	15 ms
Turn OFF time	5 ms
Protection circuit	damping & polarity protection diode


OUTPUT TECHNICAL DATA	
Type and number of contacts	DPDT AgNi
Nominal load (resistive)	8 A / 250 Vac
Current breaking power	8 A
Current of the fuse max.	—

GENERAL TECHNICAL DATA			
Operating temperature range	-10...+50°C		
Coil/contact isolation	2.5 KVac / 60 s		
Isolation between output terminals	1 KVac / 60 s (between open contact)		
Protection degree	IP 00 IEC 529, EN60529		
Overvoltage category / Pollution degree	III / 2		
Reference Standard	IEC 664-1, DIN VDE 0110.1		
Status display	green LED / yellow LED		
Connection terminal	2.5 mm² fixed screw type		
Housing material	UL94V-0 plastic material		
Approx. weight	225 g (7.94 oz)	419 g (14.78 oz)	811 g (28.60 oz)
Mounting information	vertical on rail adjacent without gap		

MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35		PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail type according to IEC60715/G32		PR/DIN/AC - PR/DIN/AS - PR/DIN/AL
Replacement relay (1)		Cat. No. 8904001
Screw type jumper	red	—
	white	—
	blue	—

48 Vdc DPDT relay modules negative common


- DC control voltage
- Negative control voltage
- Status LED display
- Pluggable relay




NOTES

The height dimension includes 35 mm DIN rail.
(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.


BLOCK DIAGRAM



4 relay module



8 relay module




16 relay module

VERSIONS	Cat. No. XR042E48	Cat. No. XR082E48	Cat. No. XR162E48
4 relay module	**R42E48**		
8 relay module		**R82E48**	
16 relay module			**R162E48**
INPUT TECHNICAL DATA			
Rated voltage	48 Vdc ± 10%		
Rated current (1 channel)	16 mA ± 10%		
Turn ON time	15 ms		
Turn OFF time	5 ms		
Protection circuit	damping & polarity protection diode		
OUTPUT TECHNICAL DATA			
Type and number of contacts	DPDT AgNi		
Nominal load (resistive)	8 A / 250 Vac		
Current breaking power	8 A		
Current of the fuse max.	—		
GENERAL TECHNICAL DATA			
Operating temperature range	-10...+50°C		
Coil/contact isolation	2.5 KVac / 60 s		
Isolation between output terminals	1 KVac / 60 s (between open contact)		
Protection degree	IP 00 IEC 529, EN60529		
Overvoltage category / Pollution degree	III / 2		
Reference Standard	IEC 664-1, DIN VDE 0110.1		
Status display	green LED / yellow LED		
Connection terminal	2.5 mm² fixed screw type		
Housing material	UL94V-0 plastic material		
Approx. weight	225 g (7.94 oz)	419 g (14.78 oz)	811 g (28.60 oz)
Mounting information	vertical on rail adjacent without gap		
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB		
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL		
Replacement relay (1)	Cat. No. 8904053		
Screw type jumper red	—		
white	—		
blue	—		

110...120 Vac/dc SPDT relay modules universal control voltage

- DC and AC control voltage
- Positive or negative control voltage
- Status LED display
- Pluggable relay




NOTES

The height dimension includes 35 mm DIN rail.
(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.


POWER SUPPLY

A1 = +	A2 = –	negative common
A1 = –	A2 = +	positive common
A1 = ~	A2 = ~	AC power supply


BLOCK DIAGRAM



4 relay module



8 relay module




16 relay module

VERSIONS	Cat. No. XR041E1A	Cat. No. XR081E1A	Cat. No. XR161E1A
4 relay module	**R41E11A**		
8 relay module		**R81E11A**	
16 relay module			**R161E11A**
INPUT TECHNICAL DATA			
Rated voltage	110 Vdc / 120 Vac ± 10%		
Rated current (1 channel)	11 mA ± 10%		
Turn ON time	7 ms		
Turn OFF time	3 ms		
Protection circuit	bridge rectifier		
OUTPUT TECHNICAL DATA			
Type and number of contacts	SPDT AgNi		
Nominal load (resistive)	12 A / 250 Vac		
Current breaking power	12 A		
Current of the fuse max.	—		
GENERAL TECHNICAL DATA			
Operating temperature range	-10...+50°C		
Coil/contact isolation	2.5 KVac / 60 s		
Isolation between output terminals	1 KVac / 60 s (between open contact)		
Protection degree	IP 00 IEC 529, EN60529		
Overvoltage category / Pollution degree	III / 2		
Reference Standard	IEC 664-1, DIN VDE 0110.1		
Status display	green LED / yellow LED		
Connection terminal	2.5 mm² fixed screw type		
Housing material	UL94V-0 plastic material		
Approx. weight	192 g (6.76 oz)	345 g (12.18 oz)	688 g (24.29 oz)
Mounting information	vertical on rail adjacent without gap		
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB		
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL		
Replacement relay (1)	Cat. No. 8904047		
Screw type jumper red	—		
white	—		
blue	—		

230 Vac SPDT relay modules


- AC control voltage
- Status LED display
- Pluggable relay




NOTES

The height dimension includes 35 mm DIN rail.
(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.


BLOCK DIAGRAM



4 relay module



8 relay module




16 relay module

VERSIONS	Cat. No. XR041E2A	Cat. No. XR081E2A	Cat. No. XR161E2A
4 relay module	**R41E22A**		
8 relay module		**R81E22A**	
16 relay module			**R161E22A**
INPUT TECHNICAL DATA			
Rated voltage	230 Vac ± 10%		
Rated current (1 channel)	10 mA ± 10%		
Turn ON time	7 ms		
Turn OFF time	2 ms		
Protection circuit	—		
OUTPUT TECHNICAL DATA			
Type and number of contacts	SPDT $AgSnO_2$		
Nominal load (resistive)	12 A / 250 Vac		
Current breaking power	12 A		
Current of the fuse max.	—		
GENERAL TECHNICAL DATA			
Operating temperature range	-10...+50°C		
Coil/contact isolation	2.5 KVac / 60 s		
Isolation between output terminals	1 KVac / 60 s (between open contact)		
Protection degree	IP 00 IEC 529, EN60529		
Overvoltage category / Pollution degree	III / 2		
Reference Standard	IEC 664-1, DIN VDE 0110.1		
Status display	green LED / yellow LED		
Connection terminal	2.5 mm² fixed screw type		
Housing material	UL94V-0 plastic material		
Approx. weight	192 g (6.76 oz)	345 g (12.18 oz)	688 g (24.29 oz)
Mounting information	vertical on rail adjacent without gap		
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB		
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL		
Replacement relay (1)	Cat. No. 8904050		
Screw type jumper red	—		
white	—		
blue	—		

Sockets without SPDT relay 12...24 Vdc negative common


- With spring clips for 16 mm (height) relay
- With 16 or 20 poles IDC connector
- Suitable for relay with 3.5 mm pitch




NOTES

The height dimension includes 35 mm DIN rail.


BLOCK DIAGRAM



4 relay module



8 relay module



16 relay module

VERSIONS	Cat. No. XZ04124D	Cat. No. XZ08124D	Cat. No. XZ16124D
4 relay module	**Z4124D**		
8 relay module		**Z8124D**	
16 relay module			**Z16124D**

INPUT TECHNICAL DATA	
Rated voltage	24 Vdc ± 10%
Rated current (1 channel)	22 mA ± 10%
Turn ON time	15 ms
Turn OFF time	5 ms
Protection circuit	damping & polarity protection diode


OUTPUT TECHNICAL DATA	
Type and number of contacts	SPDT $AgSnO_2$
Nominal load (resistive)	12 A / 250 Vac
Current breaking power	12 A
Current of the fuse max.	—

GENERAL TECHNICAL DATA			
Operating temperature range	-10...+50°C		
Coil/contact isolation	2.5 KVac / 60 s		
Isolation between output terminals	1 KVac / 60 s (between open contact)		
Protection degree	IP 00 IEC 529, EN60529		
Overvoltage category / Pollution degree	III / 2		
Reference Standard	IEC 664-1, DIN VDE 0110.1		
Status display	green LED / yellow LED		
Connection terminal	2.5 mm² fixed screw type + connettore flat 16 poli (8 relè) e 20 poli (16 relè)		
Housing material	UL94V-0 plastic material		
Approx. weight	188 g (6.63 oz)	342 g (12.06 oz)	657 g (23,17 oz)
Mounting information	vertical on rail adjacent without gap		

MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL
Replacement relay	—
Screw type jumper red	—
white	—
blue	—

Sockets without DPDT relay 12...24 Vdc negative common


- With spring clips for 16 mm (height) relay
- 16 or 20 poles IDC connector
- Suitable for relay with 5 mm pitch
- Status LED display




NOTES

The height dimension includes 35 mm DIN rail.


BLOCK DIAGRAM



4 relay module



8 relay module



16 relay module

VERSIONS	Cat. No. XZ04224D	Cat. No. XZ08224D	Cat. No. XZ16224D
4 relay module	Z4224D		
8 relay module		Z8224D	
16 relay module			Z16224D

INPUT TECHNICAL DATA	
Rated voltage	12...24 Vdc ± 10%
Rated current (1 channel)	22 mA ± 10%
Turn ON time	15 ms
Turn OFF time	5 ms
Protection circuit	damping & polarity protection diode


OUTPUT TECHNICAL DATA	
Type and number of contacts	DPDT AgNi
Nominal load (resistive)	8 A / 250 Vac
Current breaking power	8 A
Current of the fuse max.	—


GENERAL TECHNICAL DATA			
Operating temperature range	-10...+50°C		
Coil/contact isolation	2.5 KVac / 60 s		
Isolation between output terminals	1 KVac / 60 s (between open contact)		
Protection degree	IP 00 IEC 529, EN60529		
Overvoltage category / Pollution degree	III / 2		
Reference Standard	IEC 664-1, DIN VDE 0110.1		
Status display	green LED / yellow LED		
Connection terminal	2.5 mm² fixed screw type + connettore flat 16 poli (8 relè) e 20 poli (16 relè)		
Housing material	UL94V-0 plastic material		
Approx. weight	225 g (7.94 oz)	419 g (14.78 oz)	811 g (28.60 oz)
Mounting information	vertical on rail adjacent without gap		

MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB	
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL	
Replacement relay	—	
Screw type jumper red	—	
white	—	
blue	—	

Super compact 24 Vac/dc relay modules universal control voltage

- 3 kV I/O isolation
- 1 kV isolation between output contact
- Fast connection whit pluggable terminals
- DC and AC control voltage
- Positive or negative control voltage





A = 22.5 mm (0.88 in) CR version, 35 mm (1.38 in) CRE version


NOTES

The height dimension includes 35 mm DIN rail.
(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.


CR4-1 and **CRE4-1**: relay module with SPDT, inputs and outputs with pluggable terminals.

CR4-2: expansion module (4 relays with Cat. No.s K5....K8, contacts with Cat. No.s 51-52-54 ...81-82-84) which, combined with the CR4-1, enables 8 relays to be obtained, with SPDT in 45 mm width..

BLOCK DIAGRAM



BLOCK DIAGRAM



VERSIONS	Cat. No. XCRE41	Cat. No. XCR41	Cat. No. XCR42
Pluggable relay	**CRE4-1**		—
Fixed relay		**CR4-1**	**CR4-2**

INPUT TECHNICAL DATA		
Rated voltage	24 Vac/dc ± 10%	24 Vac/dc ± 10%
Rated current (1 channel)	16 mA ± 10%	16 mA ± 10%
Turn ON time	7 ms	7 ms
Turn OFF time	3 ms	3 ms
Protection circuit	bridge rectifier	bridge rectifier


OUTPUT TECHNICAL DATA		
Type and number of contacts	SPDT AgNiO per 4 relé	SPDT AgNiO per 4 relé
Nominal load (resistive)	8 A / 250 Vac	8 A / 250 Vac
Current breaking power	2000 VA	2000 VA
Current of the fuse max.	—	—


GENERAL TECHNICAL DATA		
Operating temperature range	-10...+50°C	-10...+50°C
Coil/contact isolation	2.5 KVac / 60 s	3 KVac / 60 s
Isolation between output terminals	1 KVac / 60 s (between open contact)	1 KVac / 60 s (between open contact)
Protection degree	IP 20 IEC 529, EN60529	IP 00 IEC 529, EN60529
Overvoltage category / Pollution degree	III / 2	III / 2
Reference Standard	IEC 664-1, DIN VDE 0110.1	IEC 664-1, DIN VDE 0110.1
Status display	green LED / yellow LED	green LED / yellow LED
Connection terminal	2.5 mm² fixed screw type	2.5 mm² fixed screw type
Housing material	UL94V-0 plastic material	UL94V-0 plastic material
Approx. weight	143 g (5.05 oz) (180 g [6.35 oz] pluggable version)	143 g (5.05 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap

MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL
Replacement relay (1)	Cat. No. 8904042	Cat. No. 8904042
Screw type jumper red	—	—
white	—	—
blue	—	—

Super compact 24 Vac/dc relay modules universal control voltage

- 3 kV I/O isolation
- 1 kV isolation between output contact
- Fast connection whit pluggable terminals
- DC and AC control voltage
- Positive or negative control voltage





A = 22.5 mm (0.88 in) CR version, 35 mm (1.38 in) CRE version


NOTES

The height dimension includes 35 mm DIN rail.
(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.


CR8-1 and **CR8E-1**: 8 relay module with SPST (NO), inputs and outputs with pluggable terminals.

CR8-2: expansion module (8 relays with Cat. No.s K9....K16, contacts with Cat. No.s 91-92-94 ...161-162-164) which, combined with the CR8-1, enables 16 relays to be obtained, with SPDT in 45 mm width.

BLOCK DIAGRAM




BLOCK DIAGRAM



VERSIONS	Cat. No. XCRE81	Cat. No. XCR81	Cat. No. XCR82
Pluggable relay	**CRE8-1**		**-**
Fixed relay		**CR8-1**	**CR8-2**
INPUT TECHNICAL DATA			
Rated voltage	24 Vac/dc ± 10%		24 Vac/dc ± 10%
Rated current (1 channel)	16 mA ± 10%		17 mA ± 10%
Turn ON time	7 ms		7 ms
Turn OFF time	3 ms		3 ms
Protection circuit	bridge rectifier		bridge rectifier
OUTPUT TECHNICAL DATA			
Type and number of contacts	SPST(NO) per 8 relay		SPST(NO) per 8 relay
Nominal load (resistive)	8 A / 250 Vac		8 A / 250 Vac
Current breaking power	2000 VA		2000 VA
Current of the fuse max.	—		—
GENERAL TECHNICAL DATA			
Operating temperature range	-10...+50°C		-10...+50°C
Coil/contact isolation	3 KVac / 60 s		3 KVac / 60 s
Isolation between output terminals	1 KVac / 60 s (between open contact)		1 KVac / 60 s (between open contact)
Protection degree	IP 20 IEC 529, EN60529		IP 00 IEC 529, EN60529
Overvoltage category / Pollution degree	III / 2		III / 2
Reference Standard	IEC 664-1, DIN VDE 0110.1		IEC 664-1, DIN VDE 0110.1
Status display	green LED / yellow LED		green LED / yellow LED
Connection terminal	morsetti a vite 2.5 mm^2 estraibili		morsetti a vite 2.5 mm^2 estraibili
Housing material	UL94V-0 plastic material		UL94V-0 plastic material
Approx. weight	199 g (7.02 oz) (250 g [8.83 oz] pluggable version)		199 g (7.02 oz)
Mounting information	vertical on rail adjacent without gap		vertical on rail adjacent without gap
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB		PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL		PR/DIN/AC - PR/DIN/AS - PR/DIN/AL
Replacement relay (1)	Cat. No. 8904042		Cat. No. 8904042
Screw type jumper red	—		—
white	—		—
blue	—		—

Super compact 24 Vac/dc relay modules universal control voltage

- 3 kV I/O isolation
- 1 kV isolation between output contact
- Fast connection whit pluggable terminals
- DC and AC control voltage
- Positive or negative control voltage




A = 22.5 mm (0.88 in) CR version, 35 mm (1.38 in) CRE version

NOTES

The height dimension includes 35 mm DIN rail.
(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.

BLOCK DIAGRAM



VERSIONS	Cat. No. XCRE42SC	Cat. No. XCR42SC
Pluggable relay	**CRE4-2SC**	
Fixed relay		**CR4-2SC**

INPUT TECHNICAL DATA	
Rated voltage	24 Vac/dc ± 10%
Rated current (1 channel)	25 mA ± 10%
Turn ON time	7 ms
Turn OFF time	2 ms
Protection circuit	bridge rectifier

OUTPUT TECHNICAL DATA	
Type and number of contacts	DPDT AgNi per 4 relé
Nominal load (resistive)	8 A / 250 Vac
Current breaking power	2000 VA
Current of the fuse max.	—

GENERAL TECHNICAL DATA	
Operating temperature range	-10...+50°C
Coil/contact isolation	2.5 KVac / 60 s
Isolation between output terminals	1 KVac / 60 s (between open contact)
Protection degree	IP 20 IEC 529, EN60529
Overvoltage category / Pollution degree	III / 2
Reference Standard	IEC 664-1, DIN VDE 0110.1
Status display	green LED / yellow LED
Connection terminal	morsetti a vite 2.5 mm^2 estraibili
Housing material	UL94V-0 plastic material
Approx. weight	137 g (180 g pluggable version)
Mounting information	vertical on rail adjacent without gap

MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35		PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail type according to IEC60715/G32		PR/DIN/AC - PR/DIN/AS - PR/DIN/AL
Replacement relay (1)		Cat. No. 8904052
Screw type jumper	red	—
	white	—
	blue	—

PLC interface modules quick selection table

These tables allow you to quickly select only the items, then check if all product's technical data meet your application requirements.

Input modules

Number of channels	Connection type	Notes	Type	Cat. No.	Page
8 without isolation	12 Vdc	(1) (4)	IF16S7	XIF16S7	136
8 without isolation	12 Vdc	(1) (3)	IF16LS7	XIF16LS7	136
32 without isolation	12 Vdc	(1) (4)	IF416S7	XIF416S7	136
32 without isolation	12 Vdc	(1) (3)	IF416LS7	XIF416LS7	136

Output modules


Number of channels	Input voltage	Output		Notes	Type	Cat. No.	Page
		type / no. of contacts	rated current				
8	24 Vdc	SPST(NO)	8 A	(1) (3) (5)	CR8-3	XCR83	137
8	24 Vdc	SPST(NO)	8 A	(1) (3) (5)	CRE8-3	XCRE83	137
8	24 Vdc	SPDT	10 A	(1) (3) (5)	RFE8124	XRFE8124	137
8	24 Vdc	DPDT	5 A	(1) (3) (5)	RFE8224	XRFE8224	138
16	24 Vdc	SPDT	10 A	(2) (3) (5)	RFE16124	XRFE16124	139
16	24 Vdc	DPDT	5 A	(2) (3) (5)	RFE16224	XRFE16224	139


Notes

(1) suitable for PLC Siemens S7 series
(2) suitable for PLC Telemecanique
(3) with LED to display the status
(4) without LED to display the status
(5) version with pluggable relay

PLC S7 300 & S7 400
Interface modules

- I/O modules
- With or without status LED display
- Fast connection







NOTES

(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.

BLOCK DIAGRAM



BLOCK DIAGRAM



VERSIONS	Cat. No. XIF16S7	Cat. No. XIF416LS7	Cat. No. XIF416S7
With LED to display the status	—	IF416LS7	
Without LED to display the status	IF16S7		IF416S7

INPUT TECHNICAL DATA		
Rated voltage	24 Vdc ± 10%	24 Vdc ± 10%
Rated current (1 channel)	5 mA ± 10% (only with “Status LED” version)	5 mA ± 10% (only with “Status LED” version)
Turn ON time	—	—
Turn OFF time	—	—
Protection circuit	—	—


OUTPUT TECHNICAL DATA		
Type and number of contacts	8 channels without isolation	4 x 8 channels without isolation
Nominal load (resistive)	—	—
Current breaking power	—	—
Current of the fuse max.	—	—


GENERAL TECHNICAL DATA		
Operating temperature	-10...+50°C	-10...+50°C
Coil/contact isolation	—	—
Isolation between output terminals	—	—
Protection degree	IP 00 IEC529, EN60529	IP 00 IEC529, EN60529
Overvoltage category / Pollution degree	II / 2	II / 2
Reference Standard	IEC 664-1	IEC 664-1
Status display	LED (solo su IF16LS7)	LED (solo su IF416LS7)
Connection terminals	flat cable 16 poles male and 2.5 mm² fixed screw type	flat cable 16 poles male and 2.5 mm² fixed screw type
Housing material	polyamide UL94V-0	polyamide UL94V-0
Approx. weight	—	—
Mounting information	—	—

MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35	PR/3AC, PR/3AS	PR/3AC, PR/3AS
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL
Replacement relay (1)		
Screw type jumper red	—	—
white	—	—
blue	—	—

PLC S7 300 & S7 400
Interface modules

- Very compact dimension in CR version
- Fast connection
- Pluggable relay
- Status LED display






A = 22.5 mm (0.88 in) CR version, 35 mm (1.38 in) CRE version


NOTES

(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.
(2) Version available upon request.

BLOCK DIAGRAM



BLOCK DIAGRAM



VERSIONS	Cat. No. XCRE83	Cat. No. XCR83	Cat. No. XRFE8124	
Pluggable relay	CRE8-3		RFE8124	
Fixed relay		CR8-3		—

INPUT TECHNICAL DATA		
Rated voltage	24 Vac/dc ± 10%	24 Vac/dc ± 10%
Rated current (1 channel)	16 mA ± 10%	20 mA ± 10%
Turn ON time	15 ms	15 ms
Turn OFF time	5 ms	10 ms
Protection circuit	bridge rectifier	damping & polarity protection diode


OUTPUT TECHNICAL DATA		
Type and number of contacts	SPST(NO) per 8 relay	SPDT AgNiO per 8 relé
Nominal load (resistive)	10 A / 250 Vac	10 A / 250 Vac
Current breaking power	2000 VA	10 A
Current of the fuse max.	—	—

GENERAL TECHNICAL DATA		
Operating temperature range	-10...+50°C	-10...+50°C
Coil/contact isolation	3 KVac / 60 s	2.5 KVac / 60 s
Isolation between output terminals	1 KVac / 60 s (between open contact)	1 KVac / 60 s (between open contact)
Protection degree	IP 20 IEC 529, EN60529	IP 00 IEC 529, EN60529
Overvoltage category / Pollution degree	III / 2	III / 2
Reference Standard	IEC 664-1, DIN VDE 0110.1	IEC 664-1, DIN VDE 0110.1
Status display	green LED / yellow LED	green LED / yellow LED
Connection terminal	flat cable 16 poles male	flat cable 16 poles male and 2.5 mm² fixed screw type
Housing material	UL94V-0 plastic material	UL94V-0 plastic material
Approx. weight	199 g (7.02 oz)	342 g (12.07 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap

MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail type according to IEC60715/G32	—	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL
Replacement relay (1)	Cat. No. 8904042	Cat. No. 8904001
Screw type jumper red	—	—
white	—	—
blue	—	—

PLC S7 300 & S7 400
Interface modules

- DC control voltage
- Negative control voltage
- Status LED display
- Pluggable relay
- Fast connection




CE

NOTES

(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.
(2) Version available upon request.

BLOCK DIAGRAM



VERSIONS	Cat. No. XRFE8224	
Pluggable relay	**RFE8224**	
Fixed relay		—

INPUT TECHNICAL DATA	
Rated voltage	24 Vdc ± 10%
Rated current (1 channel)	20 mA ± 10%
Turn ON time	15 ms
Turn OFF time	5 ms
Protection circuit	damping & polarity protection diode


OUTPUT TECHNICAL DATA	
Type and number of contacts	DPDT AgNiO per 8 relé
Nominal load (resistive)	5 A / 250 Vac
Current breaking power	5 A
Current of the fuse max.	—


GENERAL TECHNICAL DATA	
Operating temperature range	-10...+50°C
Coil/contact isolation	2.5 KVac / 60 s
Isolation between output terminals	1 KVac / 60 s (between open contact)
Protection degree	IP 00 IEC 529, EN60529
Overvoltage category / Pollution degree	III / 2
Reference Standard	IEC 664-1, DIN VDE 0110.1
Status display	green LED / yellow LED
Connection terminal	flat cable 16 poles male and 2.5 mm² fixed screw type
Housing material	UL94V-0 plastic material
Approx. weight	419 g (14.79 oz)
Mounting information	vertical on rail adjacent without gap

MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35		PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail type according to IEC60715/G32		PR/DIN/AC - PR/DIN/AS - PR/DIN/AL
Replacement relay (1)		Cat. No. 8904002
Screw type jumper	red	—
	white	—
	blue	—

Telemecanique PLC interface modules

- DC control voltage
- Negative control voltage
- Status LED display
- Pluggable relay
- Fast connection







NOTES

(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.

BLOCK DIAGRAM



BLOCK DIAGRAM



VERSIONS	Cat. No. XRFE16124		Cat. No. XRFE16224	
Pluggable relay	**RFE16124**		**RFE16224**	
Fixed relay		—		—
INPUT TECHNICAL DATA				
Rated voltage	24 Vdc ± 10%		24 Vdc ± 10%	
Rated current (1 channel)	20 mA ± 10%		20 mA ± 10%	
Turn ON time	15 ms		15 ms	
Turn OFF time	5 ms		5 ms	
Protection circuit	damping & polarity protection diode		damping & polarity protection diode	
OUTPUT TECHNICAL DATA				
Type and number of contacts	SPDT AgNiO per 16 relé		DPDT AgNiO per 16 relé	
Nominal load (resistive)	10 A / 250 Vac		5 A / 250 Vac	
Current breaking power	10 A		5 A	
Current of the fuse max.	—		—	
GENERAL TECHNICAL DATA				
Operating temperature range	-10...+50°C		-10...+50°C	
Coil/contact isolation	2.5 KVac / 60 s		2.5 KVac / 60 s	
Isolation between output terminals	1 KVac / 60 s (between open contact)		1 KVac / 60 s (between open contact)	
Protection degree	IP 00 IEC 529, EN60529		IP 00 IEC 529, EN60529	
Overvoltage category / Pollution degree	III / 2		III / 2	
Reference Standard	IEC 664-1, DIN VDE 0110.1		IEC 664-1, DIN VDE 0110.1	
Status display	green LED / yellow LED		green LED / yellow LED	
Connection terminal	flat cable 16 poles male and 2.5 mm² fixed screw type		flat cable 16 poles male and 2.5 mm² fixed screw type	
Housing material	UL94V-0 plastic material		UL94V-0 plastic material	
Approx. weight	657 g (23.19 oz)		811 g (28.63 oz)	
Mounting information	vertical on rail adjacent without gap		vertical on rail adjacent without gap	
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB		PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB	
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL		PR/DIN/AC - PR/DIN/AS - PR/DIN/AL	
Replacement relay (1)	Cat. No. 8904001		Cat. No. 8904002	
Screw type jumper	red	—		—
	white	—		—
	blue	—		—

Solid state relay modules quick selection table

These tables allow you to quickly select only the items, then check if all product's technical data meet your application requirements.

Input modules

Number of channels	Input voltage	Applicable load		Notes	Type	Cat. No.	Page
		Voltage	Current				
1	5...24 Vdc	5…48 Vdc	3 A	(2)	0332060	XO332060	141
1	5…24 Vdc	5…48 Vdc	500 mA	(2)	CWOT 6-2082	X766082	147
1	12…24 Vdc	5…48 Vdc	500 mA	(2)	CWOT 6-2083	X766083	146
1	12…24 Vdc	5…48 Vdc	2 A	(1)	CM1S024E	XCM1S024E	142
1	24 Vdc	5…48 Vdc	2 A	(1)	CM1S024	XCM1S024	142
1	5…12 Vdc	5…24 Vdc	5 A	(2) (4)	CKS15NA	XCKS15NA	144
1	5…24 Vdc	5…24 Vdc	30 mA	(2)	CKS1S	XCKS1S	147
1	24 Vdc	5…24 Vdc	5 A	(2) (4)	CKS15NB	XCKS15NB	144
1	5...24 Vdc	5...24 Vdc	5 A	(2) (5)	CKS15E	XCKS15E	145
1	12…24 Vdc	12...240 Vac	2 A	(1)	CM1T024E	XCM1T024E	143
1	5...24 Vdc	24...240 Vac	4 A	(2)	0332240	XO332240	141
1	24 Vdc	48...240 Vac	2 A	(1)	CM1T024	XCM1T024	143
2	12…24 Vdc	12…24 Vdc	2 x 2.5 A	(2)	CKS22	XCKS22	145
4	24 Vdc	5…48 Vdc	2 A	(1) (3) (4)	R41S24F	XR041S24F	150
4	24 Vdc	5…48 Vdc	2 A	(1) (3)	R42S24	XR042S24	148
4	24 Vdc	48...240 Vac	2 A	(1) (3)	R42T24	XR042T24	149
8	24 Vdc	5…48 Vdc	2 A	(1) (3) (4)	R81S24F	XR081S24F	150
8	24 Vdc	5…48 Vdc	2 A	(1) (3)	R82S24	XR082S24	148
8	24 Vdc	48...240 Vac	2 A	(1) (3)	R82T24	XR082T24	149
8	5...24 Vdc	12...24 Vdc	8 x 2.5 A	(2) (5)	COP082	XCOP082	151
16	24 Vdc	5…48 Vdc	2 A	(1) (3) (4)	R161S24F	XR161S24F	150
16	24 Vdc	5…48 Vdc	2 A	(1) (3)	R162S24	XR162S24	148
16	24 Vdc	48...240 Vac	2 A	(1) (3)	R162T24	XR162T24	149

Notes

(1) version with pluggable relay

(2) version with fixed relay


(3) universal control voltage, negative/positive DC command


(4) output contact with protection fuse

(5) electronic output protection

Solid state 5...24 Vdc single relay

- Fixed relay
- Compact dimensions
- Status LED display







NOTES

(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.


BLOCK DIAGRAM




BLOCK DIAGRAM




VERSIONS	Cat. No. X0332060	Cat. No. X0332240
Pluggable relay	—	—
Fixed relay	**0332060**	**0332240**
INPUT TECHNICAL DATA		
Input voltage	4…30 Vdc	4…30 Vdc
Level 1 (high) input signal	> 3 Vdc	> 3 Vdc
Level 0 (low) input signal	< 1 Vdc	< 1 Vdc
Rated current	< 35 mA	< 35 mA
Switching frequency	100 Hz max	100 Hz max
Connection terminals	2.5 mm² fixed screw type	2.5 mm² fixed screw type
OUTPUT TECHNICAL DATA		
Output voltage	5…60 Vdc	24…240 Vac (zero crossing)
Continuous load current	3 A a 20°C (see chart)	4 A a 20°C (see chart)
Max. current	4 A a 20°C (5 A / 5 s - 25 A / 10 ms)	5 A a 20°C (6 A / 5 s - 25 A / 10 ms)
Leakage current 0 signal	1 mA	5 mA
OFF/ON switching time	—	—
Protection circuit	—	10 ms max
Connection terminals	2.5 mm² fixed screw type	2.5 mm² fixed screw type
GENERAL TECHNICAL DATA		
Operating temperature	-20…-60°C (see chart)	-20…-60°C (see chart)
I/O isolation bobina/contatti	4 KVac / 60 s	4 KVac / 60 s
Protection degree	IP 00 IEC529, EN60529	IP 00 IEC529, EN60529
Reference Standard	IEC 664-1, DIN VDE 0110.1	IEC 664-1, DIN VDE 0110.1
Pollution degree	2	2
Overvoltage category	III	III
Modello del relé (1)	OPTO22	OPTO22
Status display	LED	LED
Housing material	Polyamide UL94V-0	Polyamide UL94V-0
Pesoapprossimativo	36 g (1.27 oz)	36 g (1.27 oz)
Mounting information	su guida, distanziare 4 mm dai componenti adiacenti	su guida, distanziare 4 mm dai componenti adiacenti
MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35	**PR/3/AC, PR/3/AS**	**PR/3/AC, PR/3/AS**
Mounting rail type according to IEC60715/G32	**PR/DIN/AC - PR/DIN/AS - PR/DIN/AL**	**PR/DIN/AC - PR/DIN/AS - PR/DIN/AL**
Replacement relay (1)	—	—
Screw type jumper red	—	—
white	—	—
blue	—	—






Solid state 12-24 Vdc single relay

- Low cost
- For DC load (S version)
- Pluggable relay
- Screw type jumper available
- Status LED display






NOTES


(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.

This series can be mounted without any spacing between adjacent components.


BLOCK DIAGRAM




BLOCK DIAGRAM




VERSIONS	Cat. No. XCM1S024		Cat. No. XCM1S024E	
Pluggable relay	**CM1S024**		**CM1S024E**	
Fixed relay		—		—
INPUT TECHNICAL DATA				
Input voltage	24 Vdc (19.2…28.8 Vdc)		12-24 Vdc (10…30 Vdc)	
Level 1 (high) input signal	> 19.2 Vdc		> 10 Vdc	
Level 0 (low) input signal	< 1 Vdc		< 6 Vdc	
Rated current (1 channel)	< 20 mA		< 26 mA	
Frequenza di commutazione	100 Hz max		100 Hz max	
Connection terminals	2.5 mm² fixed screw type		2.5 mm² fixed screw type	
OUTPUT TECHNICAL DATA				
Output voltage	3…50 Vdc		5…60 Vdc	
Continuous load current	2.5 A a 40°C (see chart)		2 A a 40°C (see chart)	
Max. current	4 A / 5 s - 20 A / 10 ms		3 A / 5 s - 10 A / 10 ms	
Leakage current 0 signal	0.1 mA		1 mA	
OFF/ON switching time	100 µs / 1 ms		100 µs / 1 ms	
Protection circuit	diodo		diodo	
Connection terminals	2.5 mm² fixed screw type		2.5 mm² fixed screw type	
GENERAL TECHNICAL DATA				
Operating temperature	-20...-60°C (see chart)		-20...-60°C (see chart)	
I/O isolation bobina/contatti	2.5 KVac / 60 s		4 KVac / 60 s	
Protection degree	IP 00 IEC529, EN60529		IP 00 IEC529, EN60529	
Reference Standard	IEC 664-1, DIN VDE 0110.1		IEC 664-1, DIN VDE 0110.1	
Pollution degree	3		3	
Overvoltage category	III		III	
Modello del relé (1)	HF JGX-40F		ELCO SSR91-60B	
Status display	LED		LED	
Housing material	Polyamide UL94V-0		Polyamide UL94V-0	
Approx. weight	—		—	
Mounting information	vertical on rail adjacent without gap		vertical on rail adjacent without gap	
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35	**PR/3/AC, PR/3/AS**		**PR/3/AC, PR/3/AS**	
Mounting rail type according to IEC60715/G32	**—**		**—**	
Replacement relay (1)	Cat. No. 8904404		Cat. No. 8904402	
Screw type jumper black	Cat. No. XCMB16B		Cat. No. XCMB16B	
white	—		—	
blue	—		—	






Solid state 12-24 Vdc single relay

- Low cost
- For AC load (T version)
- Pluggable relay
- Screw type jumper available
- Status LED display






NOTES


(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.

This series can be mounted without any spacing between adjacent components.


BLOCK DIAGRAM




BLOCK DIAGRAM




VERSIONS	Cat. No. XCM1T024		Cat. No. XCM1T024E	
Pluggable relay	**CM1T024**		**CM1T024E**	
Fixed relay		—		—
INPUT TECHNICAL DATA				
Input voltage	24 Vdc (19.2…28.8 Vdc)		12-24 Vdc (10…30 Vdc)	
Level 1 (high) input signal	> 19.2 Vdc		> 10 Vdc	
Level 0 (low) input signal	< 1 Vdc		< 6 Vdc	
Rated current (1 channel)	< 20 mA		< 26 mA	
Frequenza di commutazione	100 Hz max		100 Hz max	
Connection terminals	2.5 mm² fixed screw type		2.5 mm² fixed screw type	
OUTPUT TECHNICAL DATA				
Output voltage	48…240 Vac (zero crossing)		20…240 Vac (zero crossing)	
Continuous load current	2.5 A a 40°C (see chart)		2 A a 40°C (see chart)	
Max. current	4 A / 5 s - 20 A / 10 ms		3 A / 5 s - 10 A / 10 ms	
Leakage current 0 signal	1.5 mA		2 mA	
OFF/ON switching time	10 ms / 10 ms max.		10 ms / 10 ms max.	
Protection circuit	—		—	
Connection terminals	2.5 mm² fixed screw type		2.5 mm² fixed screw type	
GENERAL TECHNICAL DATA				
Operating temperature	-20...-60°C (see chart)		-20...-60°C (see chart)	
I/O isolation bobina/contatti	2.5 KVac / 60 s		4 KVac / 60 s	
Protection degree	IP 00 IEC529, EN60529		IP 00 IEC529, EN60529	
Reference Standard	IEC 664-1, DIN VDE 0110.1		IEC 664-1, DIN VDE 0110.1	
Pollution degree	3		3	
Overvoltage category	III		III	
Modello del relé (1)	HF JGX-40F		ELCO SSR91-60B	
Status display	LED		LED	
Housing material	Polyamide UL94V-0		Polyamide UL94V-0	
Approx. weight	—		—	
Mounting information	vertical on rail adjacent without gap		vertical on rail adjacent without gap	
MOUNTING ACCESSORIES				
Mounting rail type according to IEC60715/TH35	**PR/3/AC, PR/3/AS**		**PR/3/AC, PR/3/AS**	
Mounting rail type according to IEC60715/G32	—		—	
Replacement relay (1)	Cat. No. 8904405		Cat. No. 8904403	
Screw type jumper black	Cat. No. XCMB16B		Cat. No. XCMB16B	
white	—		—	
blue	—		—	






Solid state 12-24 Vdc single relay with fuse

- 5 A / 24 Vdc rated current
- Common negative or positive input
- Overload, short-circuit protected output with replaceable fuse
- Status LED display, reverse polarity protection
- 6 mm wide
- Plug-in jumper available







NOTES

(1) (1) The fast blow-out fuse is calibrated to protect the output stage of the module and it is connected in series to the positive pole; it is possible to replace the fuse with lower rated current values, selected to protect also the load and its wires; a fuse having a current rating higher than 5 A does not protect the output against short circuit and overloads.
(2) In order to assure the IP20 protection degree, the last module must be protected and insulated using the CK/PT end section.

BLOCK DIAGRAM




BLOCK DIAGRAM




VERSIONS		Cat. No. XCKS15NA	Cat. No. XCKS15NB
Pluggable relay		—	—
Fixed relay		**CKS15NA**	**CKS15NB**
INPUT TECHNICAL DATA			
Input voltage		4.5…12 Vdc	19…30 Vdc
Level 1 (high) input signal		≥4.5 Vdc	≥ 20 Vdc
Level 0 (low) input signal		≤4 Vdc	≤18 Vdc
Rated current		≤5 mA @ 12 Vdc	≤ 5 mA @ 24 Vdc
OUTPUT TECHNICAL DATA			
Output voltage		5.2…60 Vdc, max. 100 V (peak)	5.2…60 Vdc, max. 100 V (peak)
Continuous load current		5 A / 24 Vdc @ 25°C	5 A / 24 Vdc @ 25°C
Max. current		7.5 A / 1 s, 25 A / 50 ms	7.5 A / 1 s, 25 A / 50 ms
Min. applicable load		5.2 V / 10 mA	5.2 V / 10 mA
Leakage current 0 signal		25 µA @ 60 Vdc between 13 and 14	25 µA @ 60 Vdc between 13 and 14
Isolation between open contacts		3 KVac / 60 s	3 KVac / 60 s
Protection fuse (1)		F 5 A	F 5 A
GENERAL TECHNICAL DATA			
Operating temperature		-20…+60°C	-20…+60°C
I/O isolation		3 KVac / 60 s	3 KVac / 60 s
Max. switching frequency		400 Hz max.	400 Hz max.
Protection degree		IP20 IEC529 EN60529	IP20 IEC529 EN60529
Reference Standard		IEC 664-1, EN50081-1	IEC 664-1, EN50081-1
Pollution degree		2	2
Overvoltage category		II	II
Connection terminals		2.5 mm² (AWG 14), AWG26-14 spring type	2.5 mm² (AWG 14), AWG26-14 spring type
Housing material		Polyamide UL94V-0	Polyamide UL94V-0
Approx. weight		32 g (1.13 oz)	32 g (1.13 oz)
Mounting information		vertical on rail adjacent without gap	vertical on rail adjacent without gap
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35-7,5		**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32		—	—
Replacement relay (1)		—	—
Plug-in jumper	—	Cat. No. PTCCK42 (42 poles)	Cat. No. PTCCK42 (42 poles)
	white	—	—
	blue	—	—
Marking tags	blank	**CNU/8/030** Cat. No. NU008	**CNU/8/030** Cat. No. NU008
	printed	**CNU/8/CK15/10** Cat. No. N8CK21510	**CNU/8/CK15/10** Cat. No. N8CK21510
	printed	**CNU/8/CK15/20** Cat. No. N8CK21520	**CNU/8/CK15/20** Cat. No. N8CK21520
End plate		Cat. No. XCKPT	Cat. No. XCKPT

Solid state 12-24 Vdc single relay with electronic

- Electronic protection from short circuit, overload, overtemperature
- Input and output status LED
- Output extravoltage suppressor diode
- Extralow current absorbing
- Plug-in jumper available






NOTES


(1) Maximum output current of each channel depends on surrounding air temperature, on the number of output contemporarily active and on the current flowing through them; the given value is measured with 4 active outputs and 4 not active

(2) All outputs are overcurrent and overtemperature; when ovd or ovt protections cuts off the output current, the output display led turns off or reduces its light depending on ovd degree; the output turns on automatically when the ovd or ovt are removed.

BLOCK DIAGRAM




BLOCK DIAGRAM



VERSIONS	Cat. No. XCKS15E	Cat. No. XCKS22
Pluggable relay	—	—
Fixed relay	**CKS15E**	**CKS22**
INPUT TECHNICAL DATA		
Input voltage	5...24 Vdc (4.2…32 Vdc)	12…24 Vdc (range 8…33 Vdc)
Level 1 (high) input signal	> 3.5 Vdc	≥ 12 Vdc
Level 0 (low) input signal	< 3.5 Vdc	≤ 11.7 Vdc
Rated current	≤ 5 mA @ 24 Vdc	≤ 5 mA @ 24 Vdc
Input channels	1	2 with common negative
OUTPUT TECHNICAL DATA		
Output voltage	5...24 Vdc (5…32 Vdc)	12…24 Vdc (range 5…33 Vdc)
Continuous load current	5 A / 24 Vdc @ 45°C (1)	2 x 2.5 A / 24 Vdc @ 45°C
Max. current	7.5 A / 60 s, 2 5A / 50 ms peak (1)	4.4 A
Min. applicable load	5.2 V / 100 mA	10 mA
Frequenza di commutazione	200 Hz max.	—
Leakage current 0 signal	< 25 µA @ 24 Vdc	1 mA @ 24 Vdc
Isolation between open contacts	—	3 KVac / 60 s
Protezione	electronic from overload, overtemperature	—
GENERAL TECHNICAL DATA		
Operating temperature	-20 ... +60°C con protezione termica (2)	-20 ... +60°C con protezione termica (2)
I/O isolation	3 KVac / 60 s	3 KVac / 60 s
Max. switching frequency	—	1 kHz (Ton <500 ms / Toff <500 ms)
Protection degree	IP20 IEC529 EN60529	IP20 IEC529 EN60529
Reference Standard	IEC 664-1, EN50081-1	IEC 664-1, EN50081-1
Pollution degree	2	2
Overvoltage category	II	II
Connection terminals	2.5 mm² AWG26-14 fixed spring type	2.5 mm² AWG26-14 fixed spring type
Housing material	Polyamide UL94V-0	Polyamide UL94V-0
Approx. weight	30 g (1.06 oz)	32 g (1.13 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap
MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35-7,5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—	—
Replacement relay (1)	—	—
Plug-in jumper —	Cat. No. PTCCK42 (42 poles)	Cat. No. PTCCK42 (42 poles)
white	—	—
blue	—	—
Marking tags blank	**CNU/8/030** Cat. No. NU008	**CNU/8/030** Cat. No. NU008
printed	**CNU/8/CK15/10** Cat. No. N8CK21510	**CNU/8/CK15/10** Cat. No. N8CK21510
printed	**CNU/8/CK15/20** Cat. No. N8CK21520	—
End plate	Cat. No. XCKPT	Cat. No. XCKPT

Solid state 12-24 Vdc single relay with electronic SPDT


- 10...40 Vdc rated voltage
- Output with SPDT simulation
- Output voltage 5…48 Vdc 500 mA
- Max switching frequency 1 KHz
- I/O isolation 3.75 KV



NOTES

Compared with standard relays, solid state relays offers many advantages: much longer life, higher switching frequency, lower EMI emissions, higher vibrations withstand capability, wider input voltage range and 70% lower input corrent. The output of solid state relays is a N.O. type “contact” and up to now SPDT type was not available, forcing to use a standard relay when SPDT function was required. Thanks to a new technology, this new solid state relay offers all the advatages of solid state relays with a SPDT contact output type, making a step ahead possible.

BLOCK DIAGRAM



VERSIONS		Cat. No. X766083
Pluggable relay	—	
Fixed relay		**CWOT 6-2083**


INPUT TECHNICAL DATA	
Input signal	24 Vdc (range 10…40 Vdc)
Level 1 (high) input signal (ON)	>5 Vdc
Level 0 (low) input signal (OFF)	<5 Vdc
Rated current	6 mA
Protection device	suppressor diode


OUTPUT TECHNICAL DATA	
Output signal	5…48 Vdc
Continuous load current	10…500 mA
Switching delay	12 µs ON / 12 µs OFF
Protection device	suppressor diode
Tipo di uscita	NPN / PNP transistor, with changeover contact simulation

GENERAL TECHNICAL DATA		
Operating temperature		-25 …+60°C
I/O isolation		3.75 KVac / 60 s
Max. switching frequency		<1 KHz
Protection degree		IP 20 IEC529 EN60529
Reference Standard		IEC 664-1, DIN VDE
Pollution degree		2
Overvoltage category		III
Connection terminals		2.5 mm² fixed screw type
Housing material		PPE
Approx. weight		29 g (1.02 oz)
Mounting information		vertical on rail adjacent without gap
MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35-7,5		**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32		—
Replacement relay (1)		—
Screw type jumper	red	—
	white	—
	blue	—

Signal optoisolators

- Suitable for isolation and transmission of digital signal with high frequency
- Status LED display
- 5, 12 and 24 rated voltage
- I/O isolation







NOTES

(1) Version available upon request.
CKS1S can isolate I/O high frequency signal circuits (encoders, counters etc.) to eliminate influence of different ground reference voltages and ground loops, thus reducing EMI noise influence on signal transmission of sensitive signals; it is always recommended to use balanced type shielded cables (two signal wires + shield); at transmission frequencies higher than 25 Hz the LED light appears constant, it is to be intended as "transmission ON" signal.

BLOCK DIAGRAM




BLOCK DIAGRAM



VERSIONS	Cat. No. XCKS1S	Cat. No. X766082
	CKS1S	CWOT 6-2082
INPUT TECHNICAL DATA		
Input signal	3…30 Vdc	4.5…28 Vdc
Level 1 (high) input signal (ON)	≥ 3 Vdc	>4.2 Vdc
Level 0 (low) input signal (OFF)	≤ 3 Vdc	<2.7 Vdc
Rated current	≤ 10 mA @ 24 Vdc	0.1 mA
OUTPUT TECHNICAL DATA		
Output signal	3…30 Vdc	5…48 Vdc
Continuous load current	80 mA / 30 Vdc @ 25°C	10…500 mA
Min. applicable load	10 mV / 2 mA	—
Switching delay	—	12 µs ON / 12 µs OFF
GENERAL TECHNICAL DATA		
Operating temperature	-20…+60°C	-25…+60°C
I/O isolation	3 KVac / 60 s	3.75 KVac / 60 s
Max. switching frequency	100 kHz max. duty cycle 50/50, 70/30 max	<20 KHz
Protection degree	IP 20 IEC529 EN60529	IP 20 IEC529 EN60529
Reference Standard	IEC 664-1, EN50081-1	IEC 664-1, DIN VDE
Pollution degree	2	2
Overvoltage category	II	III
Connection terminals	2.5 mm² (AWG 14), AWG26-14 spring type	2.5 mm², AWG26-14 a vite
Housing material	Polyamide UL94V-0	PPE
Approx. weight	32 g (1.13 oz)	29 g (1.02 oz)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap
MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35-7,5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—	—
Replacement relay (1)		—
Plug-in jumper —	Cat. No. PTCCK42 (42 poles)	—
white	—	—
blue	—	—
Marking tags blank	**CNU/8/030** Cat. No. NU008	—
printed	—	—
printed	—	—
End plate	Cat. No. XCKPT	—

Solid state 24 Vdc relay modules

- For DC load
- Pluggable relay
- Status LED display



NOTES

(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.

VERSIONS	Cat. No. XR042S24	Cat. No. XR082S24	Cat. No. XR162S24
4 relay module	**R42S24**		
8 relay module		**R82S24**	
16 relay module			**R162S24**


INPUT TECHNICAL DATA	
Input voltage	**24 Vdc** (19.2…28.8 Vdc)
Level 1 (high) input signal	> 19.2 Vdc
Level 0 (low) input signal	< 1 Vdc
Rated current (1 channel)	< 20 mA
Switching frequency	100 Hz max

OUTPUT TECHNICAL DATA	
Output voltage	3…50 Vdc
Continuous load current	2.5 A a 40°C (see chart)
Max. current	4 A / 5 s - 20 A / 10 ms
Leakage current 0 signal	0.1 mA
OFF/ON switching time	100 µs / 1 ms
Protection circuit	diodo
Current of the fuse max.	—


GENERAL TECHNICAL DATA			
Operating temperature range	-20...-60°C (see chart)		
I/O isolation	2.5 KVac / 60 s		
Isolation between output terminals	1 KVac / 60 s (between open contact)		
Protection degree	IP 00 IEC 529, EN60529		
Overvoltage category / Pollution degree	III / 2		
Reference Standard	IEC 664-1, DIN VDE 0110.1		
Status display	green LED / yellow LED		
Connection terminal	2.5 mm² fixed screw type		
Housing material	UL94V-0 plastic material		
Approx. weight	207 g (7.31 oz)	379 g (13.38 oz)	756 g (26.69 oz)
Mounting information	vertical on rail adjacent without gap		

MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL
Replacement relay (1)	Cat. No. 8904404
Screw type jumper	—
	—
	—


BLOCK DIAGRAM




4 relay module



8 relay module




16 relay module



Solid state 24 Vdc relay modules


- For AC load
- Pluggable relay
- Status LED display



NOTES


(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.

BLOCK DIAGRAM




4 relay module

VERSIONS	Cat. No. XR042T24	Cat. No. XR082T24	Cat. No. XR162T24
4 relay module	**R42T24**		
8 relay module		**R82T24**	
16 relay module			**R162T24**




8 relay module




16 relay module

INPUT TECHNICAL DATA			
Input voltage	**24 Vdc** (19.2…28.8 Vdc)		
Level 1 (high) input signal	> 19.2 Vdc		
Level 0 (low) input signal	< 1 Vdc		
Rated current (1 channel)	< 20 mA		
Switching frequency	100 Hz max		
OUTPUT TECHNICAL DATA			
Output voltage	48…240 Vac (zero crossing)		
Continuous load current	2.5 A a 40°C (see chart)		
Max. current	4 A / 5 s - 20 A / 10 ms		
Leakage current 0 signal	1.5 mA		
OFF/ON switching time	10 ms / 10 ms max.		
Protection circuit	—		
Current of the fuse max.	—		
GENERAL TECHNICAL DATA			
Operating temperature range	-20...-60°C (see chart)		
I/O isolation bobina/contatti	2.5 KVac / 60 s		
Protection degree	1 KVac / 60 s (between open contact)		
Reference Standard	IP 00 IEC 529, EN60529		
Pollution degree	III / 2		
Overvoltage category	IEC 664-1, DIN VDE 0110.1		
Modello del relé (1)	green LED / yellow LED		
Status display	2.5 mm² fixed screw type		
Housing material	UL94V-0 plastic material		
Approx. weight (4/8/16 relé)	207 g (7.31 oz)	379 g (13.38 oz)	756 g (26.69 oz)
Mounting information	vertical on rail adjacent without gap		
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB		
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL		
Replacement relay (1)	Cat. No. 8904405		
Screw type jumper	—		



Solid state 24 Vdc relay modules with fuse

- For DC load
- Protection fuse on output
- Pluggable relay
- Status LED display




NOTES


(1) Relay model is not binding, they may be modified without prior warning. The technical data shown here is to be considered typical.

(2) The fuse must be dimensioned according to load. The max. value of 6.3 A is referred to EN60127-complying fuses and the homologation rated current of the fuse-holder. Fuses of a higher value may damage the fuse-holder and module.


BLOCK DIAGRAM



4 relay module




8 relay module



16 relay module


VERSIONS	Cat. No. XR041S24F	Cat. No. XR081S24F	Cat. No. XR161S24F
4 relay module	**R41S24F**		
8 relay module		**R81S24F**	
16 relay module			**R161S24F**
INPUT TECHNICAL DATA			
Input voltage	**24 Vdc** (19.2…28.8 Vdc)		
Level 1 (high) input signal	> 19.2 Vdc		
Level 0 (low) input signal	< 1 Vdc		
Rated current (1 channel)	< 20 mA		
Switching frequency	100 Hz max		
OUTPUT TECHNICAL DATA			
Output voltage	3…50 Vdc		
Continuous load current	2.5 A a 40°C (see chart)		
Max. current	4 A / 5 s - 20 A / 10 ms		
Leakage current 0 signal	0.1 mA		
OFF/ON switching time	100 µs / 1 ms		
Protection circuit	diodo		
Current of the fuse max.	—		
GENERAL TECHNICAL DATA			
Operating temperature range	-20...-60°C (see chart)		
I/O isolation	2.5 KVac / 60 s		
Isolation between output terminals	1 KVac / 60 s (between open contact)		
Protection degree	IP 00 IEC 529, EN60529		
Overvoltage category / Pollution degree	III / 2		
Reference Standard	IEC 664-1, DIN VDE 0110.1		
Status display	green LED / yellow LED		
Connection terminal	2.5 mm² fixed screw type		
Housing material	UL94V-0 plastic material		
Approx. weight	207 g (7.31 oz)	379 g (13.38 oz)	756 g (26.69 oz)
Mounting information	vertical on rail adjacent without gap		
MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB		
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL		
Replacement relay (1)	Cat. No. 8904404		
Screw type jumper	—		



Solid state 24 Vdc relay modules with electronic protection

- Rated current output 8 x 2.5 A / 5 - 33 Vdc
- Short circuit, overload, over temperature, overvoltage output protection
- 12-24 Vdc negative common input, 8 status LED K1 and K8
- 8 output status LED, input/output anti polarity inversion diodes
- 70 mm wide

CE



NOTES

(1) Maximum output current of each channel depends on surrounding air temperature, on the number of output contemporarily active and on the current flowing through them; the given value is measured with 4 active outputs and 4 not active.

(2) All outputs are overcurrent and overtemperature; when ovd or ovt protections cuts off the output current, the output display led turns off or reduce its light depending on ovd degree; the output turns on automatically when the ovd or ovt are removed.

BLOCK DIAGRAM

VERSIONS	Cat. No. XCOP082
4 relay module	
8 relay module	**COP082**
16 relay module	
INPUT TECHNICAL DATA	
Input voltage	**5-24 Vdc** (range 4.2…32 Vdc) negative common
Level 1 (high) input signal	> 3.5 Vdc
Level 0 (low) input signal	< 3.5 Vdc
Rated current (1 channel)	5 mA ±10%.
Switching frequency	500 Hz
OUTPUT TECHNICAL DATA	
Output voltage	12-24 Vdc, (range 5…32 Vdc) negative common
Continuous load current	8 x 2.5 A @ 25°C (1)
Max. current	4.4 A
Leakage current 0 signal	25 µA max @ 24Vdc
OFF/ON switching time	200 Hz (Ton < 500 µs / Toff < 500 µs) (2)
Protection circuit	electronic against short circuit / overload / overtemperature
Min. applicable load	5.2 Vdc/ 100 mA
GENERAL TECHNICAL DATA	
Operating temperature range	-20...-60°C (see chart)
I/O isolation	2.5 KVac / 60 s
Isolation between output terminals	1 KVac / 60 s (between open contact)
Protection degree	IP 00 IEC 529, EN60529
Overvoltage category / Pollution degree	III / 2
Reference Standard	IEC 664-1, DIN VDE 0110.1
Status display	green LED / yellow LED
Connection terminal	2.5 mm^2 fixed screw type
Housing material	UL94V-0 plastic material
Approx. weight	
Mounting information	vertical on rail adjacent without gap

MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail type according to IEC60715/G32	PR/DIN/AC - PR/DIN/AS - PR/DIN/AL
Replacement relay (1)	—
Screw type jumper	—

Passive interface modules selection table

These tables allow you to quickly select only the items, then check if all product's technical data meet your application requirements.

Sub-D / Terminal modules

Version	Dimensions AxBxC	Tipology	Type	Cat. No.	Page
9 poles	37x66x93	(6)	ISD09FM	XISD09FM	153
	37x66x93	(5)	ISD09PF	XISD09PF	153
	37x66x93	(8)	ISD09PM	XISD09PM	153
15 poles	47x66x93	(6)	ISD15FM	XISD15FM	153
	47x66x93	(5)	ISD15PF	XISD15PF	153
	47x66x93	(8)	ISD15PM	XISD15PM	153
25 poles	70x66x93	(6)	ISD25FM	XISD25FM	153
	70x66x93	(5)	ISD25PF	XISD25PF	153
	80x66x93	(5) (7)	ISD25PFL	XISD25PFL	154
	70x66x93	(8)	ISD25PM	XISD25PM	153
	80x66x93	(8) (7)	ISD25PML	XISD25PML	154
	57x80x93	(5) (11)	CPD25F	XCPD25F	155
	57x80x93	(8) (11)	CPD25M	XCPD25M	155
37 poles	107x66x93	(6)	ISD37FM	XISD37FM	153
	107x66x93	(5)	ISD37PF	XISD37PF	153
	109x66x93	(5) (7)	ISD37PFL	XISD37PFL	154
	107x66x93	(8)	ISD37PM	XISD37PM	153
	109x66x93	(8) (7)	ISD37PML	XISD37PML	154
	77x80x93	(5) (11)	CPD37F	XCPD37F	155
	77x80x93	(8) (11)	CPD37M	XCPD37M	155
50 poles	92x80x93	(5) (11)	CPD50F	XCPD50F	155
	92x80x93	(8) (11)	CPD50M	XCPD50M	155

Flat / Terminal modules

Version	Dimensions AxBxC	Tipology	Type	Cat. No.	Page
10 poles	42x66x93	(8)	IF10PMS	XIF10PMS	156
	42x66x93	(8) (7)	IF10PML	XIF10PML	156
14 poles	48x66x93	(8)	IF14PMS	XIF14PMS	156
	48x66x93	(8) (7)	IF14PML	XIF14PML	156
16 poles	58x66x93	(8)	IF16PMS	XIF16PMS	156
	58x66x93	(8) (7)	IF16PML	XIF16PML	156
20 poles	70x66x93	(8)	IF20PMS	XIF20PMS	156
	70x66x93	(8) (7)	IF20PML	XIF20PML	156
	47x80x93	(8) (11)	CPC20M	XCPC20M	157
26 poles	86x66x93	(8)	IF26PMS	XIF26PMS	156
	86x66x93	(8) (7)	IF26PML	XIF26PML	156
	57x80x93	(8) (11)	CPC26M	XCPC26M	157
34 poles	107x66x93	(8)	IF34PMS	XIF34PMS	156
	107x66x93	(8) (7)	IF34PML	XIF34PML	156
	70x80x93	(8) (11)	CPC34M	XCPC34M	157
40 poles	122x66x93	(8)	IF40PMS	XIF40PMS	156
	122x66x93	(8) (7)	IF40PML	XIF40PML	156
	77x80x93	(8) (11)	CPC40M	XCPC40M	157
50 poles	92x80x93	(8) (11)	CPC50M	XCPC50M	157
60 poles	107x80x93	(8) (11)	CPC60M	XCPC60M	157
64 poli	117x80x93	(8) (11)	CPC64M	XCPC64M	157
	92x80x93	(8) (11)	CPD50M	XCPD50M	155

Diode-holder modules

Version	Dimensions AxBxC	Tipology	Type	Cat. No.	Page
8 diodes	25x60x76	(4)	CDM08CS	XCDM08CS	159
	45x65x93	(1)	CDM08AC	XCDM08AC	160
	45x65x93	(2)	CDM08CC	XCDM08CC	160
16 diodes	50x65x93	(4)	CDM16CS	XCDM16CS	159
	92x65x93	(1)	CDM16AC	XCDM16AC	160
	92x65x93	(2)	CDM16CC	XCDM16CC	160
24 diodes	71x65x93	(4)	CDM24CS	XCDM24CS	159
	137x65x93	(1)	CDM24AC	XCDM24AC	160
	137x65x93	(2)	CDM24CC	XCDM24CC	160
	137x65x93	(2)	CDM24CC	XCDM24CC	160

Lamp testing modules

Version	Dimensions AxBxC	Tipology	Type	Cat. No.	Page
8 diodes	45x65x93	(1)	CLT08AC	XCLT08AC	161
	45x65x93	(2)	CLT08CC	XCLT08CC	161
	45x65x93			XCLP08CC	162
16 diodes	92x65x93	(1)	CLT16AC	XCLT16AC	161
	92x65x93	(2)	CLT16CC	XCLT16CC	161
	92x65x93		CLP16CC	XCLP16CC	162


Component-holder modules


Version	Dimensions AxBxC	Tipology	Type	Cat. No.	Page
4 components	25x66x93	(9)	CCM04SF	XCCM04SF	158
8 components	25x66x93	(10)	CCM08SV	XCCM08SV	158
8 components	47x66x93	(9)	CCM08SF	XCCM08SF	158
10 components	38x66x93	(3)	CCM08CV	XCCM08CV	158
12 components	70x66x93	(9)	CCM12SV	XCCM12SV	158
16 components	47x66x93	(10)	CCM16SV	XCCM16SV	158
24 components	70x66x93	(10)	CCM24SV	XCCM24SV	158


Legenda

(1) common anode
(2) common cathode
(3) with common terminal
(4) single diode
(5) female connector
(6) female + male connector
(7) with LED
(8) male connector
(9) single component with Faston terminals
(10) single component with terminal blocks
(11) compact dimensions

Passive interfaces (D-Sub/Terminals modules) ISD series








NOTES

These modules allow the transferirng to the terminals of the deriving signals on a cable with D-Sub connector type
The numeration is “pin-to-pin”.

BLOCK DIAGRAM




VERSIONS	DIMENSIONS (A x B x C)	male		female		male + female	
		Item	Cat. No.	Item	Cat. No.	Item	Cat. No.
9 poles	37x66x93 (1.46x2.60x3.66 in)	**ISD09PM**	**XISD09PM**	**ISD09PF**	**XISD09PF**	**ISD09FM**	**XISD09FM**
15 poles	47x66x93 (1.85x2.60x3.66 in)	**ISD15PM**	**XISD15PM**	**ISD15PF**	**XISD15PF**	**ISD15FM**	**XISD15FM**
25 poles	70x66x93 (2.76x2.60x3.66 in)	**ISD25PM**	**XISD25PM**	**ISD25PF**	**XISD25PF**	**ISD25FM**	**XISD25FM**
37 poles	107x66x93 (4.21x2.60x3.66 in)	**ISD37PM**	**XISD37PM**	**ISD37PF**	**XISD37PF**	**ISD37FM**	**XISD37FM**

GENERAL TECHNICAL DATA			
Rated voltage	0...50 Vac / 0...75 Vdc	0...50 Vac / 0...75 Vdc	0...50 Vac / 0...75 Vdc
Rated current	2 A max.	2 A max.	2 A max.
Operating temperature	-20…+60°C	-20…+60°C	-20…+60°C
Protection degree	IP00 IEC529; EN60529	IP00 IEC529; EN60529	IP00 IEC529; EN60529
Reference Standard	IEC 664-1; DIN VDE 0110.1	IEC 664-1; DIN VDE 0110.1	IEC 664-1; DIN VDE 0110.1
Pollution degree	2	2	2
Overvoltage category	II	II	II
Housing material	polyamide UL94V-0	polyamide UL94V-0	polyamide UL94V-0
Connection terminal blocks	2.5 mm^2 fixed screw type (AWG 14)	2.5 mm^2 fixed screw type (AWG 14)	2.5 mm^2 fixed screw type (AWG 14)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap	vertical on rail adjacent without gap

MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35	**PR/3/AC - PR/3/AS**
Mounting rail type according to IEC60715/G32	**PR/DIN/AC - PR/DIN/AS - PR/DIN/AL**
Jumper bridge black	—

Passive interfaces (D-Sub/Terminals modules) ISD series


• With LED to display the status



NOTES

These modules allow the transferirng to the terminals of the deriving signals on a cable with D-Sub connector type
The numeration is "pin-to-pin"
(1) The LEDs are predisposed for a nominal voltage of 24 Vdc and negative common.

BLOCK DIAGRAM




VERSIONS	DIMENSIONS (A x B x C)	male Item	male Cat. No.	female Item	female Cat. No.
25 poles	80x66x93 (3.15x2.60x3.66 in)	**ISD25PML**	**XISD25PML**	**ISD25PFL**	**XISD25PFL**
37 poles	109x66x93 (4.30x2.60x3.66 in)	**ISD37PML**	**XISD37PML**	**ISD37PFL**	**XISD37PFL**

GENERAL TECHNICAL DATA	
Rated voltage	12...24 Vdc ±10% (1)
Rated current	2 A max.
Operating temperature	-20…+60°C
Protection degree	IP00 IEC529; EN60529
Reference Standard	IEC 664-1; DIN VDE 0110.1
Pollution degree	2
Overvoltage category	II
Housing material	polyamide UL94V-0
Connection terminal blocks	2.5 mm^2 fixed screw type (AWG 14)
Mounting information	vertical on rail adjacent without gap

MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35		**PR/3/AC - PR/3/AS**
Mounting rail type according to IEC60715/G32		**PR/DIN/AC - PR/DIN/AS - PR/DIN/AL**
Jumper bridge	black	—

Passive interfaces (D-Sub/Terminals modules) CPD series


• Compact dimensions



NOTES

These modules allow the transferirng to the terminals of the deriving signals on a cable with D-Sub connector type.
The numeration is “pin-to-pin”.
(1) Version available upon request

BLOCK DIAGRAM



VERSIONS	DIMENSIONS (A x B x C)
25 poles	57x80x93 (2.24x3.15x3.66 in)
37 poles	77x80x93 (3.03x3.15x3.66 in)
50 poles	92x80x93 (3.62x3.15x3.66 in)


male		female	
Item	**Cat. No.**	**Item**	**Cat. No.**
CPD25M	**XCPD25M**	**CPD25F**	**XCPD25F**
CPD37M	**XCPD37M**	**CPD37F**	**XCPD37F**
CPD50M	**XCPD50M**	**CPD50F**	**XCPD50F**


GENERAL TECHNICAL DATA	
Rated voltage	0...50 Vac / 0...75 Vdc
Rated current	2 A max.
Operating temperature	-20…+60°C
Protection degree	IP00 IEC529; EN60529
Reference Standard	IEC 664-1; DIN VDE 0110.1
Pollution degree	2
Overvoltage category	II
Housing material	polyamide UL94V-0
Connection terminal blocks	2.5 mm^2 fixed screw type (AWG 14)
Mounting information	vertical on rail adjacent without gap

MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35		**PR/3/AC - PR/3/AS**
Mounting rail type according to IEC60715/G32		**PR/DIN/AC - PR/DIN/AS - PR/DIN/AL**
Jumper bridge	black	—

Passive interfaces (I.D.C./Terminal blocks) IF series

• Available with LED to display the status






NOTES

The modules allow the transfering to the terminals the deriving signals on Flat-cable through the employment of IDC ribbon cable connectors (with insulation displacement).
The numeration is "pin-to-pin".
(1) Version available upon request
(2) The LEDs are predisposed for a nominal voltage of 24 Vdc and negative common

BLOCK DIAGRAM




VERSIONS	DIMENSIONS (A x B x C)	male Item	male Cat. No.	female Item	female Cat. No.
10 poles	42x66x93 (1.65x2.60x3.66 in)	**IF10PMS (1)**	**XIF10PMS**	**IF10PML (1)**	**XIF10PML**
14 poles	48x66x93 (1.89x2.60x3.66 in)	**IF14PMS (1)**	**XIF14PMS**	**IF14PML (1)**	**XIF14PML**
16 poles	58x66x93 (2.28x2.60x3.66 in)	**IF16PMS**	**XIF16PMS**	**IF16PML**	**XIF16PML**
20 poles	70x66x93 (2.76x2.60x3.66 in)	**IF20PMS**	**XIF20PMS**	**IF20PML**	**XIF20PML**
26 poles	86x66x93 (3.39x2.60x3.66 in)	**IF26PMS**	**XIF26PMS**	**IF26PML**	**XIF26PML**
34 poles	107x66x93 (4.21x2.60x3.66 in)	**IF34PMS**	**XIF34PMS**	**IF34PML**	**XIF34PML**
40 poles	122x66x93 (4.80x2.60x3.66 in)	**IF40PMS**	**XIF40PMS**	**IF40PML**	**XIF40PML**

GENERAL TECHNICAL DATA		
Rated voltage	0...50 Vac / 0...75 Vdc	12...24 Vdc ±10% (2)
Rated current	750 mA max.	750 mA max.
Operating temperature	-20…+60°C	-20…+60°C
Protection degree	IP00 IEC529; EN60529	IP00 IEC529; EN60529
Reference Standard	IEC 664-1; DIN VDE 0110.1	IEC 664-1; DIN VDE 0110.1
Pollution degree	2	2
Overvoltage category	II	II
Housing material	polyamide UL94V-0	polyamide UL94V-0
Connection terminal blocks	2.5 mm^2 fixed screw type (AWG 14)	2.5 mm^2 fixed screw type (AWG 14)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap

MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35		**PR/3/AC - PR/3/AS**
Mounting rail type according to IEC60715/G32		**PR/DIN/AC - PR/DIN/AS - PR/DIN/AL**
Jumper bridge	black	—

Passive interfaces (I.D.C./Terminal blocks) CPC series


• Compact dimensions



NOTES

The modules allow the transferring to the terminals of the deriving signals on Flat-cable through the employment of IDC ribbon cable connectors (with insulation displacement).
The numeration is “pin-to-pin”.

BLOCK DIAGRAM




VERSIONS	DIMENSIONS (A x B x C)	without LED Item	without LED Cat. No.
20 poles	47x80x93 (1.85x3.15x3.66 in)	**CPC20M**	**XCPC20M**
26 poles	57x80x93 (2.24x3.15x3.66 in)	**CPC26M**	**XCPC26M**
34 poles	70x80x93 (2.76x3.15x3.66 in)	**CPC34M**	**XCPC34M**
40 poles	77x80x93 (3.03x3.15x3.66 in)	**CPC40M**	**XCPC40M**
50 poles	92x80x93 (3.62x3.15x3.66 in)	**CPC50M**	**XCPC50M**
60 poles	107x80x93 (4.21x3.15x3.66 in)	**CPC60M**	**XCPC60M**
64 poles	117x80x93 (4.61x3.15x3.66 in)	**CPC64M**	**XCPC64M**


GENERAL TECHNICAL DATA	
Rated voltage	0...50 Vac / 0...75 Vdc
Rated current	750 mA max.
Operating temperature	-20…+60°C
Protection degree	IP00 IEC529; EN60529
Reference Standard	IEC 664-1; DIN VDE 0110.1
Pollution degree	2
Overvoltage category	II
Housing material	polyamide UL94V-0
Connection terminal blocks	2.5 mm^2 fixed screw type (AWG 14)
Mounting information	vertical on rail adjacent without gap


MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35		**PR/3/AC - PR/3/AS**
Mounting rail type according to IEC60715/G32		**PR/DIN/AC - PR/DIN/AS - PR/DIN/AL**
Jumper bridge	black	—

Component-holders modules CCM series

- Compact dimensions
- Available with fast-on connection










NOTES

The component-holders modules allow the montage of electronic components (diodes, resistors, capacitors etc.) according to customer needs.
They are available with connections with terminal blocks or Faston, and with holes of different diameters for the terminals of the components.
(1) Version available upon request; for info call our sales dept., local agent or representative

BLOCK DIAGRAM







VERSIONS	DIMENSIONS (A x B x C)	with common terminal Item	with common terminal Cat. No.	single with terminals Item	single with terminals Cat. No.	single with Faston Item	single with Faston Cat. No.
4 components	25x66x93 (0.98x2.60x3.66 in)	—		—		**CCM04SF**	**XCCM04SF**
8 components	25x66x93 (0.98x2.60x3.66 in)	—		**CCM08SV**	**XCCM08SV**	—	
8 components	47x66x93 (1.85x2.60x3.66 in)	—		—		**CCM08SF**	**XCCM08SF**
8 components	25x55x93 (0.98x2.17x3.66 in)	**CCM08CV**	**XCCM08CV**	—		—	
12 components	70x66x93 (2.76x2.60x3.66 in)	—		—		**CCM12SF (1)**	**XCCM12SF**
16 components	47x66x93 (1.85x2.60x3.66 in)	**CCM16CV**	**XCCM16CV**	**CCM16SV**	**XCCM16SV**	—	
24 components	70x66x93 (2.76x2.60x3.66 in)	—		**CCM24SV (1)**	**XCCM24SV**	—	


GENERAL TECHNICAL DATA			
Rated voltage	0...230 V ±10%	0...230 V ±10%	0...230 V ±10%
Rated current	4 A max. (on the common)	2 A max. (on the common)	2 A max. (on the common)
Operating temperature	-20…+60°C	-20…+60°C	-20…+60°C
Protection degree	IP00 IEC529; EN60529	IP00 IEC529; EN60529	IP00 IEC529; EN60529
Reference Standard	IEC 664-1; DIN VDE 0110.1	IEC 664-1; DIN VDE 0110.1	IEC 664-1; DIN VDE 0110.1
Pollution degree	2	2	2
Overvoltage category	II	II	II
Housing material	polyamide UL94V-0	polyamide UL94V-0	polyamide UL94V-0
Connection terminal blocks	2.5 mm^2 fixed screw type (AWG 14)	2.5 mm^2 fixed screw type (AWG 14)	2.5 mm^2 fixed screw type (AWG 14)
Mounting information	vertical on rail adjacent without gap	vertical on rail adjacent without gap	vertical on rail adjacent without gap

MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35		**PR/3/AC - PR/3/AS**
Mounting rail type according to IEC60715/G32		**PR/DIN/AC - PR/DIN/AS - PR/DIN/AL**
Jumper bridge	black	—

The PMC series has changed its Cat. No. into CCM series, these are the cross reference list.


Old item	New item
PMC0001	**CCM08CV**
PMC0002	**CCM08SV**
PMC0003	**CCM16SV**
PMC0004	**CCM24SV**
PMC0005	**CCM04SF**
PMC0006	**CCM08SF**
PMC0007	**CCM12SF**

Diode-holder modules with single diodes CDM series



NOTES

BLOCK DIAGRAM




VERSIONS	DIMENSIONS (A x B x C)
8 diodes	25x60x76 (0.98x2.36x3.66 in)
16 diodes	50x65x93 (1.97x2.56x3.66 in)
24 diodes	71x65x93 (2.80x2.56x3.66 in)

single diode	
Item	**Cat. No.**
CDM08CS	**XCDM08CS**
CDM16CS	**XCDM16CS**
CDM24CS	**XCDM24CS**

GENERAL TECHNICAL DATA	
Rated voltage	0…230 V ±10%
Rated current	1 A max.
Diode type	1N4007
Repetitive peak reverse voltage	1000 V
Operating temperature	-20…+60°C
Protection degree	IP00 IEC529; EN60529
Reference Standard	IEC 664-1; DIN VDE 0110.1
Pollution degree	2
Overvoltage category	II
Housing material	polyamide UL94V-0
Connection terminal blocks	2.5 mm^2 fixed screw type (AWG 14)
Mounting information	vertical on rail adjacent without gap


MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35		**PR/3/AC - PR/3/AS**
Mounting rail type according to IEC60715/G32		**PR/DIN/AC - PR/DIN/AS - PR/DIN/AL**
Jumper bridge	black	—

Diode-holder modules with common terminal CDM series



NOTES

BLOCK DIAGRAM




VERSIONS	DIMENSIONS (A x B x C)	common anode		common cathode	
		Item	Cat. No.	Item	Cat. No.
8 diodes	45x65x93 (1.77x2.56x3.66 in)	**CDM08AC**	**XCDM08AC**	**CDM08CC**	**XCDM08CC**
16 diodes	92x65x93 (3.62x2.56x3.66 in)	**CDM16AC**	**XCDM16AC**	**CDM16CC**	**XCDM16CC**
24 diodes	137x65x93 (5.39x2.56x3.66 in)	**CDM24AC**	**XCDM24AC**	**CDM24CC**	**XCDM24CC**

GENERAL TECHNICAL DATA	
Rated voltage	0…230 V ±10%
Rated current	1 A max.
Operating temperature	1N4007
Diode type	1000 V
Repetitive peak reverse voltage	-20…+60°C
Protection degree	IP00 IEC529; EN60529
Reference Standard	IEC 664-1; DIN VDE 0110.1
Pollution degree	2
Overvoltage category	II
Housing material	polyamide UL94V-0
Connection terminal blocks	2.5 mm^2 fixed screw type (AWG 14)
Mounting information	vertical on rail adjacent without gap

MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35		**PR/3/AC - PR/3/AS**
Mounting rail type according to IEC60715/G32		**PR/DIN/AC - PR/DIN/AS - PR/DIN/AL**
Jumper bridge	black	—

LED testing modules
CLT series


- Compact dimensions
- Integrated limitation resistence
- Suitable only for LED without resistance limiter



NOTES

(1) Led test can be performed through a negative signal on the common output
(2) Led test can be performed hrough a positive signal on the common input

BLOCK DIAGRAM




VERSIONS	DIMENSIONS (A x B x C)	common negative (1) Item	common negative (1) Cat. No.	common positive (2) Item	common positive (2) Cat. No.
8 channels	45x65x93 (1.77x2.56x3.66 in)	**CLT08AC**	**XCLT08AC**	**CLT08CC**	**XCLT08CC**
16 channels	92x65x93 (3.62x2.56x3.66 in)	**CLT16AC**	**XCLT16AC**	**CLT16CC**	**XCLT16CC**

GENERAL TECHNICAL DATA	
Rated voltage	24 Vdc max. 30 Vdc
Corrente singolo canale	5 mA @ 24 Vdc
Diodes utilizzati	1N4007
Resistenza di limitazione	4,7 KΩ 1/4 W ±5%
Repetitive peak reverse voltage	700 V
Operating temperature	-20…+45°C
Housing material	polyamide UL94V-0
Protection degree	IP 00 IEC529, EN60529
Connection terminal blocks	2.5 mm^2 fixed screw type
Mounting information	vertical on rail adjacent without gap

MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35		**PR/3/AC – PR/3/AC/ZB – PR/3/AS – PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32		**PR/DIN/AC - PR/DIN/AS - PR/DIN/AL**
Jumper bridge	black	—

Lamp testing modules
CLT series

• Compact dimensions




NOTES

With AC input, the diodes rectify the current and the power will be halved.

(1) Led test can be performed through a negative signal on the common output

(2) Led test can be performed hrough a positive signal on the common input

BLOCK DIAGRAM




VERSIONS	DIMENSIONS (A x B x C)	common negative (1) Item	common negative (1) Cat. No.	common positive (2) Item	common positive (2) Cat. No.
8 channels	45x65x93 (1.77x2.56x3.66 in)			**CLP08CC**	**XCLP08CC**
16 channels	92x65x93 (3.62x2.56x3.66 in)			**CLP16CC**	**XCLP16CC**

GENERAL TECHNICAL DATA	
Rated voltage	230 Vac/dc
Rated current (1 channel)	100 mA @ 120 Vac/dc; 50 mA @ 230 Vac/dc
Diode type	1N4007
Limitation resistence	0
Repetitive peak reverse voltage	700 V
Operating temperature	-20…+45°C
Housing material	polyamide UL94V-0
Protection degree	IP 00 IEC529, EN60529
Connection terminal blocks	2.5 mm^2 fixed screw type
Mounting information	vertical on rail adjacent without gap

MOUNTING ACCESSORIES		
Mounting rail type according to IEC60715/TH35		**PR/3/AC – PR/3/AC/ZB – PR/3/AS – PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32		**PR/DIN/AC - PR/DIN/AS - PR/DIN/AL**
Jumper bridge	black	—

Distribution modules
CKF series


- Terminal blocks having a rated current of 24 A and 250 Vac rated voltage
- Four slots for four parallel connections
- Available with and without LED status display
- 6 mm wide



NOTES

1) Modules without output status LED display allow the distribution of any voltage up to 250 V
2) Modules with output status LED display allow the distribution of 12-24 Vac/dc voltage and are available on request; modules suitable for 48 Vac/dc, 120 Vac/dc with status LED display are available upon request
(3) In order to assure the IP20 protection degree, the last module must be protected and insulated using the CK/PT end section

BLOCK DIAGRAM



VERSIONS

Item	Cat. No.	Item	Cat. No.
Status signal on input and output side	**CKFAA**	**XCKFAA**	
Status signal on input side		**CKFAX**	**XCKFAX**

INPUT TECHNICAL DATA

Input voltage	12 – 24 Vac/dc
Rated current (1 channel)	≤10 mA @ 24 Vdc
Bridge voltage	≤24 Vac/dc
Distributable current to the bridge	≤24 A

OUTPUT TECHNICAL DATA

Output voltage	5 – 24 Vac/dc (2)
Rated current (1 channel)	≤10 mA @ 24 Vdc
Distributable voltage to the bridge	≤24 Vac/dc
Distributable current to the bridge	≤24 A

GENERAL TECHNICAL DATA

Operating temperature	-20 – +60°C	
I/O isolation	3 kVac / 60 s	
Isolation between terminals	3 kVac / 60 s	
Protection degree (3)	IP20 IEC529 EN60529	
Reference Standard	IEC 664.1, EN50081-1	
Pollution degree	2	
Overvoltage category	II	
Connection terminals	2.5 mm² AWG26-14 spring type	
Housing material	polyamide UL94V-0	
Approx. weight	24 g (0.85 oz)	40 g (1.41 oz)
Mounting information	adjacent without gap	

MOUNTING ACCESSORIES


Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	
Mounting rail type according to IEC60715/G32	—	
Jumper bridge	**PTC/CK/42**	Cat. No. PTCCK42 (42 poles)
End section	**CK/PT**	Cat. No. XCKPT
Marking tags blank	**CNU/8/030**	Cat. No. NU008
printed	**CNU/8/023**	Cat. No. N8023
printed	**CNU/8/024**	Cat. No. N8024


APPLICATIONS


The use of the CKF modules for the connection and distribution of the common input and output supplies allows of to feed a maximum number of modules which is limited by the 24 A maximum current allowed by its 2.5mm2 (AWG 26-14) terminal blocks; calculation of the distributed maximum current must consider the maximum simultaneous activation of all relays; if the distributed current exceeds 24 A, it will be necessary to divide it on more CKF modules.

Modular diodes-holder modules CKD series

- Easily expandable modules by means of a jumper
- Jumper insertion possibility on each of the 4 levels
- 6 mm wide









NOTES


(1) In this model 1N4007 type diodes are mounted, their maximum average forward rectifier current is 1 A @ 50°C and 0.75 A @ 100°C. A model with BY255 type diodes and with an average forward rectifier current of 3 A @ 50°C, is also available but only upon request

(2) In order to assure the IP20 protection degree, the last module must be protected and insulated using the CK/PT end section

BLOCK DIAGRAM








VERSIONS	Item	Cat. No.	Item	Cat. No.	Item	Cat. No.
Single diode	**CKD3CS**	**XCKD3CS**	—		—	
Common anode diodes array			**CKD4AC**	**XCKD4AC**	—	
Common cathode diodes array			**CKD4CC**	**XCKD4CC**	—	
Lamp / LED test circuits			—		**CKD2LT**	**XCKD2LT**

GENERAL TECHNICAL DATA	
Rated voltage	230 Vac/dc
Rated current	≤ 1 A @ 25°C (diode type 1N4007) (1)
Repetitive peak reverse voltage	1000 V
Distributable voltage to the bridge	≤ 230 Vac/dc
Distributable current to the bridge	≤ 24 A
Operating temperature	-20 – + 60 °C
Protection degree (3)	IP20 IEC529 EN60529
Reference Standard	IEC 664.1, EN50081-1
Pollution degree	2
Overvoltage category	II
Connection terminals	2.5 mm^2, AWG26-14 spring type
Housing material	polyamide UL 94V0
Approx. weight	27 g (0.95 oz)
Mounting information	adjacent without gap

MOUNTING ACCESSORIES			
Mounting rail type according to IEC60715/TH35		**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	
Mounting rail type according to IEC60715/G32		—	
Jumper bridge		**PTC/CK/42**	Cat. No. PTCCK42 (42 poles)
End section		**CK/PT**	Cat. No. XCKPT
Marking tags	blank	**CNU/8/030**	Cat. No. NU008
	printed	**CNU/8/CKD**	Cat. No. N8CKD020
	printed		

Housing for custom applications CH series


• Available on 4 measures



NOTES

(1) Maximum height of the components measured between the circuit and the cover

BLOCK DIAGRAM



VERSIONS

	Item	Cat. No.
right side with hook for DIN rail, 12.5 mm	**CH-B12.5**	**XBB125**
left side housing, 5.5 mm	**CH-C5**	**XBC050**
left side housing, 10 mm	**CH-C10**	**XBC010**
left side housing, 22.5 mm	**CH-C22.5**	**XBC225**
left side housing, 32.5 mm	**CH-C32.5**	**XBC325**
openable hinged cover	**CH-S**	**XBS000**
vented cover	**CH-CA**	**XBCA00**
enclosed cover	**CH-C**	**XBC000**
fixed hinged cover	**CH-CF**	**XBCF00**

GENERAL TECHNICAL DATA

Material	Poliammide UL94V-0
Colour	RAL 5014
Temperature	max 80 °C
Dissipated power	max 7 W
Protection degree	fino a IP30
Number of poles for every side	16 +16 (5.08)
Number of poles on the top	10 (5.08)
Mounting information	

MOUNTING ACCESSORIES

Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AS**
Mounting rail type according to IEC60715/G32	—
Jumper bridge red	—
white	—
blue	—

APPLICATIONS

CH electronic housings

With the CH (Cabur Housing) series containers, Cabur proposes a modular system which allows you to obtain boxes with four width sizes 17.5 mm - 35 mm - 45 mm - composed by 10 easy-to-assemble parts.
The CS can have a maximum size of 102 x 74 mm and can be inserted on 4 small columns formed in the base which holds it in position.
Additional anchorage of the CS is possible with a 2.2 x 4.5 mm self-threading screw to be screwed into the central column, also allowing small CS to be mounted.
The conductors are connected with 2.5 mm pluggable terminals, which are readily available.
16 connection poles which can be used with pitch of 5.08 on each side and 10 on the front side.
The CH-S front closure, with panel opening, provides access to the internal circuit for work on the potentiometers, jumpers and micro-switches.
The side covers are availbale with ventilating holes or closed, and are pre-cutted with 5.08 mm pitch, to make possible an easy cut into necessary lenght with a pair of scissors, for an easy fit to final dimensions.
The following are required for a composition of a housing::

• 1 CH-B12.5 base 12.5 mm wide
• 1 cover (4 sizes available)

CH-C5	5 mm wide
CH-C10	10 mm wide
CH-C22.5	22.5 mm wide
CH-C32.5	32.5 mm wide

(by adding together the width of the base 12.5 mm with the width of the cover chosen from the 4 available, the total width of the housing is obtained)

• 1 front closure in two versions:

CH-S	with panel opening
CH-CF	fixed


• 2 side closures in two versions:

CH-C	without vents
CH-CA	with vents

Maximum inside height (1)	CH-B12.5	CH-C5	CH-C10	CH-C22.5	CH-C32.5	CH-S	CH-CA CH-C
12.1 mm	1	1				1	2
19.1 mm	1		1			1	2
31.6 mm	1			1		1	2
41.6 mm	1				1	1	2

Housing for custom applications CK series

- 6 mm wide, expandable modules
- 6 spring-clamp 2,5 mm² / AWG 26 ÷ 14 terminal blocks
- Jumper insertion possibility on each of the 4 levels
- Hinged front cover access to the printed circuit board




NOTES

(1) 6 spring-clamp terminal blocks included with solder contact


(2) In order to assure the IP20 protection degree, the last module must be protected and insulated using the CK/PT end section

BLOCK DIAGRAM


CKB e CKBG



CKBX2




CKPT



CKS



CKPCB



VERSIONS	Item	Cat. No.
standard base	**CKB** (1)	**XCKB**
base element with ground contact	**CKBG** (1)	**XCKBG**
expansion module	**CKBX2** (1)	**XCKX2**
end section	**CK/PT**	**XCKPT**
front hinge cover	**CK/S**	**XCKS**
printed circuit board	**CK/PCB**	**8901028**

GENERAL TECHNICAL DATA		
Rated voltage of each terminal block		230 Vac/dc ± 10%
Rated current of each terminal block		≤ 24 A
Operating temperature		-40...+ 100°C
Protection degree (2)		IP20 IEC529 EN60529
Connection terminals		2.5 mm², AWG26-14 spring type
Housing material		polyamide UL 94V0
Approx. weight		20 g (CKB, CKBG), 15 g (CKX2, CK/PT) 20 g (CK/PT), 1 g (CK/S), 5 g (CK/PCB)
Parallel bridge	**PTC/CK/42**	Cat. No. PTCCK42 (42 poli)
Marking tags blank	**CNU/8/030**	Cat. No. NU008
printed	**CNU/8/- - -**	(see terminal blocks catalogue)
Mounting information		on rail


MOUNTING ACCESSORIES	
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—
Jumper bridge red	—
white	—
blue	—

APPLICATIONS

With the CK series modular housings, Cabur offers a modular system that provides housings with increasing dimensions in width for simple components as diodes, resistors or more complex circuits with or without the support of a printed circuit board. For the composition of an housing the following items are necessary:

- a base support element, available in two versions: CKB and CKBG; the latter is provided with an electric metal contact on the DIN rail that allows to connect the internal circuit to the ground. Ground contact towards the DIN rail can carry an impulsive current value of 5 KA (8/20 peak). Both models have an external width of 6 mm and internal width of 5 mm; they are also equipped with 6 springclamp terminal blocks and 4 slots for the insertion of a jumper;
- one or more CKBX2 type expansion modules similar to the base support element, having therefore an external width of 6 mm and a central slot that allows the housing of the bulky components with a height exceeding the overall height of the base support element; the expansion module is also equipped with 6 spring-clamp terminal blocks and 4 slots for the insertion of a jumper;
- the CK/S front cover, granting access to the interior of the product, is also available. Once in open position it has such a dimension in order to guarantee a IPXXB degree of protection, even when it is not employed;
- in order to assure the IPXXB protection degree, the last module must be protected and insulated using the CK/PT end section;
- the CK/PCB printed circuit board is also available; it is useful in low volume custom applications where a special pcb is not designed and also where one requires a prototype without tooling a special printed circuit board.


Ground contact on CKBG




CKBX2



CKB



CK/PCB




Plug-in jumper for CK series

Notes:

(1) Example of a pre-cut 9 position jumper

(2) CK/PT end section must be mounted on last module to assure IP20 protection degree

(3) 32 A is the maximum current; however this value is limited by the rated current of the spring-clamp terminal blocks down to 24 A; for instance, having a jumper of 11 poles (1 for common and 10 for distribution) a current of 2.4 A can be distributed on every poles



(1)

VERSIONS	Item	Cat. No.
	PTC/CK/42	PTCCK42

GENERAL TECHNICAL DATA	
Protection degree (2)	IP20 IEC529; EN60529
Number of poles	42
Pitch	6 mm (0.24 in)
Rated current carrying capacity of jumper (3)	32 A
Insulation color	—
Material	tin copper alloy
Approx. weight	27 g (0.95 oz) (42 poles)

Plug-in jumper for CW..7 series



VERSIONS	Item	Cat. No.	Item	Cat. No.	Item	Cat. No.
	CWBK 7-0802	X766802	CWBK 7-0803	X766803	CWBK 7-0804	X766804

GENERAL TECHNICAL DATA			
Protection degree	IP20 IEC529; EN60529	IP20 IEC529; EN60529	IP20 IEC529; EN60529
Number of poles	16	16	16
Pitch	6.2 mm (2.44 in)	6.2 mm (2.44 in)	6.2 mm (2.44 in)
Rated current carrying capacity of jumper	16 A	16 A	16 A
Insulation color	red	white	blue
Material	—	—	—
Approx. weight	4 g (0.14 oz)	4 g (0.14 oz)	4 g (0.14 oz)

Plug-in jumper for CWRE series




VERSIONS	Item	Cat. No.
	CWBK 7-0813	X766813

GENERAL TECHNICAL DATA	
Protection degree	IP20 IEC529; EN60529
Number of poles	16
Pitch	6.2 mm (2.44 in)
Rated current carrying capacity of jumper	16 A
Insulation color	blue
Material	—
Approx. weight	6 g (0.21 oz)

Screw type jumper for JVS series

Notes:
Suitable for JVS protection devices







VERSIONS	Item	Cat. No.	Item	Cat. No.	Item	Cat. No.
	JGB2P	XJGB2P	JGB3P	XJGB3P	JGB4P	XJGB4P

GENERAL TECHNICAL DATA			
Protection degree	IP20 IEC529; EN60529	IP20 IEC529; EN60529	IP20 IEC529; EN60529
Number of poles	2	3	4
Pitch	18 mm (0.71 in)	18 mm (0.71 in)	18 mm (0.71 in)
Rated current carrying capacity of jumper	100 A	100 A	100 A
Insulation color	—	—	—
Material	T2 copper	T2 copper	T2 copper
Treatment	silver plated	silver plated	silver plated

Screw type jumper for CM series



VERSIONS	Item	Cat. No.	Item	Cat. No.
	XCMB16B	XCMB16B	XCMB27B	XCMB27B


GENERAL TECHNICAL DATA		
Protection degree	IP20 IEC529; EN60529	IP20 IEC529; EN60529
Number of poles	8	8
Pitch	16 mm (0.63 in)	27 mm (1.06 in)
Rated current carrying capacity of jumper	10 A @ 250 V	10 A @ 250 V
Insulation color	black	black
Material	—	—
Approx. weight	3 g (0.10 oz)	3 g (0.10 oz)


Marking system
CNU/8 series

Notes:
These are the tags suited to be used for the marking of the terminals on CK series, supplied in tables of 100 elements. They are manufactured in white polyamide and are provided with black printing; to be applied directly into position either before or after assembling the relays to the din rail. They have a 6 mm standard pitch and are 8 mm high. In the table below the types suited to be used with CK interface modules are listed; they are available in numbers or symbols marking patterns. For the complete range, please refer to the terminal blocks catalogue on the accessories section.


N8CK1610


N8CK1620


N8CK2518


N8CKD020


Marking	Type of card (100 elements)	Cat. No.
Tags suited for CKR16 for the marking of 2 modules from 1 to 10 channels	**CNU/8/CK16/10**	N8CK1610
Tags suited for CKR16 for the marking of 2 modules from 11 to 20 channels	**CNU/8/CK16/20**	N8CK1620
Tags suited for CKR25 & CKS21U for the marking of 2 modules from 1 to 18 channels	**CNU/8/CK25/18**	N8CK2518
Tags suited for CKS15 to for the marking of 2 modules from 1 to 10 channels	**CNU/8/CK15/10**	N8CK1510
Tags suited for CKS15 for the marking of 2 modules from 11 to 20 channels	**CNU/8/CK15/20**	N8CK1520
Tags suited for CKD for the marking of 2 modules from 1 to 20 diodes	**CNU/8/CKD**	N8CKD020
N°. 100 tags with "+" symbol	**CNU/8/023**	N8023
N°. 100 tags with "–" symbol	**CNU/8/024**	N8024
N°. 100 tags with "~" symbol	**CNU/8/026**	N8026
N°. 100 blank tags	**CNU/8/030**	NU008

DIN rail clamp





BLOCK DIAGRAM







VERSIONS	Item	Cat. No.	Item	Cat. No.
	CDIN-2	**XCDIN-2**	**CDIN-4**	**XCDIN-4**

GENERAL TECHNICAL DATA		
Type of material	P13-FE00	P13-FE00
Treatment	black passivated	aluminium
Mounting information		
Mounting rail type according to IEC60715/TH35-7.5	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**	**PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB**
Mounting rail type according to IEC60715/G32	—	—

Mounting rails

- according to IEC 60715/TH35 - 7,5
- according to IEC 60715/TH35 - 15
- **supports for TH/35 type rail**







DESCRIPTION	**TYPE** / CAT. NO.	BLOCK DIAGRAMS
IEC 60715/TH35 - 7.5 rail of passivated steel	**PR/3/AC** Cat. No. PR003	
IEC 60715/TH35 - 7.5 rail of white zinc-plated steel "SENDZMIR" system	**PR/3/AC/ZB** Cat. No. PR903	
IEC 60715/TH35 - 7.5 rail of passivated steel with slots	**PR/3/AS** Cat. No. PR005	
IEC 60715/TH35 - 7.5 rail of white zinc-plated steel "SENDZMIR" system with slots	**PR/3/AS/ZB** Cat. No. PR905	
IEC 60715/TH35 - 15 rail of passivated steel	**PR/3/PP** Cat. No. PR007	
IEC 60715/TH35 - 15 rail of white zinc-plated steel "SENDZMIR" system	**PR/3/PP/ZB** Cat. No. PR907	
IEC 60715/TH35 - 15 rail of passivated steel with slots	**PR/3/PA** Cat. No. PR006	
IEC 60715/TH35 - 15 rail of white zinc-plated steel "SENDZMIR" system with slots	**PR/3/PA/ZB** Cat. No. PR906	
Support for IEC 60715/TH35 rail of nickel plated steel and with rapid mounting system 4 MA	**ACI121017** Cat. No. Z121017	
Support for IEC 60715/TH35 rail of nickel plated steel and with rapid mounting system 5 MA	**ACI121019** Cat. No. Z121019	

Mounting rails

- according to IEC 60715 “G32” type rail
- according to IEC 60715/TH15 - 5.5



DESCRIPTION	TYPE / CAT. NO.	IMAGES
IEC 60715 “G32” type rail of passivated steel	**PR/DIN/AC** Cat. No. PR001	
IEC 60715 “G32” type rail of white zinc-plated steel “SENDZMIR” system	**PR/DIN/AC/ZB** Cat. No. PR901	
IEC 60715 “G32” type rail of passivated steel with slots	**PR/DIN/AS** Cat. No. PR004	
IEC 60715 “G32” type rail of white zinc-plated steel “SENDZMIR” system with slots	**PR/DIN/AS/ZB** Cat. No. PR904	
IEC 60715 “G32” type rail of aluminium	**PR/DIN/AL** Cat. No. PR002	
IEC 60715/TH15 – 5.5 rail of passivated steel	**PR/2/AC** Cat. No. PR009	
IEC 60715/TH15 – 5.5 rail of white zinc-plated steel “SENDZMIR” system	**PR/2/AC/ZB** Cat. No. PR909	
IEC 60715/TH15 – 5.5 rail of passivated steel with slots	**PR/2/AS** Cat. No. PR010	
IEC 60715/TH15 – 5.5 rail of white zinc-plated steel “SENDZMIR” system with slots	**PR/2/AS/ZB** Cat. No. PR910	

Index by Catalogue number

CAT. NO.	TYPE	PAGE
8901027	CH/PCB	165
8901028	CK/PCB	166
N8023	CNU/8/023	169
N8024	CNU/8/024	169
N8026	CNU/8/026	169
N8CK1510	CNU/8/CK15/10	169
N8CK1520	CNU/8/CK15/20	169
N8CK1610	CNU/8/CK16/10	169
N8CK1620	CNU/8/CK16/20	169
N8CK2518	CNU/8/CK25/18	169
N8CKD020	CNU/8/CKD	169
NU008	CNU/8/030	169
PR001	PR/DIN/AC	171
PR002	PR/DIN/AL	171
PR003	PR/3/AC	170
PR004	PR/DIN/AS	171
PR005	PR/3/AS	170
PR006	PR/3/PA	170
PR007	PR/3/PP	170
PR009	PR/2/AC	171
PR010	PR/2/AS	171
PR901	PR/DIN/AC/ZB	171
PR903	PR/3/AC/ZB	170
PR904	PR/DIN/AS/ZB	171
PR905	PR/3/AS/ZB	170
PR906	PR/3/PA/ZB	170
PR907	PR/3/PP/ZB	170
PR909	PR/2/AC/ZB	171
PR910	PR/2/AS/ZB	171
PTCCK42	PTC/CK/42	167
X756500	CWAA6-0500	85
X756501	CWAA6-0501	85
X756502	CWAA6-0502	85
X756503	CWAA6-0503	86
X756504	CWAA6-0504	86
X756505	CWAA6-0505	86
X756506	CWAA6-0506	87
X756507	CWAA6-0507	87
X756508	CWAA6-0508	87
X756509	CWNAA6-0509	81
X756510	CWNAA6-0510	80
X756511	CWNAF6-0511	89
X756512	CWNAF6-0512	89
X756516	CWUAA6-0516	79
X756517	CWUAA6-0517	79
X756522	CWBRA6-0522	101
X756524	CWNFA6-0524	96
X756526	CWPAA7-0526	88
X756527	CWPAA7-0527	88
X756530	CWAA7-0530	82
X756531	CWAA7-0531	82
X756532	CWAA7-0532	82
X756533	CWAA7-0533	83
X756534	CWAA7-0534	83
X756535	CWAA7-0535	83
X756536	CWAA7-0536	84
X756537	CWAA7-0537	84
X756538	CWAA7-0538	84
X756539	CWNAA7-0539	80
X756811	CWTPF7-0811	93
X756816	CWPT6-0816	91
X756817	CWPT6-0817	91
X756831	CWTHF7-0831	93
X756844	CWTH6-0844	92
X756847	CWTH6-0847	92
X756871	CWTHF7-0871	93
X756890	CWTPR7-0890	90
X756891	CWPZB7-0891	90
X766082	CWOT6-2082	147
X766083	CWOT6-2083	146
X766184	CWCV7-6184	102
X766813	CWBK7-0813	167
X766842	CWRE7-0842	115
X766845	CWRE7-0845	115
X766846	CWRE7-0846	115
X766847	CWRE7-0847	115
X766848	CWRE7-0848	115
XAR1	AR1	53
XAR2	AR2	53
XAR4	AR4	54
XAR6	AR6	54
XBB125	CH-B12.5	165
XBC000	CH-C	165
XBC010	CH-C10	165
XBC050	CH-C5	165
XBC225	CH-C22.5	165
XBC325	CH-C32.5	165
XBCA00	CH-CA	165
XBCF00	CH-CF	165
XBS000	CH-S	165
XCCIS1	CCIS-1	94
XCCISR	CCIS-R	94
XCCM04SF	CCM04SF	158
XCCM08CV	CCM08CV	158
XCCM08SF	CCM08SF	158
XCCM08SV	CCM08SV	158
XCCM12SF	CCM12SF	158
XCCM16CV	CCM16CV	158
CCM16SV	CCM16SV	158
XCCM24SV	CCM24SV	158
XCDIN2	CDIN-2	169
XCDIN4	CDIN-4	169
XCDM08AC	CDM08AC	160
XCDM08CC	CDM08CC	160
XCDM08CS	CDM08CS	159
XCDM16AC	CDM16AC	160
XCDM16CC	CDM16CC	160
XCDM16CS	CDM16CS	159
XCDM24AC	CDM24AC	160
XCDM24CC	CDM24CC	160
XCDM24CS	CDM24CS	159
XCEPBCB	CEP-BCB	168
XCEPBCR	CEP-BCR	168
XCEPD1	CEP-D1	63
XCEPD3	CEP-D3	63
XCEPMTW	CEP-MTW	168
XCEPRCC	CEP-RCC	168
XCEPRCP	CEP-RCP	168
XCEPSS	CEP-SS	168
XCKB	CKB	166
XCKBG	CKBG	166
XCKD2LT	CKD2LT	164
XCKD3CS	CKD3CS	164
XCKD4AC	CKD4AC	164
XCKD4CC	CKD4CC	164
XCKFAA	CKFAA	163
XCKFAX	CKFAX	163
XCKPT	CK/PT	166
XCKR16	CKR16	114
XCKR25	CKR25	114
XCKS	CK/S	166
XCKS15E	CKS15E	145
XCKS15NA	CKS15NA	144
XCKS15NB	CKS15NB	144
XCKS1S	CKS1S	147
XCKS22	CKS22	145
XCKX2	CKBX2	166
XCL1R	CL1R	52
XCL5R	CL5R	52
XCLP08CC	CLP08CC	162
XCLP16CC	CLP16CC	162
XCLT08AC	CLT08AC	161
XCLT08CC	CLT08CC	161
XCLT16AC	CLT16AC	161
XCLT16CC	CLT16CC	161
XCM1A012	CM1A012	110
XCM1A024	CM1A024	110
XCM1A120	CM1A120	110
XCM1A230	CM1A230	110
XCM1A230Z	CM1A230Z	110
XCM1C012	CM1C012	107
XCM1C024	CM1C024	107
XCM1C024Z	CM1C024Z	107
XCM1C048	CM1C048	107
XCM1C110	CM1C110	107
XCM1C110U	CM1C110U	107
XCM1S024	CM1S024	142
XCM1S024E	CM1S024E	142
XCM1T024	CM1T024	143
XCM1T024E	CM1T024E	143
XCM2A012	CM2A012	111
XCM2A024	CM2A024	111
XCM2A024Z	CM2A024Z	111
XCM2A120	CM2A120	111
XCM2A230	CM2A230	111
XCM2A230Z	CM2A230Z	111
XCM2C012	CM2C012	108
XCM2C024	CM2C024	108
XCM2C024U	CM2C024U	108
XCM2C024Z	CM2C024Z	108
XCM2C048	CM2C048	108
XCM2C110	CM2C110	108
XCM2C110Z	CM2C110Z	108
XCM4A024	CM4A024	112
XCM4C012	CM4C012	109
XCM4C024	CM4C024	109
XCOP082	COP082	151
XCPC20M	CPC20M	157
XCPC26M	CPC26M	157
XCPC34M	CPC34M	157
XCPC40M	CPC40M	157
XCPC50M	CPC50M	157
XCPC60M	CPC60M	157
XCPC64M	CPC64M	157
XCPD25F	CPD25F	155
XCPD25M	CPD25M	155
XCPD37F	CPD37F	155
XCPD37M	CPD37M	155
XCPD50F	CPD50F	155
XCPD50M	CPD50M	155
XCR41	CR4-1	132
XCR42	CR4-2	132
XCR42SC	CR4-2SC	134
XCR81	CR8-1	133
XCR82	CR8-2	133
XCR83	CR8-3	137
XCRE41	CRE4-1	132
XCRE42SC	CRE4-2SC	134
XCRE81	CRE8-1	133
XCRE83	CRE8-3	137
XCSA120BC	CSA120BC	48
XCSA120CB	CSA120CB	48
XCSA120CC	CSA120CC	48
XCSA120DC	CSA120DC	48
XCSA240FC	CSA240FC	49
XCSB150C	CSB150C	40
XCSB85C	CSB85C	39
XCSBC	CSBC	55
XCSBD	CSBD	59
XCSBP30	CSBP30	57
XCSC75B	CSC75B	58
XCSD15B	CSD15B	17
XCSD15C	CSD15C	17
XCSD30C	CSD30C	18
XCSD30E	CSD30E	18
XCSD30F	CSD30F	18
XCSD50B	CSD50B	19
XCSD50C	CSD50C	19
XCSD70C	CSD70C	20
XCSE10	CSE10	51
XCSE3	CSE3	50
XCSE5	CSE5	50
XCSF10	CSF10	27
XCSF10B	CSF10B	27
XCSF10D	CSF10D	27
XCSF10P	CSF10P	27
XCSF120B	CSF120B	26
XCSF120C	CSF120C	26
XCSF120CP	CSF120CP	26
XCSF120D	CSF120D	26
XCSF240B	CSF240B	28
XCSF240C	CSF240C	28
XCSF240CP	CSF240CP	28
XCSF240D	CSF240D	28
XCSF3	CSF3	23
XCSF30B	CSF30B	22
XCSF30C	CSF30C	22
XCSF3A	CSF3A	23
XCSF3B	CSF3B	23
XCSF3P	CSF3P	23
XCSF5	CSF5	25
XCSF500C	CSF500C	29
XCSF500D	CSF500D	29
XCSF565	CSF5-65	30
XCSF5B	CSF5B	25
XCSF5BP	CSF5BP	25
XCSF5D	CSF5D	25
XCSF85B	CSF85B	24
XCSF85C	CSF85C	24
XCSF85CP	CSF85CP	24
XCSG10	CSG10	41
XCSG2400C	CSG2400C	47
XCSG2400D	CSG2400D	47
XCSG240C	CSG240C	42
XCSG42	CSG42	45
XCSG500C	CSG500C	43
XCSG500D	CSG500D	43
XCSG720C	CSG720C	44
XCSG720D	CSG720D	44
XCSG960C	CSG960C	46
XCSG960D	CSG960D	46
XCSP120C	CSP120C	33
XCSP240C	CSP240C	34
XCSP85C	CSP85C	32
XCSUPS1	CS-UPS1	56
XCSUPS2	CS-UPS2	56
XCSW120B	CSW120B	36
XCSW120C	CSW120C	36
XCSW240B	CSW240B	37
XCSW240C	CSW240C	37
XCSW240D	CSW240D	37
XF03DKBG5B	F03DKBG5B	71
XF03DPCG5C	F03DPCG5C	72
XF06DKBG5B	F06DKBG5B	71
XF06DPCG5C	F06DPCG5C	72
XF07TDVST2	F07TDVST2	65
XF100TDVST2	F100TDVST2	65
XF100TYT2	F100TYT2	69
XF10TYG9	F10TYG9	70
XF12DKBG5B	F12DKBG5B	71
XF12DPCG5C	F12DPCG5C	72
XF150TDS84C	F150TDS84C	66
XF16DKCG5B	F16DKCG5B	71
XF16DPCG5C	F16DPCG5C	72
XF16TDVST2	F16TDVST2	65
XF16TYT2	F16TYT2	69
XF180TDS84C	F180TDS84C	66
XF200TDDS84C	F200TDDS84C	67
XF20DKCG5B	F20DKCG5B	71
XF20DPCG5C	F20DPCG5C	72
XF20TYS9	F20TYS9	70
XF25TYT2	F25TYT2	69
XF300TDSS84C	F300TDSS84C	68
XF30DKCS5B	F30DKCS5B	71
XF30DPGS5C	F30DPGS5C	72
XF30TDVST2	F30TDVST2	65
XF36TYT2	F36TYT2	69
XF400TDSS84C	F400TDSS84C	68
XF42TDVST2	F42TDVST2	65
XF500TDSS84C	F500TDSS84C	68
XF50TYT2	F50TYT2	69
XF55TDVST2	F07TDVST2	65
XF600TDSS84C	F600TDSS84C	68
XF75TDVST2	F75TDVST2	65
XIF10PML	IF10PML	156
XIF10PMS	IF10PMS	156
XIF14PML	IF14PML	156
XIF14PMS	IF14PMS	156
XIF16PML	IF16PML	156
XIF16PMS	IF16PMS	156

Index by Catalogue number

CAT. NO.	TYPE	PAGE
XIF16S7	IF16S7	136
XIF20PML	IF20PML	156
XIF20PMS	IF20PMS	156
XIF26PML	IF26PML	156
XIF26PMS	IF26PMS	156
XIF34PML	IF34PML	156
XIF34PMS	IF34PMS	156
XIF40PML	IF40PML	156
XIF40PMS	IF40PMS	156
XIF416LS7	IF416LS7	136
XIF416S7	IF416S7	136
XISD09FM	ISD09FM	153
XISD09PF	ISD09PF	153
XISD09PM	ISD09PM	153
XISD15FM	ISD15FM	153
XISD15PF	ISD15PF	153
XISD15PM	ISD15PM	153
XISD25FM	ISD25FM	153
XISD25PF	ISD25PF	153
XISD25PFL	ISD25PFL	154
XISD25PM	ISD25PM	153
XISD25PML	ISD25PML	154
XISD37FM	ISD37FM	153
XISD37PF	ISD37PF	153
XISD37PFL	ISD37PFL	154
XISD37PM	ISD37PM	153
XISD37PML	ISD37PML	154
XJGB2P	JGBG2P	167
XJGB3P	JGBG3P	167
XJGB4P	JGBG4P	167
XJVS1C1P	JVS1-C1P	61
XJVS1E1P	JVS1-E1P	61
XJVS1N1P	JVS1-N1P	61
XNPNPNP	CI-NPN/PNP	103
XO332060	O332060	141
XO332240	O332240	141
XR041E12	R41E12	125
XR041E1A	R41E11A	128
XR041E24	R41E24	117
XR041E24P	R41E24P	118
XR041E2A	R41E22A	129
XR041EAD	R41EAD	119
XR041S24F	R41S24F	150
XR041U24F	R41U24F	120
XR042E12	R42E12	126
XR042E24	R42E24	121
XR042E24P	R42E24P	122
XR042E48	R42E48	127
XR042EAD	R42EAD	123
XR042S24	R42S24	148
XR042T24	R42T24	149
XR081E12	R81E12	125
XR081E1A	R81E11A	128
XR081E24	R81E24	117
XR081E24P	R81E24P	118
XR081E2A	R81E22A	129
XR081EAD	R81EAD	119
XR081S24F	R81S24F	150
XR081U24F	R81U24F	120
XR082E12	R82E12	126
XR082E24	R82E24	121
XR082E24P	R82E24P	121
XR082E48	R82E48	127
XR082EAD	R82EAD	123
XR082S24	R82S24	148
XR082T24	R82T24	149
XR161E12	R161E12	125
XR161E1A	R161E11A	128
XR161E24	R161E24	117
XR161E24P	R161E24P	118
XR161E2A	R161E22A	129
XR161EAD	R161EAD	119
XR161S24F	R161S24F	150
XR161U24F	R161U24F	120
XR162E12	R162E12	126
XR162E24	R162E24	121
XR162E24P	R162E24P	121
XR162E48	R162E48	127
XR162EAD	R162EAD	123
XR162S24	R162S24	148
XR162T24	R162T24	149
XRE1024D	RE1024D	105
XRE1824D	RE1824D	105
XRE2024D	RE2024D	106
XRF1012D	RF1012D	106
XRF1024D	RF1024D	105
XRF1824D	RF1824D	105
XRFA024D	RFA024D	105
XRFE16124	RFE16124	139
XRFE16224	RFE16224	139
XRFE8124	RFE8124	137
XRFE8224	RFE8224	138
XRMP081CM	RMP081CM	124
XSSAPIPO1	CA-PI/PO1	78
XW000926	GWMV10	100
XW000927	GWMA0	100
XW000928	SW01VA	95
XW000929	SW05VA	95
XW000930	SW10VA	95
XW000931	SW20VA	96
XW000932	SW50VA	96
XW000933	ADC08V10	98
XW000934	ADC08A0	98
XW000935	ADC08A4	98
XW000936	DAC08V10	99
XW000937	DAC08A0	99
XW000938	DAC08A4	99
XZ04124D	Z4124D	130
XZ04224D	Z4224D	131
XZ08124D	Z8124D	130
XZ08224D	Z8224D	131
XZ16124D	Z16124D	130
XZ16224D	Z16224D	131
Z121017	ACI121017	170
Z121019	ACI121019	170

Alphabetical index

CAT. NO.	CODE	PAGE
ACI121017	Z121017	170
ACI121019	Z121019	170
ADC08A0	XW000934	98
ADC08A4	XW000935	98
ADC08V10	XW000933	98
AR1	XAR1	53
AR2	XAR2	53
AR4	XAR4	54
AR6	XAR6	54
CA-PI/PO1	XSSAPIPO1	78
CCIS-1	XCCIS1	94
CCIS-R	XCCISR	94
CCM04SF	XCCM04SF	158
CCM08CV	XCCM08CV	158
CCM08SF	XCCM08SF	158
CCM08SV	XCCM08SV	158
CCM12SF	XCCM12SF	158
CCM16CV	XCCM16CV	158
CCM16SV	CCM16SV	158
CCM24SV	XCCM24SV	158
CDIN-2	XCDIN2	169
CDIN-4	XCDIN4	169
CDM08AC	XCDM08AC	160
CDM08CC	XCDM08CC	160
CDM08CS	XCDM08CS	159
CDM16AC	XCDM16AC	160
CDM16CC	XCDM16CC	160
CDM16CS	XCDM16CS	159
CDM24AC	XCDM24AC	160
CDM24CC	XCDM24CC	160
CDM24CS	XCDM24CS	159
CEP-BCB	XCEPBCB	168
CEP-BCR	XCEPBCR	168
CEP-D1	XCEPD1	63
CEP-D3	XCEPD3	63
CEP-MTW	XCEPMTW	168
CEP-RCC	XCEPRCC	168
CEP-RCP	XCEPRCP	168
CEP-SS	XCEPSS	168
CH/PCB	8901027	165
CH-B12.5	XBB125	165
CH-C	XBC000	165
CH-C10	XBC010	165
CH-C22.5	XBC225	165
CH-C32.5	XBC325	165
CH-C5	XBC050	165
CH-CA	XBCA00	165
CH-CF	XBCF00	165
CH-S	XBS000	165
CI-NPN/PNP	XNPNPNP	103
CK/PCB	8901028	166
CK/PT	XCKPT	166
CK/S	XCKS	166
CKB	XCKB	166
CKBG	XCKBG	166
CKBX2	XCKX2	166
CKD2LT	XCKD2LT	164
CKD3CS	XCKD3CS	164
CKD4AC	XCKD4AC	164
CKD4CC	XCKD4CC	164
CKFAA	XCKFAA	163
CKFAX	XCKFAX	163
CKR16	XCKR16	114
CKR25	XCKR25	114
CKS15E	XCKS15E	145
CKS15NA	XCKS15NA	144
CKS15NB	XCKS15NB	144
CKS1S	XCKS1S	147
CKS22	XCKS22	145
CL1R	XCL1R	52
CL5R	XCL5R	52
CLP08CC	XCLP08CC	162
CLP16CC	XCLP16CC	162
CLT08AC	XCLT08AC	161
CLT08CC	XCLT08CC	161
CLT16AC	XCLT16AC	161
CLT16CC	XCLT16CC	161
CM1A012	XCM1A012	110
CM1A024	XCM1A024	110
CM1A120	XCM1A120	110
CM1A230	XCM1A230	110
CM1A230Z	XCM1A230Z	110
CM1C012	XCM1C012	107
CM1C024	XCM1C024	107
CM1C024Z	XCM1C024Z	107
CM1C048	XCM1C048	107
CM1C110	XCM1C110	107
CM1C110U	XCM1C110U	107
CM1S024	XCM1S024	142
CM1S024E	XCM1S024E	142
CM1T024	XCM1T024	143
CM1T024E	XCM1T024E	143
CM2A012	XCM2A012	111
CM2A024	XCM2A024	111
CM2A024Z	XCM2A024Z	111
CM2A120	XCM2A120	111
CM2A230	XCM2A230	111
CM2A230Z	XCM2A230Z	111
CM2C012	XCM2C012	108
CM2C024	XCM2C024	108
CM2C024U	XCM2C024U	108
CM2C024Z	XCM2C024Z	108
CM2C048	XCM2C048	108

Alphabetical index

CAT. NO.	CODE	PAGE
CM2C110	XCM2C110	108
CM2C110Z	XCM2C110Z	108
CM4A024	XCM4A024	112
CM4C012	XCM4C012	109
CM4C024	XCM4C024	109
CNU/8/023	N8023	169
CNU/8/024	N8024	169
CNU/8/026	N8026	169
CNU/8/030	NU008	169
CNU/8/CK15/10	N8CK1510	169
CNU/8/CK15/20	N8CK1520	169
CNU/8/CK16/10	N8CK1610	169
CNU/8/CK16/20	N8CK1620	169
CNU/8/CK25/18	N8CK2518	169
CNU/8/CKD	N8CKD020	169
COP082	XCOP082	151
CPC20M	XCPC20M	157
CPC26M	XCPC26M	157
CPC34M	XCPC34M	157
CPC40M	XCPC40M	157
CPC50M	XCPC50M	157
CPC60M	XCPC60M	157
CPC64M	XCPC64M	157
CPD25F	XCPD25F	155
CPD25M	XCPD25M	155
CPD37F	XCPD37F	155
CPD37M	XCPD37M	155
CPD50F	XCPD50F	155
CPD50M	XCPD50M	155
CR4-1	XCR41	132
CR4-2	XCR42	132
CR4-2SC	XCR42SC	134
CR8-1	XCR81	133
CR8-2	XCR82	133
CR8-3	XCR83	137
CRE4-1	XCRE41	132
CRE4-2SC	XCRE42SC	134
CRE8-1	XCRE81	133
CRE8-3	XCRE83	137
CSA120BC	XCSA120BC	48
CSA120CB	XCSA120CB	48
CSA120CC	XCSA120CC	48
CSA120DC	XCSA120DC	48
CSA240FC	XCSA240FC	49
CSB150C	XCSB150C	40
CSB85C	XCSB85C	39
CSBC	XCSBC	55
CSBD	XCSBD	59
CSBP30	XCSBP30	57
CSC75B	XCSC75B	58
CSD15B	XCSD15B	17
CSD15C	XCSD15C	17
CSD30C	XCSD30C	18
CSD30E	XCSD30E	18
CSD30F	XCSD30F	18
CSD50B	XCSD50B	19
CSD50C	XCSD50C	19
CSD70C	XCSD70C	20
CSE10	XCSE10	51
CSE3	XCSE3	50
CSE5	XCSE5	50
CSF10	XCSF10	27
CSF10B	XCSF10B	27
CSF10D	XCSF10D	27
CSF10P	XCSF10P	27
CSF120B	XCSF120B	26
CSF120C	XCSF120C	26
CSF120CP	XCSF120CP	26
CSF120D	XCSF120D	26
CSF240B	XCSF240B	28
CSF240C	XCSF240C	28
CSF240CP	XCSF240CP	28
CSF240D	XCSF240D	28
CSF3	XCSF3	23
CSF30B	XCSF30B	22
CSF30C	XCSF30C	22
CSF3A	XCSF3A	23
CSF3B	XCSF3B	23
CSF3P	XCSF3P	23
CSF5	XCSF5	25
CSF500C	XCSF500C	29
CSF500D	XCSF500D	29
CSF5-65	XCSF565	30
CSF5B	XCSF5B	25
CSF5BP	XCSF5BP	25
CSF5D	XCSF5D	25
CSF85B	XCSF85B	24
CSF85C	XCSF85C	24
CSF85CP	XCSF85CP	24
CSG10	XCSG10	41
CSG2400C	XCSG2400C	47
CSG2400D	XCSG2400D	47
CSG240C	XCSG240C	42
CSG42	XCSG42	45
CSG500C	XCSG500C	43
CSG500D	XCSG500D	43
CSG720C	XCSG720C	44
CSG720D	XCSG720D	44
CSG960C	XCSG960C	46
CSG960D	XCSG960D	46
CSP120C	XCSP120C	33
CSP240C	XCSP240C	34
CSP85C	XCSP85C	32
CS-UPS1	XCSUPS1	56
CS-UPS2	XCSUPS2	56
CSW120B	XCSW120B	36
CSW120C	XCSW120C	36
CSW240B	XCSW240B	37
CSW240C	XCSW240C	37
CSW240D	XCSW240D	37
CWAA6-0500	X756500	85
CWAA6-0501	X756501	85
CWAA6-0502	X756502	85
CWAA6-0503	X756503	86
CWAA6-0504	X756504	86
CWAA6-0505	X756505	86
CWAA6-0506	X756506	87
CWAA6-0507	X756507	87
CWAA6-0508	X756508	87
CWAA7-0530	X756530	82
CWAA7-0531	X756531	82
CWAA7-0532	X756532	82
CWAA7-0533	X756533	83
CWAA7-0534	X756534	83
CWAA7-0535	X756535	83
CWAA7-0536	X756536	84
CWAA7-0537	X756537	84
CWAA7-0538	X756538	84
CWBK7-0813	X766813	167
CWBRA6-0522	X756522	101
CWCV7-6184	X766184	102
CWNAA6-0509	X756509	81
CWNAA6-0510	X756510	80
CWNAA7-0539	X756539	80
CWNAF6-0511	X756511	89
CWNAF6-0512	X756512	89
CWNFA6-0524	X756524	96
CWOT6-2082	X766082	147
CWOT6-2083	X766083	146
CWPAA7-0526	X756526	88
CWPAA7-0527	X756527	88
CWPT6-0816	X756816	91
CWPT6-0817	X756817	91
CWPZB7-0891	X756891	90
CWRE7-0842	X766842	115
CWRE7-0845	X766845	115
CWRE7-0846	X766846	115
CWRE7-0847	X766847	115
CWRE7-0848	X766848	115
CWTH6-0844	X756844	92
CWTH6-0847	X756847	92
CWTHF7-0831	X756831	93
CWTHF7-0871	X756871	93
CWTPF7-0811	X756811	93
CWTPR7-0890	X756890	90
CWUAA6-0516	X756516	79
CWUAA6-0517	X756517	79
DAC08A0	XW000937	99
DAC08A4	XW000938	99
DAC08V10	XW000936	99
F03DKBG5B	XF03DKBG5B	71
F03DPCG5C	XF03DPCG5C	72
F06DKBG5B	XF06DKBG5B	71
F06DPCG5C	XF06DPCG5C	72
F07TDVST2	XF07TDVST2	65
F07TDVST2	XF55TDVST2	65
F100TDVST2	XF100TDVST2	65
F100TYT2	XF100TYT2	69
F10TYG9	XF10TYG9	70
F12DKBG5B	XF12DKBG5B	71
F12DPCG5C	XF12DPCG5C	72
F150TDS84C	XF150TDS84C	66
F16DKCG5B	XF16DKCG5B	71
F16DPCG5C	XF16DPCG5C	72
F16TDVST2	XF16TDVST2	65
F16TYT2	XF16TYT2	69
F180TDS84C	XF180TDS84C	66
F200TDDS84C	XF200TDDS84C	67
F20DKCG5B	XF20DKCG5B	71
F20DPCG5C	XF20DPCG5C	72
F20TYS9	XF20TYS9	70
F25TYT2	XF25TYT2	69
F300TDSS84C	XF300TDSS84C	68
F30DKCS5B	XF30DKCS5B	71
F30DPGS5C	XF30DPGS5C	72
F30TDVST2	XF30TDVST2	65
F36TYT2	XF36TYT2	69
F400TDSS84C	XF400TDSS84C	68
F42TDVST2	XF42TDVST2	65
F500TDSS84C	XF500TDSS84C	68
F50TYT2	XF50TYT2	69
F600TDSS84C	XF600TDSS84C	68
F75TDVST2	XF75TDVST2	65
GWMA0	XW000927	100
GWMV10	XW000926	100
IF10PML	XIF10PML	156
IF10PMS	XIF10PMS	156
IF14PML	XIF14PML	156
IF14PMS	XIF14PMS	156
IF16PML	XIF16PML	156
IF16PMS	XIF16PMS	156
IF16S7	XIF16S7	136
IF20PML	XIF20PML	156
IF20PMS	XIF20PMS	156
IF26PML	XIF26PML	156
IF26PMS	XIF26PMS	156
IF34PML	XIF34PML	156
IF34PMS	XIF34PMS	156
IF40PML	XIF40PML	156
IF40PMS	XIF40PMS	156
IF416LS7	XIF416LS7	136
IF416S7	XIF416S7	136
ISD09FM	XISD09FM	153
ISD09PF	XISD09PF	153
ISD09PM	XISD09PM	153
ISD15FM	XISD15FM	153
ISD15PF	XISD15PF	153
ISD15PM	XISD15PM	153
ISD25FM	XISD25FM	153
ISD25PF	XISD25PF	153
ISD25PFL	XISD25PFL	154
ISD25PM	XISD25PM	153
ISD25PML	XISD25PML	154
ISD37FM	XISD37FM	153
ISD37PF	XISD37PF	153
ISD37PFL	XISD37PFL	154
ISD37PM	XISD37PM	153
ISD37PML	XISD37PML	154
JGBG2P	XJGB2P	167
JGBG3P	XJGB3P	167
JGBG4P	XJGB4P	167
JVS1-C1P	XJVS1C1P	61
JVS1-E1P	XJVS1E1P	61
JVS1-N1P	XJVS1N1P	61
0332060	X0332060	141
0332240	X0332240	141
PR/2/AC	PR009	171
PR/2/AC/ZB	PR909	171
PR/2/AS	PR010	171
PR/2/AS/ZB	PR910	171
PR/3/AC	PR003	170
PR/3/AC/ZB	PR903	170
PR/3/AS	PR005	170
PR/3/AS/ZB	PR905	170
PR/3/PA	PR006	170
PR/3/PA/ZB	PR906	170
PR/3/PP	PR007	170
PR/3/PP/ZB	PR907	170
PR/DIN/AC	PR001	171
PR/DIN/AC/ZB	PR901	171
PR/DIN/AL	PR002	171
PR/DIN/AS	PR004	171
PR/DIN/AS/ZB	PR904	171
PTC/CK/42	PTCCK42	167
R161E11A	XR161E1A	128
R161E12	XR161E12	125
R161E22A	XR161E2A	129
R161E24	XR161E24	117
R161E24P	XR161E24P	118
R161EAD	XR161EAD	119
R161S24F	XR161S24F	150
R161U24F	XR161U24F	120
R162E12	XR162E12	126
R162E24	XR162E24	121
R162E24P	XR162E24P	121
R162E48	XR162E48	127
R162EAD	XR162EAD	123
R162S24	XR162S24	148
R162T24	XR162T24	149
R41E11A	XR041E1A	128
R41E12	XR041E12	125
R41E22A	XR041E2A	129
R41E24	XR041E24	117
R41E24P	XR041E24P	118
R41EAD	XR041EAD	119
R41S24F	XR041S24F	150
R41U24F	XR041U24F	120
R42E12	XR042E12	126
R42E24	XR042E24	121
R42E24P	XR042E24P	122
R42E48	XR042E48	127
R42EAD	XR042EAD	123
R42S24	XR042S24	148
R42T24	XR042T24	149
R81E11A	XR081E1A	128
R81E12	XR081E12	125
R81E22A	XR081E2A	129
R81E24	XR081E24	117
R81E24P	XR081E24P	118
R81EAD	XR081EAD	119
R81S24F	XR081S24F	150
R81U24F	XR081U24F	120
R82E12	XR082E12	126
R82E24	XR082E24	121
R82E24P	XR082E24P	121
R82E48	XR082E48	127
R82EAD	XR082EAD	123
R82S24	XR082S24	148
R82T24	XR082T24	149
RE1024D	XRE1024D	105
RE1824D	XRE1824D	105
RE2024D	XRE2024D	106
RF1012D	XRF1012D	106
RF1024D	XRF1024D	105
RF1824D	XRF1824D	105
RFA024D	XRFA024D	105
RFE16124	XRFE16124	139
RFE16224	XRFE16224	139
RFE8124	XRFE8124	137
RFE8224	XRFE8224	138

Alphabetical index

CAT. NO.	CODE	PAGE
RMP081CM	XRMP081CM	124
SW01VA	XW000928	95
SW05VA	XW000929	95
SW10VA	XW000930	95
SW20VA	XW000931	96
SW50VA	XW000932	96
Z16124D	XZ16124D	130
Z16224D	XZ16224D	131
Z4124D	XZ04124D	130
Z4224D	XZ04224D	131
Z8124D	XZ08124D	130
Z8224D	XZ08224D	131